

Quantification of PM_{2.5} organic carbon sampling artifacts in US networks

J. C. Chow^{1,2}, J. G. Watson^{1,2}, L.-W. A. Chen¹, J. Rice³, and N. H. Frank³

¹Division of Atmospheric Sciences, Desert Research Institute, 2215 Raggio Parkway, Reno, Nevada, USA

²Institute of Earth Environment, Chinese Academy of Sciences, No. 10, Fenghui South Road, High-tech Zone, P.O. Box 17, Xian 710075, China

³Office of Air Quality Planning & Standards, US Environmental Protection Agency, 4201 Alexander Dr., Research Triangle Park, North Carolina, USA

Received: 18 August 2009 – Published in Atmos. Chem. Phys. Discuss.: 18 December 2009

Revised: 13 March 2010 – Accepted: 5 April 2010 – Published: 15 June 2010

Abstract. Field blanks (bQF) and backup filters (quartz-fiber behind quartz-fiber filter; QBQ) have been adopted by US long-term air quality monitoring networks to estimate PM_{2.5} organic carbon (OC) sampling artifacts. This study documents bQF and QBQ carbon levels for the: 1) Interagency Monitoring of Protected Visual Environments (IMPROVE); 2) Speciation Trends Network (STN; part of the Chemical Speciation Network [CSN]); and 3) Southeastern Aerosol Research and Characterization (SEARCH) networks and examines the similarities/differences associated with network-specific sampling protocols. A higher IMPROVE sample volume and smaller filter deposit area results in PM_{2.5} areal density ($\mu\text{g}/\text{cm}^2$ on filter) 3–11 times those of STN/CSN and SEARCH samples for the same ambient PM_{2.5} concentrations, thus reducing the relative contribution of sampling artifacts from passive OC adsorption. A relatively short (1–15 min) passive exposure period of STN/CSN and SEARCH bQF OC ($0.8\text{--}1\ \mu\text{g}/\text{cm}^2$) underestimates positive and negative OC artifacts resulting from passive adsorption or evaporation of semi-volatile organic compounds on quartz-fiber filters. This is supported by low STN/CSN and SEARCH bQF levels and lack of temporal or spatial variability among the sites within the networks. With a much longer period, ~ 7 days of ambient passive exposure, average IMPROVE bQF and QBQ OC are comparable (2.4 ± 0.5 and $3.1\pm 0.8\ \mu\text{g}/\text{cm}^2$, respectively) and more than twice levels found in the STN/CSN and SEARCH networks. Sampling artifacts in STN/CSN were estimated from collocated

IMPROVE samples based on linear regression. At six of the eight collocated sites in this study, STN/CSN bQFs underestimated OC artifacts by 11–34%. Using a preceding organic denuder in the SEARCH network minimized passive adsorption on QBQ, but OC on QBQ may not be attributed entirely to the negative sampling artifact (e.g., evaporated or volatilized OC from the front filter deposits after sample collection).

1 Introduction

PM_{2.5} and PM₁₀ (particulate matter with aerodynamic diameters <2.5 and $10\ \mu\text{m}$, respectively) sampling onto quartz-fiber filters is accompanied by positive (e.g., adsorption of organic vapors) and negative (e.g., volatilization of organic aerosols after sample collection) artifacts. The positive artifact, as indicated by field blanks and backup filters, is believed to exceed the negative artifact for most samples (ten Brink et al., 2004; Watson et al., 2009). Without blank or backup filter subtraction, the artifact inflates organic carbon (OC) concentrations. The artifact also biases elemental carbon (EC) values by as much as $\sim 50\%$, especially when measured by thermal-optical transmittance (TOT), because light attenuation due to charring of the adsorbed organic gases within the filter has a greater influence than charring of the surface particle deposit (Chen et al., 2004; Chow et al., 2004a). In addition, OC sampling artifacts could affect PM_{2.5} and PM₁₀ trends, mass closure, visibility degradation assessment (Chow et al., 2002a; Watson, 2002), and estimates of radiative forcing (MacCracken, 2008).



Correspondence to: J. C. Chow
(judith.chow@dri.edu)

Composition of the adsorbed/desorbed material, its exchange between gas and particle phases, the degree to which filters become saturated, and how the sign and amount of artifact differ among filter media and sampling environments have been studied, but these issues are not well understood (Arhami et al., 2006; Arp et al., 2007; Cadle et al., 1983; Chow et al., 1994, 1996, 2002b, 2006, 2008a; Eatough et al., 1989, 2003; Fan et al., 2004; Fitz, 1990; Hart and Pankow, 1994; Kim et al., 2001, 2005; Kirchstetter et al., 2001; Lewtas et al., 2001; Mader and Pankow, 2000, 2001a, b; Matsumoto et al., 2003; McDow and Huntzicker, 1990; Noll and Birch, 2008; Olson and Norris, 2005; Salma et al., 2007; Subramanian et al., 2004; ten Brink et al., 2004; Turpin et al., 1994; Vecchi et al., 2009; Viana et al., 2006; Watson and Chow, 2002; Watson et al., 2009). Several approaches have been used to estimate the OC sampling artifact-including passive field blank (bQF) subtraction, quartz-fiber backup filter (QBQ) adjustment, filter slicing (e.g., examination of artifact distribution homogeneity within quartz-fiber filters), pre-filter organic denuders, and regression intercepts (Watson et al., 2009).

Frank (2006) developed the SANDWICH method to estimate artifact-free OC or OC mass (OCM). This method assumes that all of the unaccounted PM_{2.5} mass measured on a Teflon®-membrane filter (i.e., when weighted sums of elements and ions are subtracted) can be associated with the carbonaceous component. This assumes that Teflon®-membrane filters are inert and their tendency to adsorb organic vapors is low. Teflon®-membrane filters are expected to have a minimal positive OC artifact, although their negative OC artifact might be larger than that of quartz-fiber filters.

In the US, the: 1) Interagency Monitoring of Protected Visual Environments (IMPROVE; Malm et al., 1994) network, 2) Speciation Trends Network (STN; part of the Chemical Speciation Network (CSN); Chu, 2004), and 3) Southeastern Aerosol Research and Characterization study (SEARCH; Hansen et al., 2003) are three long-term PM_{2.5} chemical speciation programs that include OC and EC measurements with different approaches to sampling, analysis, and OC artifact assessment and correction. Of the 181 IMPROVE sites, nearly 94% (170 sites) are located in National Parks and wilderness areas that represent different regions of the US. These sites are far away from population centers and local pollution sources, with a 100–1000 km zone of representation (40 CFR part 50; US EPA 2006a). Regional or non-urban PM_{2.5} sites are affected by naturally occurring aerosol from windblown dust, wildfires, and marine aerosol, as well as by pollution generated in urban and industrial areas that may be more than 1000 km distant. Urban STN/CSN sites represent a mixture of particles from many sources within the urban complex, including, but not dominated by, neighborhood-scale (500 m to 4 km) sources. Urban-scale (4 to 100 km) sites are usually located on city roof-tops of two- to four-story buildings-away from




Fig. 1. Sampling locations for the 181 Interagency Monitoring of Protected Visual Environments (IMPROVE) sites (circles, mostly non-urban), 239 Speciation Trends Network (STN)/Chemical Speciation Network (CSN) sites (triangles, mostly urban), and eight paired Southeastern Aerosol Research and Characterization study (SEARCH) sites (squares, urban vs. non-urban/suburban pairs [Mississippi GLF (urban Gulfport) and OAK (non-urban Oak Grove near Hattiesburg); Alabama BHM (urban north Birmingham) and CTR (non-urban Centreville, south of Tuscaloosa); Georgia JST (urban Jefferson Street in Atlanta) and YRK (non-urban Yorkville, west northwest of Atlanta); and Florida PNS (urban Pensacola) and OLF (suburban outlying field northwest of Pensacola, classified as non-urban)]). The six IMPROVE locations that include quartz-fiber behind quartz-fiber filters (QBQ) are indicated by purple crosses (Mount Rainier National Park, WA [MORA1]; Yosemite National Park, CA [YOSE1]; Hance Camp, Grand Canyon National Park, AZ [HANC1]; Chiricahua National Monument, AZ [CHIR1]; Okefenokee National Wildlife Reserve, GA [OKEF1]; and Shenandoah National Park, WV [SHEN1]). The eight collocated IMPROVE/CSN sites are indicated by red stars (Puget Sound, WA [PUGO1]; Mount Rainier National Park, WA [MORA1]; Fresno, CA [FRES1]; Phoenix, AZ [PHOE1]; Tonto National Monument, AZ [TONT1]; Big Bend National Park [BIBE1]; Dolly Sods Wilderness [DOSO1]; and Washington DC [WASH1]). MORA1 (Mount Rainier, WA), which is included both in the IMPROVE QBQ and the collocated IMPROVE/CSN sites, is indicated in dark green.

highly travelled roads, industries, and residential heating to represent human exposure-typically in an urban area with population >200 000 (US EPA, 1997; Chow et al., 2002c). The SEARCH network was designed to evaluate human exposure at urban versus rural environments in the southeastern US (Mississippi, Alabama, Georgia, and Florida). Figure 1 shows the sampling site locations, and Table 1 summarizes network characteristics relevant to the OC artifact.

IMPROVE artifact corrections using monthly median OC on QBQ (OC_{QBQ}) at six sites (shown in Fig. 1) assume that vapors are adsorbed uniformly throughout the front (QF) and backup (QBQ) filters. This implies that a saturation level is attained. Otherwise, organic vapors would be scavenged preferentially in the upper layers of QF before the gas is transmitted to QBQ. Since a subset of filters is used for blank subtraction, it also is assumed that saturated OC artifact

Table 1. Sampling protocols for carbon in the IMPROVE, STN/CSN, and SEARCH networks from 1 January 2005 to 31 December 2006.

Network ^a	IMPROVE	STN/CSN	CSN	SEARCH
Sampler Type ^b	IMPROVE	Andersen RAAS	R&P 2300	PCM3
Number of channels	4 single-channel modules	4 channels (3 used)	12 single-channel modules (4 used)	3 channels
Carbon denuder	None	None	None	Activated carbon denuder
Inlet type ^c	AHHL cyclone	AHHL cyclone	Harvard Impactor	WINS impactor
Filter holder and types	Polycarbonate cassette	Teflon®-coated holder preceded by a diffuser	Teflon®-coated aluminum holder and Teflon® support screens	Savillex-molded Teflon®
Sampling frequency	3rd day	3rd day	3rd day/6th day	3rd day
Flow rate	22.8 L/min	7.3 L/min	10.0 L/min	16.7 L/min
Filter deposit area	3.53 cm ²	11.76 cm ² d	11.76 cm ² d	7.12 cm ²
Filter face velocity	107.2 cm/s	10.3 cm/s	14.2 cm/s	39.1 cm/s
Sample volume	32.7 m ³	10.5 m ³	14.4 m ³	24 m ³
Quartz-fiber filter: pre-fire temperature and duration	900 °C for 4 h	900 °C for 3 h	900 °C for 3 h	900 °C for 3 h
Quartz filter type	25 mm Pall QF or QBQ	47 mm Whatman ^f QF	47 mm Whatman ^f QF	37 mm Pall Organic carbon denuder/QBQ
Quartz filter pack configuration ^h				
Sites with backup filters (QBQ)	6	0	0	8%
Passive deposition duration	7 days ⁱ	1–15 min ^j	variable ^l	1–15 min
Laboratory blank ^k frequency	2%	2–3%	2–3%	2%
Trip blank ^l frequency	0%	3%	3%	0%
Field blank ^m frequency	2%	10%	10%	10%
Field blank analysis frequency	100%	100%	100%	10% on QF
Backup filter analysis frequency	100%	0	0	10%
Sample shipping method	Second day box with icepack	Priority overnight cooler with icepack	Priority overnight cooler with icepack	Priority overnight cooler with icepack
Temperature for sample storage	4 °C	< -15 °C	< -15 °C	ice < -15 °C 4 °C
Number of sites (2006)	181	18	14	8

^a Networks IMPROVE: Interagency Monitoring of Protected Visual Environments network (Malm et al., 1994)

STN/CSN: Speciation Trends Network/Chemical Speciation Network (Flanagan et al., 2006); starting in May 2007, STN/CSN sites collect ~5% bQF and ~30% QBQ. In 2008, all of the STN/CSN sites (except the Texas Commission on Environmental Quality [TCEQ] non-trends sites) installed MetOne SASS samplers for mass, elements, and ion analyses. As of October 2009, the modified IMPROVE Module C, URG 3000N sampler (URG Corp; Chapel Hill, NC) is placed at all STN/CSN sites using Pallflex® Tissuequartz at a flow rate of 22.8 L/min on 25 mm filters for organic and elemental carbon (OC and EC) following the IMPROVE-A thermal/optical reflectance (TOR) protocol (Chow et al., 2007).

SEARCH: Southeastern Aerosol Research and Characterization study (Hansen et al., 2003); eight sites (Mississippi pair: urban Gulfport [GLF] in Gulfport and non-urban Oak Grove [OAK] near Hattiesburg; Alabama pair: urban Birmingham [BHM] in north Birmingham and non-urban Centreville [CTR], south of Tuscaloosa; Georgia pair: urban Jefferson Street [JST] in Atlanta and non-urban Yorkville [YRK] west northwest of Atlanta; and Florida pair: urban Pensacola [PNS] in Pensacola and suburban outlying field [OLF] northwest of Pensacola).

^b Sampler Descriptions

IMPROVE (new units manufactured by special order from URG, Inc. [Chapel Hill, NC]): Four parallel filter modules, each with up to four sequential sample sets (Eldred et al., 1990). Module A collects PM_{2.5} through an Air and Industrial Hygiene Laboratory (AIHL) cyclone followed by a 25 mm Teflon®-membrane filter analyzed for mass by gravimetry and for elements by X-ray fluorescence (XRF). Module B collects PM_{2.5} through a sodium carbonate denuder (Ashbaugh et al., 2004) followed by an AIHL cyclone and a 37 mm nylon-membrane filter analyzed by ion chromatography (IC) for nitrate (NO₃⁻) and sulfate (SO₄²⁻). Module C collects PM_{2.5} through an AIHL cyclone followed by a 37 mm Pall quartz-fiber filter for OC and EC by the IMPROVE-A thermal/optical reflectance (TOR) protocol. Module D collects through a lowered PM₁₀ inlet at 16.7 L/min followed by a 25 mm Pall Teflon®-membrane filter for mass by gravimetry.

Table 1. Continued.

SASS (Spiral Aerosol Speciation Sampler, Met One, Grants Pass, OR): Spiral centrifugal impaction inlets were originally used on this sampler (thus the name), but excessive re-entrainment from impaction surfaces caused these to be replaced with sharp-cut cyclones (Watson and Chow, 2010). The Super SASS can contain up to eight parallel channels, but the STN/CSN configuration uses three channels of a five channel version, each channel containing one 47 mm filter with a 6.7 L/min flow rate. For STN/CSN, Channel 1 contains a Whatman Teflon®-membrane filter for mass by gravimetry and elements by XRF; Channel 2 can be used for a field blank; (Channel 3 includes a magnesium oxide-coated aluminum (Al) honeycomb after the cyclone followed by a Nylasorb nylon-membrane filter for water-soluble anions i.e., NO₃⁻ and SO₄⁼) and cations (i.e., ammonium [NH₄⁺] and water-soluble sodium [Na⁺] and potassium [K⁺]) by IC; Channel 4 contains a Whatman QMA quartz-fiber filter for OC and EC by the STN thermal/optical transmittance (TOT) protocol (Peterson and Richards, 2002); Channel 5 is available for field blanks or special study samples.

RAAS (Reference Ambient Air Sampler, Andersen [now Thermo Scientific] Model 25-400; Franklin, MA, no longer manufactured; Watson and Chow, 2002): Contains four parallel channels with two 2.5 µm AIHL cyclones; all filters are 47 mm in diameter. In the STN/CSN configuration, only three channels are used: Channel 1 contains a Whatman QMA quartz-fiber filter at 7.3 L/min for OC and EC by the STN TOT protocol; Channel 2 contains a Whatman Teflon®-membrane filter at 16.7 L/min for mass by gravimetry and elements by XRF; Channel 3 is empty, but can be used for replicates or blanks at a flow of 16.7 L/min; Channel 4 contains a magnesium oxide-coated denuder followed by a Whatman Nylasorb nylon-membrane filter at a flow rate of 7.3 L/min for total NO₃⁻ by IC.

URG MASS (URG, Chapel Hill, NC): Uses two parallel modules with 47 mm filters operating at 16.7 L/min. Module 1 includes a louvered PM₁₀ inlet followed by a PM_{2.5} WINS impactor, a magnesium oxide-coated denuder, and a stacked filter pack with a Whatman Teflon®-membrane filter on top for mass by gravimetry and elements by XRF and a Nylasorb nylon-membrane backup filter for anions and cations by IC. Module 2 contains a louvered PM₁₀ inlet followed by a WINS PM_{2.5} impactor, which includes a Whatman QMA quartz-fiber filter for OC and EC by the STN TOT protocol.

R&P 2300 (Rupprecht & Patashnick [now Thermo Scientific] Model 2300; Franklin, MA): Twelve modules are available that can be programmed to be operated in parallel or sequentially. The non-trends CSN sites in Texas use four parallel channels with 47 mm diameter filters. Module 1 contains a Whatman Teflon®-membrane filter with 16.7 L/min for mass by gravimetry and elements by XRF; Module 2 contains an additional Teflon®-membrane filter for anion and cation analyses by IC; Module 3 contains a quartz-fiber filter, with an optional quartz-fiber backup filter, at 10 L/min for OC and EC by the IMPROVE_A TOR protocol; Module 4 contains a sodium carbonate-coated honeycomb denuder followed by a Nylasorb nylon 10 L/min for total NO₃⁻ by IC.

R&P Partisol Plus 2025 Sequential Federal Reference Method (FRM; Rupprecht & Patashnick [now Thermo Scientific] Model 2025; Franklin, MA): Contains two parallel modules operated in a sequential mode using 47 mm diameter filters at 16.7 L/min. Filters are stored in a 16 cassette magazine. Both modules are preceded by a louvered PM₁₀ inlet followed by a sharp cut cyclone PM_{2.5} inlet. Module 1 contains a Pall Teflon®-membrane filter for mass by gravimetry, elements by XRF, and cations and anions by IC. Module 2 contains a quartz-fiber filter for OC and EC by the IMPROVE_A TOR protocol (Chow et al., 2007).

PCM3 (Particle Composition Monitor, Aerosol Research Associates, Plano, TX; Edgerton et al., 2005): Uses three parallel channels operated at 16.7 L/min with a URG PM₁₀ cyclone followed by a PM_{2.5} WINS impactor. Solenoid valves behind the filter packs allow up to four sample sets to be acquired sequentially. Channel 1 contains sodium carbonate-coated annular denuder followed by a citric acid-coated annular denuder, then followed by a three-stage filter packs in: a 47 mm Teflon®-membrane filter for mass by gravimetry and elements by XRF, followed by a 47 mm Nylasorb Nylon-membrane filter for volatilized NO₃⁻ by IC, followed by a 47 mm citric acid-impregnated filter for volatilized NH₄⁺ by automated colorimetry (AC). Channel 2 contains a sodium carbonate-coated annular denuder followed by a citric acid-coated annular denuder and a 47 mm Nylasorb nylon-membrane filter for total NH₄⁺ and total NO₃⁻ by AC and IC, respectively. Channel 3 samples through a URG PM₁₀ cyclone, followed by an activated carbon honeycomb denuder to remove carbon vapors, then through a WINS PM_{2.5} impactor onto a 37 mm Pall quartz-fiber filter followed by a backup quartz-fiber filter for OC and EC by the IMPROVE_A TOR protocol (Chow et al., 2007).

^c All inlets are made of anodized aluminum.

^d RTI uses 11.76 cm² for quartz-fiber filters and 11.70 cm² exposed area for Teflon®-membrane filters for the STN/CSN sites.

^e DRI uses 11.78 cm² for quartz-fiber and Teflon®-membrane exposed area for Texas non-trends CSN sites.

^f Whatman QMA filters were switched to Pallflex® Tissuquartz (Ann Arbor, MI) quartz-fiber filters as of May 2007 for the STN/CSN sites.

^g Field blank is kept in the inlet and outlet of the 16 filter cassette magazines for as long as 5–7 days depending on the sampling frequency but is in sampling position (without air being drawn through it) for only a few seconds.

^h QF = quartz-fiber front filter only, QBQ = quartz-fiber behind quartz-fiber filter, with the backup quartz-fiber used to estimate adsorbed organic vapors.

ⁱ Field blanks (bQF) usually in samplers for 1–15 min, but in some cases for as long as 5–7 days.

^j Based on the assumption of once per week site visits.

^k Laboratory blanks are selected from each batch of 100 unexposed filters and submitted for acceptance testing.

^l Trip blanks (tbQF) accompany batches of shipped filters but are not removed from their storage containers.

^m Field blanks accompany batches of shipped filters, but are removed from storage containers and left exposed to passive sampling. Only the IMPROVE network exposes field blanks for the same length of times as the sampled filters.

values are invariant with respect to the filter batch, sampled environment, passive/active deposition, and sampling period. Kirchstetter et al. (2001) suggested that each filter may have a different capacity for organic vapor adsorption. The slicing method applied by Watson et al., (2009) further showed that adsorbed OC is neither uniformly distributed throughout the filter depth, nor does the adsorbed OC on the backup filter always equal that on the front filter. However, the number of samples examined was too small to draw broad generalizations.

Urban environments, where most of the STN/CSN sites are located, contain volatile organic compounds (VOCs) and semi-volatile organic compounds (SVOCs) adsorbable to quartz-fiber filters. SVOCs in fresh emission plumes gradually come into equilibrium as the plumes age. Oxidation of low-volatility hydrocarbons has been suggested to be a main pathway for secondary organic aerosol (SOA) formation (Robinson et al., 2007). By the time urban plumes transport to rural and remote atmospheres (e.g., most IMPROVE sites), many SVOCs could have been scavenged or converted to more stable PM compounds (Yu et al., 2004; Lane et al., 2008). Average OC_{QBQ} measurements in the IMPROVE network were ~19% higher than OC on bQF (OC_{bQF}) levels, but this difference is within the standard deviation of the average (Watson et al., 2009). The fact that levels of OC_{QBQ} and OC_{bQF} are similar reflects relatively low SVOC concentrations at most of the IMPROVE regional-background environments. In contrast, Watson et al. (2009) showed that OC_{QBQ} from an urban site (Fort Meade, MD) contained twice the levels of OC_{bQF}.

This study examines the methods and results of OC artifact assessment in these networks by: 1) documenting procedures to acquire blank and backup filters; 2) comparing laboratory blank, bQF, trip blank (tbQF), and QBQ filter OC levels for the period from 1 January 2005 to 31 December 2006; and 3) assessing blank OC levels from eight collocated IMPROVE and STN/CSN sites using the SANDWICH method (Frank, 2006). These results should be of interest to those using data from these and similar networks for various data analysis purposes.

Three hypotheses are tested using data from the three networks:

H1: The OC sampling artifact represented by bQF or QBQ depends on sampling protocol and differs among ambient networks.

H2: Sampling artifact and SVOC content are lower at non-urban (rural and remote) sites than urban sites due to aerosol aging.

H3: Artifact-free OC concentrations can be better estimated by the SANDWICH method (Frank, 2006) than by direct OC measurements.

2 Methods

As shown in Table 1, seven different filter samplers are used among the three networks with flow rates ranging from 6.7 to 22.8 liters per minute (L/min). The largest variability is in STN/CSN, which uses five types of samplers, varying from single channel (e.g., URG MASS [Chapel Hill, NC] and Rupprecht & Patashnick [R&P; now Thermo Scientific] Partisol-Plus Model 2025 Sequential Federal Reference Method [FRM] sampler [Franklin, MA]) to five parallel channels [e.g., MetOne Spiral Aerosol Speciation Sampler; SASS; Grants Pass, OR]). STN sites were originally required to use one of three samplers (i.e., MetOne SASS, Andersen RAAS, or URG MASS). In 2005, about 75% of the STN/CSN sites used 6.7 L/min MetOne SASS samplers. The Texas Commission on Environmental Quality (TCEQ) uses the R&P 2025 to collect PM_{2.5} at non-trends CSN sites.

The IMPROVE and SEARCH networks use 25 mm and 37 mm diameter Pallflex® Tissuquartz (Ann Arbor, MI) quartz-fiber filters, respectively, while STN/CSN used 47 mm Whatman QMA filters (Clifton, NJ), which contain a 5% borosilicate binder. Deposit areas range from 3.53 cm² (IMPROVE) to 11.78 cm² (R&P 2025) and face velocities range from 9.5 cm/s (MetOne) to 107.2 cm/s (IMPROVE). The different filter holder configurations (e.g., single/tandem filter packs vs. magazine [R&P 2025, with a stack of 16 filter cassettes]) and materials (e.g., polycarbonate, aluminum, or Teflon®-coated) also might affect the magnitude of the OC artifact (Watson and Chow, 2009).

Prior to sampling, quartz-fiber filters are treated at 900 °C for three to four hours and acceptance tested. After this treatment, average blank levels are 0.15±0.15 µg OC or total carbon (TC=OC+EC)/cm² and 0±0.02 µg EC/cm² for Pallflex® quartz-fiber filters, and 0.10±0.10 µg OC/cm² and 0±0.01 µg EC/cm² for Whatman QMA quartz-fiber filters. Approximately 2–3% of laboratory blanks are maintained for each network. Acceptance criteria are <2.0, 1.5, and 0.5 µg/cm² for TC, OC, and EC, respectively, in the IMPROVE and SEARCH networks, and <1 µg/cm² for TC in STN/CSN.

STN/CSN collects 3% trip blanks, which are loaded into filter holders and accompany the sampled filters to and from each sampling site. Trip blanks are intended to assess contamination during shipping and are not installed in the sampler or exposed to ambient air.

Field blanks (e.g., dynamic blanks) accompany sample shipments and are placed in the sampler along with the sampled filters (Chow and Richards, 1990). The only difference between samples and bQF is that air is not drawn through bQF. The bQF fraction of total sample number varies by tenfold among the networks: ~2% of sample filters for IMPROVE, ~10% for STN/CSN sites and SEARCH, and ~10–25% for R&P 2025 sites in Texas. The passive period for bQF has been 1–15 min for STN/CSN and SEARCH, and ~7 days for IMPROVE and R&P 2025 sites in Texas sites.

Since the bQF fraction of all samples is only 2–10% of the total number of samples, average OC_{bQF} concentrations are used to correct sampled values with the standard deviation of the average representing the blank precision. Outliers are identified (i.e., values >3 or 4 times the standard deviation). The small number of outliers likely results from inadvertent contamination during filter shipping/receiving or sample loading/unloading and are excluded from the averages and standard deviations.

QBQs are obtained from six IMPROVE and all eight of the SEARCH sites (Watson et al., 2009). Both networks collect QBQ every third day with the exception of daily sampling at two SEARCH sites (i.e., Jefferson Street, Atlanta, GA and Birmingham, AL; see Fig. 1). Ten percent of SEARCH QBQ are randomly selected for analysis. Without preceding organic denuders, the IMPROVE OC_{QBQ} represents a combination of positive and negative OC artifacts. SEARCH corrects the organic sampling artifact by calculating the quarterly mean concentrations for the QBQ and bQF and attributing them to negative and positive artifacts, respectively. OC_{bQF} is multiplied by two to account for passive adsorption on both QF and QBQ. Thus,

$$\text{OC}_{\text{artifactcorrected}} = \text{OC}_{\text{QF}} + \text{OC}_{\text{QBQ}} - 2\text{OC}_{\text{bQF}} \quad (1)$$

where:

OC_{QF} = Quartz-fiber front filter OC

OC_{QBQ} = Quartz-fiber behind quartz-fiber filter OC

OC_{bQF} = field blank OC from the quartz-fiber front filter

To compare carbon measurements between the IMPROVE network and STN/CSN, collocated PM_{2.5} data were acquired from three urban vs. non-urban paired sites (see Fig. 1; Seattle and Mt. Rainier, WA; Phoenix and Tonto National Monument, AZ; and Washington, DC and Dolly Sods Wilderness, WV; Solomon et al., 2004). In addition, collocated measurements are available from the urban Fresno, CA (Watson et al., 2000) and the non-urban Big Bend, TX (Chow et al., 2004b) sites. As indicated in Table 2, four types of STN/CSN samplers were collocated with the IMPROVE samplers. The IMPROVE-STN/CSN data pairs from 2001 to 2006 with complete mass, elements, ions (i.e., a minimum of nitrate [NO₃⁻] and sulfate [SO₄⁼]) and carbon measurements are included. Prior to May 2007, the STN/CSN used a customized thermal/optical transmittance (STN TOT) carbon analysis protocol (Peterson and Richards, 2002) while the IMPROVE_A and SEARCH networks followed the IMPROVE thermal/optical reflectance (TOR) protocol (Chow et al., 1993, 2001, 2004a, 2005, 2007). Since blank and backup filter EC levels are expected to be negligible, the analysis protocols should return equivalent OC and TC results. As noted in the footnote to Table 1, a new STN/CSN carbon sampling and analysis protocol was fully implemented in October 2009 to be consistent with the IMPROVE network.

3 Results

3.1 Blank and backup filter levels

Table 3 compares average bQF levels for TC, OC, and EC in terms of areal density (µg/cm²) and ambient concentration equivalents (µg/m³), based on exposed filter areas and 24 h sample volumes for each instrument, respectively. EC values are at or near minimum detection limits (i.e., 0.06 µg/cm²), accounting for 0 to 5% of TC, indicating that passive PM deposition is negligible. As a result, TC and OC are not statistically different and will be used interchangeably. Average bQF levels for individual sampling sites and the number of bQF acquired for IMPROVE and STN/CSN are available as supplemental information (Tables S1–S4, <http://www.atmos-chem-phys.net/10/5223/2010/acp-10-5223-2010-supplement.pdf>) and in more detailed reports (Chow et al., 2008b; Watson et al., 2008). OC_{bQF} at some sampling locations statistically differ from the network mean, although the small number of bQF at some sites may not represent the true distribution of OC_{bQF} levels during the two-year sampling period.

IMPROVE bQF TC (i.e., TC_{bQF}) areal density levels (2.41±0.48 µg/cm²) are 2.5 to 3 times those of the other networks (i.e., 0.97±0.27 µg/cm² for STN/CSN and 0.81±0.61 µg/cm² for SEARCH). This probably results from the 7-day IMPROVE passive exposure period that better represents exposure of the sample filter than the 1–15 min bQF exposure experienced by STN/CSN and SEARCH. Earlier studies in urban Los Angeles, California, and Pittsburgh, Pennsylvania, suggested a minimum exposure time for VOC passive adsorption of several hours (Subramanian et al., 2004; Turpin et al., 1994). Ambient-equivalent TC_{bQF} concentrations, however, are four times higher for STN/CSN (1.03±0.21 µg/m³) than for IMPROVE (0.26±0.05 µg/m³) and SEARCH (0.24±0.18 µg/m³) samples. This is attributed to the lower flow rate (e.g., 6.7 L/min for MetOne SASS, compared to 22.8 L/min for IMPROVE and 16.7 L/min for SEARCH) and larger exposed area of the filter deposit (11.76 cm² for SASS, compared to 3.53 cm² for IMPROVE and 7.12 cm² for SEARCH).

Figure 2 shows that most of the site average OC_{bQF} areal densities are 2–2.5 µg/cm² for IMPROVE, 0.5–1 µg/cm² for STN/CSN, and <0.5 µg/cm² for SEARCH. For STN/CSN, average OC_{bQF} varies more than twofold among sampler types, from 0.74±0.66 µg/cm² (URG MASS) to 1.49±0.8 µg/cm² (R&P 2025). Table 3 shows that the two R&P samplers (R&P 2300 and R&P 2025) reported the highest OC_{bQF} (1.3–1.5 µg/cm²). The greased inlet impaction plate and variable passive exposure periods (e.g., minutes to 7 days) for the R&P 2300 may affect OC_{bQF} levels. Detailed records of bQF exposure periods are not available.

There were 3628 bQF and 2335 tbQF acquired in STN/CSN during 2005 and 2006. Average areal

Table 2. Collocated IMPROVE and STN/CSN PM_{2.5} speciation data from 16 October 2001 to 31 December 2006.

Type	Site Name	Inclusive Period	Number of Samples	IMPROVE ^a			STN ^a Sampler Type			
				Module C Sampler	# of Field Blanks	MetOne SASS	Anderson RAAS	URG MASS	R&P 2025	# of Field Blanks
Special Study	Puget Sound (PUSO), Seattle (Beacon Hill), WA	16/10/2001–29/12/2003	224	X	8				X	25
	Mount Rainier NP (MORA), WA	16/10/2001–01/11/2002	69	X	6				X	12
	Phoenix (PHOE), AZ	16/10/2001–29/12/2003	201	X	6	X				26
	Tonto National Monument (TONT), AZ	16/10/2001–29/12/2003	181	X	8	X				28
	Washington DC (WASH)	16/10/2001–29/12/2003	206	X	5		X			25
	Dolly Sods Wilderness (DOSO), WA	16/10/2001–29/12/2003	140	X	5		X			26
	Total			1021		38				
Long-term Sites	Fresno (FRES), CA	01/01/2005–31/12/2006	227 ^b	X	7		X			18
	Big Bend NP (BIBE), TX	01/01/2005–31/12/2006	81 ^b	X	7				X ^c	15
	Total		308		14					33

^a See Table 1 for sampler specifications. ^b For carbon analysis alone, the completed 2005 and 2006 data would provide 308 sample pairs and 47 field blanks. ^c Big Bend NP (BIBE) is a CSN site.

Table 3. Comparison of average field blank (bQF), trip blank (tbQF), and backup (QBQ) filter carbon levels (\pm standard deviation) among the IMPROVE, STN/CSN, and SEARCH networks for the period from 1 January 2005 to 31 December 2006.

Network	Filter Type	Type of PM _{2.5} Speciation Sampler	Site Count	No. of Field Blanks	TC	OC	EC	TC	OC	EC
IMPROVE ^c	bQF	IMPROVE Module C	181	886	2.41 \pm 0.48	2.37 \pm 0.45	0.04 \pm 0.05	0.26 \pm 0.05	0.26 \pm 0.05	0 \pm 0.01
	QBQ	IMPROVE Module C	6	1401	3.23 \pm 0.96	3.08 \pm 0.83	0.16 \pm 0.13	0.35 \pm 0.1	0.33 \pm 0.09	0.02 \pm 0.01
STN/CSN ^c	bQF	All Samples	239 ^a	3628	0.97 \pm 0.27	0.95 \pm 0.25	0.02 \pm 0.03	1.03 \pm 0.21	1.01 \pm 0.21	0.01 \pm 0.02
		Andersen RAAS	22	249	0.88 \pm 0.33	0.88 \pm 0.33	0.01 \pm 0.03	0.99 \pm 0.38	0.98 \pm 0.37	0.01 \pm 0.03
		MetOne SASS	185	2,572	0.86 \pm 0.39	0.85 \pm 0.38	0.01 \pm 0.05	1.05 \pm 0.47	1.04 \pm 0.47	0.01 \pm 0.06
		URG MASS	7	150	0.75 \pm 0.66	0.74 \pm 0.66	0 \pm 0.02	0.37 \pm 0.32	0.36 \pm 0.32	0 \pm 0.01
		R&P 2300 Sequential Speciation	15	236	1.33 \pm 0.52	1.3 \pm 0.51	0.03 \pm 0.11	1.09 \pm 0.42	1.06 \pm 0.41	0.02 \pm 0.09
		R&P 2025 Sequential	24	421	1.57 \pm 0.77	1.49 \pm 0.76	0.08 \pm 0.12	0.78 \pm 0.38	0.73 \pm 0.37	0.04 \pm 0.06
		FRM								
	tbQF	All Samples	239 ^a	2335	0.98 \pm 0.26	0.95 \pm 0.23	0.02 \pm 0.03	0.89 \pm 0.33	0.87 \pm 0.32	0.02 \pm 0.02
		Andersen RAAS	22	241	0.84 \pm 0.38	0.83 \pm 0.34	0.01 \pm 0.05	0.94 \pm 0.42	0.93 \pm 0.38	0.01 \pm 0.05
		MetOne SASS	185	1832	0.89 \pm 0.45	0.88 \pm 0.45	0.01 \pm 0.03	1.09 \pm 0.56	1.08 \pm 0.55	0.01 \pm 0.04
SEARCH ^c	bQF	PCM3	8	144	0.81 \pm 0.61	0.76 \pm 0.57	0.04 \pm 0.06	0.24 \pm 0.18	0.23 \pm 0.17	0.01 \pm 0.02
		QBQ	8	257	1.29 \pm 0.52	1.19 \pm 0.52	0.1 \pm 0.06	0.38 \pm 0.15	0.35 \pm 0.15	0.03 \pm 0.02
		FRM								

^a 253 if counting 14 sites where sampler type changed between 1 January 2005 and 31 December 2006; ^b Data is not available. ^c Carbon analysis follows the IMPROVE_A thermal/optical reflectance (TOR) protocol (Chow et al., 2007) for the IMPROVE and SEARCH network and the STN thermal/optical transmittance (TOT) protocol (Chu et al., 2004; Peterson and Richards, 2002) for STN/CSN. ^d Areal density on filters in $\mu\text{g}/\text{cm}^2$ is based on sample loading divided by the exposed area (e.g., 3.53 cm^2 for IMPROVE samplers, 11.76 cm^2 for STN/CSN speciation samplers, except 11.78 cm^2 for R&P 2300 and R&P 2025 samplers, and 7.12 cm^2 for SEARCH PCM3 samplers as noted in Table 1). ^e Equivalent ambient concentration in $\mu\text{g}/\text{m}^3$ is based on the sample loading divided by the nominal sampler volume (varies from 9.6 m^3 for MetOne SASS to 32.7 m^3 for the IMPROVE sampler as noted in Table 1).

densities are the same: 0.95 \pm 0.25 $\mu\text{g}/\text{cm}^2$ for OC_{bQF} and 0.95 \pm 0.23 $\mu\text{g}/\text{cm}^2$ for OC_{tbQF}. OC_{bQF} and OC_{tbQF} areal densities are also similar for a given sampler type, agreeing within \pm 0.05 $\mu\text{g}/\text{cm}^2$ (Table 3). Trip blanks (tbQF) are not exposed to ambient air and are expected to have lower

concentrations. The similarity of the STN/CSN OC_{bQF} and OC_{tbQF} and the SEARCH OC_{bQF} support hypothesis (H1) that the short bQF exposure period (1–15 min) is insufficient to represent the passively adsorbed VOCs experienced by the sample filters.




Fig. 2. Field blank organic carbon (OC_{bQF}) concentration density ($\mu\text{g}/\text{cm}^2$) for: (a) 181 IMPROVE sites, (b) 239 STN/CSN sites, and (c) eight SEARCH sites for the period from 1 January 2005 to 31 December 2006 (each bar represents the concentration sector less than or equal to the assigned value).

Average OC_{QBQ} areal density is $3.1 \pm 0.8 \mu\text{g}/\text{cm}^2$ for IMPROVE and $1.2 \pm 0.5 \mu\text{g}/\text{cm}^2$ for SEARCH, 30 and 60% higher than the corresponding OC_{bQF} reported in Table 3, respectively. With the denuded SEARCH PCM3 sampler, average OC_{QBQ} is $0.43 \pm 0.97 \mu\text{g}/\text{cm}^2$ higher than OC_{bQF} . While OC_{QBQ} is intended to quantify negative OC artifacts that should be added to OC_{QF} (see Eq. 1), it also could be interpreted as a better representation of actual bQF levels, since QBQ spends more passive exposure time in the sampler than bQF.

Average ambient-equivalent OC_{QBQ} concentrations are similar: $0.33 \pm 0.09 \mu\text{g}/\text{m}^3$ for IMPROVE and $0.35 \pm 0.15 \mu\text{g}/\text{m}^3$ for SEARCH. These levels are 30–50% higher than OC_{bQF} of 0.26 ± 0.05 and $0.23 \pm 0.17 \mu\text{g}/\text{m}^3$ for IMPROVE and SEARCH, respectively, but $\sim 65\%$ lower than OC_{bQF} of $1.01 \pm 0.21 \mu\text{g}/\text{m}^3$ (for all sampler types) found in the STN/CSN sites.

Figure 3 shows that OC_{bQF} seasonal variations are most apparent for the IMPROVE network, varying by more than 40% from winter ($1.97 \pm 0.61 \mu\text{g}/\text{cm}^2$) to summer ($2.92 \pm 0.78 \mu\text{g}/\text{cm}^2$). There are no apparent changes in fractional contributions of the IMPROVE thermal carbon fractions among the four seasons. Seasonal variations of OC_{QBQ} fractions (Fig. 3b) follow the same pattern as those of the IMPROVE field blanks with a summer high and winter low. Short passive exposure times at STN/CSN and SEARCH sites resulted in little to no seasonal variability: OC_{bQF} spans 0.8–1.1 $\mu\text{g}/\text{cm}^2$ and 0.52–1.0 $\mu\text{g}/\text{cm}^2$, respectively.

Figure 4 shows little difference between urban and non-urban IMPROVE OC_{bQF} , but SEARCH OC_{bQF} is 17% higher at non-urban compared to urban sites. Average OC_{QBQ} for the SEARCH samples was $\sim 28\%$ higher at the urban ($1.51 \pm 1.50 \mu\text{g}/\text{cm}^2$) compared to non-urban ($1.18 \pm 0.98 \mu\text{g}/\text{cm}^2$) sites (Fig. 5). The urban increment for OC_{QBQ} is mostly in the OC1 fraction, which is 2.4 times higher at urban than at non-urban sites (0.51 ± 0.84 vs. $0.21 \pm 0.35 \mu\text{g}/\text{cm}^2$). OC2 is $\sim 11\%$ higher (0.42 ± 0.37 vs. $0.38 \pm 0.48 \mu\text{g}/\text{cm}^2$) at the urban sites, while the other thermal fraction levels are similar. These results are consistent with hypothesis H2, indicating more SVOC adsorption at the urban sites. Average OC_{QBQ} levels from the six non-urban IMPROVE sites ($3.1 \pm 0.8 \mu\text{g}/\text{cm}^2$) are 2.6 times higher than OC_{QBQ} from the four non-urban SEARCH sites ($1.18 \pm 0.98 \mu\text{g}/\text{cm}^2$), consistent with the denuder removing adsorbable organic vapors.

Blank TC areal densities in Fig. 6 show that STN/CSN $tbQF$ TC (i.e., TC_{tbQF}) areal densities are similar for urban and non-urban sites, but they differ among samplers, consistent with two-year average $tbQF$ levels in Table 3. Using the URG MASS sampler, Table 4 shows TC_{tbQF} areal densities at the Seattle and Mount Rainier sites are 0.53 ± 0.19 and $0.67 \pm 0.12 \mu\text{g}/\text{cm}^2$, respectively, lower than the 0.84 – $1.12 \mu\text{g}/\text{cm}^2$ found at sites using the Andersen RAAS or MetOne SASS samplers. TC_{bQF} and TC_{tbQF} levels




Fig. 3. Seasonal variations of blanks among: (a) IMPROVE field blanks (OC_{bQF}), (b) IMPROVE backup filters (OC_{QBQ}; six sites), (c) STN/CSN field blanks (OC_{bQF}), (d) STN/CSN trip blanks (OC_{tbQF}), (e) SEARCH denuded field blanks (OC_{dbQF}), and (f) SEARCH denuded backup filters (OC_{dQBQ}; eight sites). IMPROVE.A protocol thermal carbon fractions are defined as OC1 (140 °C), OC2 (280 °C), OC3 (480 °C), and OC4 (580 °C) in 100% helium (He); and EC1 (580 °C), EC2 (740 °C), and EC3 (840 °C) in 98% He/2% oxygen (O₂), and charring/pyrolysis carbon (OP; carbon evolved when reflectance returns to its initial value); OC = OC1 + OC2 + OC3 + OC4 + OP. EC levels (EC1 + EC2 + EC3 – OP) were negligible for blank and backup filters and are not plotted.

Table 4. Average blank TC concentrations for the eight collocated IMPROVE–STN/CSN sites.

Site Code	Site Name	Instrument Used	Number of Pairs		Field Blank TC Areal Density				
			IMPROVE-STN QF (number)	IMP_bQF ^a (µg/cm ²)	IMP_bQF ^a (number)	STN_bQF ^b (µg/cm ²)	STN_bQF ^b (number)	STN_tbQF ^b (µg/cm ²)	STN_tbQF ^b (number)
PUSO	Seattle, WA	URG MASS	224	2.66 ± 0.54	8	0.68 ± 0.41	25	0.53 ± 0.19	9
MORA	Mount Rainier, WA	URG MASS	69	1.44 ± 0.36	6	0.66 ± 0.42	12	0.67 ± 0.12	4
PHOE	Phoenix, AZ	MetOne SASS	201	2.63 ± 0.58	6	1.40 ± 0.77	26	1.12 ± 0.50	10
TONT	Tonto Monument, AZ	MetOne SASS	181	2.00 ± 1.05	8	0.87 ± 0.31	28	0.86 ± 0.32	9
WASH	Washington DC	Andersen RAAS	206	2.49 ± 0.87	5	0.87 ± 0.40	25	0.84 ± 0.26	10
DOSO	Dolly Sods, WV	Andersen RAAS	140	2.57 ± 0.31	5	1.18 ± 0.68	26	0.97 ± 0.38	8
FRES	Fresno, CA	MetOne SASS	227	2.58 ± 0.50	7	0.74 ± 0.23	18	0.94 ± 0.48	11
BIBE	Big Bend National Park, TX	R&P 2025 Sequential FRM	81	2.40 ± 0.68	7	1.44 ± 0.48	15	N/A ± N/A	N/A

^a Carbon analysis follows the IMPROVE.A thermal/optical reflectance (TOR) protocol (Chow et al., 2007a) for the IMPROVE network. bQF is quartz-fiber filter field blank.

^b Carbon analysis follows the STN thermal/optical transmittance (TOT) protocol (Chu et al., 2004) for STN/CSN. tbQF is quartz-fiber filter trip blank.




Fig. 4. Comparison of field blank (bQF) carbon fraction concentrations between the urban and non-urban sites among the IMPROVE, STN/CSN, and SEARCH networks for the period from 1 January 2005 to 31 December 2006. There are 11 urban and 170 non-urban IMPROVE sites, 239 STN/CSN urban sites, and four urban and four non-urban SEARCH sites. The urban IMPROVE sites are Atlanta, GA (ATLA1); Baltimore, MD (BALT1); Birmingham, AL (BIRM1); Chicago, IL (CHIC1); Detroit, MI (DETR1); Fresno, CA (FRES1); Houston, TX (HOUS1); New York, NY (NEYO1); Phoenix, AZ (PHOE1); Pittsburgh (PITT1); Washington DC (WASH1) [<http://vista.cira.colostate.edu/improve/>].




Fig. 5. Comparison of quartz-fiber backup filter (QBQ) carbon fractions between urban and non-urban sites in the IMPROVE and SEARCH networks for the period from 1 January 2005 to 31 December 2006. Carbon fractions follow the IMPROVE.A thermal/optical reflectance (TOR) protocol (Chow et al., 2007).

are similar, with a few bQF levels higher than those of tbQF. These blanks were not always acquired together.

IMPROVE TC_{bQF} areal densities are 2–3 times higher than those of STN/CSN TC_{bQF} or TC_{tbQF}. In addition to variations in passive exposure time, IMPROVE uses the




Fig. 6. Time series of IMPROVE and STN/CSN blank TC concentrations at eight collocated sites from 1 January 2005 to 31 December 2006 (IMP_bQF: IMPROVE field blanks; STN_bQF: STN/CSN field blanks; STN_tbQF: STN/CSN trip blanks).

Pallflex® Tissuquartz while STN/CSN used QMA quartz-fiber filters prior to 2007, and these filters may differ in: 1) capacity and affinity for VOC and gaseous SVOC adsorption and desorption, and 2) the rate to reach saturation or equilibrium between gaseous SVOC and particulate OC. The effects of these differences cannot be determined from available data.

For the collocated IMPROVE vs. STN/CSN comparison at the eight sites, IMPROVE TC_{bQF} is most consistent among the four urban sites (Seattle, Phoenix, Washington DC, and Fresno), ranging from 2.5–2.7 µg/cm², with lower areal densities measured at two non-urban sites: Mount Rainier National Park (1.4±0.4 µg/cm²) and Tonto National

Monument ($2.0 \pm 1.1 \mu\text{g}/\text{cm}^2$). Collocated STN/CSN TC_{bQF} are 40–75% lower than IMPROVE, with larger variability, ranging from 0.66 ± 0.42 (Mount Rainier using URG MASS) to $1.44 \pm 0.48 \mu\text{g}/\text{cm}^2$ (Big Bend using R&P 2025). This is consistent with hypothesis H1 that longer passive deposition periods result in higher field blank levels. The number of blanks is insufficient to evaluate seasonal variability for individual sites.

Site-averaged non-blank corrected ambient TC concentrations ($\mu\text{g}/\text{m}^3$) at each collocated IMPROVE and STN/CSN site are within ± 30 –50% of each other. STN/CSN site-averaged TC areal densities ($\mu\text{g}/\text{cm}^2$) are 9–20% of those for collocated IMPROVE samples. TC_{bQF} to TC_{QF} ratios are larger for non-urban than urban sites due to the lower ambient TC_{QF} levels. For example, the average TC_{bQF} reaches $\sim 49\%$ of TC_{QF} at the Dolly Sods site for the STN/CSN sampler, but it is only 12% for the collocated IMPROVE sampler. The actual difference could be larger if STN/CSN underestimates OC_{bQF} adsorption due to the short passive exposure period.

3.2 Regression method

A regression method similar to that of White and Macias (1989) is used to evaluate the relative sampling artifact among collocated samples. If the collocated IMPROVE and STN/CSN samples measure the same TC, a linear regression of collocated data pairs should yield a slope of 1.0, an intercept of 0, and a correlation of 1.0, within experimental precision. A statistically significant positive or negative intercept at $\text{TC}=0$ can be interpreted as the difference in organic sampling artifacts. A robust perpendicular least squares regression method (Dutter and Huber, 1981) is used to avoid biases caused by a few outliers and to account for the presence of errors in both variables. Using Phoenix data as an example, Fig. 7 shows a positive STN/CSN TC sampling artifact of $1.65 \mu\text{g}/\text{m}^3$ or $1.34 \mu\text{g}/\text{cm}^2$ (using MetOne SASS sampling volume and deposit area) relative to the IMPROVE sampler. Reversing the independent and dependent variables in Fig. 7 does not change the conclusion when using a robust regression.

Figure 8 shows that the regression intercepts are positive for each season at the eight sites, consistent with lower flow rates for the STN/CSN samples. For five of the eight sites, the intercept is largest during summer, ranging from 0.22 – $2.03 \mu\text{g}/\text{m}^3$. It is highest during spring at the Mount Rainier and Tonto sites, and highest during fall at the Fresno site. The intercepts in Table 5 represent the average of four seasons. The largest two intercepts are found at the Phoenix ($1.34 \mu\text{g}/\text{cm}^2$) and Big Bend ($1.29 \mu\text{g}/\text{cm}^2$) sites using the MetOne SASS and R&P 2025 samplers, respectively, while the lowest two are found at the Seattle ($0.24 \mu\text{g}/\text{cm}^2$) and Mount Rainier ($0.50 \mu\text{g}/\text{cm}^2$) sites using the URG MASS samplers.

Based on the sample volume/deposit area for each sampler type (Table 1), the relationship between IMPROVE




Fig. 7. Linear regression of uncorrected STN/CSN TC vs. IMPROVE TC acquired from the Phoenix, AZ site (PHOE1). The non-zero intercept indicates sampling artifacts between STN/CSN and the IMPROVE network.




Fig. 8. The uncorrected STN–IMPROVE TC regression intercept for the entire data set and seasonally-segregated data from the eight collocated sites. Site names are PUSO1 (Seattle, WA); MORA1 (Mount Rainier, WA); PHOE1 (Phoenix, AZ); TONT1 (Tonto National Monument, AZ); WASH1 (Washington DC); DOSO1 (Dolly Sods Wilderness, WV); FRES1 (Fresno, CA); and BIBE1 (Big Bend National Park, TX).

and STN/CSN sampling artifacts (i.e., TC_{IMP} vs. TC_{STN} in $\mu\text{g}/\text{cm}^2$) can be expressed as:

$$\text{TC}_{\text{STN}} = \text{TC}_{\text{STN,art}} + b \times \text{TC}_{\text{IMP}} \quad (2)$$

where the intercept, $\text{TC}_{\text{STN,art}}$ in $\mu\text{g}/\text{cm}^2$, represents the additional artifact in TC_{STN} relative to TC_{IMP} . Regression statistics are summarized in Table 5. Table 6 shows that STN/CSN TC_{bQF} is 11–34% lower than $\text{TC}_{\text{STN,art}}$ at all sites except for the non-urban Tonto and Dolly Sod sites. Measured STN/CSN TC_{bQF} is similar to calculated $\text{TC}_{\text{STN,art}}$

Table 5. Robust regression statistics of uncorrected STN/CSN TC against IMPROVE TC for data from the eight collocated sites.

Site Code	Site Name ^a	Sampling Period	TC Concentration		TC Areal Density		Correlation (<i>r</i>)	N
			Slope	Intercept (μg/m ³)	Slope	Intercept (μg/cm ²)		
PUSO	Seattle, WA	16/10/2001–29/12/2003	0.91	0.12	0.220	0.24	0.98	224
MORA	Mount Rainier, WA	22/10/2001–20/10/2002	0.87	0.25	0.220	0.50	0.97	69
PHOE	Phoenix, AZ	16/10/2001–29/12/2003	1.08	1.65	0.088	1.34	0.94	201
TONT	Tonto Monument, AZ	16/10/2001–29/12/2003	1.06	0.85	0.088	0.69	0.92	181
WASH	Washington DC	16/10/2001–26/12/2003	1.08	0.95	0.096	0.85	0.92	206
DOSO	Dolly Sods, WV	16/10/2001–29/12/2003	0.87	0.83	0.096	0.74	0.67	140
FRES	Fresno, CA	01/01/2005–31/12/2006	1.16	1.10	0.088	0.90	0.95	227
BIBE	Big Bend National Park, TX	01/01/2005–31/12/2006	1.22	0.64	0.220	1.29	0.79	81

^a See Table 4 for STN/CSN sampler specifications.

Table 6. Comparison between calculated and measured sampling artifact for the eight collocated IMPROVE/STN sites.

Site Code	Site Name	Sampling Period	IMP TC _{bQF} (μg/cm ²) ^a	STN/CSN TC _{bQF} (μg/cm ²) ^b	Calculated TC _{STNart} (μg/cm ²) ^c	Difference (%) ^d
PUSO	Seattle, WA	16/10/2001–29/12/2003	2.66±0.54	0.68	0.83	−0.18
MORA	Mount Rainier, WA	22/10/2001–20/10/2002	1.44±0.36	0.66	0.82	−0.19
PHOE	Phoenix, AZ	16/10/2001–29/12/2003	2.63±0.58	1.40	1.57	−0.11
TONT	Tonto Monument, AZ	16/10/2001–29/12/2003	2.00±1.05	0.87	0.87	0.01
WASH	Washington DC	16/10/2001–26/12/2003	2.49±0.87	0.87	1.09	−0.20
DOSO	Dolly Sods, WV	16/10/2001–29/12/2003	2.57±0.31	1.18	0.99	0.19
FRES	Fresno, CA	01/01/2005–31/12/2006	2.58±0.50	1.44	1.82	−0.21
BIBE	Big Bend National Park, TX	01/01/2005–31/12/2006	2.40±0.68	0.74	1.13	−0.34

^a IMPROVE field blank total carbon (TC_{bQF})

^b STN/CSN field blanks

^c Calculated STN/CSN total carbon artifact

^d $\frac{\text{measured STN/CSN TC}_{bQF} - \text{calculated TC}_{STNart}}{\text{calculated TC}_{STNart}} \times 100$

at the Tonto site. The Dolly Sods site exhibits low TC_{bQF} levels (e.g., 0.4 and 0.3 μg/cm²; see Fig. 6), and a lower correlation (*r* = 0.7) was found between IMPROVE and STN (Andersen RAAS) samples at this site.

3.3 Organic carbon Mass (OCM) estimated by the SANDWICH method

The SANDWICH method was applied to 716 collocated filter pairs taken at four urban (i.e., Seattle, WA; Phoenix, AZ; Washington DC; and Fresno, CA) sites from 28 April 2001 to 29 December 2004. The number of sample pairs varied from 27 at the Fresno Supersite to 354 at the Seattle site. Total carbonaceous mass (TCM) was calculated by subtracting NO₃[−], SO₄[−], ammonium (NH₄⁺), an estimate for water (H₂O), and crustal components from the measured PM_{2.5} mass. The calculated OCM is derived by subtracting measured EC from TCM:

$$\text{TCM} = \text{PM}_{2.5} - (\text{SO}_4^- + \text{Retained NO}_3^- + \text{NH}_4^+ + \text{H}_2\text{O} + \text{Crustal Material} + \text{Blank}) \quad (3)$$

$$\text{OCM} = \text{TCM} - \text{EC} \quad (4)$$

where:

$$\text{Crustal Material} = 3.73 \times \text{Si} + 1.63 \times \text{Ca} + 2.42 \times \text{Fe} + 1.94 \times \text{Ti} \quad (5)$$

Blank = 0.3 – 1.5 μg/m³ for STN/CSN; 0 for IMPROVE

All IMPROVE data were blank-subtracted (in μg/m³). For STN/CSN, a nominal OC_{bQF} value of 0.3–1.5 μg/m³ is used for carbon blank subtraction (Frank, 2006), which varies by sampler type. This interval overlaps with the OC_{bQF} of 0.66±0.94 μg/m³ at the Seattle, Phoenix, and Washington DC, sites; OC_{bQF} for the Fresno site were not available. Retained NO₃[−] was calculated using the daily average temperature and relative humidity during the sampling period; and particle-bound water was calculated using the Aerosol Inorganics Model (AIM) as described by Frank (2006).

OCM concentrations from the SANDWICH method are converted to measured OC using a multiplier that accounts for unmeasured hydrogen, oxygen, and other elements in the organic compounds (i.e., El Zanan et al., 2005; Turpin and Lim, 2001; White and Roberts, 1977):

$$\text{OCM} = X \times \text{OC} \quad (6)$$

where:

X = unmeasured element multiplier (assumed to be 1.4 for fresh and 1.8 for aged aerosol);

OC = measured particulate organic carbon.

For IMPROVE samples, average OCM concentrations are $3.99 \pm 2.96 \mu\text{g}/\text{m}^3$, $4.40 \pm 3.45 \mu\text{g}/\text{m}^3$, $3.00 \pm 3.16 \mu\text{g}/\text{m}^3$, and $6.73 \pm 3.56 \mu\text{g}/\text{m}^3$ at the Seattle, Phoenix, Washington DC, and Fresno sites, respectively (Table 7). Better agreement with measured OC was found for a multiplier of 1.4 rather than 1.8 for all but the Fresno site. Agreement between $\text{OC} \times 1.4$ and OCM for the IMPROVE samples was 95%, 100%, 123%, and 71% at the Seattle, Phoenix, Washington DC, and Fresno sites, respectively. For STN/CSN samples, agreement was 90% (URG MASS) at the Seattle site, 79% (Andersen RAAS) at the Washington DC site, and 123% and 88% (both using MetOne SASS) at the Phoenix and Fresno sites, respectively.

To assess whether low, mid-range, or high concentration samples exhibit differences, Table 7 compares estimated 10th, 50th, and 90th percentiles, respectively. The percent differences between the average and median (50% of total) are similar (within $\pm 25\%$) for the sites using IMPROVE samples for multipliers of 1.4 or 1.8. At low concentrations (the 10th percentile), OCM by the SANDWICH method is 217–279% higher than measured OCM concentrations at the Washington DC site. Using STN/CSN samples, OCM by the SANDWICH method is also twofold higher at low concentrations for the Phoenix site; but the agreement is reasonable (117%) for high concentration samples (90th percentile) at this and other STN/CSN sites.

4 Deviations from hypotheses

Findings from this study are used to address the three hypotheses (H1 to H3):

H1: The OC sampling artifact represented by bQF or QBQ depends on sampling protocol and differs among ambient networks.

This hypothesis is valid based on observations. The IMPROVE, STN/CSN, and SEARCH networks use different sampling configurations, flow rates, filter material, and filter sizes. For bQF, which accompany sample filters to the field and are intended to emulate their passive deposition and adsorption, only the IMPROVE network provides an adequate (~ 7 days) passive exposure period for blank subtraction. The limited exposure times (1–15 min) in the STN/CSN and SEARCH networks are of insufficient duration to represent passive adsorption on the sampled filter. Based on both the network averages and collocated-site comparisons, IMPROVE TC_{bQF} (or OC_{bQF}) areal density ranges from 2.0 to 2.5 $\mu\text{g}/\text{cm}^2$, while STN/CSN and SEARCH field blanks are close to or below 1 $\mu\text{g}/\text{cm}^2$. STN/CSN field and trip blank TC and OC concentrations are similar ($\sim 0.95 \pm 0.23 \mu\text{g}/\text{cm}^2$), within $\pm 5\%$ for site averages. Among the five STN/CSN samplers, URG MASS reports the lowest OC_{bQF} levels.

Regression analysis using uncorrected TC from collocated IMPROVE-STN/CSN samples show higher STN/CSN than

IMPROVE areal densities ($\mu\text{g}/\text{cm}^2$) artifact at the same site. Without blank correction, STN/CSN sampling artifacts in $\mu\text{g}/\text{m}^3$ could be 5–11 times higher than those in IMPROVE, depending on the sampler type. When corrected with respective field blanks, STN/CSN TC concentrations are still higher at most sites, indicating that STN/CSN field blanks underrepresent the organic artifact by ~ 20 –30% (assuming IMPROVE bQF fully represents the artifact), but the number of bQF available for comparison was limited.

QBQ filters stay in the field for more than 24 hours with filtered air drawn through them for 24 hours. With a similar level of sampling artifact in areal density ($\mu\text{g}/\text{cm}^2$), STN/CSN and SEARCH TC (or OC) concentration ($\mu\text{g}/\text{m}^3$) would be more influenced than those of IMPROVE due to smaller sampling volumes and larger filter sizes. The average OC_{QBQ} concentration is $0.33 \pm 0.1 \mu\text{g}/\text{m}^3$ for IMPROVE and $0.35 \pm 0.15 \mu\text{g}/\text{m}^3$ for SEARCH (with preceding denuder).

H2: Sampling artifact and SVOC content are lower at non-urban sites than urban sites due to aerosol aging.

Comparisons between urban and non-urban sites in the SEARCH network are consistent with this hypothesis, but they are not sufficient to prove it. Average OC_{QBQ} was $\sim 25\%$ higher at the urban sites, with $1.51 \pm 1.50 \mu\text{g}/\text{cm}^2$ at urban sites and $1.18 \pm 0.98 \mu\text{g}/\text{cm}^2$ at the non-urban sites in the SEARCH network. The increments between the urban and non-urban sites were ~ 2.6 times for OC1 and 11% for OC2. The majority of this low temperature OC is gaseous VOCs. However, during the collocated IMPROVE-STN/CSN comparisons, TC_{bQF} were not always lower at non-urban than urban sites, although this depends on the extent of VOC saturation. The contrast between urban and non-urban sites only can provide indirect indication of aging effect since the degree of aging is not certain.

H3: Artifact-free OC concentrations can be better estimated by the SANDWICH method (Frank, 2006) than by direct OC measurements.

This hypothesis is invalid based on observations. The SANDWICH method (Frank, 2006) assumes PM_{2.5} mass closure, but many species are not measured on Teflon®-membrane filters, including carbon, NO_3^- , SO_4^{2-} , and NH_4^+ . Different collection/retention efficiencies of Teflon®-membrane, quartz-fiber, and nylon-membrane filters with respect to these species have not been well quantified. In addition, the mass of water and unidentified species may generate more uncertainties (Tierney and Connor, 1967; Kajino et al., 2006). All of these contribute to mass closure uncertainties. Even if organic carbon mass (OCM) can be calculated from the SANDWICH method, this study shows that variation in OCM concentration due to the choice of OC multiplier (e.g., 1.4 or 1.8) is comparable to the magnitude of the organic sampling artifact (5–30% of OCM). It is difficult to determine whether the excess OCM mass, if any, is due to sampling artifact or the correction coefficient used to convert OC to OCM.

Table 7. Estimates of organic carbon mass (OCM) based on the SANDWICH method for the four collocated IMPROVE/STN sites.

Site	Seattle, WA	Phoenix AZ	Washington DC	Fresno, CA
Site Type	Urban	Urban	Urban	Urban
Site Code	PUSO	PHOE	WASH	FRES
Number of Collocated Pairs	354	290	45	27
Sampler Type	IMPROVE	IMPROVE	IMPROVE	IMPROVE
Sampling Period	12/07/2001–29/12/2004	28/04/2001–30/09/2004	08/07/2004–29/12/2004	03/09/2004–23/12/2004
SANDWICH OCM $\mu\text{g}/\text{m}^3$				
Average	3.99±2.96	4.40±3.45	3.00±3.16	6.73±3.56
10%tile	1.22	1.48	0.58	2.86
50%tile	3.16	3.27	2.47	6.16
90%tile	8	8.66	6.23	11.29
Measured OC $\mu\text{g}/\text{m}^3$				
Average	2.70±2.06	3.13±2.27	2.63±1.51	3.42±1.66
10%tile	0.87	1.32	0.90	1.47
50%tile	1.91	2.25	2.51	3.18
90%tile	5.28	6.10	4.21	5.52
Measured OC×1.4/OCM				
Average	95%	100%	123%	71%
10%tile	100%	125%	217%	72%
50%tile	85%	96%	142%	72%
90%tile	92%	99%	95%	68%
Measured OC×1.8/OCM				
Average	122%	128%	158%	91%
10%tile	128%	161%	279%	93%
50%tile	109%	124%	183%	93%
90%tile	119%	127%	122%	88%
Sampler Type	URG MASS	MetOne SASS	Andersen RAAS	MetOne SASS
Sampling Period	12/07/2001–29/12/2004	28/04/2001–30/09/2004	08/07/2004–29/12/2004	03/09/2004–23/12/2004
SANDWICH OCM $\mu\text{g}/\text{m}^3$				
Average	4.63±3.27	4.48±3.62	4.85±5.14	7.66±4.37
10%tile	1.57	1.03	0.65	3.08
50%tile	3.72	3.64	4.03	6.72
90%tile	9.59	9.12	9.05	14.22
Measured OC $\mu\text{g}/\text{m}^3$				
Average	2.98±2	3.94±2.43	2.75±1.86	4.8±2.71
10%tile	1.16	1.58	0.56	1.81
50%tile	2.38	3.34	2.78	4.12
90%tile	6.06	7.59	5.62	8.91
Measured OC×1.4/OCM				
Average	90%	123%	79%	88%
10%tile	103%	215%	121%	82%
50%tile	90%	128%	97%	86%
90%tile	88%	117%	87%	88%
Measured OC×1.8/OCM				
Average	116%	158%	102%	113%
10%tile	133%	276%	155%	106%
50%tile	115%	165%	124%	110%
90%tile	114%	150%	112%	113%

The SANDWICH method did not work well for samples with low concentrations, for which the calculated and measured OC ratio exceeded 200% with the STN/CSN sampler (e.g., Phoenix, AZ). Even though the SANDWICH method did not provide a better representation of OC or OC artifact, it is a useful tool to estimate OC when carbon measurements are not available.

5 Conclusions

There is no simple way to correct for sampling artifacts using current measurements. With the newly implemented STN/CSN carbon measurements (USEPA, 2006b), using the modified IMPROVE Module C sampler (i.e., URG 3000N sampler), sampling artifacts will be reduced via a higher flow rate (e.g., 22.8 L/min instead of 6.7 L/min) and a smaller deposit area (3.53 cm² instead of 11.76 cm²). In addition, bQF will remain in the sampler for the same period as QF and QBQ samples at all STN/CSN sites. For each network, blank corrections should be made and uncertainties propagated, even though the reported OC is under-corrected for adsorbed organic vapors due to inadequate passive deposition period for field blanks. Each network should acquire bQFs and QBQs at the same frequency and passive deposit duration (e.g., once per month on an every-sixth-day sampling schedule; expose field blanks for a minimum of three days). More research, perhaps through controlled experiments, are warranted on: 1) sample duration for filter saturation of adsorbed gases; 2) dependence of adsorbed gas saturation on particle composition, temperature, relative humidity, and sampling face velocity; 3) evaporation rates of semi-volatile organic compounds during sampling; and 4) source-specific tests (e.g., diesel, gasoline, and wood smoke).

Acknowledgements. This work was partially supported by US EPA STAR Grant number RD-83108601-0, the US EPA/National Park Service under contract number C2350064010, the California Air Resources Board under contract number 04-307, and the Nazir and Mary Ansari Foundation. The information expressed in this paper does not necessarily reflect the policies of the US Environmental Protection Agency.

Edited by: R. Cohen

References

- Arhami, M., Kuhn, T., Fine, P. M., Delfino, R. J., and Sioutas, C.: Effects of sampling artifacts and operating parameters on the performance of a semicontinuous particulate elemental carbon/organic carbon monitor, *Environ. Sci. Technol.*, 40(3), 945–954, 2006.
- Arp, H. P. H., Schwarzenbach, R. P., and Goss, K. U.: Equilibrium sorption of gaseous organic chemicals to fiber filters used for aerosol studies, *Atmos. Environ.*, 418241–8252, 2007.
- Ashbaugh, L. L., McDade, C. E., White, W. H., Wakabayashi, P., Collett Jr., J. L., and Xiao-Ying, Y.: Efficiency of IMPROVE network denuders for removing nitric acid, in *Proceedings, Regional and Global Perspectives on Haze: Causes, Consequences and Controversies*, 32-1-32-8, 2004.
- Cadle, S. H., Groblicki, P. J., and Mulawa, P. A.: Problems in the sampling and analysis of carbon particulate, *Atmos. Environ.*, 17(3), 593–600, 1983.
- Chen, L.-W. A., Chow, J. C., Watson, J. G., Moosmüller, H., and Arnott, W. P.: Modeling reflectance and transmittance of quartz-fiber filter samples containing elemental carbon particles: Implications for thermal/optical analysis, *J. Aerosol Sci.*, 35(6), 765–780, 2004.
- Chow, J. C. and Richards, L. W.: San Joaquin Valley Air Quality Study/Atmospheric Utility Signatures - Predictions and Experiment (AUSPEX), Part E: Monitoring and analysis for aerosols and visibility, Volume II: Standard Operating Procedures, prepared for Pacific Gas and Electric Company, San Francisco, CA by Desert Research Institute, Reno, NV, 1990.
- Chow, J. C., Watson, J. G., Pritchett, L. C., Pierson, W. R., Frazier, C. A., and Purcell, R. G.: The DRI Thermal/Optical Reflectance carbon analysis system: Description, evaluation and applications in US air quality studies, *Atmos. Environ.*, 27A(8), 1185–1201, 1993.
- Chow, J. C., Fujita, E. M., Watson, J. G., Lu, Z., Lawson, D. R., and Ashbaugh, L. L.: Evaluation of filter-based aerosol measurements during the 1987 Southern California Air Quality Study, *Environ. Mon. Assess.*, 30(1), 49–80, 1994.
- Chow, J. C., Watson, J. G., Lu, Z., Lowenthal, D. H., Frazier, C. A., Solomon, P. A., Thuillier, R. H., and Magliano, K. L.: Descriptive analysis of PM_{2.5} and PM₁₀ at regionally representative locations during SJAQS/AUSPEX, *Atmos. Environ.*, 30(12), 2079–2112, 1996.
- Chow, J. C., Watson, J. G., Crow, D., Lowenthal, D. H., and Merrifield, T. M.: Comparison of IMPROVE and NIOSH carbon measurements, *Aerosol Sci. Technol.*, 34(1), 23–34, 2001.
- Chow, J. C., Bachmann, J. D., Wierman, S. S. G., Mathai, C. V., Malm, W. C., White, W. H., Mueller, P. K., Kumar, N. K., and Watson, J. G.: 2002 Critical review discussion - Visibility: Science and regulation, *J. Air Waste Manage. Assoc.*, 52(9), 973–999, 2002a.
- Chow, J. C., Watson, J. G., Edgerton, S. A., and Vega, E.: Chemical composition of PM₁₀ and PM_{2.5} in Mexico City during winter 1997, *Sci. Total Environ.*, 287(3), 177–201, 2002b.
- Chow, J. C., Engelbrecht, J. P., Watson, J. G., Wilson, W. E., Frank, N. H., and Zhu, T.: Designing monitoring networks to represent outdoor human exposure, *Chemosphere*, 49, 961–978, 2002c.
- Chow, J. C., Watson, J. G., Chen, L.-W. A., Arnott, W. P., Moosmüller, H., and Fung, K. K.: Equivalence of elemental carbon by Thermal/Optical Reflectance and Transmittance with

- different temperature protocols, *Environ. Sci. Technol.*, 38, 16, 4414–4422, 2004a.
- Chow, J. C., Watson, J. G., Kuhns, H. D., Etyemezian, V., Lowenthal, D. H., Crow, D. J., Kohl, S. D., Engelbrecht, J. P., and Green, M. C.: Source profiles for industrial, mobile, and area sources in the Big Bend Regional Aerosol Visibility and Observational (BRAVO) Study, *Chemosphere*, 54(2), 185–208, 2004b.
- Chow, J. C., Watson, J. G., Chen, L.-W. A., Paredes-Miranda, G., Chang, M.-C. O., Trimble, D., Fung, K. K., Zhang, H., and Zhen Yu, J.: Refining temperature measures in thermal/optical carbon analysis, *Atmos. Chem. Phys.*, 5, 2961–2972, doi:10.5194/acp-5-2961-2005, 2005.
- Chow, J. C., Watson, J. G., Lowenthal, D. H., Chen, L.-W. A., and Magliano, K. L.: Particulate carbon measurements in California's San Joaquin Valley, *Chemosphere*, 62(3), 337–348, 2006.
- Chow, J. C., Watson, J. G., Chen, L.-W. A., Chang, M. C. O., Robinson, N. F., Trimble, D., and Kohl, S. D.: The IMPROVE_A temperature protocol for thermal/optical carbon analysis: Maintaining consistency with a long-term database, *J. Air Waste Manage. Assoc.*, 57(9), 1014–1023, 2007.
- Chow, J. C., Doraiswamy, P., Watson, J. G., Chen, L.-W. A., Ho, S. S. H., and Sodeman, D. A.: Advances in integrated and continuous measurements for particle mass and chemical composition, *J. Air Waste Manage. Assoc.*, 58(2), 141–163, 2008a.
- Chow, J. C., Watson, J. G., Chen, L.-W. A., Trimble, D. L., Ho, S. S. H., and Veropoulos, K.: Methods to assess carbonaceous aerosol sampling artifacts for IMPROVE and other long-term networks, prepared by Desert Research Institute, Reno, NV, 2008b.
- Chu, S. H.: PM_{2.5} episodes as observed in the speciation trends network, *Atmos. Environ.*, 38(31), 5237–5246, 2004.
- Chu, S. H., Paisie, J. W., and Jang, B. W. L.: PM data analysis – a comparison of two urban areas: Fresno and Atlanta, *Atmos. Environ.*, 38(20), 3155–3164, 2004.
- Dutter, R. and Huber, P. J.: Numerical methods for the non linear robust regression problem, *J. Stat. Comp. Simulation*, 13(2), 79–113, 1981.
- Eatough, D. J., Sedar, B., Lewis, L., Hansen, L. D., Lewis, E. A., and Farber, R. J.: Determination of semivolatile organic compounds in particles in the Grand Canyon area, *Aerosol Sci. Technol.*, 10438–10449, 1989.
- Eatough, D. J., Long, R. W., Modey, W. K., and Eatough, N. L.: Semi-volatile secondary organic aerosol in urban atmospheres: Meeting a measurement challenge, *Atmos. Environ.*, 37(9–10), 1277–1292, 2003.
- Edgerton, E. S., Hartsell, B. E., Saylor, R. D., Jansen, J. J., Hansen, D. A., and Hidy, G. M.: The Southeastern Aerosol Research and Characterization Study Part II: Filter-based measurements of fine and coarse particulate matter mass and composition, *J. Air Waste Manage. Assoc.*, 55(10), 1527–1542, 2005.
- El Zanan, H. S., Lowenthal, D. H., Zielinska, B., Chow, J. C., and Kumar, N. K.: Determination of the organic aerosol mass to organic carbon ratio in IMPROVE samples, *Chemosphere*, 60(4), 485–496, 2005.
- Eldred, R. A., Cahill, T. A., Wilkinson, L. K., Feeney, P. J., Chow, J. C., and Malm, W. C.: Measurement of fine particles and their chemical components in the NPS/IMPROVE Networks, in *Transactions, Visibility and Fine Particles*, edited by: Mathai, C. V., 187–196, 1990.
- Fan, X. H., Lee, P. K. H., Brook, J. R., and Mabury, S. A.: Improved measurement of seasonal and diurnal differences in the carbonaceous components of urban particulate matter using a denuder-based air sampler, *Aerosol Sci. Technol.*, 38, Suppl. 2, 63–69, 2004.
- Fitz, D. R.: Reduction of the positive organic artifact on quartz filters, *Aerosol Sci. Technol.*, 12(1), 142–148, 1990.
- Flanagan, J. B., Jayanty, R. K. M., Rickman Jr., E. E., and Peterson, M. R.: PM_{2.5} Speciation Trends Network: Evaluation of whole-system uncertainties using data from sites with collocated samplers, *J. Air Waste Manage. Assoc.*, 56(4), 492–499, 2006.
- Frank, N. H.: Retained nitrate, hydrated sulfates, and carbonaceous mass in Federal Reference Method fine particulate matter for six eastern cities, *J. Air Waste Manage. Assoc.*, 56(4), 500–511, 2006.
- Hansen, D. A., Edgerton, E. S., Hartsell, B. E., Jansen, J. J., Kandasamy, N., Hidy, G. M., and Blanchard, C. L.: The Southeastern Aerosol Research and Characterization Study: Part 1 – Overview, *J. Air Waste Manage. Assoc.*, 53(12), 1460–1471, 2003.
- Hart, K. M. and Pankow, J. F.: High-volume air sampler for particle and gas sampling 2. Use of backup filters to correct for the adsorption of gas-phase polycyclic aromatic hydrocarbons on the front filter, *Environ. Sci. Technol.*, 28(4), 655–661, 1994.
- Kajino, M., Winwarter, W., and Ueda, H.: Modeling retained water content in measured aerosol mass. *Atmos. Environ.*, 40(27), 5202–5213, 2006.
- Kim, B. M., Cassmassi, J., Hogo, H., and Zeldin, M. D.: Positive organic carbon artifacts on filter medium during PM_{2.5} sampling in the South Coast Air Basin, *Aerosol Sci. Technol.*, 34(1), 35–41, 2001.
- Kim, E., Hopke, P. K., and Qin, Y.: Estimation of organic carbon blank values and error structures of the speciation trends network data for source apportionment, *J. Air Waste Manage. Assoc.*, 55(8), 1190–1199, 2005.
- Kirchstetter, T. W., Corrigan, C. E., and Novakov, T.: Laboratory and field investigation of the adsorption of gaseous organic compounds onto quartz filters, *Atmos. Environ.*, 35(9), 1663–1671, 2001.
- Lane, T. E., Donahue, N. M., and Pandis, S. N.: Simulating secondary organic aerosol formation using the volatility basis-set approach in a chemical transport model, *Atmos. Environ.*, 42(32), 7439–7451, 2008.
- Lewtas, J., Pang, Y., Booth, D., Reimer, S., Eatough, D. J., and Gundel, L. A.: Comparison of sampling methods for semi-volatile organic carbon associated with PM_{2.5}, *Aerosol Sci. Technol.*, 34(1), 9–22, 2001.
- MacCracken, M. C.: Critical review: Prospects for future climate change and the reasons for early action, *J. Air Waste Manage. Assoc.*, 58(6), 735–786, 2008.
- Mader, B. T. and Pankow, J. F.: Gas/solid partitioning of semivolatile organic compounds (SOCs) to air filters – 1. Partitioning of polychlorinated dibenzodioxins, polychlorinated dibenzofurans and polycyclic aromatic hydrocarbons to Teflon® membrane filters, *Atmos. Environ.*, 34(28), 4879–4887, 2000.
- Mader, B. T. and Pankow, J. F.: Gas/solid partitioning of semivolatile organic compounds (SOCs) to air filters – 3.

- An analysis of gas adsorption artifacts in measurements of atmospheric SOCs and organic carbon (OC) when using Teflon® membrane filters and quartz fiber filters, *Environ. Sci. Technol.*, 35(17), 3422–3432, 2001a.
- Mader, B. T. and Pankow, J. F.: Gas/solid partitioning of semivolatile organic compounds (SOCs) to air filters – 2. Partitioning of polychlorinated dibenzodioxins, polychlorinated dibenzofurans, and polycyclic aromatic hydrocarbons to quartz fiber filters, *Atmos. Environ.*, 35(7), 1217–1223, 2001b.
- Malm, W. C., Sisler, J. F., Huffman, D., Eldred, R. A., and Cahill, T. A.: Spatial and seasonal trends in particle concentration and optical extinction in the United States, *J. Geophys. Res.*, 99(D1), 1347–1370, 1994.
- Matsumoto, K., Hayano, T., and Uematsu, M.: Positive artifact in the measurement of particulate carbonaceous substances using an ambient carbon particulate monitor, *Atmos. Environ.*, 37(33), 4713–4717, 2003.
- McDow, S. R. and Huntzicker, J. J.: Vapor adsorption artifact in the sampling of organic aerosol: Face velocity effects, *Atmos. Environ.*, 24A(10), 2563–2571, 1990.
- Noll, J. and Birch, M. E.: Effects of sampling artifacts on occupational samples of diesel particulate matter, *Environ. Sci. Technol.*, 42(14), 5223–5228, 2008.
- Olson, D. A. and Norris, G. A.: Sampling artifacts in measurement of elemental and organic carbon: Low-volume sampling in indoor and outdoor environments, *Atmos. Environ.*, 39(30), 5437–5445, 2005.
- Peterson, M. R. and Richards, M. H.: Thermal-optical-transmittance analysis for organic, elemental, carbonate, total carbon, and OCX₂ in PM_{2.5} by the EPA/NIOSH method, in *Proceedings, Symposium on Air Quality Measurement Methods and Technology-2002*, edited by: Winegar, E. D. and Tropp, R. J., 83-1-83-19, 2002.
- Robinson, A. L., Donahue, N. M., Shrivastava, M. K., Weitkamp, E. A., Sage, A. M., Grieshop, A. P., Lane, T. E., Pierce, J. R., and Pandis, S. N.: Rethinking organic aerosols: Semivolatile emissions and photochemical aging, *Science*, 315(5816), 1259–1262, 2007.
- Salma, I., Ocskay, R., Chi, X. G., and Maenhaut, W.: Sampling artefacts, concentration and chemical composition of fine water-soluble organic carbon and humic-like substances in a continental urban atmospheric environment, *Atmos. Environ.*, 41(19), 4106–4118, 2007.
- Solomon, P. A., Klamser, T., Egeghy, P., Crumpler, D., and Rice, J., STN/IMPROVE comparison study – Preliminary results, 2004.
- Subramanian, R., Khlystov, A. Y., Cabada, J. C., and Robinson, A. L.: Positive and negative artifacts in particulate organic carbon measurements with denuded and undenuded sampler configurations, *Aerosol Sci. Technol.*, 38, Suppl. 1, 27–48, 2004.
- ten Brink, H. M., Maenhaut, W., Hitzenberger, R., Gnauk, T., Spindler, G., Even, A., Chi, X. G., Bauer, H., Puxbaum, H., Putaud, J. P., Tursic, J., and Berner, A.: INTERCOMP2000: The comparability of methods in use in Europe for measuring the carbon content of aerosol, *Atmos. Environ.*, 38(38), 6507–6519, 2004.
- Tierney, G. P. and Conner, W. D.: Hygroscopic effects on weight determinations of particulates collected on glass-fiber filters, *J. Am. Ind. Hyg. Assoc.*, 28, 363–365, 1967.
- Turpin, B. J., Huntzicker, J. J., and Hering, S. V.: Investigation of organic aerosol sampling artifacts in the Los Angeles Basin, *Atmos. Environ.*, 28(19), 3061–3071, 1994.
- Turpin, B. J. and Lim, H. J.: Species contributions to PM_{2.5} mass concentrations: Revisiting common assumptions for estimating organic mass, *Aerosol Sci. Technol.*, 35(1), 602–610, 2001.
- USEPA: Guidance for network design and optimum site exposure for PM_{2.5} and PM₁₀, prepared by US Environmental Protection Agency, Research Triangle Park, NC, USA, 1997.
- USEPA: 40 CFR Part 50: National Ambient Air Quality Standards for Particulate Matter; Final Rule, *Federal Register*, 71(200), 61144–61233, 2006a.
- US EPA: Modification of Carbon Procedures in the Speciation Network and FAQs, PM_{2.5} Speciation Trends Network Newsletter, April, 2–3, 2006b.
- Vecchi, R., Valli, G., Fermo, P., D’Alessandro, A., Piazzalunga, A., and Bernardoni, V.: Organic and inorganic sampling artefacts assessment, *Atmos. Environ.*, 43(10), 1713–1720, 2009.
- Viana, M., Chi, X., Maenhaut, W., Cafmeyer, J., Querol, X., Alastuey, A., Mikuska, P., and Vecera, Z.: Influence of sampling artefacts on measured PM, OC, and EC levels in Carbonaceous aerosols in an urban area, *Aerosol Sci. Technol.*, 40(2), 107–117, 2006.
- Watson, J. G., Chow, J. C., Bowen, J. L., Lowenthal, D. H., Hering, S. V., Ouchida, P., and Oslund, W.: Air quality measurements from the Fresno Supersite, *J. Air Waste Manage. Assoc.*, 50(8), 1321–1334, 2000.
- Watson, J. G.: Visibility: Science and regulation – A summary of the 2002 Critical Review, *EM*, 8, June, 36–43, 2002.
- Watson, J. G. and Chow, J. C.: Comparison and evaluation of in-situ and filter carbon measurements at the Fresno Supersite, *J. Geophys. Res.*, 107, D21, ICC 3-1–ICC 3-15, 2002.
- Watson, J. G., Chow, J. C., Chen, L.-W. A., Kohl, S. D., Tropp, R. J., Trimble, D. L., Chancellor, S., Sodeman, D. A., and Ho, S. S. H.: Assessment of carbon sampling artifacts in the IMPROVE, STN/CSN, and SEARCH networks, prepared by Desert Research Institute, Reno, NV, USA, 2008.
- Watson, J. G. and Chow, J. C.: Ambient aerosol sampling, in *Aerosol Measurement: Principles, Techniques and Applications*, edited by: Kulkarni, P. S. and Baron, P., John Wiley and Sons, New York, NY, 2010.
- Watson, J. G., Chow, J. C., and Chen, L.-W. A.: Methods to assess carbonaceous aerosol sampling artifacts for IMPROVE and other long-term networks, *J. Air Waste Manage. Assoc.*, 59(8), 898–911, 2009.
- White, W. H. and Roberts, P. T.: On the nature and origins of visibility-reducing aerosols in the Los Angeles air basin, *Atmos. Environ.*, 11(9), 803–812, 1977.
- White, W. H. and Macias, E. S.: Carbonaceous particles and regional haze in the Western United States, *Aerosol Sci. Technol.*, 10(1), 111–117, 1989.
- Yu, S. C., Dennis, R. L., Bhave, P. V., and Eder, B. K.: Primary and secondary organic aerosols over the United States: estimates on the basis of observed organic carbon (OC) and elemental carbon (EC), and air quality modeled primary OC/EC ratios, *Atmos. Environ.*, 38, 5257–5268, 2004.