



Supplement of

Potential new tracers and their mass fraction in the emitted PM₁₀ from the burning of household waste in stoves

András Hoffer et al.

Correspondence to: András Hoffer (hoffer@almos.uni-pannon.hu)

The copyright of individual parts of the supplement might differ from the article licence.

Table S1. The retention indices of the identified tracer compounds.

	Retention time	Kovats RI	Lee RI	References	
				Kovats RI	Lee RI
o-Terphenyl (o-TPH)	27.86	1888.3	316.5		317.42 (Marynowski et al. 2004), 317.9 (Li et al. 2016)
m-Terphenyl (m-TPH)	32.15	2157.7	357.6		356.74 (Marynowski et al. 2004), 356.95 (Li et al. 2016)
p-Terphenyl (p-TPH)*	32.74	2196.3	363.2		362.4 (Marynowski et al. 2004), 362.8 (Li et al. 2016)
1,3,5-Triphenylbenzene (135-TPB)*	42.32	2944.4	463.7	3007 (Simoneit et al., 2005)	463.4 (Li et al. 2016)
1,2,4-Triphenylbenzene (124-TPB)*	39.38	2691.9	431.1	2630 (Simoneit et al., 2005), 2741, estimated with error: 55 (http://www.chemspider.com/Chemical-Structure.452244.html (ref. to NIST))	
m,p-Quaterphenyl (m,p-QTPH)	43.48	3049.3	476.5		476.3 (https://pubchem.ncbi.nlm.nih.gov/compound/1166-19-4) 482.98 (Li et al. 2016)
p-Quaterphenyl (p-QTPH)*	43.99	3095.7	482.2		
2-(Benzoyloxy)ethyl vinyl terephthalate (2-BEVT)	38.43	2615.7	420.6	2636 (Tsuge et al. 2011)	
2,4,6-Triphenyl-1-hexen (SSS)*	36.21	2444.0	396.5	2484 (Tsuge et al. 2011)	
2-Methylene-4-phenylheptanedinitrile (ASA)	26.72	1822.6	305.6	1843 (Tsuge et al. 2011)	
2-Methylene-4,6-diphenylhexanenitrile (ASS)	31.31	2101.5	349.6	2129 (Tsuge et al. 2011)	
4,6-Diphenylhept-6-enenitrile (SSA)	31.95	2144.7	355.7	2175 (Tsuge et al. 2011)	
2-Phenethyl-4-phenylpent-4-enenitrile (SAS)	32.35	2171.0	359.5	2200 (Tsuge et al. 2011)	

* The retention behaviour was studied with authentic standards

References

- Li, M. J., Wang, H., Shi, S. B., Fang, R. H., Tang, Q., and Wang, D. W.: The occurrence and distribution of phenylanthracenes, terphenyls and quaterphenyls in selected lacustrine shales and related oils in China, *Organic Geochemistry*, 95, 55-70, 10.1016/j.orggeochem.2016.02.010, 2016.
- 5 Marynowski, L., Pieta, M., and Janeczek, J.: Composition and source of polycyclic aromatic compounds in deposited dust from selected sites around the Upper Silesia, Poland, *Geological Quarterly*, 48, 169-179, 2004.
- Simoneit, B. R. T., Medeiros, P. M., and Didyk, B. M.: Combustion products of plastics as indicators for refuse burning in the atmosphere, *Environmental Science & Technology*, 39, 6961-6970, 10.1021/es050767x, 2005.
- 10 Tsuge, S., H. Ohtani and C. Watanabe.: *Pyrolysis-GC/MS data book of synthetic polymers: pyrograms, thermograms and MS of pyrolyzates*, Elsevier, available at: <https://www.elsevier.com/books/pyrolysis-gc-ms-data-book-of-synthetic-polymers/tsuge/978-0-444-53892-5> (last access: 22 November 2021), 2011.

Table S2. The absolute emission factors (mg kg⁻¹) and the mass fraction (µg g⁻¹ PM) of the identified tracer compound for waste burning. The values in parentheses are the relative standard deviation (%) obtained for a given type of waste under different burning conditions.

	135-TPB	o-TPH	m-TPH	p-TPH	m,p-QTPH	p-QTPH	2-BEVT	124-TPB	SSS	ASA	ASS	SSA	SAS	Melamine	
Emission Factor (mg kg ⁻¹)	ABS	2.1 (75)	1.5 (39)	21 (48)	8.7 (44)	0.27 (69)	<LOQ	<LOQ	0.93 (76)	<LOQ	9.2 (130)	2.2 (104)	1.4 (95)	4.2 (115)	-
	LDF	0.060 (111)	0.0067 (15)	0.057 (224)	<LOQ	<LOQ	<LOQ	<LOQ	0.0062 (94)	1.1 (161)	1.7 (223)	0.67 (222)	0.60 (222)	1.2 (222)	51 (81)
	OSB	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ
	PAP	0.16 (75)	<LOQ	0.62 (105)	<LOQ	0.0061 (141)	<LOQ	<LOQ	0.022 (87)	0.83 (104)	0.041 (47)	0.11 (110)	0.036 (118)	0.040 (104)	<LOQ
	PE	<LOQ	<LOQ	0.42 (173)	<LOQ	<LOQ	<LOQ	<LOQ	0.011 (173)	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ
	PET	1.1 (50)	2.1 (37)	61 (46)	87 (50)	10 (51)	6.7 (53)	2.8 (199)	4.4 (49)	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ
	PP	0.026 (173)	0.090 (109)	1.6 (9)	<LOQ	<LOQ	<LOQ	<LOQ	0.011 (173)	0.13 (173)*	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ
	PS	40 (117)	3.0 (107)	57 (37)	35 (26)	1.9 (50)	0.55 (69)	0.012 (224)*	9.8 (49)	150 (206)	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ
	PU	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ
	PVC	0.17 (105)	0.28 (71)	2.1 (36)	0.57 (173)	0.052 (93)	<LOQ	<LOQ	<LOQ	1.5 (150)*	0.28 (173)*	<LOQ	<LOQ	<LOQ	<LOQ
	RAG	0.13 (51)	0.12 (40)	5.3 (51)	8.0 (52)	0.86 (58)	0.58 (68)	0.060 (117)	0.68 (64)	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ
	TIRE	<LOQ	0.044 (173)	0.63 (173)	<LOQ	<LOQ	0.011 (173)	<LOQ	0.033 (173)	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ
	WOOD	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ
	Mass fraction (µg g ⁻¹ PM)	ABS	24 (41)	18 (13)	250 (18)	100 (14)	3.2 (35)	<LOQ	<LOQ	10 (43)	<LOQ	90 (116)	22 (90)	15 (87)	43 (100)
LDF		23 (116)	1.9 (224)	11 (224)	<LOQ	<LOQ	<LOQ	<LOQ	2.2 (108)	380 (160)	500 (222)	200 (221)	180 (222)	350 (221)	19000 (79)
OSB		<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ
PAP		75 (79)	<LOQ	290 (107)	<LOQ	2.9 (141)	<LOQ	<LOQ	10.0 (90)	380 (106)	19 (51)	51 (112)	17 (119)	18 (106)	<LOQ
PE		<LOQ	<LOQ	17 (173)	<LOQ	<LOQ	<LOQ	<LOQ	0.43 (173)	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ
PET		100 (41)	190 (26)	5400 (37)	7700 (43)	920 (44)	590 (50)	250 (199)	390 (44)	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ
PP		0.49 (173)	3.8 (105)	57 (37)	<LOQ	<LOQ	<LOQ	<LOQ	0.21 (173)	5.3 (173)*	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ
PS		800 (116)	56 (98)	1100 (40)	690 (29)	34 (17)	9.7 (33)	0.24 (224)*	190 (52)	2900 (208)	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ
PU		<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ
PVC		6.2 (121)	9.6 (96)	67 (69)	24 (173)	1.9 (108)	<LOQ	<LOQ	<LOQ	59 (157)*	11 (173)*	<LOQ	<LOQ	<LOQ	<LOQ
RAG		15 (51)	14 (41)	610 (52)	920 (52)	100 (58)	67 (68)	6.9 (117)	78 (63)	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ
TIRE		<LOQ	1.1 (173)	15 (173)	<LOQ	<LOQ	0.26 (173)	<LOQ	0.79 (173)	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ
WOOD		<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ	<LOQ

* Possible contamination