

## ***Interactive comment on* “Characteristics of Arctic low-tropospheric humidity inversions based on radio soundings” by T. Nygård et al.**

**T. Nygård et al.**

tiina.nygard@fmi.fi

Received and published: 10 January 2014

We admit that this may generate a bias, as the humidity sensor may be wet when rising above the cloud top. We have added a note on this on Section 2.2 in the manuscript. In practice it is, however, impossible to quantitatively estimate the bias in this study. This is because the amount of condensate in the sensor depends on the cloud particle concentration, phase, and size distribution, as well as on the level of turbulence both inside and above the cloud.

Some radiosonde instruments take care of the issue effectively. For example, Vaisala Radiosonde RS92 has two humidity sensors, of which one is pulse heated. The purpose of the heating is to minimize condensation that may occur during the flight. This

Full Screen / Esc

Printer-friendly Version

Interactive Discussion

Discussion Paper



results in reliable humidity measurements also when emerging from a cloud. In general, if a radiosonde humidity sensor experiences condensation while emerging from a cloud, the condensate gets fast frozen in freezing temperatures. That leads into unrealistic constant large humidity values for the rest of the flight, which are removed in the quality control of the data. We did not see this type of behavior in our vertical profiles of humidity.

---

Interactive comment on Atmos. Chem. Phys. Discuss., 13, 22575, 2013.

ACPD

13, C10857–C10858,  
2014

---

[Interactive  
Comment](#)

[Full Screen / Esc](#)

[Printer-friendly Version](#)

[Interactive Discussion](#)

[Discussion Paper](#)

C10858

