



1 **High- and low-temperature pyrolysis profiles describe volatile** 2 **organic compound emissions from western US wildfire fuels**

3

4 **Kanako Sekimoto^{1,2,3,‡}, Abigail R. Koss^{1,2,4,*}, Jessica B. Gilman¹, Vanessa Selimovic⁵,**
5 **Matthew M. Coggon^{1,2}, Kyle J. Zarzana^{1,2}, Bin Yuan^{1,2,6}, Brian M. Lerner^{1,2,†}, Steven S.**
6 **Brown^{1,4}, Carsten Warneke^{1,2}, Robert J. Yokelson⁵, James M. Roberts¹, Joost de Gouw^{1,2,4}**

7

8 ¹ NOAA Earth System Research Laboratory (ESRL), Chemical Sciences Division, Boulder, CO
9 80305, USA

10 ² Cooperative Institute for Research in Environmental Sciences, University of Colorado Boulder,
11 Boulder, CO 80309, USA

12 ³ Graduate School of Nanobioscience, Yokohama City University, Yokohama, Kanagawa 236-
13 0027, Japan

14 ⁴ Department of Chemistry and Biochemistry, University of Colorado, Boulder, CO 80302, USA

15 ⁵ Department of Chemistry, University of Montana, Missoula, MT 59812, USA

16 ⁶ Institute for Environmental and Climate Research, Jinan University, Guangzhou, China

17 * Now at Department of Civil & Environmental Engineering, Massachusetts Institute of
18 Technology, Cambridge, MA 02142, USA

19 † Now at Aerodyne Research, Inc., Billerica, MA 01821, USA

20

21 [‡]K. Sekimoto and A. Koss are equally contributing first authors.

22 *Correspondence to:* Kanako Sekimoto (sekimoto@yokohama-cu.ac.jp)

23

24

25 **Abstract.** Biomass burning is a large source of volatile organic compounds (VOCs) and many
26 other trace species to the atmosphere, which can act as precursors to the formation of secondary
27 pollutants such as ozone and fine particles. Measurements collected with a proton-transfer-
28 reaction time-of-flight mass spectrometer during the FIREX 2016 laboratory intensive were
29 analyzed with Positive Matrix Factorization (PMF), in order to understand the instantaneous
30 variability in VOC emissions from biomass burning, and to simplify the description of these



31 types of emissions. Despite the complexity and variability of emissions, we found that a solution
32 including just two emission profiles, which are mass spectral representations of the relative
33 abundances of emitted VOCs, explained on average 85% of the VOC emissions across various
34 fuels representative of the western US (including various coniferous and chaparral fuels). In
35 addition, the profiles were remarkably similar across almost all of the fuel types tested. For
36 example, the correlation coefficient r of each profile between Ponderosa pine (coniferous tree)
37 and Manzanita (chaparral) is higher than 0.9. We identified the two VOC profiles as resulting
38 from “high-temperature” and “low-temperature” pyrolysis processes known to form VOCs in
39 biomass burning. “High-temperature” and “low-temperature” pyrolysis processes do not
40 correspond exactly to the commonly used “flaming” and “smoldering” categories as described by
41 modified combustion efficiency (MCE). The average atmospheric properties (e.g. OH reactivity,
42 volatility, etc) of the high- and low-temperature profiles are significantly different. We also
43 found that the two VOC profiles can describe previously reported VOC data for laboratory and
44 field burns. This indicates that the high- and low-temperature pyrolysis profiles could be widely
45 useful to model VOC emissions from many types of biomass burning in the western US, with a
46 few exceptions such as burns of duff and rotten wood.

47

48

49 **1 Introduction**

50 Biomass burning is a large source of volatile organic compounds (VOCs) and other trace
51 species to the atmosphere. Reactions involving these VOCs produce ozone and fine particles,
52 which are important air pollutants and radiative forcing agents (Alvarado et al., 2009; Alvarado
53 et al., 2015; Yokelson et al., 2009; Jaffe et al., 2012). Some VOCs from fires also have direct
54 health effects (Naeher et al., 2007; Roberts et al. 2011). Biomass burning occurs in wildfires,
55 controlled burns of wildland and agricultural fuels, and in residential wood stoves and industrial
56 processes. Given the variety of fuels and burning conditions, it is unsurprising that the VOC
57 composition of biomass burning emissions varies greatly between different fire states, locations,
58 and studies. Therefore, it is important to understand VOC emissions from biomass burning in
59 detail and develop a predictive capability that explains some of the variability in VOC emissions.

60 Multiple complex processes take place in biomass burning, including (i) distillation with
61 release of water vapor and terpenes, (ii) pyrolysis of solid biomass giving off flammable gases,



(iii) flaming combustion, and (iv) non-flaming processes loosely lumped with smoldering combustion such as glowing (gasification) of biomass (Yokelson et al., 1996; Yokelson et al., 1997; Collard and Blin, 2014; Liu et al., 2016). In a given fire, these processes occur simultaneously, but the relative importance of each process can change with time, which relates to the variability in integrated VOC emissions between different fires. This variability is often parameterized as a function of modified combustion efficiency ($MCE = \Delta CO_2 / (\Delta CO + \Delta CO_2)$) (Yokelson et al., 1996). CO_2 and CO are representative gases emitted from the flaming and smoldering combustion processes, respectively, and are measured in most biomass burning studies. MCE is generally higher in flaming combustion (> 0.9) and lower in smoldering combustion (< 0.9) (Akagi et al., 2011).

The National Oceanic and Atmospheric Administration (NOAA) led the Fire Influence on Regional and Global Environments Experiment (FIREX) 2016 laboratory intensive conducted at the U.S. Forest Service Fire Sciences Laboratory in Missoula, Montana to study emissions of trace gases and aerosol from wildfires. Emissions from various fuels representative of the western U.S. were sampled under controlled conditions by extensive instrumentation (<https://www.esrl.noaa.gov/csd/projects/firex/firelab/instruments.html>). Experiments included so-called stack burns, in which emissions from an evolving burn were entrained into a large-diameter stack and sampled by various instruments. VOCs were measured by several instruments, including a PTR-ToF-MS (proton-transfer-reaction time-of-flight mass spectrometer) which captured gas-phase emissions with a fast time response during stack burns. The measurements show variability in VOC composition as the fire shifts between a dynamic mix of distillation, pyrolysis, flaming combustion, and “smoldering” combustion (here we use smoldering as a rough term to include various “non-flame” processes such as gasification). Ions measured with the PTR-ToF-MS were interpreted using a combination of gas-chromatographic pre-separation experiments, literature review, time-series analysis, and comparison to other instruments (Koss et al., 2017). Approximately 90% of the instrument signal could be attributed to identified VOCs.

The aims of this work are to understand the variation in gas-phase emissions both over the course of a fire and on a fire-integrated basis, and simplify predictions of the emission of secondary organic aerosol (SOA) and ozone precursors. To do this, the VOCs observed by PTR-ToF-MS in stack burns were analyzed using positive matrix factorization (PMF). We show that much of the observed variability in VOCs can be explained by only two factors: a high-



93 temperature pyrolysis factor and a low-temperature pyrolysis factor, which are named based on
94 the main processes of the VOC emissions from biomass burning. The two factors are compared
95 between fuels. Importantly, the high-temperature factor is quantitatively similar between
96 different fuels, and the same is true for the low-temperature factor. The VOCs present in each
97 factor are discussed in terms of composition, reactivity with OH, and propensity to form
98 secondary organic aerosol. The relative importance of high- and low-temperature pyrolysis
99 factors is quantified for each fuel and discussed with respect to physical properties of the fuel
100 and the burn dynamics. We also investigate how well VOC emissions in biomass burning can be
101 modeled by the two PMF emission profiles through comparisons with previously reported data
102 from laboratory burns and wildfires. Finally, emissions of some specific compounds are
103 discussed.

104

105

106 **2 Methods**

107 **2.1 VOC measurements by PTR-ToF-MS**

108 Fire emissions were measured during the FIREX 2016 intensive at the Fire Sciences
109 Laboratory in Missoula, Montana. The facility consists of a large combustion chamber and has
110 been described in detail previously (Christian et al., 2003; Christian et al., 2004; Burling et al.,
111 2010).

112 VOC measurements were performed using several instruments, including a PTR-ToF-MS.
113 This instrument employed a high-resolution ToF mass analyzer (Aerodyne Research Inc, MA,
114 USA; ToFwerk AG, Thun, Switzerland) and measured with a time resolution of 2 Hz. VOCs and
115 some inorganic compounds were ionized by proton transfer from H_3O^+ reagent ions. We include
116 the inorganic compounds in the discussion of VOCs. Species with a proton affinity higher than
117 that of water can be measured, which includes many unsaturated and polar compounds. The mass
118 resolution of the instrument (3000-5000 FWHM $m/\Delta m$) was sufficient to determine the
119 elemental composition of ions and separate many isobaric compounds. Before each fire,
120 background air in the combustion chamber was measured directly for several minutes. The
121 instrument has been described in detail by Yuan et al. (2016; 2017), and operation, calibration,
122 and peak identification during the FIREX 2016 laboratory intensive were described by Koss et al.
123 (2017).



124

125 **2.2 Fuel and biomass burn descriptions**

126 Fifteen types of natural fuel mixtures, most of which are representative of important western
 127 U.S. ecosystems, were burned. The names below are largely taken from the dominant plant
 128 species: (i) Ponderosa pine, (ii) Lodgepole pine, (iii) Loblolly pine, (iv) Douglas fir, (v)
 129 Engelmann spruce, (vi) Subalpine fir, (vii) Juniper, (viii) Bear grass, (ix) Ceanothus, (x)
 130 Chamise-contaminated, (xi) Chamise-uncontaminated, (xii) Manzanita-contaminated, (xiii)
 131 Manzanita-uncontaminated, (xiv) Sagebrush, and (xv) Excelsior (aspen wood shavings).
 132 “Contaminated” chaparral fuels (Manzanita and Chamise) were collected from a heavily air-
 133 polluted site near San Dimas, CA, while “uncontaminated” fuels were collected from a cleaner
 134 site in North Mountain, CA. Individual components of various fuel complexes, including canopy,
 135 litter, duff, and rotten wood, were also burned separately. More details on the fires and fuels are
 136 given by Selimovic et al. (2017) including: fuel moisture, pre- and post-fire weight, weight of
 137 fuel components, and elemental composition (C, H, N, S, and Cl by weight). Each fuel type was
 138 burned several times. All fires consumed most of the fuel.

139

140 **2.3 PMF analysis**

141 Measurements by PTR-ToF-MS were analyzed using positive matrix factorization (PMF), a
 142 numerical method that can be used to determine major compositional categories of emissions,
 143 their compositional profiles, and their relative enhancements over time. PMF was conducted
 144 using the PMF Evaluation Tool v. 2.08A (Ulbrich et al., 2009). The basic principles of PMF and
 145 application to atmospheric chemistry measurements have been previously described (Ulbrich et
 146 al., 2009; Paatero and Tapper, 1994; Paatero, 1997).

147 More than 1000 ions were quantified in the PTR-ToF-MS mass spectra between m/z 12-217.
 148 Of these, 574 were selected for PMF analysis (Table S2). These 574 ions were resolved from
 149 neighboring peaks, were enhanced during at least one fire, and exclude primary (e.g., H_3O^+ and
 150 $\text{H}_3\text{O}^+(\text{H}_2\text{O})$) and contaminant ions (e.g., Teflon fragments and transition metals) (Koss et al.,
 151 2017). The ion signals (in units of normalized counts-per-second; ncps), which are normalized to
 152 the H_3O^+ ion intensities and corrected for ToF-duty cycle, humidity dependence, and H_3O^+ ion
 153 depletion as described by Koss et al. (2017), were analyzed using PMF. Typically, raw ion
 154 signals in units of “counts-per-second (cps)” have been used for PMF analysis. However, cps



VOC ion signals are affected by temporal variability (depletion and instability) in primary ion intensity and humidity during the fire. To obtain PMF results that exclude instrument effects, the normalized and corrected ion signals are used in this analysis. The uncertainties of the normalized and corrected ion signals were calculated based on those originating from the raw (cps) ion signals. We chose to use instrument signal rather than mixing ratio because many ion masses cannot be unambiguously related to a single VOC contributor: they have several contributors, or result from fragmentation, and cannot be converted to mixing ratio. However, variability in these ion signals still contains information useful for PMF. To interpret the PMF results, we did convert to mixing ratio where possible (Section 2.4).

In this work, we applied PMF to extended time series, in which all fires of a particular fuel type (e.g., Ponderosa pine) were consolidated into a single data matrix (Figure S1), as well as time series of single fire data. Each fuel type was burned several times. Some individual fires of a particular fuel did not necessarily capture the full possible range of high- and low-temperature fire conditions, because of variability in the relative amounts of fuel parts, fuel moisture content, when fuel was added, or other differences. PMF using the consolidated time series makes it possible to capture the widest possible range of fire conditions. This approach also simplifies the comparison of average emission profiles between different types of fuels. Details on preparation of ion signal and uncertainty datasets are described in the Supporting Information (§1).

The discussion in Section 3 is based on the 2-factor PMF solutions. Out of the 574 ions, 434 ions were fitted well and together represented 99% of the total ion signal. A total of 140 ions were not well fitted as the difference between their measurements and the PMF reconstruction was higher than 50%; these ions are excluded from the factors presented here. Ulbrich et al. (2009) suggest that poor retrieval of ions with less than 5% of total signal is not uncommon.

2.4 Calculations of OH reactivity and volatility

To characterize key chemical properties of the emission profiles derived from PMF analysis, we compare the OH reactivity and volatility of VOCs in each profile. These calculations require conversion of the emission profiles from instrument signal (ncps) to mixing ratio (ppbv). Fragment ions, cluster ions, and ions not well fitted by PMF were excluded from the 574 ions used in PMF analysis and calibration factors were applied to the remaining 400 ions to convert them to mixing ratio. Of these, 156 have known VOC contributors, and account for 90% of the



total instrument signal of non-primary and non-contaminant ions between m/z 12-217. (This corresponds to an average of 92% of the total VOC concentration detected by PTR-ToF-MS). Details on identification of the VOC contributors to ion masses and calibration are described by Koss et al. (2017).

We quantified the importance of the 156 identified ions to OH chemistry by multiplying the VOC + OH reaction rate coefficient ($\text{cm}^3/\text{molecule}/\text{sec}$) with the VOC fraction in the profile (ppbv VOC/ppbv of total VOC emitted) with a scaling factor to convert from VOC molar emission (ppbv VOC) to number density ($\text{molecule}/\text{cm}^3$ at experimental conditions of 900 mbar and 26°C). The resulting OH reactivity is in units of per second per ppbv of total VOCs measured with PTR-ToF-MS ($1/\text{sec}/\text{ppbv}$ of total VOC emitted). For ions with more than one contributor, a weighted average rate constant was determined. Rate constants were taken from the literature (Atkinson and Arey, 2003; NIST Chemical Kinetics Database; Cicerone and Zellner, 1983; Gilman et al., 2015) or estimated from structurally similar VOCs. Details can be found elsewhere (Koss et al., 2017).

We also quantified volatility using the saturation concentration at 25°C (C_0 , $\mu\text{g m}^{-3}$). Saturation concentrations were taken from the literature (Rumble, 2017-2018; NIST Chemistry WebBook; Yaws, 2015) where possible, and otherwise estimated based on the elemental composition of the ion (Li et al., 2016). Volatility determined from elemental composition is uncertain, especially for compounds with very low volatility where the uncertainty can be several orders of magnitude (Li et al., 2016). We determined volatility for the 400 non-fragmentary ions. We define volatility bins as follows, after Li et al. (2016): volatile organic compounds (VOC, $C_0 > 3 \times 10^6 \mu\text{g m}^{-3}$), intermediate volatility compounds (IVOC, $300 < C_0 < 3 \times 10^6 \mu\text{g m}^{-3}$), and semivolatile compounds (SVOC, $0.3 < C_0 < 300 \mu\text{g m}^{-3}$). Separation into such volatility bins is commonly used as an aid to discussion of SOA formation potential and gas/particle partitioning (Donahue et al., 2011).

211

212

213 3 Results and discussion

214 3.1 Two-factor parameterization of VOC emissions from biomass burning

Figure 1a shows the time series of selected VOC ion signals from burning a representative mixture of Ponderosa pine fuels. In these lab fires, total VOC emissions (red line in Figure 1a)



often increase immediately and substantially during the initial combustion (for 98 seconds after starting the burn in this example), and then total emissions gradually decrease as the flames die out. Emissions of individual VOCs can be seen to fall into two categories: (i) higher emissions during the first part of the fire, e.g. naphthalene, which correlates with the PMF factor we will largely attribute below to high-temperature pyrolysis (blue line in Figure 1a), and (ii) higher emissions during the latter part of the fire, e.g., syringol, which correlates with the PMF factor we will attribute below to low-temperature pyrolysis (green line in Figure 1a). This separation into two categories is typical for most fires, with a few exceptions discussed later (e.g., burns of duff and rotten wood).

These two PMF factors (Figure 1b) describe the total VOC emissions remarkably well for most fuels: the differences between the measured ion signals and the calculated ion signals based on the PMF fits are less than 15% on average (Table S1b). For most of the fuels, the time series of the first and second factors are strongly correlated with those of naphthalene and syringol, respectively (correlation coefficient (r) > 0.90). In this work, we primarily attribute these two factors to high-temperature pyrolysis and low-temperature pyrolysis, respectively, and will use these names to describe these factors. The main source of VOC emissions is pyrolysis of fuel biopolymers, and *not* the flaming and/or gasification combustion processes that are described by MCE and often referenced in biomass burning literature. Our association between the factors and pyrolysis temperature is related more rigorously to the distribution of products observed as a function of pyrolysis temperature in the next section. When allowing more than two factors in PMF, the time series and mass spectral profiles of the additional factors can be represented as an “intermediate” or “splitting” of high- and/or low-temperature factors which can be described by a linear combination of the two factors. As examples, Figures S2 and S3 show the correlation between n -factor solutions ($n = 3, 4$) and PMF results from high- and low-temperature factors for Ponderosa pine datasets. This suggests that only two factors, i.e., high- and low-temperature pyrolysis factors, were needed to explain most of the variability we observed for the VOC emissions from biomass burning.

There are notable exceptions to the two-factor solution, including an infrequently observed, but important, third factor that we call a “distillation” factor, and a fourth profile observed during burns of duff. Several fires contain a distillation phase, in which a brief burst of VOCs, typically enriched in terpenes, is emitted immediately prior to ignition. However, PMF captured this phase



for only a limited number of burns in which the distillation phase contained sufficient gas-phase emissions and lasted long enough (~30 seconds). When a two-factor solution is used, the terpenes are largely grouped with the high-temperature pyrolysis factor. Duff is defined as a “layer of moderately to highly decomposed leaves, needles, fine twigs, and other organic material found between the mineral soil surface and litter layer of forest soil” (Reardon, 2007). The duff PMF solutions have residuals larger than 80% when solved with only two factors. This means that duff burns have a unique VOC emission pattern that cannot be explained by only high- and low-temperature factors. These exceptions are discussed in more detail later.

3.2 VOC emission profiles of high- and low-temperature pyrolysis factors

The mass spectral profiles of the relative abundances of emitted VOCs for the individual PMF factors obtained from a given fuel type are similar for replicate burns of the same fuel type. When comparing the PMF profiles for two individual burns of the Ponderosa pine realistic mixture, the Pearson correlation coefficient (r) is higher than 0.96 for both the high- and low-temperature pyrolysis factors (Figure 2a). Importantly, the mass spectra for the high-temperature pyrolysis factor are also very similar between different fuels, and the same is true for the low-temperature pyrolysis factor. For example, the correlations of each profile between (i) Douglas fir and Ponderosa pine, (ii) Manzanita (chaparral) and Ponderosa, and (iii) Bear grass and Ponderosa have a slope near 1 and $r \geq 0.91$ (Figures 2b-d). In contrast, the correlation between the high- and low-temperature mass spectra is lower ($r < 0.86$ as clearly seen in Figure 2e). Figure 3 shows the average VOC emission profiles of the two factors obtained using PMF results of 15 different fuels. The fractions of individual ion peaks in the emission profiles are summarized in Table S2. These average profiles are in good agreement with profiles of individual fuels: a best fit of $0.96 < \text{slope} < 1.04$ and $r > 0.92$, except for high-temperature factor of Excelsior with $r = 0.83$ (Table S1c and Figure S4). Excelsior is an unusual fuel in that it consists of fine shavings of a single fuel component (wood). VOC composition in high- and low-temperature profiles is discussed in Section 3.3.1.

For most emitted VOCs, their relative contributions from the high-temperature versus low-temperature factors are qualitatively related to the temperature of the pyrolysis reactions thought to be the main production mechanism of the VOCs, such as depolymerization, fragmentation, and aromatization (Yokelson et al., 1996; Yokelson et al., 1997; Collard and Blin, 2014; Liu et



al., 2016). Figure 4a shows the contribution of each factor to selected pyrolysis products from major fuel biopolymers, i.e., hemicellulose, cellulose, and lignin. The contributions of individual VOCs are expressed by their normalized fractions ($F_{\text{high-T}}$ and $F_{\text{low-T}}$) of high- and low-temperature factors: $F_{\text{high-T}} = \text{Fraction}_{\text{high-T}} / (\text{Fraction}_{\text{high-T}} + \text{Fraction}_{\text{low-T}})$ and $F_{\text{low-T}} = \text{Fraction}_{\text{low-T}} / (\text{Fraction}_{\text{high-T}} + \text{Fraction}_{\text{low-T}})$, where $\text{Fraction}_{\text{high-T}}$ and $\text{Fraction}_{\text{low-T}}$ correspond to fractions (in ppbv/total VOC ppbv) of individual species in the high- and low-temperature VOC profiles (Figure 3), respectively. Figure 4b also shows the relationship between pyrolysis temperature and representative products for individual biopolymers as reported in the literature (Collard and Blin, 2014). During the heating of biomass, different chemical bonds within the biopolymers are broken, which results in the release of VOCs and in rearrangement reactions within the matrix of the residue. Low temperature pyrolysis breaks the bonds between the monomer units of the polymers. Depolymerization in lignin (300-500 °C) produces guaiacols, (iso)eugenol, and syringol. Furans and furfurals are dominantly formed from cellulose and hemicellulose (300-400 °C). These compounds have a higher contribution from the low-temperature factor ($F_{\text{low-T}} = 60\text{-}100\%$). Higher temperatures allow reaction of functional groups and covalent bonds in polymers and monomers. The resulting fragmentation emits various VOCs: for example, hydroxyacetone, acetaldehyde, and acetic acid from depolymerization of cellulose and/or hemicellulose. These VOCs have roughly equal contributions from low- and high-temperature factors. The release of oxygenated compounds during depolymerization and fragmentation increases the carbon percentage of the residual biopolymers. Benzene rings and aromatic polycyclic structures form, which is termed char. Higher temperature pyrolysis breaks progressively stronger bonds in char (> 500 °C). This aromatization process gives off aromatic compounds with short substituents (e.g., phenol), non-substituted aromatics (e.g., benzene), and polycyclic aromatic hydrocarbons (PAHs such as naphthalene). Most of those aromatics have a large contribution from the high-temperature factor ($F_{\text{high-T}} = 60\text{-}100\%$). As the temperature increases, substituents of the aromatic rings disappear and PAHs are dominantly produced. This is consistent with the contribution of the high-temperature factor to phenol ($F_{\text{high-T}} = 60\%$), benzene (77%), and naphthalene (92%).

The VOCs that comprise the two profiles mostly consist of the pyrolysis products described above and their analogs. During a fire, the emissions of any particular VOC can be described by a linear combination of the high-temperature and low-temperature pyrolysis time series. Some



VOCs are emitted mainly from the high-temperature pyrolysis; some mainly from the low-temperature profile; and others have a mixed contribution. This is quantified by $F_{\text{high-T}}$ as described above. We sorted the VOCs by $F_{\text{high-T}}$, to show how the chemical composition of emissions changes from high- to low-temperature pyrolysis process. Figure 5 shows the chemical characteristics of compounds that are mostly emitted in the high-temperature pyrolysis ($F_{\text{high-T}} = 80\text{-}100\%$ in panel (a)), mostly emitted in the low-temperature pyrolysis ($F_{\text{high-T}} = 0\text{-}20\%$ in panel (e)), or have mixed contributions from both pyrolysis ($F_{\text{high-T}} = 60\text{-}80\%$ in panel (b), $40\text{-}60\%$ in (c), and $20\text{-}40\%$ in (d)). $F_{\text{high-T}}$ of each individual VOC is shown in Figure S5. In the category emitted mostly by the high-temperature pyrolysis, important compounds include alkyl-substituted aromatics and aliphatic alkenes (Figures 5a and b), whereas carbonyls have more equal contributions from the high- and low-temperature pyrolysis processes. It should be noted that terpenes (e.g., (oxygenated) monoterpenes and isoprene) emitted from distillation are grouped with the high-temperature pyrolysis (Figures 5a and b; Section 3.6).

Several nitrogen (N)-containing compounds also fall into high or low temperature categories consistent with behavior previously reported in the literature. The main N-containing compounds detected by PTR-ToF-MS are isocyanic acid (HNCO), nitrous acid (HONO), hydrogen cyanide (HCN), and ammonia (NH_3). HNCO, HONO, and HCN have a high contribution of the high-temperature factor ($F_{\text{high-T}} = 80\text{-}100\%$ in Figure 5a), while NH_3 falls into the category with a large contribution from the low-temperature factor ($F_{\text{low-T}} = 86\%$ in Figure 5e). Nitrogen in biomass typically exists as amino acids/proteins and pyrrole/pyridine (aromatic N-heterocycles). During the pyrolysis of those N-functionalities at high temperature ($700\text{-}1100\text{ }^\circ\text{C}$), HCN is identified as the main product in most cases (Johnson and Kang, 1971; Haidar et al., 1981; Patterson et al., 1968; Houser et al., 1980). NH_3 , resulting from the lower-temperature pyrolysis of proteins, has been classified as smoldering combustion gases and falls here into the low temperature profile (Yokelson et al., 1996).

The present analysis predominantly focuses on VOCs. The VOC emissions from biomass burning are dominated by pyrolysis reactions of biopolymers. However, this does not mean that emissions of all species are related to pyrolysis. For example, flaming combustion releases CO_2 , NO_x , HONO, and black carbon, etc. This is a separate process and cannot be expected to be captured by our VOC framework.



341 3.3 Chemical characteristics of VOC emissions depending on pyrolysis temperature

342 3.3.1 VOC composition

343 The VOC emission profiles for the high- and low-temperature factors are shown in Figure 3
344 and they mainly consist of hydrocarbons, oxygenates with $n=1-7$ oxygen atoms, and nitrogen-
345 and/or sulfur-containing hydrocarbons (Figure 6). In each emission profile, about half of the
346 fraction (in ppbv) is accounted for by a combination of the following seven compounds: (i)
347 ethene (C_2H_4), (ii) formaldehyde ($HCHO$), (iii) methanol (CH_3OH), (iv) acetaldehyde
348 (CH_3CHO), (v) acrolein ($CH_2=CHCHO$), (vi) acetic acid (CH_3COOH) and glycolaldehyde
349 ($HOCH_2CHO$), and (vii) ammonia (NH_3). The other half includes several fundamental structures,
350 with a variety of functionalities, as discussed later. Oxygenates with one oxygen are predominant
351 in both emission profiles, accounting for 39% of molar emissions in the high-temperature profile
352 and 36% in the low-temperature profile. Emissions of highly oxygenated compounds (≥ 2
353 oxygen atoms) and ammonia are higher in the low-temperature profile than in the high-
354 temperature profile. The fractions of hydrocarbons and compounds that contain both N and O,
355 such as $HNCO$, are lower in the low-temperature profile.

356 VOCs emitted from biomass burning can be generally organized into major structural groups:
357 furans, aromatics, oxygenated aromatics, aliphatic compounds, and so on. Within each structural
358 category, compounds can have various functionalities, such as alcohol or alkene substituents
359 (Hatch et al., 2015). VOC composition classified by 11 structures and 17 functionalities is shown
360 in Figures 7 and 8. Some VOCs have multiple functional groups. These are counted once in each
361 relevant category. For example, guaiacol is counted in “Oxygenated aromatic” structural
362 category as “Alcohol” and “Ether (methoxy)” functional groups.

363 The most dominant emissions are attributable to aliphatic oxygenates, i.e., 62% of molar
364 emissions in the high-temperature profile and 60% in the low-temperature profile (Figure 7).
365 This is due to the specific compounds (ii)-(vi) described above. The low-temperature profile is
366 twice as rich in aromatic oxygenates (≥ 2 oxygen atoms) and furans as the high-temperature
367 profile, while the high-temperature profile is enriched in aliphatic (mostly alkenes) and aromatic
368 hydrocarbons. Terpenes (including isoprene, monoterpenes, sesquiterpenes, and oxygenated
369 monoterpenes) emitted from distillation, not from pyrolysis, are dominantly grouped with the
370 high-temperature factor. Compared to the low-temperature profile, the high-temperature profile
371 is enriched in the following functional groups: C-C double bond ($>C=C<$), C-C triple bond ($-$



372 $\text{C}\equiv\text{C}$ -), diene ($\text{>C}=\text{C}-\text{C}=\text{C}<$), polycyclic aromatic hydrocarbon (PAH), nitrile ($-\text{C}\equiv\text{N}$), amide ($-\text{C}(=\text{O})-\text{N}-$), nitro ($-\text{NO}_2$), nitrate ($-\text{NO}_3$), thiol/sulfide ($-\text{S}(\text{H})$) (Figure 8). The low-temperature
 373 profile is enriched in alcohols ($-\text{OH}$), ethers (mostly methoxy groups: $-\text{O}-\text{CH}_3$), esters ($-\text{C}(=\text{O})-\text{O}-$), and amines ($-\text{NH}_2$; mostly ammonia). The emissions of compounds with carbonyl groups
 374 ($\text{>C}=\text{O}$) and acids ($-\text{C}(=\text{O})-\text{OH}$) are similar. These results are consistent with the contributions
 375 of VOC to the high- and low-temperature factors described in Section 3.2.
 376
 377

378

379 3.3.2 OH reactivity

380 The hydroxyl radical (OH) is an important driver of daytime oxidation chemistry.
 381 Quantifying the VOC reactivity with OH provides insight into which VOC emissions may be
 382 most important for ozone and secondary organic aerosol (SOA) formation. Interestingly, the two
 383 profiles have a similar average per-molecule (weighted by abundance) rate constant with OH:
 384 $15.7 \times 10^{-12} \text{ cm}^3/\text{molecule/s}$ for the high-temperature profile and $15.8 \times 10^{-12} \text{ cm}^3/\text{molecule/s}$ for
 385 the low-temperature profile. However, the reactivity is provided by very different VOCs in each
 386 profile. Aliphatic oxygenates are important in both profiles, but more so in the high-temperature
 387 profile (30% of reactivity) than in the low-temperature profile (24% of reactivity). In the high-
 388 temperature profile, the reactivity also has a large contribution from terpenes and aliphatic
 389 hydrocarbons, while in the low-temperature profile, the reactivity is largely due to furans and
 390 aromatics (Figure 9a). Since the total VOC emissions in real-world fires come from a mixture of
 391 the high- and low- temperature pyrolysis factors, the total OH reactivity can be estimated from
 392 the relative importance of the high- and low-temperature pyrolysis in a given fire.
 393

393

394 3.3.3 Volatility

395 Volatility is another important chemical characteristic affecting secondary organic aerosol
 396 (SOA) yield and formation rate. The low-temperature emission profile contains more compounds
 397 that are of higher molecular weight, more oxygenated, and of lower volatility (Figure 9b). The
 398 SOA yields of many of these compounds are unknown, but the lower volatility and higher
 399 oxygen content of the low-temperature profile suggests a potentially more efficient SOA
 400 formation. We note that the compounds with $\text{C}_0 < 10^2 \mu\text{g m}^{-3}$ shown in Figure 9b should be
 401 primarily in the particle phase and not measureable by PTR-MS without long delay times
 402 (Pagonis et al., 2017). However, the volatility of these compounds (calculated from the elemental



composition) has an uncertainty of several orders of magnitude. Also, the cyclic compounds that are abundant in the low-temperature profile, such as aromatic oxygenates, produce multifunctional ring-opening-products that are known to be efficient SOA precursors (Yee et al., 2013). In a similar manner to the OH reactivity, the total volatility distribution can be estimated from the relative importance of the high- and low-temperature pyrolysis in a given fire.

3.4 Relationship of fuel characteristics to relative importance of high- and low-temperature pyrolysis factors

To use the PMF profiles (Figure 3) for estimates of VOC emissions from other fires, it is necessary to know the relative fire-integrated contributions of high- and low-temperature pyrolysis for those fires. As a step in this direction, in the present work, we found that fire-integrated molar emission ratios of total VOCs from high-temperature pyrolysis to low-temperature pyrolysis, $\sum \text{VOC}_{\text{high-T}}$ (in ppbv)/ $\sum \text{VOC}_{\text{low-T}}$ (in ppbv), are related to which parts of the plants are burned (blue bars in Figure 10). When leafy fuels (i.e., canopy, shrub, and herbaceous fuels) are burned, the fraction of total VOC emissions originating from high-temperature pyrolysis is higher than those from low-temperature pyrolysis. These results imply that surface-to-volume ratios and the content of biopolymers in a given fuel can strongly affect the relative importance of high- and low-temperature pyrolysis. Leaves have high surface-to-volume ratios and despite higher fuel moisture, at least the surface may tend to heat up easily, resulting in a higher contribution from the high-temperature factor. The higher monoterpene content of foliage may explain why low-temperature distillation products like monoterpenes are associated with the high-T pyrolysis factor.

In contrast, the burn of rotten wood was found to contain VOC emissions from low-temperature pyrolysis only. Our brown rotten wood samples were enriched in lignin (Kirk and Cowling, 1984). Lignin is relatively resistant to thermal decomposition compared to cellulose and hemicellulose. The temperature range where pyrolytic decomposition occurs significantly is 280-500 °C for lignin, 240-350 °C for cellulose, and 200-260 °C for hemicellulose (Liu et al., 2016; Babu, 2008), as shown in Figure 4b. In our laboratory fires, the rotten wood first smoldered for an extended period, and then flames were observed. However, only the low-temperature profile was observed. This suggests that it is more difficult for lignin-rich fuels to reach high enough temperatures to emit the “high-temperature pyrolysis” VOCs. Therefore, we



do not see the same gradient in pyrolysis products that is observed for other fuel burns mainly consisting of cellulose and hemicellulose. Nitrogen content and speciation also vary between different biomass components, and temperature and differences in biopolymer content have been shown to strongly affect the composition of nitrogen-containing emissions (Hansson et al., 2004; Ren et al., 2011; Coggon et al. 2016). This is consistent with the observed differences in nitrogen speciation between the two profiles.

3.5 High- and low-temperature pyrolysis profiles describe total VOC emissions

Previous studies have found a correlation between the emission factors of certain VOCs and the fire-integrated modified combustion efficiency (MCE) (Yokelson et al., 1996; Yokelson et al., 1997; Selimovic et al., 2017). Thus, one might expect that the high- and low-temperature pyrolysis factors would also show a strong relationship to MCE. However, MCE does not parameterize the relative amounts of high- and low-temperature pyrolysis products very well (red bars in Figure 10). The basic reason is that the CO₂ emission is overwhelmingly from flaming combustion, which is *not* the main source of most VOC emissions, and is not expected to correlate with a linear combination of the high- and low-temperature pyrolysis processes, while CO emissions are reasonably well correlated with an average of high- and low-temperature emissions (Figure S6). CO₂ and the PMF profiles are not correlated in rotten wood burns. The CO₂ emissions are enhanced by shifting from the smoldering to flaming combustion, but VOC emission patterns are not changed from the low- to high-temperature pyrolysis (Figure S6). Consequently, CO₂ and MCE, which indicate the separation between flaming and smoldering combustions, are not appropriate to estimate the high-/low-temperature pyrolysis VOC emissions.

Studies of laboratory burns and wildfires have reported variable emission ratios (or factors) for various VOCs, even for similar fuel types. Here we investigate how well total VOC emissions in biomass burning can be fit by the average VOC emission profiles (Figure 3) using emission factors and ratios reported in the literature for laboratory and field burns (Gilman et al., 2015; Stockwell et al., 2015; Akagi et al., 2011). When fitting the present high- and low-temperature factors to the other biomass burning data, total VOC emissions can be described with different relative fractions of the factors (Figure S7). For example, the best fit to a laboratory study by Gilman et al. (2015), using fuels from southwestern, southeastern, and



northern U.S. (e.g., pine, spruce, fir, chaparral, mesquite, and oak), includes 32% high-temperature and 68% low-temperature VOC emissions; for another laboratory study by Stockwell et al. (2015) including several types of grass, spruce, and chaparral, 59% high-temperature and 41% low temperature; temperate forest fires reported by Akagi et al. (2011), 77% high temperature and 23% low temperature, while in the case of chaparral fires, 48% high-temperature and 52% low temperature. The fitting can be done with high correlation coefficient ($r \geq 0.92$) for all the literature data (Figure S7). This is further evidence that at most two factors can explain the majority of VOC variability.

473

3.6 Emission of specific compounds

3.6.1 Distillation phase

At the beginning of many burn experiments, a white smoke is visible immediately prior to ignition. This “distillation phase” does not result from pyrolysis or combustion, but rather a gradual heating and release of water and volatile compounds trapped within the biomass. This phase of the fire was not distinguished by PMF. The distillation phase from coniferous fuels is enriched in some compounds highly relevant to atmospheric chemistry, especially terpenes (Koss et al., 2017). But this phase lasts only a short time (typically less than 10 seconds), in which only a short spike in emissions is observed. Accordingly, PMF cannot capture this phase effectively even if a large number of factors is chosen. As an exception, the distillation phase of Sage, enriched in terpenes and a specific oxygenated monoterpene (camphor), can be distinguished as a third PMF factor, because that phase lasted longer than 30 seconds in that fire. The reported overall residual of 15% includes the poorly fitted distillation phase, and we stress that it typically accounts for only a small portion of the overall emissions. Additionally, with the exception of terpenes, the composition of the distillation profile is similar to that of the high-temperature profile.

For some fuel burns other than coniferous fuels (e.g., Manzanita), VOC emissions during the distillation phase are quite small, although distillation smoke is visible. In these cases, PMF incorporates this phase into the low-temperature pyrolysis factor. There may be a relationship between the VOC emission process coincident with distillation (low- or high-temperature) and the presence of visible smoke. For instance, perhaps here the temperatures are low enough that the compounds are able to re-condense into visible smoke.



496

497 **3.6.2 Duff burn**

498 A fourth factor can be resolved from the PMF analysis of duff burns. The distribution of
499 VOC structures and functionality in the duff emission profiles (Figure 11a) is similar to the low-
500 temperature pyrolysis profile (Figure 11b). The major difference is much higher emission of
501 aliphatic nitrogen-containing compounds: 56% more of these compounds are emitted per-ppbv
502 VOC in the duff profile than in the low-temperature profile. The additional emissions are mostly
503 nitriles and amides, especially hydrogen cyanide (HCN), acetonitrile, and acetamide. Pyrroles
504 and pyridines are also enhanced, but are much less abundant overall.

505 The organic portion of duff is enriched in nitrogen relative to other components of coniferous
506 fuels. The nitrogen to carbon ratio in the Subalpine fir duff (N:C ratio = 0.028 by weight) was a
507 factor of 2.1 higher than the average of other Subalpine fir components, and the Engelmann
508 spruce duff N:C ratio (0.022) was 1.3 times higher than other Engelmann spruce components.
509 Coggon et al. (2016), who investigated VOC emissions from the burning of herbaceous and
510 arboraceous fuels, also found that the nitrogen-containing fraction of VOCs emitted from
511 biomass burning increased with the nitrogen content of the fuel.

512 However, the nitrogen content cannot entirely explain why duff has a unique emission profile.
513 Other fuels, such as Ceanothus and Ponderosa pine litter, have similar N:C ratios (0.025, 0.024,
514 and 0.022, respectively) but are explained well by the 2-factor PMF solution consisting of high-
515 and low-temperature pyrolysis factors. The contradiction may be due to differences in the
516 speciation of nitrogen-containing organics. In woody and leafy fuels, proteins and amino acids
517 account for 80-85% of the organic nitrogen (Ren and Zhao, 2015). In soils, proteins account for
518 typically only 40% of organic nitrogen, and heterocyclic nitrogen compounds (pyrroles and
519 pyridines) account for 35% (Schulten and Schnitzer, 1997). Pyrolysis of nitrogen heterocycles
520 releases HCN, while proteins and amino acids may release more NH₃ (Leppälahti and Koljonen,
521 1995). This is consistent with the higher HCN and nitriles characteristic of the duff emission
522 profile.

523

524 **3.6.3 Variation in specific VOCs between fuels**



When comparing emission profiles of individual fuels to the average profiles shown in Figure 3, there are some specific compounds whose emissions are notably higher ($> \times 5$) or lower ($< \times 0.2$) than the average (Figure S4). Here we highlight several key features:

- (i) For Ponderosa/Lodgepole/Loblolly pines, Douglas/Subalpine firs, and Juniper, the emission of benzoquinone ($\text{C}_6\text{H}_4\text{O}_2 \cdot \text{H}^+$, m/z 109.028) is quite low in the high-temperature pyrolysis: 7-21% of the average emission for the pines and firs, and 2% for Juniper (Figures S4a-1~4, 6, and 7).
- (ii) For fuels other than coniferous fuels and Sage, i.e., Bear grass, Excelsior, Ceanothus, Chamise, and Manzanita, emissions of monoterpenes ($\text{C}_{10}\text{H}_{16} \cdot \text{H}^+$, m/z 137.132) are only 2-15% of the average (Figures S4a-8~14).
- (iii) Excelsior emits especially low quantities of nitrogen-containing compounds, especially nitriles (hydrogen cyanide, acetonitrile, acrylonitrile, and propane nitrile) and pyridine, in the high-temperature pyrolysis (Figure S4a-9). This is because the nitrogen content in Excelsior is significantly lower than other fuels. The Excelsior N:C ratio (0.005 by weight) is 3.6 times lower than the average of other fuels (0.017 ± 0.006).
- (iv) High-temperature pyrolysis of Ceanothus produces quite high emission of benzofuran-type compounds (Figure S4a-10). Benzofuran ($\text{C}_8\text{H}_6\text{O} \cdot \text{H}^+$, m/z 119.049) and methylbenzofuran and possibly its isomer such as cinnamaldehyde ($\text{C}_9\text{H}_8\text{O} \cdot \text{H}^+$, m/z 133.065) are 5.5 and 10.1 times higher than the average, respectively.
- (v) Sage specifically emits camphor ($\text{C}_{10}\text{H}_{16}\text{O} \cdot \text{H}^+$, m/z 153.127) in high-temperature pyrolysis (Figure S4a-15).
- (vi) There are a limited number of exceptions in low-temperature profiles (Figure S4b). This means that low-temperature pyrolysis gives almost identical VOC emissions, independent of fuel types.

4 Conclusions

This work focused on interpretation of VOC emissions from biomass burning. We provided an understanding of VOC variability based on known chemical and physical processes to release VOCs from fires. We explained most of the observed variability between VOC emissions from fuel types and over the course of a fire using just two emission profiles: (i) high-temperature



556 pyrolysis profile and (ii) low-temperature pyrolysis profile. The results are summarized as
557 follows:

- 558 1. The two profiles can explain the variability in VOC emissions composition between
559 different fuel types and over the course of individual fires, with an average residual of <
560 15%.
- 561 2. The high-temperature profile is quantitatively similar between different fuel types ($r >$
562 0.92), and likewise for the low-temperature profile.
- 563 3. The two profiles are significantly different in terms of VOC composition, volatility, and
564 contributors to OH reactivity. The high-temperature pyrolysis profile is enriched in
565 aliphatic unsaturated hydrocarbons, (polycyclic) aromatic hydrocarbons, terpenes
566 (emitted from distillation), HCN, HNCO, and HONO. The resulting OH reactivity is
567 primarily attributed to terpenes, aliphatic hydrocarbons, and non-aromatic oxygenates.
568 The low-temperature pyrolysis profile is enriched in aromatic oxygenates, furans, and
569 NH_3 . The OH reactivity is contributed significantly by furans and aromatics.
- 570 4. The fire-integrated molar emission ratios of total VOCs from high-temperature
571 pyrolysis to low-temperature pyrolysis are related to the biopolymer composition and
572 surface-to-volume ratios of fuels. Higher surface-to-volume ratios lead to total VOC
573 emissions enriched in products resulting from high-temperature pyrolysis than from
574 those resulting from low-temperature pyrolysis.
- 575 5. The two VOC profiles can model previously reported VOC data for laboratory and field
576 burns ($r \geq 0.92$).
- 577 6. MCE, which parameterizes flaming and smoldering combustion, is not appropriate to
578 estimate the high-/low-temperature pyrolysis VOC emissions. This suggests that the
579 high- and low-temperature pyrolysis profiles may provide information on emissions that
580 is not accessible with a broader definition of smoldering combustion implicit in the use
581 of MCE.
- 582 7. Duff burns emit a specific VOC profile which is similar to that of low-temperature
583 pyrolysis, but additionally includes aliphatic nitrogen-containing compounds, especially
584 HCN, acetonitrile, and acetamide.

585 Our framework provides a way to understand VOC emission variability in other laboratory and
586 field studies of biomass burning.



587 Future work should include a quantitative comparison of the VOC PMF results to
588 measurements of aerosol, inorganic gases, and organic species not measured by PTR-ToF-MS.
589 Such a comparison would help define the relationship between VOCs and characteristics of
590 primary organic aerosol (POA). We note that the primary aerosols have also been shown to have
591 distinct profiles that correlate with different pyrolysis and combustion processes in the fire
592 (Reece et al., 2017; Haslett et al., 2017).

593

594

595 **Acknowledgments**

596 K. Sekimoto acknowledges the Postdoctoral Fellowships for Research Abroad from Japan
597 Society for the Promotion of Science (JSPS) and a Grant-in-Aid for Young Scientists (B)
598 (15K16117) from the Ministry of Education, Culture, Sports, Science and Technology of Japan.
599 A. Koss acknowledges support from the NSF Graduate Fellowship Program. M. Coggon
600 acknowledges the Visiting Postdoctoral Fellowship from Cooperative Institute for Research in
601 Environmental Sciences (CIRES). V. Selimovic and R. J. Yokelson were supported by NOAA-
602 CPO grant NA16OAR4310100. J. de Gouw worked as a consultant for Aerodyne Research Inc.
603 during part of the preparation phase of this manuscript. We thank for support from NOAA AC4
604 external funding, and thank the USFS Missoula Fire Sciences Laboratory for their assistance and
605 cooperation. This work was also supported in part by NOAA's Climate Change and Health of the
606 Atmosphere initiatives.

607

608

609 **References**

- 610 Akagi, S. K., Yokelson, R. J., Wiedinmyer, C., Alvarado, M. J., Reid, J. S., Karl, T., Crounse, J.
611 D., and Wennberg, P. O.: Emission factors for open and domestic biomass burning for use in
612 atmospheric models, Atmos. Chem. Phys., 11, 4039-4072, [https://doi.org/10.5194/acp-11-](https://doi.org/10.5194/acp-11-4039-2011)
613 4039-2011, 2011.
- 614 Alvarado, M. J., Wang, C., and Prinn, R. G.: Formation of ozone and growth of aerosols in young
615 smoke plumes from biomass burning: 2. Three-dimensional Eulerian studies, J. Geophys. Res.,
616 114 (D9), D09307, <http://doi.org/10.1029/2008JD011186>, 2009.



- 617 Alvarado, M. J., Lonsdale, C. R., Yokelson, R. J., Akagi, S. K., Coe, H., Craven, J. S., Fischer, E.
 618 V., McMeeking, G. R., Seinfeld, J. H., Soni, T., Taylor, J. W., Weise, D. R., and Wold, C. E.:
 619 Investigating the links between ozone and organic aerosol chemistry in a biomass burning
 620 plume from a prescribed fire in California chaparral, *Atmos. Chem. Phys.*, 15 (12), 6667-6688,
 621 <http://doi.org/10.5194/acp-15-6667-2015>, 2015.
- 622 Atkinson, R. and Arey, J. Atmospheric degradation of volatile organic compounds, *Chem. Rev.*,
 623 103 (12), 4605-4638, <http://doi.org/10.1021/cr0206420>, 2003.
- 624 Babu, B. V.: Biomass pyrolysis: a state-of-the-art review. *Biofuels*, *Bioprod. Bioref.*, 2, 393-414,
 625 <http://dpo.org/10.1002/bbb.92>, 2008.
- 626 Burling, I. R., Yokelson, R. J., Griffith, D. W. T., Johnson, T. J., Veres, P., Roberts, J. M.,
 627 Warneke, C., Urbanski, S. P., Reardon, J., Weise, D. R., Hao, W. M., and de Gouw, J.:
 628 Laboratory measurements of trace gas emissions from biomass burning of fuel types from the
 629 southeastern and southwestern United States, *Atmos. Chem. Phys.*, 10, 11115-11130,
 630 <https://doi.org/10.5194/acp-10-11115-2010>, 2010.
- 631 Christian, T. J., Kleiss, B., Yokelson, R. J., Holzinger, R., Crutzen, P. J., Hao, W. M., Saharjo, B.
 632 H., and Ward, D. E.: Comprehensive laboratory measurements of biomass-burning emissions:
 633 1. Emissions from Indonesian, African and other fuels, *J. Geophys. Res.*, 108 (D23), 4719,
 634 <http://doi.org/10.1029/2003JD003704>, 2003.
- 635 Christian, T. J., Kleiss, B., Yokelson, R. J., Holzinger, R., Crutzen, P. J., Hao, W. M., Shirai, T.,
 636 and Blake, D. R.: Comprehensive laboratory measurements of biomass-burning emissions: 2.
 637 First intercomparison of open-path FTIR, and GC-MS/FID/ECD, *J. Geophys. Res.*, 109 (D2),
 638 D02311, <http://doi.org/10.1029/2003JD003874>, 2004.
- 639 Cicerone, R. J., and Zellner, R.: The atmospheric chemistry of hydrogen cyanide (HCN), *J.*
 640 *Geophys. Res.*, 88 (C15), 10689-10696, <http://doi.org/10.1029/JC088iC15p10689>, 1983.
- 641 Coggon, M. M., Veres, P. R., Yuan, B., Koss, A., Warneke, C., Gilman, J. B., Lerner, B. M.,
 642 Peischl, J., Aikin, K. C., Stockwell, C. E., Hatch, L. E., Ryerson, T. B., Roberts, J. M.,
 643 Yokelson, R. J., and de Gouw, J. A.: Emissions of nitrogen-containing organic compounds
 644 from the burning of herbaceous and arboraceous biomass: Fuel composition dependence and
 645 the variability of commonly used nitrile tracers, *Geophys. Res. Lett.*, 43(18), 9903-9912,
 646 doi:10.1002/2016GL070562, 2016.



- 647 Collard, F. X., and Blin, J.: A review on pyrolysis of biomass constituents: Mechanisms and
 648 composition of the products obtained from the conversion of cellulose, hemicelluloses and
 649 lignin, *Renew. Sustainable Energy Rev.*, 38, 594-608,
 650 <http://doi.org/10.1016/j.rser.2014.06.013>, 2014.
- 651 Donahue, N. M., Epstein, S. A., Pandis, S. N., and Robinson, A. L.: A two-dimensional volatility
 652 basis set: 1. Organic-aerosol mixing thermodynamics, *Atmos. Chem., Phys.*, 11, 3303-3318,
 653 <http://doi.org/10.5194/acp-11-3303-2011>, 2011.
- 654 Gilman, J. B., Lerner, B. M., Kuster, W. C., Goldan, P. D., Warneke, C., Veres, P. R., Roberts, J.
 655 M., de Gouw J. A., Burling, I. R., and Yokelson, R. J.: Biomass burning emissions and
 656 potential air quality impacts of volatile organic compounds and other trace gases from fuels
 657 common in the US, *Atmos. Chem. Phys.*, 15 (24), 13915-13938, [http://doi.org/10.5194/acp-](http://doi.org/10.5194/acp-15-13915-2015)
 658 [15-13915-2015](http://doi.org/10.5194/acp-15-13915-2015), 2015.
- 659 Haidar, N. F., Patterson, J. M., Moors, M., and Smith, W. T.: Effects of structure on pyrolysis
 660 gases from amino acids, *J. Agric. Food. Chem.*, 29 (1), 163-165,
 661 <http://doi.org/10.1021/jf00103a040>, 1981.
- 662 Hansson, K.-M., Samuelsson, J., Tullin, C. and Åmand, L.-E.: Formation of HNCO, HCN, and
 663 NH₃ from the pyrolysis of bark and nitrogen-containing model compounds, *Combust. Flame*,
 664 137 (3), 265–277, doi:10.1016/J.COMBUSTFLAME.2004.01.005, 2004.
- 665 Haslett, S. L., Thomas, J. C., Morgan, W. T., Hadden, R., Liu, D., Allan, J. D., Williams, P. I.,
 666 Sekou, K., Liousse, C., and Coe, H.: Highly-controlled, reproducible measurements of aerosol
 667 emissions from African biomass combustion, *Atmos. Chem. Phys. Discuss.*,
 668 <http://doi.org/10.5194/acp-2017-679>, in review, 2017.
- 669 Hatch, L. E., Luo, W., Pankow, J. F., Yokelson, R. J., Stockwell, C. E., and Barsanti, K. C.:
 670 Identification and quantification of gaseous organic compounds emitted from biomass
 671 burning using two-dimensional gas chromatography–time-of-flight mass spectrometry, *Atmos.*
 672 *Chem. Phys.*, 15, 1865-1899, <https://doi.org/10.5194/acp-15-1865-2015>, 2015.
- 673 Houser, T. J., McCarville, and M. E., Biftu, T.: Kinetics of the thermal decomposition of
 674 pyridine in a flow system, *Int. J. Chem. Kinet.*, 12 (8), 555-568,
 675 <http://doi.org/10.1002/kin.550120806>, 1980.
- 676 Jaffe, D. A., and Wigder, N. L.: Ozone production from wildfires: A critical review, *Atmos.*
 677 *Environ.*, 51, 1-10, <http://doi.org/10.1016/j.atmosenv.2011.11.063>, 2012.



- 678 Johnson, W. R., and Kan, J. C.: Mechanisms of hydrogen cyanide formation from the pyrolysis
 679 of amino acids and related compounds, *J. Org. Chem.*, 36 (1), 189-192,
 680 <http://doi.org/10.1021/jo00800a038>, 1971.
- 681 Kirk, T. K., and Cowling, E. B.: Biological decomposition of solid wood, *Adv. Chem.*, 207 (12),
 682 455-487, <http://doi.org/10.1021/ba-1984-0207.ch012>, 1984.
- 683 Koss, A. R., Sekimoto, K., Gilman, J. B., Selimovic, V., Coggon, M. M., Zarzana, K. J., Yuan,
 684 B., Lerner, B. M., Brown, S. S., Jimenez, J. L., Krechmer, J., Roberts, J. M., Warneke, C.,
 685 Yokelson, R. J., and de Gouw, J.: Non-methane organic gas emissions from biomass burning:
 686 identification, quantification, and emission factors from PTR-ToF during the FIREX 2016
 687 laboratory experiment, *Atmos. Chem. Phys. Discuss.*, <https://doi.org/10.5194/acp-2017-924>,
 688 in review, 2017.
- 689 Leppälähti, J., and Koljonen, T.: Nitrogen evolution from coal, peat and wood during
 690 gasification: Literature review, *Fuel Process. Technol.*, 43, 1-45, [http://doi.org/10.1016/0378-](http://doi.org/10.1016/0378-3820(94)00123-B)
 691 [3820\(94\)00123-B](http://doi.org/10.1016/0378-3820(94)00123-B), 1995.
- 692 Li, Y., Pöschl, U., and Shiraiwa, M.: Molecular corridors and parameterizations of volatility in
 693 the chemical evolution of organic aerosols, *Atmos. Chem. Phys.*, 16 (5), 3327-3344,
 694 <http://doi.org/10.5194/acp-16-3327-2016>, 2016.
- 695 Liu, W. -J., Li, W. -W., Jiang, H., and Yu, H. -Q.: Fates of chemical elements in biomass during
 696 its pyrolysis, *Chem. Rev.*, 117 (9), 6367-6398, <http://doi.org/10.1021/acs.chemrev.6b00647>,
 697 2016.
- 698 Mackie, J. C., Colket, M. B., III, and Nelson, P. F.: Shock tube pyrolysis of pyridine, *J. Phys.*
 699 *Chem.*, 94 (10), 4099-4106, <http://doi.org/10.1021/j100373a040>, 1990.
- 700 Manion, J. A., Huie, R. E., Levin, R. D., Burgess D. R., Jr., Orkin, V. L., Tsang, W., McGivern,
 701 W. S., Hudgens, J. W., Knyazev, V. D., Atkinson, D. B., Chai, E., Tereza, A. M., Lin, C. -Y.,
 702 Allison, T. C., Mallard, W. G., Westley, F., Herron, J. T., Hampson, R. F., and Frizzell, D. H.:
 703 NIST Chemical Kinetics Database, NIST Standard Reference Database 17, Version 7.0 (Web
 704 Version), Release 1.6.8, Data version 2015.12, National Institute of Standards and
 705 Technology, Gaithersburg, Maryland, 20899-8320. Web address: <http://kinetics.nist.gov/>,
 706 last access: 28 November 2017, 2017.




- 707 Naeher, L. P., Brauer, M., Lipsett, M., Zelikoff, J. T., Simpson, C. D., Koenig, J. Q., and Smith,
 708 K. R.: Woodsmoke health effects: A review, *Inhal. Toxicol.*, 19 (1), 67-106,
 709 <https://doi.org/10.1080/08958370600985875>, 2007.
- 710 NIST Chemistry WebBook, Web address: <http://webbook.nist.gov/chemistry/>, last access: 28
 711 November 2017, 2017.
- 712 Paatero, P., and Tapper, U.: Positive matrix factorization: A non-negative factor model with
 713 optimal utilization of error estimates of data values, *Environmetrics*, 5 (2), 111-126,
 714 <http://doi.org/10.1002/env.3170050203>, 1994.
- 715 Paatero, P.: Least squares formulation of robust non-negative factor analysis, *Chemometr. Intell.*
 716 *Lab.*, 37 (1), 23-35, [https://doi.org/10.1016/S0169-7439\(96\)00044-5](https://doi.org/10.1016/S0169-7439(96)00044-5), 1997.
- 717 Pagonis, D., Krechmer, J. E., de Gouw, J. A., Jimenez, J. L. and Ziemann, P. J.: Effects of gas-
 718 wall partitioning in Teflon tubing and instrumentation on time-resolved measurements of gas-
 719 phase organic compounds, *Atmos. Meas. Tech.*, 10, 4687–4696, doi:10.5194/amt-2017-279,
 720 2017.
- 721 Patterson, J. M., Tsamasfyros, A., and Smith, W. T.: Pyrolysis of pyrrole, *J. Heterocycle Chem.*,
 722 5 (5), 727-729, <http://doi.org/10.1002/jhet.5570050527>, 1968.
- 723 Reardon, J.: Duff. *In: FireWords: Fire Science Glossary* [electronic]. U.S. Department of
 724 Agriculture, Forest Service, Rocky Mountain Research Station, Fire Science Laboratory
 725 (Producer). Available: <http://www.firewords.net>, last update 2007.
- 726 Reece, S. M., Sinha, A., and Grieshop, A. P.: Primary and photochemically aged aerosol
 727 emissions from biomass cookstoves: Chemical and physical characterization, *Environ. Sci.*
 728 *Technol.*, 51 (16), 9379-9390, <http://doi.org/10.1021/acs.est.7b01881>, 2017.
- 729 Ren, Q., Zhao, C., Chen, X., Duan, L., Li, Y. and Ma, C.: NO_x and N₂O precursors (NH₃ and
 730 HCN) from biomass pyrolysis: Co-pyrolysis of amino acids and cellulose, hemicellulose and
 731 lignin, *Proc. Combust. Inst.*, 33(2), 1715–1722, <http://doi.org/10.1016/J.PROCI.2010.06.033>,
 732 2011.
- 733 Ren, Q., and Zhao, C.: Evolution of fuel-N in gas phase during biomass pyrolysis, *Renew. Sust.*
 734 *Energ. Rev.*, 50, 408-418, <http://doi.org/10.1016/j.rser.2015.05.043>, 2015.
- 735 Roberts, J. M., Veres, P. R., Cochran, A. K., Warneke, C., Burling, I. R., Yokelson, R. J., Lerner,
 736 B., Gilman, J. B., Kuster, W. C., Fall, R., and de Gouw, J.: Isocyanic acid in the atmosphere



- 737 and its possible link to smoke-related health effects, *Proc. Natl. Acad. Sci.*, 208 (22), 8966-
 738 8971, <http://doi.org/10.1073/pnas.1103352108>, 2011.
- 739 Rumble, J. R. *CRC Handbook of Chemistry and Physics*, 98th Ed. (2017-2018).
- 740 Schulten, H. –R. and Schnitzer, M.: The chemistry of soil organic nitrogen: a review, *Biol. Fert.*
 741 *Soils.*, 26, 1-15, 1997.
- 742 Selimovic, V., Yokelson, R. J., Warneke, C., Roberts, J. M., de Gouw, J., Reardon, J., and
 743 Griffith, D. W. T.: Aerosol optical properties and trace gas emissions by PAX and OP-FTIR
 744 for laboratory-simulated western US wildfires during FIREX, *Atmos. Chem. Phys. Discuss.*,
 745 <http://doi.org/10.5194/acp-2017-859>, in review, 2017.
- 746 Stockwell, C. E., Veres, P. R., Williams, J., and Yokelson, R. J.: Characterization of biomass
 747 burning emissions from cooking fires, peat, crop residue, and other fuels with high-resolution
 748 proton-transfer-reaction time-of-flight mass spectrometry, *Atmos. Chem. Phys.*, 15 (15), 845-
 749 865, <http://doi.org/10.5194/acp-15-845-2015>, 2015.
- 750 Ulbrich, I. M., Canagaratna, M. R., Zhang, Q., Worsnop, D. R., and Jimenez, J. L.: Interpretation
 751 of organic components from Positive Matrix Factorization of aerosol mass spectrometric data,
 752 *Atmos. Chem. Phys.*, 9 (9), 2891-2918, <http://doi.org/10.5194/acp-9-2891-2009>, 2009.
- 753 Yaws, C. L.: *The Yaws Handbook of Vapor Pressure: Antoine Coefficients*, Elsevier Science,
 754 2015.
- 755 Yee, L. D., Kautzman, K. E., Loza, C. L., Schilling, K. A., Coggon, M. M., Chhabra, P. S., Chan,
 756 M. N., Chan, A. W. H., Hersey, S. P., Crounse, J. D., Wennberg, P. O., Flagan, R. C., and
 757 Seinfeld, J. H.: Secondary organic aerosol formation from biomass burning intermediates:
 758 phenol and methoxyphenols, *Atmos. Chem. Phys.*, 13 (16), 8019–8043,
 759 <http://doi.org/10.5194/acp-13-8019-2013>, 2013.
- 760 Yokelson, R. J., Griffith, D. W. T., and Ward, D. E.: Open-path Fourier transform infrared
 761 studies of large-scale laboratory biomass fires, *J. Geophys. Res. Atmos.*, 101 (D15), 21067-
 762 21080, <http://doi.org/10.1029/96JD01800>, 1996.
- 763 Yokelson, R. J., Susott, R., Ward, D. E., Reardon, J., and Griffith, D. W. T.: Emissions from
 764 smoldering combustion of biomass measured by open-path Fourier transform infrared
 765 spectroscopy, *J. Geophys. Res. Atmos.*, 102 (D15), 18865-18877,
 766 <http://doi.org/10.1029/97JD00852>, 1997.



- 767 Yokelson, R. J., Crounse, J. D., de Carlo, P. F., Karl, T., Urbanski, S., Atlas, E., Campos, T.,
768 Shinozuka, Y., Kapustin, V., Clarke, A. D., Weinheimer, A., Knapp, D. J., Montzka, D. D.,
769 Holloway, J., Weibring, P., Flocke, F., Zheng, W., Toohey, D., Wennberg, P. O., Wiedinmyer,
770 C., Mauldin, L., Fried, A., Richter, D., Walega, J., Jimenez, J. L., Adachi, K., Buseck, P. R.,
771 Hall, S. R., and Shetter, R.: Emissions from biomass burning in the Yucatan, Atmos. Chem.
772 Phys., 9 (15), 5785-5812, <http://doi.org/10.5194/acp-9-5785-2009>, 2009.
- 773 Yuan, B., Koss, A., Warneke, C., Gilman, J. B., Lerner, B. M., Stark, H., and de Gouw, J. A.: A
774 high resolution time-of-flight chemical ionization mass spectrometer utilizing hydronium ions
775 (H_3O^+ ToF-CIMS) for measurements of volatile organic compounds in the atmosphere,
776 Atmos. Meas. Tech., 9 (6), 2735-2752, <http://doi.org/10.5194/amt-9-2735-2016>, 2016.
- 777 Yuan, B., Koss, A., Warneke, C., Coggon, M., Sekimoto, K., and de Gouw, J. A.: Proton-
778 transfer-reaction mass spectrometry: Applications in atmospheric sciences, Chem. Rev., 117
779 (21), 13187-13229, <http://doi.org/10.1021/acs.chemrev.7b00325>, 2017.
- 780



781

782

783 **Figure 1. Results for an example burn of Ponderosa pine realistic mixture (Fire #02). (a)**

784 **Time series of ion signals of 574 ion peaks, naphthalene ($C_{10}H_8 \cdot H^+$, m/z 129.070), and**

785 **syringol ($C_8H_{10}O_3 \cdot H^+$, m/z 155.070). (b) PMF results of 2-factor solution. The grey and pink**

786 **colors are stacked, not overlapped.**

787






Figure 2. Comparison of mass spectral profiles: (a) Ponderosa pine realistic mixture (Fire #72) vs. Ponderosa pine realistic mixture (Fire #02) for high- and low-temperature pyrolysis factors. (In this case, PMF was separately performed for data of Fire #02 and #72.) (b) Douglas fir vs. Ponderosa pine for high- and low-temperature factors. (c) Manzanita (contaminated) vs. Ponderosa pine for both the factors. (d) Bear grass vs. Ponderosa pine for both the factors. (e) Low- vs. high-temperature pyrolysis factor for Ponderosa pine and Manzanita (contaminated). Data points in individual panels correspond to well-fitted 434 ion peaks. Correlation coefficient (r) is obtained using logarithmic fraction, i.e., $\log(\text{ncps}/\text{total VOC ncps})$.




Figure 3. Average VOC emission profiles of high- and low-temperature pyrolysis factors, obtained using consolidated PMF results of 15 different fuels.




Figure 4. (a) Normalized fraction of factors for selected biomass pyrolysis products, obtained using PMF results of 15 different fuels. (b) Diagram of the relationship between pyrolysis temperature and products for hemicellulose, cellulose, and lignin.






Figure 5. Contributions, shown as normalized fractions, of VOCs relative to the high- and low-temperature factors: (a) $F_{\text{High-T}} = 100\text{--}80\%$ and $F_{\text{Low-T}} = 0\text{--}20\%$, (b) $F_{\text{High-T}} = 80\text{--}60\%$ and $F_{\text{Low-T}} = 20\text{--}40\%$, (c) $F_{\text{High-T}} = 60\text{--}40\%$ and $F_{\text{Low-T}} = 40\text{--}60\%$, (d) $F_{\text{High-T}} = 40\text{--}20\%$ and $F_{\text{Low-T}} = 60\text{--}80\%$, and (e) $F_{\text{High-T}} = 20\text{--}0\%$ and $F_{\text{Low-T}} = 80\text{--}100\%$. In this figure, molar emissions (in units of ppbv) of all the ion peaks in VOC emission profiles (Figure 2b) are described. The inner circle in each pie chart shows the elemental composition of the emissions. The outer circle provides more detailed information on specific compounds, structures, and functionalities found in each group. Details of molar fractions in each category are summarized in Table S3.




Figure 6. VOC composition in the high- and low-temperature emission profiles.




Figure 7. VOC composition in (a) high-temperature pyrolysis and (b) low-temperature pyrolysis emission profiles (Figure 3) sorted by 11 structural categories and 17 functional groups. Some VOCs have multiple structures. These are counted once in each relevant category. For example, benzofuran is counted in the structural categories of “Oxy. aromatic” and “Furans” as “Not substituted/alkyl” functional group. Structures detected with low abundance (<0.002 ppbv/total VOC ppbv) are mostly not-substituted or alkyl-substituted.




Figure 8. VOC composition in high- and low-temperature pyrolysis emission profiles (Figure 3) sorted by 17 functional groups. Each group includes various structures and elemental composition. Some VOCs have multiple functional groups. These are counted once in each relevant category. For example, guaiacol is counted in the categories of “Alcohol” and “Ether (methoxy)”.




Figure 9. High- and low-temperature emission profiles compared by (a) OH reactivity and (b) volatility, described by saturation concentration ($\mu\text{g m}^{-3}$).





Figure 10. Ratios of fire-integrated molar emissions ($\Sigma \text{VOC}_{\text{High-T}} / \Sigma \text{VOC}_{\text{Low-T}}$) or MCE for different type fuel parts, obtained using PMF results of 15 different fuels.



(a) VOC emission profile of duff burn



(b) Duff profile vs. Low-temp. profile




Figure 11. (a) VOC emission profile of duff burn of Engelmann spruce and Subalpine fir. (b) Scatter plot of duff emission profile (Engelmann spruce) versus average low-temperature pyrolysis profile.