

Towards the connection between snow microphysics and melting layer: Insights from multi-frequency and dual-polarization radar observations during BAECC

Haoran Li¹, Jussi Tiira¹, Annakaisa von Lerber², and Dmitri Moisseev^{1,2}

¹Institute for Atmospheric and Earth System Research / Physics, Faculty of Science, University of Helsinki, Finland

²Finnish Meteorological Institute, Helsinki, Finland

Correspondence: Haoran Li (haoran.li@helsinki.fi)

Abstract. In stratiform rainfall, the melting layer (ML) is often visible in radar observations as an enhanced reflectivity band, the so-called bright band. Despite the ongoing debate on the exact microphysical processes taking place in the ML and on how they translate into radar measurements, both model simulations and observations indicate that the radar-measured ML properties are influenced by snow microphysical processes that take place above it. There is still, however, a lack of comprehensive observations to link the two. To advance our knowledge of precipitation formation in ice clouds and provide new insights into radar signatures of snow growth processes, we have investigated this link. This study is divided into two parts. Firstly, surface-based snowfall measurements are used to develop a new method for identifying rimed and unrimed snow from X- and Ka-band Doppler radar observations. Secondly, this classification is used in combination with multi-frequency and dual-polarization radar observations collected during the Biogenic Aerosols - Effects on Clouds and Climate (BAECC) experiment in 2014 to investigate the impact of precipitation intensity, aggregation, riming, and dendritic growth on the ML properties. The results show that the radar-observed ML properties are highly related to the precipitation intensity. The previously reported bright band "sagging" is mainly connected to the increase of precipitation intensity. Ice particle riming plays a secondary role. In moderate to heavy rainfall, riming may cause additional bright band sagging, while in light precipitation the sagging is associated with unrimed snow. The correlation between ML properties and dual-polarization radar signatures in the snow region above appears to be arising through the connection of the radar signatures and ML properties to the precipitation intensity. In addition to advancing our knowledge of the link between ML properties and snow processes, the presented analysis demonstrates how multi-frequency Doppler radar observations can be used to get a more detailed view of cloud processes and establish a link to precipitation formation.

1 Introduction

Stratiform precipitation is prevalent in mid- to high- latitudes. In such precipitation systems, ice particles nucleated at the cloud top descend and grow on their way down by going through various microphysical processes, e.g., vapor deposition, aggregation and/or riming (Lamb and Verlinde, 2011). In the case of rainfall, these ice particles transform into raindrops in the melting layer (ML). The melting of ice particles is capable of modulating the thermal structure of the ML through the

exchange of latent heat with the environment (Stewart et al., 1984; Carlin and Ryzhkov, 2019) and, as a result, can change the dynamics of precipitation (e.g., Heymsfield, 1979; Szeto et al., 1988; Fabry and Zawadzki, 1995). It has been shown that ML properties are modified by the ambient environment such as relative humidity (RH, Willis and Heymsfield, 1989; Battaglia et al., 2003; Carlin and Ryzhkov, 2019) as well as microphysical processes taking place in the ML (Heymsfield et al., 2015), and
5 by snow microphysical processes occurring above, e.g., aggregation and riming (Stewart et al., 1984; Klaassen, 1988; Fabry and Zawadzki, 1995; Zawadzki et al., 2005; von Lerber et al., 2014; Kumjian et al., 2016; Xie et al., 2016; Wolfensberger et al., 2016; Trömel et al., 2019). In addition, the microwave attenuation in the ML is sensitive to the parameterization of snow microphysics (von Lerber et al., 2014) and can be significant at mm-wavelength (Matrosov, 2008; Haynes et al., 2009; Li and Moisseev, 2019).

10 To cm-wavelength weather radars, the ML appears as a band of the increased reflectivity, the so-called bright band, while to mm-wavelength radars such appearance is less distinct (e.g., Lhermitte, 1988; Sassen et al., 2005; Kollias and Albrecht, 2005). Properties of the ML and its radar manifestation bright band are influenced by cloud dynamics and microphysics, which can be directly probed by aircraft-mounted in-situ measurements (e.g., Stewart et al., 1984; Willis and Heymsfield, 1989; Heymsfield et al., 2015) despite the inability to conduct continuous long-term operation with such setups. Remote sensing
15 of the ML with radars dates back to the 1940s (Ryde, 1946). Atlas (1957) have found that the strength of the bright band is weakened when melting graupel particles present, which was further confirmed by Klaassen (1988) and Zawadzki et al. (2005). A comprehensive long-term analysis of the ML appearance in vertically pointing X-band radar and UHF wind profiler observations has been performed by Fabry and Zawadzki (1995). They have compiled a record of the main ML features that were later used in modeling studies (e.g., Szyrmer and Zawadzki, 1999; Zawadzki et al., 2005; von Lerber et al., 2014). As
20 the ML bridges snow and rain, the raindrop size distributions below the ML seem to be related to the bright band's reflectivity values (Huggel et al., 1996; Sarma et al., 2016). As presented by Wolfensberger et al. (2016), the thickness of the ML depends on riming, particle fall velocities as well as the bright band intensity. Meanwhile, the downward extension of the bright band, called the saggy bright band, may be linked to riming as suggested by previous studies (Trömel et al., 2014; Kumjian et al., 2016; Ryzhkov et al., 2016; Xie et al., 2016; Erlingis et al., 2018). Recently, Carlin and Ryzhkov (2019) have incorporated
25 the cooling effects of melting snowflakes in the ML model and proposed that the saggy bright band may be explained by a combination of processes instead of a single factor. From the perspective of observation, there seems to be a lack of statistical studies untangling the impacts of snow growth processes on the observed ML properties.

Over the last few years, multi-frequency radar measurements of clouds and precipitation have become more easily attainable, which has led to the proliferation of studies demonstrating the advantages of using these observations for the investigation of
30 snow microphysical processes (e.g., Kneifel et al., 2011, 2015; Leinonen et al., 2012a, 2013, 2018; Tyynelä and Chandrasekar, 2014; Leinonen and Moisseev, 2015; Leinonen and Szyrmer, 2015; Grecu et al., 2018; Chase et al., 2018; Mason et al., 2018, 2019). The potential dependence of dual-wavelength ratios (DWRs) at Ka-W-bands and X-Ka-bands on riming was observed by Kneifel et al. (2015). Dias Neto et al. (2019) have presented the strong aggregation signatures close to the ML using multi-frequency radar observations. This rapid aggregation could manifest itself as a dark band in W-band cloud radar observations,
35 namely the dip of radar reflectivity just above the ML top (Lhermitte, 1988; Sassen et al., 2005, 2007; Heymsfield et al.,

2008). Such reflectivity dip just above the ML may even be present in X-band radar measurements of light precipitation (Fabry and Zawadzki, 1995) but has not been well addressed. Mason et al. (2018) have incorporated the Doppler velocity and radar reflectivity observations from vertically-pointing Ka- and W-band radars into an optimal estimation scheme to infer the riming fraction, among other parameters. In addition to multi-frequency radar observations, dual-polarization radar measurements
5 show promise in improving our understanding of ice precipitation processes (e.g., Bechini et al., 2013; Giangrande et al., 2016; Kumjian et al., 2016; Ryzhkov et al., 2016; Moisseev et al., 2015, 2017; Li et al., 2018; Oue et al., 2018; Vogel and Fabry, 2018; Moisseev et al., 2019; Tiira and Moisseev, 2020). Therefore, the utilization of collocated multi-frequency and dual-polarization radar observations may pave the way for a better understanding of the connection between dry and melting snow microphysics.

The detailed properties of ice particles are complex as manifested by the extraordinary variety in their habit, size, mass and concentration (Korolev et al., 2000, 2003; Bailey and Hallett, 2009). This complexity is exacerbated by the diversity of ice
10 growth processes that take place in ice clouds (Li et al., 2018; Oue et al., 2018; Barrett et al., 2019; Moisseev et al., 2015, 2017, 2019; Tiira and Moisseev, 2020). Despite the recent attempts to resolve the ice microphysics (e.g., Mason et al., 2018, 2019; Barrett et al., 2019), direct characterization of ice particles and their growth processes is still challenging. In some cases, ML properties could emphasise radar signatures of such processes (Zawadzki et al., 2005; Kumjian et al., 2016; Li and Moisseev,
15 2020) and therefore provide an additional information. However, there is an ongoing debate on the link between snow growth processes, such as riming and aggregation, their radar signatures and ML properties (e.g., Kumjian et al., 2016; Carlin and Ryzhkov, 2019; Heymsfield et al., 2015). This study is aiming to advance our understanding of the link and resolve at least some of the discussed topics. During the Biogenic Aerosols Effects on Clouds and Climate (BAECC) experiment (Petäjä et al., 2016), vertically-pointing X-, Ka- and W-band cloud radars were deployed at the University of Helsinki research station in
20 Hyytiälä, Finland. These observations were supplemented by Range-Height Indicator (RHI) scans carried out by the Finnish Meteorological Institute (FMI) C-band dual-polarization radar, providing a set of unique synergistic observations ideally suited to studying the connection between the growth and melting processes of snowflakes.

The paper is organized as follows. Section 2 introduces the instrumentation used in this study, followed by the illustration of detecting the ML and separating unrimed and rimed snow in Sect. 3. A sanity check of the snow classification and the statistical
25 results of multi-frequency and dual-polarization radar observations are provided in Sect. 4. Conclusions are presented in Sect. 5.

2 Measurements

The BAECC field campaign was conducted at the University of Helsinki Hyytiälä Station from February to September 2014 (Petäjä et al., 2016). This experiment provides comprehensive vertically-pointing multi-frequency radar rainfall observations,
30 which are used in this study. A 2D-video disdrometer (2DVD) was used to measure rain rate and calibrate X-band radar reflectivity. The collocated observations were aided by the FMI C-band dual-polarization weather radar. In addition to the radar setup during BAECC, long-term snow observations were made by a National Aeronautics and Space Administration (NASA) Particle Imaging Package (PIP, Newman et al., 2009; Tiira et al., 2016; von Lerber et al., 2017).

2.1 2DVD and vertically-pointing radars

The ARM 2DVD used in this study is a new generation of the one described in (Kruger and Krajewski, 2002). It relies on two cameras as well as two light sources placed in orthogonal directions and records image projections of raindrops as they fall cross the cameras' field of view. The 2DVD is often used for recording the size distributions, fall velocities and shapes of raindrops. Based on these information, the rain rate and reflectivity at a given radar frequency can be derived.

The X/Ka-band scanning Atmospheric Radiation Measurement (ARM) cloud radar (X/Ka-SACR) and W-band ARM cloud radar (MWACR) have the range gate spacing of 25 m, 25 m and 30 m, respectively (Kollias et al., 2014; Kneifel et al., 2015; Falconi et al., 2018). The original time resolution of 2 s was averaged to 10 s for these radars. The half-power beam widths of X-SACR, Ka-SACR and MWACR are 1.27° , 0.33° and 0.38° , respectively. X- and Ka-SACR are dual-polarization radar systems installed on the same pedestal, recording the co-polar (e.g., ρ_{hv} , Z_{dr}) and cross-polar (e.g., cross-polar correlation coefficient, linear depolarization ratio LDR) measurements, respectively. MWACR had a small antenna pointing error of 0.5° to 1° , which may lead to significant error in the vertical Doppler velocity which, but does not affect reflectivity measurements.

To mitigate the potential attenuation from wet radome and raindrops, the simulated X-band radar reflectivity from 2DVD data was used to match the measured X-band reflectivity at 500 m where the near-field effect is minimized (Sekelsky, 2002; Falconi et al., 2018). As the Ka-band reflectivity can be significantly affected by the attenuation from the ML, rain as well as a wet radome (Li and Moisseev, 2019), the relative calibration was made at precipitation top where the Rayleigh assumption can be applied at Ka- and X-bands. During BAECC, a radiosonde was launched four times per day, out of which the temporally closest one was used as input to the millimeter-wave propagation model (Liebe, 1985) to correct for the gaseous attenuation at all radar frequencies.

2.2 Dual-polarization weather radar

The FMI C-band dual-polarization weather radar located in Ikaalinen, 64 km west from the Hyytiälä station, operates in the simultaneous transmission and receiving mode (Doviak et al., 2000). This radar performs RHI scans over the measurement site every 15 minutes. The range and azimuth resolutions are 500 m and 1° , respectively. The dual-polarization measurements used in this study are Z_{dr} , which was calibrated during light rainfalls (Bringi and Chandrasekar, 2001; Li et al., 2018). For data analysis, the Python ARM Radar Toolkit (Helmus and Collis, 2016) was used.

2.3 NASA Particle Imaging Package

The PIP is an improved version of the Snowflake Video Imager (Newman et al., 2009), which uses a high frame rate camera, operating at 380 frames per second, to record the silhouettes of precipitation particles. The field of view of this camera is 48×64 mm with a spatial resolution of 0.01 mm^2 . The focal plane of this camera is 1.3 m. Because the measurement volume is not enclosed, the wind-induced effects on the measurements are minimized (Newman et al., 2009). The data-processing software defines the size of each particle using the disk-equivalent diameter (D_{deq}) which is the diameter of a disk with the same area of a particle shadow. Particle size distribution (PSD) and fall velocity are recorded as a function of D_{deq} in the PIP software.

Based on these PIP products, von Lerber et al. (2017) have derived particle mass and fall velocity as a function of the observed maximum particle diameter ($D_{\max, \text{ob}}$), which is obtained by fitting an ellipsoid model to each particle. Here and hereafter, D represents $D_{\max, \text{ob}}$. The snowfall measurements started as a part of the BA ECC field campaign were continued and data collected during the experiment and additional three winters were used in this study. The collected data were processed using
5 the method by von Lerber et al. (2017).

3 Methods

3.1 Detection of ML boundaries

The height where melting starts ranges from the surface to several km above, mainly depending on the temperature profiles. Thus, prior to addressing the general characteristics of ML, it is important to detect ML boundaries. Fabry and Zawadzki
10 (1995) have employed the gradient of reflectivity to determine the ML boundaries using single-polarization X-band radar measurements. The vertically-pointing X-/Ka-band radars used in this study provide dual-polarization observations, i.e. ρ_{hv} and LDR, respectively. These observations supply additional information to estimate the ML boundaries (Giangrande et al., 2008). However, care should be taken in how this information is used. Wolfensberger et al. (2016) have suggested the use of ρ_{hv} could underestimate the ML top, as the significant drop in ρ_{hv} may not happen until a significant amount of ice has
15 already melted. To mitigate this issue, we determined the upper boundary of ML by finding the local minimum of the X-band reflectivity gradient around the ρ_{hv} -detected ML top, which is similar to (Wolfensberger et al., 2016). The validity of utilizing the radar reflectivity in determining the ML top is further confirmed in our recent study (Li and Moisseev, 2020). The ML bottom was determined in a similar way to derive the radar reflectivity at the melting bottom. Note that cases where precipitation fall streaks are significantly slanted, as shown in (Fabry and Zawadzki, 1995), were excluded.

20 3.2 Diagnosing snowflake rime mass fraction

The rime mass fraction (FR), defined as the ratio of accreted ice mass by riming to the total snowflake mass, has been used to quantify the riming extent in ice microphysical schemes (Morrison and Milbrandt, 2015) and in observational studies (e.g., Moisseev et al., 2017; Li et al., 2018). The rime mass fraction can be defined as

$$\text{FR} = 1 - \frac{\int_{D_{\min}}^{D_{\max}} N(D)m_{\text{ur}}(D)dD}{\int_{D_{\min}}^{D_{\max}} N(D)m_{\text{ob}}(D)dD} \quad (1)$$

25 where D_{\max} and D_{\min} are maximum and minimum particle sizes, respectively, $m_{\text{ob}}(D)$ and $m_{\text{ur}}(D)$ are masses of observed and unrimed snowflakes as a function of D , respectively, and $N(D)$ is the PSD. In this study, FR was computed using ground-based observations of PSD and snowflake masses retrieved from PIP observations as described in (von Lerber et al., 2017). The masses of unrimed ice particles were derived assuming the following. Firstly, unrimed snowflakes were present in PIP observations. Secondly, the ice particles belonging to the lightest 5% are representative of unrimed snowflakes. Following these

assumptions, the mass-dimension relation $m_{ur}(D) = 0.0053D^{2.05}$ that is representative of unrimed snowflakes was derived. This relation is similar to the one derived from aircraft measurements (Heymsfield et al., 2004). Further discussion on the definition of $m_{ur}(D)$ is referred to (Moisseev et al., 2017) and (Li et al., 2018).

Mason et al. (2018) have shown that the extent of riming can be retrieved using radar-measured DWR (Matrosov, 1998; Hogan et al., 2000) and mean Doppler velocity (V). If the radar reflectivity is expressed in dB, then the DWR can be written as

$$DWR(\lambda_1, \lambda_2) = Z_{\lambda_1} - Z_{\lambda_2} \quad (2)$$

where Z_{λ_1} and Z_{λ_2} are observed radar reflectivities at the wavelength of λ_1 and λ_2 , respectively. Z_{λ} can be expressed as

$$Z_{\lambda} = 10 \log_{10} \left(\int_{D_{min}}^{D_{max}} \frac{\lambda^4}{\pi^5 |K_{\lambda}|^2} N(D) \sigma_{b,\lambda}(D, m_{ob}(D)) dD \right) \quad (3)$$

where $|K_{\lambda}|^2$ is the dielectric constant of liquid water, and $\sigma_{b,\lambda}(D, m_{ob}(D))$ is the backscattering coefficient of snow particles at a given wavelength. In X-SACR, Ka-SACR and MWACR data files $|K_{\lambda}|^2$ is set to 0.93, 0.88, and 0.70, respectively. The values of $\sigma_{b,\lambda}$ were taken from the single-scattering databases (Leinonen and Moisseev, 2015; Leinonen and Szyrmer, 2015; Tyynelä and von Lerber, 2019). These three datasets were combined into a single lookup table of ice particle scattering properties defined as a function of maximum diameter and mass. For given D and m_{ob} , the backscattering cross section was estimated using linear interpolation in the log-log space. The mean Doppler velocity can be derived in the same way,

$$V_{\lambda} = \frac{\int_{D_{min}}^{D_{max}} v(D) N(D) \sigma_{b,\lambda}(D, m_{ob}(D)) dD}{\int_{D_{min}}^{D_{max}} N(D) \sigma_{b,\lambda}(D, m_{ob}(D)) dD} \quad (4)$$

where $v(D)$ is the fall velocity of snowflakes with the same D and can be derived together with $m(D)$ following (von Lerber et al., 2017). To minimize the impact of varying air density (ρ_{air}), V_{λ} was adjusted to the air condition of 1000 hPa and 0°C (air density $\rho_{air,0}$) with a factor of $(\frac{\rho_{air,0}}{\rho_{air}})^{0.54}$ (Heymsfield et al., 2007). ρ_{air} was derived from the temperature and relative humidity obtained from the temporally closest sounding.

Dias Neto et al. (2019) have shown that the size growth of snowflakes close to the ML is accelerated due to the enhanced aggregation. Therefore, relatively large aggregates are prevalent snow types close to the ML, and are better represented by DWR(X,Ka) than DWR(Ka,W) (see the comparison by Barrett et al., 2019). The use of lower radar frequency (X- and Ka-bands) avoids estimating the non-neglectable W-band attenuation caused by ML as well as supercooled liquid water (Li and Moisseev, 2019). Therefore, the potential link between FR and simulated Doppler radar measurements at X- and Ka bands was accessed, with the utilization of in-situ snowfall observations from BA ECC to the winters of 2014-2018.

The dependence of DWR(X, Ka) and V_X on FR can be computed using Eq. (1), (2) and (4). For comparison, the $m_{ob} - D$ and $v - D$ relations of aggregates of unrimed radiating assemblages, side planes, bullets and columns (LH74 unrimed), aggregates of densely rimed radiating assemblages of dendrites (LH74 rimed) and lump graupel (LH74 graupel) presented in (Locatelli

and Hobbs, 1974) were used. To compute the $DWR(X, Ka)$ and V_X using the literature relations, we assumed that $N(D)$ can be parameterized as

$$N(D) = N_0 e^{-\Lambda D} \quad (5)$$

here the intercept parameter N_0 cancels out while computing DWR and V_X , so the radar variables depend on Λ , which controls the average size of ice particles in $N(D)$. We have varied Λ^{-1} between 0 and 11 mm to mimic different snowfall conditions, which is similar to what was done in (Leinonen and Szyrmer, 2015). Table 1 summarizes the fitted expressions of $DWR(X, Ka) = aV_X^b$ for these three particle types. Since snow microphysics as well as the corresponding radar measurements can significantly change with precipitation intensity (Moisseev et al., 2017), the computed values were separated into four subgroups according to precipitation rate (PR).

Table 1. Fitted parameters for $DWR(X, Ka) = aV_X^b$. Aggregates of unrimed radiating assemblages, side planes, bullets and columns (LH74 unrimed), aggregates of densely rimed radiating assemblages of dendrites (LH74 rimed) and lump graupel (LH74 graupel) in (Locatelli and Hobbs, 1974) are shown for a reference. The last column shows the root mean square error (RMSE) of fitting. The confidence interval is marked by “\” when the parameter is manually fixed.

Fitted parameters		a (95% confidence interval)	b (95% confidence interval)	RMSE [dB]
LH74	unrimed	2.6 (2.2 3)	7.3 (6.1 8.5)	1.9
	rimed	0.2 (0.09 0.31)	9.8 (8.1 11.5)	1.8
	graupel	0.35 (0.19 0.51)	2.5 (2.03 2.97)	0.8
$PR \leq 0.15 \text{ mm h}^{-1}$	FR \in [0 0.2]	1.3 (1.02 1.58)	7.3 (\)	2
	FR \in [0.4 0.6]	0.2 (0.14 0.26)	2.96 (2.26 3.66)	0.5
$0.15 \text{ mm h}^{-1} < PR \leq 0.5 \text{ mm h}^{-1}$	FR \in [0 0.2]	0.75 (0.64 0.86)	7.3 (\)	2.4
	FR \in [0.4 0.6]	0.47 (0.37 0.57)	3.1 (2.7 3.5)	1.1
$0.5 \text{ mm h}^{-1} < PR \leq 1 \text{ mm h}^{-1}$	FR \in [0 0.2]	0.69 (0.61 0.77)	7.3 (\)	2.2
	FR \in [0.4 0.6]	0.52 (0.4 0.64)	2.9 (2.3 3.5)	0.85
$1 \text{ mm h}^{-1} < PR \leq 4 \text{ mm h}^{-1}$	FR \in [0 0.2]	0.6 (0.59 0.61)	7.3 (\)	2.3
	FR \in [0.4 0.6]	0.75 (0.59 0.91)	2.85 (2.16 3.54)	1.2

10 Simulations of $DWR(X, Ka)-V_X$ for four groups of precipitation rate are presented in Fig. 1. Most cases with $FR \leq 0.2$ are centered around the curve of LH74 unrimed, whose velocity-diameter relation is similar with low density snowflakes (Tiira et al., 2016). It seems that riming happens more frequently in heavier precipitation. In contrast, much fewer unrimed cases are present in heavier precipitation (Fig. 1 c,d). Heavily rimed snowflakes ($FR > 0.5$, red dots) are characterized by low $DWR(X, Ka)$ and high V_X , contrasting with the unrimed/lightly rimed cases (blue dots). Specifically, snowflakes with large




Figure 1. Scatter plot of $DWR(X, Ka)$ vs. V_X (1000 hPa and 0°C) colored with FR. Mass-size and velocity-size relations from (Locatelli and Hobbs, 1974) are adopted for reference (dashed lines). Observed mass-size and velocity-size relations are derived using the approach developed by von Lerber et al. (2017), and the particle back-scattering coefficient $\sigma_{b,\lambda}$ is adopted from (Leinonen and Moisseev, 2015; Leinonen and Szyrmer, 2015). The solid blue and red curves separate unrimed (light blue shading), transitional (no shading) and rimed snow (light red shading) in our classification scheme.

sizes and low velocities usually are rather slightly rimed ($FR \leq 0.2$). For the cases where FR exceeds 0.5, most $DWR(X, Ka)$ values are below 3 dB, indicating that heavily rimed particles are usually associated with small snowflakes. Inspired by this distinct feature, we have fitted the $DWR(X, Ka) = aV_X^b$ relations for cases with $FR \leq 0.2$ and $0.4 \leq FR \leq 0.6$ (shown in Table 1), which separate the observations into three types: unrimed, transitional and rimed snow. For the sake of comparison, the power b for unrimed snow was adopted from the fit for LH74 unrimed. In this study, these fitted relations were employed for classifying unrimed and rimed snow. The presence of supercooled liquid water does not significantly affect X-band reflectivity but may lead to appreciable attenuation at Ka-band which translates to enhanced $DWR(X, Ka)$ after the relative calibration at precipitation top. For the liquid water path of 500 g m^{-2} , the estimated Ka-band attenuation is in the order of 1 dB (Kneifel et al., 2015). Therefore, cases with $DWR(X, Ka) < 1$ dB were rejected when identifying unrimed snow.

4 Results

To study how ML properties depend on the precipitation intensity, snowflake riming fraction and PSD, all rainfall cases observed during the BAECC experiment were analyzed. Given the need for coinciding multi-frequency vertically pointing radar measurements and the radar scans performed during the experiment, we have identified 4147 vertical profiles of observations in 24 stratiform rainfall events corresponding to about 11.5 h. Table 2 summaries the dates used in this study (quicklooks are available at <https://github.com/HaoranLiHelsinki/ACP-2020-Quicklooks>, last access: 06 July 2020). Due to the periodic changes of radar scans, the multi-frequency radar measurements recorded in the vertically-pointing mode were available only in some inconsecutive time periods for an event. During the analysis, the mean radar Doppler velocity was scaled to the air density at 1000 hPa and 0°C as previously described. It should be noted that the RHI scans by the FMI C-band weather radar were performed every 15 min. Therefore, the profiles of specific differential phase and differential reflectivity are recorded much less frequently than the vertically-pointing radar observations. The RHI observations are nonetheless presented here in order to link the features observed in this study to the previous reports (Giangrande et al., 2016; Kumjian et al., 2016; Li et al., 2018; Vogel and Fabry, 2018). Figure 2 shows the flow chart of the data process in this study.

Table 2. Summary of the studied events

Event	Date	Event	Date
1	2014 May 09	13	2014 August 10
2	2014 May 11	14	2014 August 12
3	2014 May 16	15	2014 August 13
4	2014 May 29	16	2014 August 14
5	2014 May 31	17	2014 August 18
6	2014 June 04	18	2014 August 19
7	2014 June 06	19	2014 August 20
8	2014 June 12	20	2014 August 24
9	2014 June 13	21	2014 August 25
10	2014 July 15	22	2014 August 26
11	2014 July 16	23	2014 August 27
12	2014 July 30	24	2014 September 09

4.1 Sanity check of the snow classification

At the first step of our data analysis, the classification of unrimed and rimed snow using $DWR(X,Ka) - V_X$ observations at the ML top, proposed in the previous section, was evaluated against previous studies. As shown in Fig. 3, both $DWR(X,Ka)$ and V_X tend to increase as the precipitation intensifies. Most cases of rimed snow fall in the region where $DWR(X,Ka) < 4$ dB and V_X is higher than for unrimed snow. The V_X of unrimed snow rarely exceeds 1.5 m/s. Those outliers of rimed snow in Fig. 1 (a)




Figure 2. Flow chart of the data process in this study. The snow classification part as discussed in Section 3.1 is in light blue. Variables used in snow classification are in green. Radar observations during BAECC is in black. The sanity check in next section is represented by the dashed black diagram.

may be attributed to the local vertical air motions, which contaminate the measured mean Doppler velocity. It should be noted that the snow observations in Fig. 1 are limited to $\text{PR} \leq 4 \text{ mm h}^{-1}$, namely the maximum radar reflectivity at the ML bottom ($Z_{X,\text{rain}}$) is around 33 dBZ, as computed by using the localized $Z - R$ relation (Leinonen et al., 2012b).

The reflectivity enhancement in the ML, which is defined as the difference between the Z_X maximum in the ML and the Z_X at the melting bottom ($Z_{X,\text{rain}}$), was also studied. Zawadzki et al. (2005) have analyzed the UHF Doppler wind profiler observations in $V_{\text{UHF,snow}}/V_{\text{UHF,rain}}$ - reflectivity enhancement space and found that the augmentation of rimed snowflake mass can increase $V_{\text{UHF,snow}}/V_{\text{UHF,rain}}$ and decrease reflectivity enhancement. As shown in Fig. 4, despite the scattered distribution of reflectivity enhancement, the majority of cases with high $V_{X,\text{snow}}/V_{X,\text{rain}}$ are dominated by rimed snow while most unrimed cases are below $V_{X,\text{snow}}/V_{X,\text{rain}} = 0.25$. Such dependence of $V_{X,\text{snow}}/V_{X,\text{rain}}$ on riming is in line with the results in (Zawadzki et al., 2005), indicating the reasonable snow classification employed in this study.




Figure 3. Distribution of (a) $DWR(X,Ka)$ and (b) V_X above the ML as a function of $Z_{X,rain}$. Note that no transitional snow type between unrimed and rimed is presented.




Figure 4. Scatter plot of $V_{X,snow}/V_{X,rain}$ vs. reflectivity enhancement in the ML. The reflectivity enhancement is defined as the difference between the reflectivity peak in the ML and the reflectivity in rain just below the ML.

4.2 Vertical profiles of multi-frequency radar measurements in ML

To obtain a general idea of how the ML is modulated by riming and aggregation, statistics of vertically-pointing radar observations were made. As the ML properties are modulated by precipitation intensity (Fabry and Zawadzki, 1995; Carlin and Ryzhkov, 2019), the observations were grouped by PR. For ease of comparison, the vertical axis is shifted such that the reference height is the ML top.

4.2.1 X-band reflectivity, ρ_{hv} and DWR(X,Ka)




Figure 5. Normalized X-band radar profiles grouped by PR. $t_{unrimed}$ and t_{rimed} indicate the total observing time in each group for unrimed and rimed cases, respectively. The median values of X-band reflectivity at the ML bottom for unrimed ($Z_{X,unrimed}$) and rimed ($Z_{X,rimed}$) cases are marked just below the ML bottom with the standard values in brackets. The median and standard deviations (in parentheses) of relative humidity (RH) at the ML top for unrimed ($RH_{unrimed}$) and rimed (RH_{rimed}) cases in each group are presented near the ML top. The median and standard deviations (in parentheses) of PR for unrimed ($PR_{unrimed}$) and rimed (PR_{rimed}) cases in each group are presented in the lower part. Shaded regions represent the standard derivation.

Figure 5 shows the profiles of radar reflectivity and ρ_{hv} measured by X-SACR and grouped by PR. Note that to generalize the observations, the vertical axis is shifted such that the ML top is the reference height of 0 m, and each reflectivity profile was normalized by offsetting the difference between $Z_{X,rain}$ and the median value of $Z_{X,rain}$ in the corresponding PR group.

- The same procedure was made to ρ_{hv} and the following measurements. For most cases, the relative humidity (RH) around the ML top is above 95% with no dependence on PR. Thus, the effect of dry air infiltration, e.g., decreasing reflectivity and ML thickness, descending dual-polarization measurements (Carlin and Ryzhkov, 2019), should be minimized. Considering the

general aspects of Fig. 5, it is clear that the ML thickness and reflectivity peak increase with PR, which is inline with previous results (Fabry and Zawadzki, 1995; Wolfensberger et al., 2016; Trömel et al., 2019).




Figure 6. Same as Fig. 5, but for $DWR(X,Ka)$. Note that the radar calibration is made by matching the X- and Ka-band radar reflectivities at precipitation top.

The ρ_{hv} and radar reflectivity have been used in identifying the bright band sagging (Kumjian et al., 2016; Ryzhkov et al., 2016; Xie et al., 2016). When $PR > 1 \text{ mm h}^{-1}$, the level of ρ_{hv} minimum of rimed snow seems to be lower than the unrimed, however, the opposite holds when $PR \leq 1 \text{ mm h}^{-1}$ which seems controversial to the expectation that the bright band sagging is mainly caused by riming (Kumjian et al., 2016). In our observations, both ρ_{hv} dip and reflectivity peak descend with the increase of PR. Therefore, it appears that precipitation intensity is an important factor affecting the formation of the saggy bright band. This finding is inline with a recent simulation study (Carlin and Ryzhkov, 2019), which proposes that the saggy bright band can also be attributed to other factors, such as the aggregation process, the increased precipitation intensity and the sudden decrease of RH. For unrimed snow, the response of ρ_{hv} to the melting is obviously later than X-band reflectivity, which indicates that the utilization of ρ_{hv} for detecting the ML top should be applied with caution.

The reflectivity peak is smaller for rimed snow than unrimed for a given PR, provided that the Rayleigh scattering is not violated. When $PR > 1 \text{ mm h}^{-1}$ the reflectivity peaks of rimed and unrimed snow are closer, which can be explained by the non-Rayleigh scattering of very large aggregates at X-band as discussed by Fabry and Zawadzki (1995). Another notable finding is that the Z_X at the ML top for rimed snow is smaller than unrimed, which indicates that rimed snowflakes may have smaller

sizes for a given PR. This is further confirmed in the $DWR(X,Ka)$ profiles as shown in Fig. 6. From the aggregation region to the ML top, the $DWR(X,Ka)$ of rimed snow is significantly smaller than unrimed snow. In particular, very weak $DWR(X,Ka)$ for rimed snow could be identified just above the ML. This indicates that the aggregation process, the dominating factor of growing snow size close to the ML (Fabry and Zawadzki, 1995), can be heavily suppressed for rimed snow. Heymsfield et al. (2015) have reported the enhanced maximum particle size below the 0°C isotherm using in-situ measurements, and attributed it to the continuing aggregation in the ML. Such continuing aggregation in conjunction with the changing scattering properties (the water coating) may be responsible for the continuing increase of $DWR(X,Ka)$ in the ML.

Interestingly, the $DWR(X,Ka)$ profile below the ML is higher for the rimed cases and progressively converges towards the unrimed profile as PR increases. For light precipitation, the rain drops are small enough to be Rayleigh scatterers at Ka-band, thus the difference of $DWR(X,Ka)$ in rain between unrimed and rimed cases roots from the differences in attenuation. If the supercooled liquid water attenuation of rimed cases is more significant, the corresponding $DWR(X,Ka)$ in rain would be smaller than the unrimed cases. However, the reverse is observed. von Lerber et al. (2014) have shown that the melting layer attenuation of rimed snowflakes is smaller than unrimed ones, which could possibly explain the larger $DWR(X,Ka)$ of rimed cases in rain. With the increase of precipitation intensity, the $DWR(X,Ka)$ of rimed cases in rain decreases towards the unrimed profile. This can be attributed to several factors, such as the enhanced liquid attenuation above the melting layer and the non-Rayleigh scattering of large raindrops at Ka-band. We hesitate to determine the role of non-Rayleigh scattering in rain, since raindrops characterized by different non-Rayleigh scattering size regions can lead to opposite effects on $DWR(X,Ka)$ as shown by Li and Moisseev (2019).

4.2.2 Ka-band LDR and reflectivity

LDR usually increases in the ML, as melting increases the dielectric constant of nonspherical ice particles. Figure 7 shows the profiles of LDR (Ka-SACR) as well as ρ_{hv} (X-SACR). Both LDR peak and ρ_{hv} dip of rimed snow are lower than unrimed snow when $PR > 1 \text{ mm h}^{-1}$, while the reverse is observed for lighter precipitation. Despite the rather good agreement between LDR and ρ_{hv} observations, it appears that LDR systematically reveals lower ML bottom than ρ_{hv} , indicating that LDR can be suitable in discriminating rain and melting snow (Illingworth and Thompson, 2011; Dias Neto et al., 2019). The smaller LDR peak for rimed snow is correlated with the smaller X-band reflectivity enhancement as shown in Fig. 5, which is consistent with (Illingworth and Thompson, 2011; Sandford et al., 2017).

As shown in Fig. 8, the Ka-band reflectivity enhancement in the ML decreases as the precipitation intensifies. This is similar with the observations presented by Fabry and Zawadzki (1995) who found that the reflectivity peak in the ML observed by an X-band radar is less pronounced than that measured by an UHF radar when the reflectivity in rain exceeds 25 dBZ. With the increase of precipitation intensity, the size of snowflakes generally grows. Therefore, there are less hydrometeors satisfying the Rayleigh criteria and the non-Rayleigh scattering becomes more significant. As a result, the reflectivity peak in the ML is not as pronounced as in the scenario of Rayleigh scattering. In addition, the ML attenuation increases as PR intensifies (Li and Moisseev, 2019), which further impedes the increase of reflectivity in the ML. This also explains the lower reflectivity enhancement in the ML for rimed snow when $PR > 0.5 \text{ mm h}^{-1}$. As shown in Fig. 6, rimed snowflakes are usually smaller,

thus the non-Rayleigh effect and ML attenuation (von Lerber et al., 2014) are not as significant as the larger unrimed ice particles.




Figure 7. Same as Fig. 5, but for LDR observed by Ka-SACR.

When $PR \leq 0.15 \text{ mm h}^{-1}$, a weak reflectivity dip, the dark band, appears at the top of ML for unrimed snow, which may also be observed by cm-wavelength radars Fabry and Zawadzki (1995). In literature, the dark band has different definitions.

5 For ground-based radars, Kollias and Albrecht (2005) referred the dip of radar reflectivity below the ML top as dark band. The dark band which is present just above the ML top, as observed by the spaceborne W-band radar, can be caused by the strong signal attenuation from large snow aggregates as discussed in (Sassen et al., 2007). Meanwhile, the change of PSD during the aggregation process can also contribute to this reflectivity dip, which is named dark band by Sassen et al. (2005) and dim band by Heymsfield et al. (2008). In this study, the dark band is identified as the decrease of radar reflectivity just above the ML top

10 as shown in (Sassen et al., 2005, 2007; Heymsfield et al., 2008).

4.2.3 W-band reflectivity

W-band reflectivity can be heavily affected by a wet radome, rain, ML, supercooled liquid water and gaseous attenuation (Kneifel et al., 2015; Li and Moisseev, 2019). Such attenuation coupled with precipitation microphysical processes as well as the change of particle scattering regimes can modulate the W-band reflectivity profiles. As shown in Fig. 9, the decrease of

15 W-band reflectivity with height is mainly caused by rain attenuation. This effect is enhanced as PR increases, which has been adopted to retrieve PR (Matrosov, 2007). From dry to melting snow, there is a jump in W-band reflectivity, and the extent of




Figure 9. Same as Fig. 5, but for W-band. Note that the reflectivity profiles at W-band are shifted by matching the radar reflectivity at the ML bottom ($Z_{W,\text{rain}}$) while the value of $Z_{W,\text{rain}}$ is not shown due to the unknown W-band attenuation.

4.3 Weather radar measurements

Recent studies have demonstrated the potential of polarimetric measurements in revealing cloud microphysics and improving precipitation forecasts (Tiira and Moisseev, 2020; Trömel et al., 2019). Given the importance of precipitation intensity to the ML, it is necessary to address how the dual-polarization observations are dependent on PR. Therefore, we have analyzed the statistical profiles of Z_{dr} and K_{dp} observed by the RHI scan of FMI C-band dual-polarization radar. The vertical axis of weather radar RHI observations was shifted to the same level as we did for vertically-pointing radars.

Significant dependence of Z_{dr} and K_{dp} on PR can be found in Fig. 10. In cases where $\text{PR} > 0.15 \text{ mm h}^{-1}$, Z_{dr} decreases significantly to around 0 dB just above the ML. This is mainly due to the aggregation process, which leads to increased particle size and decreased density. In contrast, Z_{dr} does not change just above the ML when $\text{PR} \leq 0.15 \text{ mm h}^{-1}$, indicating that very weak aggregation happens in light precipitation. Li et al. (2018) have shown that Z_{dr} is a function of snow shape, canting angle distribution and density, and generally decreases with the increase of radar reflectivity. It would be interesting to study the riming impact on Z_{dr} profiles (Vogel and Fabry, 2018); unfortunately, we were not able to perform such a comparison due to the very limited number of RHI profiles during the studied events. It should be noted that the beam width of FMI C-band radar




Figure 10. Normalized Z_{dr} and K_{dp} profiles observed by FMI C-band radar with RHI scanning. Number of RHI profiles is presented at the bottom. The ML top (as retrieved from X-SACR observations) is used as the reference height in the vertical axis.

is 1° , resulting in vertical projection of around 1.1 km over the Hyytiälä station. This explains why the height of Z_{dr} starts increasing is approximately 500 m higher than the ML top determined by X-SACR.

High K_{dp} values were observed when PR exceeds 1 mm h^{-1} while no detectable K_{dp} signal can be found when $\text{PR} \leq 1 \text{ mm h}^{-1}$. This is in line with the previous finding that the enhanced K_{dp} is indicative of intense precipitation (Bechini et al., 2013).

- 5 When $\text{PR} > 1 \text{ mm h}^{-1}$, the enhanced K_{dp} starts at around 3000 m above the ML with the expected temperature of around -20°C , which is related to the dendritic growth region (Bechini et al., 2013; Moisseev et al., 2015). Overall, these observations indicate that the dependence of ML properties on the dual-polarization signatures above, may mainly be due to correlation of these signatures with precipitation intensity.

5 Conclusions

In this work, the connection between the precipitation melting layer and snow microphysics was studied using vertically-pointing multi-frequency Doppler radar and C-band dual-polarization weather radar observations. Using surface-based snowfall measurements collected over five winters at the University of Helsinki measurement station and supplemented by the single particle scattering datasets of aggregated snowflakes and rimed ice particles, a connection between rime mass fraction and radar observations at X- and Ka-bands was established and used in classifying unrimed and rimed snow. The sanity checks show that the results of this classification are consistent with the previous study using single-frequency radar observations (Zawadzki et al., 2005). Statistics of vertically-pointing multi-frequency dual-polarization radars and RHI scans of C-band polarimetric weather radar show that

- 10 1. The radar-observed melting layer properties show a detectable connection to the precipitation intensity. The increase in precipitation intensity can lead to the saggy bright band, i.e., the descending of reflectivity peak and ρ_{hv} dip.
2. Riming can affect melting layer properties in the following ways,
 - 15 (a) In moderate to heavy rainfall, riming may cause additional bright band sagging. However, the opposite effect is observed in light precipitation, namely, such sagging is associated with unrimed snow.
 - (b) X-band radar reflectivity peak is smaller for rimed snow than unrimed for a given precipitation intensity, if the non-Rayleigh scattering effect is not significant.
 - (c) If the non-Rayleigh scattering effect is distinct, e.g., at Ka- or W-band, the reflectivity peak can be larger for rimed snow.
 - (d) The reflectivity dip at the melting layer top (dark band) is obscured for rimed snow, while it is pronounced for unrimed snow. This suggests that the aggregation process may be suppressed by riming.
- 20 3. The decrease of Z_{dr} towards the melting layer is pronounced in heavy precipitation but is insignificant in light precipitation.

A well-calibrated triple-frequency radar setup has been shown potential in studying the microphysics of snowfall. However, such measurements may not be well suited to rainfall due to the highly uncertain W-band attenuation caused by the melting layer as well as the supercooled water. The approach presented explores the possibility of adding the Doppler velocity to distinguish between unrimed and rimed conditions and is less affected by the attenuation from supercooled water. Such instrumentation as the X/Ka-SACR mounted on the same platform takes much less effort in pointing alignment. Its application may also be expanded to space-borne radars. For example, instead of launching triple-frequency radars, implementing the Doppler capability with sufficient sensitivity on either of the radars on a dual-wavelength platform may be served as an option.

- 30 A coordinated radar setup as employed during BAECC facilitates the synergy of multiple radar frequencies and polarimetric observations at various scan modes. Due to the periodical changes of radar scanning modes during BAECC, the total stratiform rainfall cases are limited to ~ 11.5 h. More such observations can be utilized to evaluate and consolidate the presented

conclusions. If such coordinated measurement with high time resolution can be obtained in the future, our understanding of snow microphysical processes may be further advanced.

Data availability. Quicklooks of radar observations used in this study are available from <https://github.com/HaoranLiHelsinki/ACP-2020-Quicklooks>.

5 The FMI radar data are available from the Finnish Meteorological Institute open data portal: <http://en.ilmatieteenlaitos.fi/open-data-sets-available>.

The ARM data used in this study are available from Atmospheric Radiation Measurement (ARM) Climate Research Facility (ARM Climate Research Facility, 2006, 2010, 2011).

PIP data are available from <https://github.com/dmoisseev/Snow-Retrievals-2014-2015>.

10 *Author contributions.* HL and DM designed and conceptualized the study. HL performed the investigation and did the data analysis. DM contributed with the research supervision. JT processed the FMI C-band radar raw data. AvL developed the snow retrieval algorithm based on PIP products. HL wrote the original draft. All co-authors contributed to reviewing and editing this draft.

Competing interests. The authors declare that they have no conflict of interest.

Acknowledgements. We would like to thank the personnel of Hyytiälä station for their support in field observation. Special thanks to Matti

15 Leskinen for his help in data analysis. The research of Haoran Li, Jussi Tiira and Dmitri Moisseev were supported by the Academy of Finland Finnish Center of Excellence program (grant 307331) and ERA-PLANET, trans-national project iCUPE (grant agreement 689443), funded under the EU Horizon 2020 Framework Programme. Annakaisa von Lerber was funded by Academy of Finland (PostDoc grant 333901). Haoran Li was also funded by China Scholarship Council. The instrumentation used in this study was supported by NASA Global Precipitation Measurement Mission ground validation program and by the Office of Science U.S. Department of Energy ARM program.

References

- ARM Climate Research Facility: Marine W-Band (95 GHz) ARM Cloud Radar (MWACR). 2014-01-15 to 2014-09-13, ARM Mobile Facility (TMP) U. of Helsinki Research Station (SMEAR II), Hyttiala, Finland; AMF2 (M1), Compiled by Isom B., Bharadwaj N. , Lindenmaier I., Nelson D., Hardin J. and Matthews A., Atmospheric Radiation Measurement (ARM) Climate Research Facility Data Archive: Oak Ridge, Tennessee,USA, <https://doi.org/10.5439/1150242> (last access: 10 February 2018), 2006.
- ARM Climate Research Facility: Ka-Band Scanning ARM Cloud Radar (KASACRVPT). 2014-01-15 to 2014-09-13, ARM Mobile Facility (TMP) U. of Helsinki Research Station (SMEAR II), Hyttiala, Finland; AMF2 (M1), Compiled by Isom B., Bharadwaj N. , Lindenmaier I., Nelson D., Hardin J. and Matthews A., Atmospheric Radiation Measurement (ARM) Climate Research Facility Data Archive: Oak Ridge, Tennessee,USA, <https://doi.org/10.5439/1046201> (last access: 10 February 2018), 2010.
- ARM Climate Research Facility: X-Band Scanning ARM Cloud Radar (XSACRVPT). 2014-01-15 to 2014-09-13, ARM Mobile Facility (TMP) U. of Helsinki Research Station (SMEAR II), Hyttiala, Finland; AMF2 (M1), compiled by: Isom B., Bharadwaj N. , Lindenmaier I., Nelson D., Hardin J. and Matthews A., Atmospheric Radiation Measurement (ARM) Climate Research Facility Data Archive: Oak Ridge, Tennessee,USA, <https://doi.org/10.5439/1150303> (last access: 10 February 2018), 2011.
- Atlas, D.: Drop size and radar structure of a precipitation streamer, *Journal of Meteorology*, 14, 261–271, 1957.
- Bailey, M. P. and Hallett, J.: A comprehensive habit diagram for atmospheric ice crystals: Confirmation from the laboratory, AIRS II, and other field studies, *Journal of the Atmospheric Sciences*, 66, 2888–2899, 2009.
- Barrett, A. I., Westbrook, C. D., Nicol, J. C., and Stein, T. H.: Rapid ice aggregation process revealed through triple-wavelength Doppler spectrum radar analysis, *Atmospheric Chemistry and Physics*, 19, 5753–5769, 2019.
- Battaglia, A., Kummerow, C., Shin, D.-B., and Williams, C.: Constraining microwave brightness temperatures by radar brightband observations, *Journal of Atmospheric and Oceanic Technology*, 20, 856–871, 2003.
- Bechini, R., Baldini, L., and Chandrasekar, V.: Polarimetric radar observations in the ice region of precipitating clouds at C-band and X-band radar frequencies, *Journal of Applied Meteorology and Climatology*, 52, 1147–1169, 2013.
- Bringi, V. N. and Chandrasekar, V.: *Polarimetric Doppler weather radar: principles and applications*, Cambridge university press, 2001.
- Carlin, J. T. and Ryzhkov, A. V.: Estimation of Melting-Layer Cooling Rate from Dual-Polarization Radar: Spectral Bin Model Simulations, *Journal of Applied Meteorology and Climatology*, 58, 1485–1508, 2019.
- Chase, R. J., Finlon, J. A., Borque, P., McFarquhar, G. M., Nesbitt, S. W., Tanelli, S., Sy, O. O., Durden, S. L., and Poellot, M. R.: Evaluation of Triple-Frequency Radar Retrieval of Snowfall Properties Using Coincident Airborne In Situ Observations During OLYMPEX, *Geophysical Research Letters*, 45, 5752–5760, 2018.
- Dias Neto, J., Kneifel, S., Ori, D., Trömel, S., Handwerker, J., Bohn, B., Hermes, N., Mühlbauer, K., Lenefer, M., and Simmer, C.: The TRIPLE-frequency and Polarimetric radar Experiment for improving process observations of winter precipitation, *Earth System Science Data*, 11, 845–863, <https://doi.org/10.5194/essd-11-845-2019>, 2019.
- Doviak, R., Bringi, V., Ryzhkov, A., Zahrai, A., and Zrnić, D.: Considerations for polarimetric upgrades to operational WSR-88D radars, *Journal of Atmospheric and Oceanic Technology*, 17, 257–278, 2000.
- Erlingis, J. M., Gourley, J. J., Kirstetter, P.-E., Anagnostou, E. N., Kalogiros, J., Anagnostou, M. N., and Petersen, W.: Evaluation of operational and experimental precipitation algorithms and microphysical insights during IPHEX, *Journal of Hydrometeorology*, 19, 113–125, 2018.

- Fabry, F. and Zawadzki, I.: Long-term radar observations of the melting layer of precipitation and their interpretation, *Journal of the Atmospheric Sciences*, 52, 838–851, 1995.
- Falconi, M. T., Lerber, A. v., Ori, D., Marzano, F. S., and Moisseev, D.: Snowfall retrieval at X, Ka and W bands: consistency of backscattering and microphysical properties using BAecc ground-based measurements, *Atmospheric Measurement Techniques*, 11, 3059–3079, 2018.
- 5 Giangrande, S. E., Krause, J. M., and Ryzhkov, A. V.: Automatic designation of the melting layer with a polarimetric prototype of the WSR-88D radar, *Journal of Applied Meteorology and Climatology*, 47, 1354–1364, 2008.
- Giangrande, S. E., Toto, T., Bansemmer, A., Kumjian, M. R., Mishra, S., and Ryzhkov, A. V.: Insights into riming and aggregation processes as revealed by aircraft, radar, and disdrometer observations for a 27 April 2011 widespread precipitation event, *Journal of Geophysical Research: Atmospheres*, 121, 5846–5863, 2016.
- 10 Grecu, M., Tian, L., Heymsfield, G. M., Tokay, A., Olson, W. S., Heymsfield, A. J., and Bansemmer, A.: Nonparametric Methodology to Estimate Precipitating Ice from Multiple-Frequency Radar Reflectivity Observations, *Journal of Applied Meteorology and Climatology*, 57, 2605–2622, 2018.
- Haynes, J. M., L'Ecuyer, T. S., Stephens, G. L., Miller, S. D., Mitrescu, C., Wood, N. B., and Tanelli, S.: Rainfall retrieval over the ocean with spaceborne W-band radar, *Journal of Geophysical Research: Atmospheres*, 114, 2009.
- 15 Helmus, J. J. and Collis, S. M.: The Python ARM Radar Toolkit (Py-ART), a library for working with weather radar data in the Python programming language, *Journal of Open Research Software*, 4, 2016.
- Heymsfield, A. J., Bansemmer, A., Schmitt, C., Twohy, C., and Poellot, M. R.: Effective ice particle densities derived from aircraft data, *Journal of the atmospheric sciences*, 61, 982–1003, 2004.
- Heymsfield, A. J., Bansemmer, A., and Twohy, C. H.: Refinements to ice particle mass dimensional and terminal velocity relationships for ice
20 clouds. Part I: Temperature dependence, *Journal of the Atmospheric Sciences*, 64, 1047–1067, 2007.
- Heymsfield, A. J., Bansemmer, A., Matrosov, S., and Tian, L.: The 94-GHz radar dim band: Relevance to ice cloud properties and CloudSat, *Geophysical Research Letters*, 35, 2008.
- Heymsfield, A. J., Bansemmer, A., Poellot, M. R., and Wood, N.: Observations of ice microphysics through the melting layer, *Journal of the Atmospheric Sciences*, 72, 2902–2928, 2015.
- 25 Heymsfield, G. M.: Doppler radar study of a warm frontal region, *Journal of the Atmospheric Sciences*, 36, 2093–2107, 1979.
- Hogan, R. J., Illingworth, A. J., and Sauvageot, H.: Measuring crystal size in cirrus using 35- and 94-GHz radars, *Journal of Atmospheric and Oceanic Technology*, 17, 27–37, 2000.
- Huggel, A., Schmid, W., and Waldvogel, A.: Raindrop size distributions and the radar bright band, *Journal of Applied Meteorology*, 35, 1688–1701, 1996.
- 30 Illingworth, A. and Thompson, R.: Radar bright band correction using the linear depolarisation ratio, in: *Proc. Eighth Int. Symp. on Weather Radar and Hydrology*, pp. 64–68, 2011.
- Klaassen, W.: Radar observations and simulation of the melting layer of precipitation, *Journal of the Atmospheric Sciences*, 45, 3741–3753, 1988.
- Kneifel, S., Kulie, M., and Bennartz, R.: A triple-frequency approach to retrieve microphysical snowfall parameters, *Journal of Geophysical
35 Research: Atmospheres*, 116, 2011.
- Kneifel, S., Lerber, A., Tiira, J., Moisseev, D., Kollias, P., and Leinonen, J.: Observed relations between snowfall microphysics and triple-frequency radar measurements, *Journal of Geophysical Research: Atmospheres*, 120, 6034–6055, 2015.
- Kollias, P. and Albrecht, B.: Why the melting layer radar reflectivity is not bright at 94 GHz, *Geophysical research letters*, 32, 2005.

- Kollias, P., Jo, I., Borque, P., Tatarevic, A., Lamer, K., Bharadwaj, N., Widener, K., Johnson, K., and Clothiaux, E. E.: Scanning ARM cloud radars. Part II: Data quality control and processing, *Journal of Atmospheric and Oceanic Technology*, 31, 583–598, 2014.
- Korolev, A., Isaac, G., and Hallett, J.: Ice particle habits in stratiform clouds, *Quarterly Journal of the Royal Meteorological Society*, 126, 2873–2902, 2000.
- 5 Korolev, A. V., Isaac, G. A., Cober, S. G., Strapp, J. W., and Hallett, J.: Microphysical characterization of mixed-phase clouds, *Quarterly Journal of the Royal Meteorological Society: A journal of the atmospheric sciences, applied meteorology and physical oceanography*, 129, 39–65, 2003.
- Kruger, A. and Krajewski, W. F.: Two-dimensional video disdrometer: A description, *Journal of Atmospheric and Oceanic Technology*, 19, 602–617, 2002.
- 10 Kumjian, M. R., Mishra, S., Giangrande, S. E., Toto, T., Ryzhkov, A. V., and Bansemer, A.: Polarimetric radar and aircraft observations of saggy bright bands during MC3E, *Journal of Geophysical Research: Atmospheres*, 121, 3584–3607, 2016.
- Lamb, D. and Verlinde, J.: *Physics and chemistry of clouds*, Cambridge University Press, 2011.
- Leinonen, J. and Moisseev, D.: What do triple-frequency radar signatures reveal about aggregate snowflakes?, *Journal of Geophysical Research: Atmospheres*, 120, 229–239, 2015.
- 15 Leinonen, J. and Szyrmer, W.: Radar signatures of snowflake riming: A modeling study, *Earth and Space Science*, 2, 346–358, 2015.
- Leinonen, J., Kneifel, S., Moisseev, D., Tyynelä, J., Tanelli, S., and Nousiainen, T.: Evidence of nonspheroidal behavior in millimeter-wavelength radar observations of snowfall, *Journal of Geophysical Research: Atmospheres*, 117, 2012a.
- Leinonen, J., Moisseev, D., Leskinen, M., and Petersen, W. A.: A climatology of disdrometer measurements of rainfall in Finland over five years with implications for global radar observations, *Journal of Applied Meteorology and Climatology*, 51, 392–404, 2012b.
- 20 Leinonen, J., Moisseev, D., and Nousiainen, T.: Linking snowflake microstructure to multi-frequency radar observations, *Journal of Geophysical Research: Atmospheres*, 118, 3259–3270, 2013.
- Leinonen, J., Lebsock, M. D., Tanelli, S., Sy, O. O., Dolan, B., Chase, R. J., Finlon, J. A., von Lerber, A., Moisseev, D., et al.: Retrieval of snowflake microphysical properties from multifrequency radar observations, *Atmospheric Measurement Techniques*, 2018.
- Lhermitte, R. M.: Observation of rain at vertical incidence with a 94 GHz Doppler radar: An insight on Mie scattering, *Geophysical Research Letters*, 15, 1125–1128, 1988.
- 25 Li, H. and Moisseev, D.: Melting layer attenuation at Ka- and W-bands as derived from multi-frequency radar Doppler spectra observations, *Journal of Geophysical Research: Atmospheres*, 124, <https://doi.org/10.1029/2019JD030316>, 2019.
- Li, H. and Moisseev, D.: Two layers of melting ice particles within a single radar bright band: Interpretation and implications, *Geophysical Research Letters*, 47, <https://doi.org/10.1029/2020GL087499>, 2020.
- 30 Li, H., Moisseev, D., and von Lerber, A.: How does riming affect dual-polarization radar observations and snowflake shape?, *Journal of Geophysical Research: Atmospheres*, 123, 6070–6081, 2018.
- Liebe, H. J.: An updated model for millimeter wave propagation in moist air, *Radio Science*, 20, 1069–1089, 1985.
- Locatelli, J. D. and Hobbs, P. V.: Fall speeds and masses of solid precipitation particles, *Journal of Geophysical Research*, 79, 2185–2197, 1974.
- 35 Mason, S., Chiu, C., Hogan, R., Moisseev, D., and Kneifel, S.: Retrievals of Riming and Snow Density From Vertically Pointing Doppler Radars, *Journal of Geophysical Research: Atmospheres*, 123, 13–807, 2018.

- Mason, S. L., Hogan, R. J., Westbrook, C. D., Kneifel, S., Moisseev, D., and Terzi, L. v.: The importance of particle size distribution and internal structure for triple-frequency radar retrievals of the morphology of snow, *Atmospheric Measurement Techniques*, 12, 4993–5018, 2019.
- Matrosov, S. Y.: A dual-wavelength radar method to measure snowfall rate, *Journal of Applied Meteorology*, 37, 1510–1521, 1998.
- 5 Matrosov, S. Y.: Potential for attenuation-based estimations of rainfall rate from CloudSat, *Geophysical research letters*, 34, 2007.
- Matrosov, S. Y.: Assessment of radar signal attenuation caused by the melting hydrometeor layer, *IEEE Transactions on Geoscience and Remote Sensing*, 46, 1039–1047, 2008.
- Moisseev, D., von Lerber, A., and Tiira, J.: Quantifying the effect of riming on snowfall using ground-based observations, *Journal of Geophysical Research: Atmospheres*, 122, 4019–4037, 2017.
- 10 Moisseev, D., Lautaportti, S., Alku, L., Tabakova, K., O’Connor, E. J., Leskinen, M., and Kulmala, M.: Inadvertent Localized Intensification of Precipitation by Aircraft, *Journal of Geophysical Research: Atmospheres*, 124, 2094–2104, <https://doi.org/10.1029/2018JD029449>, <https://agupubs.onlinelibrary.wiley.com/doi/abs/10.1029/2018JD029449>, 2019.
- Moisseev, D. N., Lautaportti, S., Tyynela, J., and Lim, S.: Dual-polarization radar signatures in snowstorms: Role of snowflake aggregation, *Journal of Geophysical Research: Atmospheres*, 120, 12 644–12 655, 2015.
- 15 Morrison, H. and Milbrandt, J. A.: Parameterization of cloud microphysics based on the prediction of bulk ice particle properties. Part I: Scheme description and idealized tests, *Journal of the Atmospheric Sciences*, 72, 287–311, 2015.
- Newman, A. J., Kucera, P. A., and Bliven, L. F.: Presenting the snowflake video imager (SVI), *Journal of Atmospheric and Oceanic technology*, 26, 167–179, 2009.
- Oue, M., Kollias, P., Ryzhkov, A., and Luke, E. P.: Toward exploring the synergy between cloud radar polarimetry and Doppler spectral
20 analysis in deep cold precipitating systems in the Arctic, *Journal of Geophysical Research: Atmospheres*, 123, 2797–2815, 2018.
- Petäjä, T., O’Connor, E. J., Moisseev, D., Sinclair, V. A., Manninen, A. J., Väänänen, R., von Lerber, A., Thornton, J. A., Nicoll, K., Petersen, W., et al.: BA ECC: A field campaign to elucidate the impact of biogenic aerosols on clouds and climate, *Bulletin of the American Meteorological Society*, 97, 1909–1928, 2016.
- Ryde, J.: The attenuation and radar echoes produced at centimeter wavelengths by various meteorological phenomena., *Meteorological
25 Factors in Radio Wave Propagation*, London, pp. 169–189, 1946.
- Ryzhkov, A., Zhang, P., Reeves, H., Kumjian, M., Tschallener, T., Trömel, S., and Simmer, C.: Quasi-vertical profiles—A new way to look at polarimetric radar data, *Journal of Atmospheric and Oceanic Technology*, 33, 551–562, 2016.
- Sandford, C., Illingworth, A., and Thompson, R.: The potential use of the linear depolarization ratio to distinguish between convective and stratiform rainfall to improve radar rain-rate estimates, *Journal of Applied Meteorology and Climatology*, 56, 2927–2940, 2017.
- 30 Sarma, A. C., Deshamukhya, A., Narayana Rao, T., and Sharma, S.: A study of raindrop size distribution during stratiform rain and development of its parameterization scheme in the framework of multi-parameter observations, *Meteorological Applications*, 23, 254–268, 2016.
- Sassen, K., Campbell, J. R., Zhu, J., Kollias, P., Shupe, M., and Williams, C.: Lidar and triple-wavelength Doppler radar measurements of the melting layer: A revised model for dark-and brightband phenomena, *Journal of Applied Meteorology*, 44, 301–312, 2005.
- 35 Sassen, K., Matrosov, S., and Campbell, J.: CloudSat spaceborne 94 GHz radar bright bands in the melting layer: An attenuation-driven upside-down lidar analog, *Geophysical Research Letters*, 34, 2007.
- Sekelsky, S. M.: Near-field reflectivity and antenna boresight gain corrections for millimeter-wave atmospheric radars, *Journal of Atmospheric and Oceanic Technology*, 19, 468–477, 2002.

- Stewart, R. E., Marwitz, J. D., Pace, J. C., and Carbone, R. E.: Characteristics through the melting layer of stratiform clouds, *Journal of the Atmospheric Sciences*, 41, 3227–3237, 1984.
- Szeto, K. K., Lin, C. A., and Stewart, R. E.: Mesoscale circulations forced by melting snow. Part I: Basic simulations and dynamics, *Journal of the Atmospheric Sciences*, 45, 1629–1641, 1988.
- 5 Szyrmer, W. and Zawadzki, I.: Modeling of the melting layer. Part I: Dynamics and microphysics, *Journal of the Atmospheric Sciences*, 56, 3573–3592, 1999.
- Tiira, J. and Moisseev, D. N.: Unsupervised classification of vertical profiles of dual polarization radar variables, *Atmospheric Measurement Techniques*, 13, 1227–1241, 2020.
- Tiira, J., Moisseev, D. N., von Lerber, A., Ori, D., Tokay, A., Bliven, L. F., and Petersen, W.: Ensemble mean density and its connection to
10 other microphysical properties of falling snow as observed in Southern Finland, *Atmospheric Measurement Techniques*, 9, 2016.
- Trömel, S., Ryzhkov, A. V., Zhang, P., and Simmer, C.: Investigations of backscatter differential phase in the melting layer, *Journal of Applied Meteorology and Climatology*, 53, 2344–2359, 2014.
- Trömel, S., Ryzhkov, A. V., Hickman, B., Mühlbauer, K., and Simmer, C.: Polarimetric radar variables in the layers of melting and den-
15 dritic growth at X band—implications for a nowcasting strategy in stratiform rain, *Journal of Applied Meteorology and Climatology*, 58, 2497–2522, 2019.
- Tyynelä, J. and Chandrasekar, V.: Characterizing falling snow using multifrequency dual-polarization measurements, *Journal of Geophysical Research: Atmospheres*, 119, 8268–8283, 2014.
- Tyynelä, J. and von Lerber, A.: Validation of microphysical snow models using in-situ, multi-frequency and dual-polarization radar measure-
20 ments in Finland, 124, 13 273–13 290, <https://doi.org/10.1029/2019JD030721>, <https://agupubs.onlinelibrary.wiley.com/doi/abs/10.1029/2019JD030721>, 2019.
- Vogel, J. M. and Fabry, F.: Contrasting Polarimetric Observations of Stratiform Riming and Nonriming Events, *Journal of Applied Meteorology and Climatology*, 57, 457–476, 2018.
- von Lerber, A., Moisseev, D., Leinonen, J., Koistinen, J., and Hallikainen, M. T.: Modeling radar attenuation by a low melting layer with
optimized model parameters at C-band, *IEEE Transactions on Geoscience and Remote Sensing*, 53, 724–737, 2014.
- 25 von Lerber, A., Moisseev, D., Bliven, L. F., Petersen, W., Harri, A.-M., and Chandrasekar, V.: Microphysical properties of snow and their link to Z e–S relations during BAECC 2014, *Journal of Applied Meteorology and Climatology*, 56, 1561–1582, 2017.
- Willis, P. T. and Heymsfield, A. J.: Structure of the melting layer in mesoscale convective system stratiform precipitation, *Journal of the Atmospheric Sciences*, 46, 2008–2025, 1989.
- Wolfensberger, D., Scipion, D., and Berne, A.: Detection and characterization of the melting layer based on polarimetric radar scans, *Quarterly Journal of the Royal Meteorological Society*, 142, 108–124, 2016.
- 30 Xie, X., Evaristo, R., Simmer, C., Handwerker, J., and Trömel, S.: Precipitation and microphysical processes observed by three polarimetric X-band radars and ground-based instrumentation during HOPE, *Atmospheric Chemistry and Physics*, 16, 7105–7116, 2016.
- Zawadzki, I., Szyrmer, W., Bell, C., and Fabry, F.: Modeling of the melting layer. Part III: The density effect, *Journal of the Atmospheric Sciences*, 62, 3705–3723, 2005.