Local to regional methane emissions from the Upper Silesia Coal Basin (USCB) quantified using UAV-based atmospheric measurements

Truls Andersen¹, Zhao Zhao², Marcel de Vries¹, Jaroslaw Necki⁴, Justyna Swolkien⁵, Malika Menoud⁶, Thomas Röckmann⁶, Anke Roiger⁷, Andreas Fix⁷, Wouter Peters^{1,3}, and Huilin Chen^{1,2*}

¹Centre for Isotope Research, Energy and Sustainability Institute Groningen (ESRIG), University of Groningen, Groningen, Netherlands

²Joint International Research Laboratory of Atmospheric and Earth System Sciences, School of Atmospheric Sciences, Nanjing University, Nanjing, China

- ³Meteorology and Air Quality, Wageningen University and Research Centre, Wageningen, Netherlands ⁴Faculty of Physics and Applied Computer Science, AGH University of Science and Technology, Krakow, Poland ⁵Faculty Civil Engineering and Resource Management, AGH University of Science and Technology, Krakow, Poland ⁶Institute for Marine and Atmospheric Research Utrecht (IMAU), Utrecht University, Utrecht, Netherlands ⁷Deutsches Zentrum für Luft- und Raumfahrt e.V. (DLR), Institut für Physik der Atmosphäre, Oberpfaffenhofen, Germany
- 15 Correspondence to: Huilin Chen (huilin.chen@rug.nl or huilin.chen@nju.edu.cn)

5

Abstract. Coal mining accounts for ~ 12 % of the total anthropogenic methane (CH₄) emissions worldwide. The Upper Silesian Coal Basin, Poland, where large quantities of CH₄ are emitted to the atmosphere via ventilation shafts of underground hard coal (anthracite) mines, is one of the hot spots of methane emissions in Europe. However, coalbed CH₄ emissions into the atmosphere are poorly characterized. As part of the Carbon Dioxide and CH₄ mission 1.0 (CoMet 1.0) that took place in

- 20 May June 2018, we flew a recently developed active AirCore system aboard an unmanned aerial vehicle (UAV) to obtain CH₄ and CO₂ mole fractions 150-300 m downwind of five individual ventilation shafts in the USCB. In addition, we also measured δ^{13} C-CH₄, δ^{2} H-CH₄, ambient temperature, pressure, relative humidity, surface wind speeds, and directions. We used 34 UAV flights and two different approaches (IG approach and MB approach) to quantify the emissions from individual shafts. The quantified emissions were compared to both annual and hourly inventory data and were used to derive the estimates of
- 25 CH₄ emissions in the USCB. We found a high correlation ($R^2 = 0.7 0.9$) between the quantified and hourly inventory databased shaft-averaged CH₄ emissions, which in principle would allow regional estimates of CH₄ emissions to be derived by upscaling individual hourly inventory data of all shafts. Currently, such inventory data is available only for the five shafts we quantified. As an alternative, we have developed three upscaling approaches, i.e., by scaling the E-PRTR annual inventory, the quantified shaft-averaged emission rate, and the shaft-averaged emission rate that are derived from the hourly emission
- 30 inventory. These estimates are in the range of 256 383 kt CH₄/year for the IG approach and 228 339 kt CH₄/year for the

MB approach, respectively. This study shows that the UAV-based active AirCore system can be a useful tool to quantify local to regional point source methane emissions.

1 Introduction

Methane (CH₄) is the second most abundant anthropogenic greenhouse gas (GHG), only second to carbon dioxide (CO₂).
Although its abundance is lower than that of CO₂, CH₄ has a warming potential 28 times greater on a 100-year time frame (Etminan et al., 2016; Van Dingenen et al., 2018). In 2020, its mole fraction reached a global mean of higher than 1870 ppb (Dlugokencky, 2020), a level more than 2.5 times that of preindustrial times. This is mainly attributed to anthropogenic emissions over the last 270 years. Natural CH₄ is produced through reservoirs like wetlands and oceans, while anthropogenic CH₄ originates from sources like agriculture, waste management, biomass burning, and exploitation, distribution and use of fossil fuels (Kirschke et al., 2013; Saunois et al., 2016b).

Exploitation of fossil fuels is one of the major contributors of anthropogenic CH4. In the years 2003 to 2017, fossil fuel production and use contributed to an average of 35 % (range 30 – 42 %) of the total annual anthropogenic CH4 emissions, with a mean emission estimate of 128 (range 113 – 154) Tg CH4/year (Saunois et al., 2016a,b 2020). However, the
magnitudes of CH4 emissions are characterized with high uncertainties (Kirschke et al., 2013; Saunois et al., 2017; Turner et al., 2019), with uncertainties of fossil fuel production and use ranging from 20 to 35 % (Saunois et al., 2020). A substantial part of the emitted CH4 from fossil fuel production and use (~33 %, i.e., 41 Tg CH4/year) comes from atmospheric emissions of CH4 from coal mine operations, including underground mining and opencast mining, as well as post-mining activities. Coal mining accounts for ~ 12 % of the total anthropogenic methane emissions worldwide (Saunois et al., 2020). When hard coal is extracted by cracking the coal from the bedrock, as well as when the coal is processed via both crushing and pulverization, large quantities of CH4 are released (Zazzeri et al., 2016). The CH4 stored in the coalbed originates from carbonification of biomass (Swolkień, 2020). In the underground mines, some CH4 is captured via drainage

- systems and then transported to the surface where it is utilized. The remaining CH4 that has not been captured is released into the mine working area and is then diluted with airflow and vented directly to the atmosphere through
 ventilation shafts at the surface to keep the concentration of coal gas within limits for working safety. For many mines, the
- exact amount of CH₄ emitted to the atmosphere through these ventilation shafts is poorly characterized and even if data loggers are used to monitor the emissions for reporting to inventories, they lack accuracy and continuity (Swolkień, 2020). Without accurate estimates of emissions, it is challenging to develop appropriate mitigation strategies as well as reliable future climate projections.
- 60

Stationary towers (Werner et al., 2003; Andrews et al., 2014; Satar et al., 2016) and aircraft measurements (Karion et al., 2013; Krautwurst et al., 2017; Hannun et al., 2020) are commonly used techniques to obtain atmospheric in-situ

measurements, and in recent years the use of unmanned aerial vehicles (UAVs) have also become a key part of the monitoring and measuring of greenhouse gases. In comparison to aircraft, UAVs are easy to maintain, cheap to obtain,

easy to operate, and require less efforts to obtain permits for flying (Villa et al., 2016; Kunz et al., 2020). These UAVs 65 measure and analyze GHGs in a number of different ways; direct in-situ measurement by lightweight sensors (Nathan et al., 2015; Kunz et al., 2020; Martinez et al., 2020; Tuzson et al., 2020), tethered UAV sampling (Turnbullet al., 2014; Brosv et al., 2017; Allen et al., 2019; Shah et al., 2020), and on-board sampling for later analysis (Lowry et al., 2015; Brownlow et al., 2016; Chang et al., 2016; Greatwood et al., 2017; Andersen et al., 2018).

70

75

80

This study is part of the Carbon Dioxide and Methane (CoMet) mission. The CoMet aims at preparing the validation activities for the upcoming German-French Climate satellite mission MERLIN (Ehret et al., 2017; Fix et al., 2018). In this context, CoMet tries to obtain independent observations of GHG emissions by developing and evaluating new methodologies that can also be used for the validation of satellite measurements (Fix et al., 2018; Swolkień, 2020; Fiehn et al., 2020). Here, in-situ as well as active and passive remote sensing measurements are used to quantify CO_2 and CH_4 emissions, which are deployed on different airborne and mobile ground-based platforms. One of the focuses of the CoMet campaign is to quantify the regional CH₄ emissions from the Upper Silesian Coal Basin (USCB) (Nickl et al., 2020). The USCB, located in the southern part of Poland, is a region containing extensive hard coal mining, and is home to more than 70 mining facilities, including coal piles, coal waste heaps, and underground mining networks. According to the European Pollutant Release and Transfer Register (E-PRTR), the USCB emitted 447 kt CH4 in 2018, with individual coal mine ventilation shafts ranging between emission rates of 0.03 to 20 kt CH₄/year. This makes the USCB a strong contributor to the annually

emitted CH4 from Europe, being responsible for 27.3 % of the total European CH4 emissions of 1642 kt CH4/year in 2017 according to E-PRTR. With the large emission of CH₄, and large uncertainties, the USCB is an important region to study and quantify emitted CH₄ from the contributing sources.

85

Between May 18 and June 1 2018, we performed 59 UAV-based active AirCore flights downwind of individual coal mine ventilation shafts, quantifying the CO_2 and CH_4 emissions using both an inverse Gaussian (IG) approach and a mass balance approach (MB). Isotopic signatures of δ^{13} C-CH₄ and δ^{2} H-CH₄ were also obtained by analyzing air samples collected by AirCore during flight. Here we present quantified emissions of shafts using 34 active AirCore flights that fulfill the flight selection criteria (Andersen et al., 2021) based on atmospheric sampling of CO₂ and CH₄ downwind of five individual

- 90 coal mine ventilation shafts spread across the USCB. These are compared to individual coal mine ventilation shaft inventories, and are then scaled up to estimate the regional USCB CH₄ emissions. The upscaled results are compared to regional inventories from E-PRTR as well as previous regional emission estimates from Fiehn et al. (2020) and Kostinek et al. (2021). Isotopic signatures of δ^{13} C-CH₄ and δ^2 H-CH₄ are presented for all five individual coal mine ventilation shafts and compared to previous measurements and known isotopic signature sources. We show that a strong correlation (R2
- 95

= 0.7 - 0.9) was found between the quantified and hourly inventory data-based shaft-averaged CH4 emissions.

Based on the correlation, we estimated regional CH4 emissions by upscaling shaft-averaged CH4 emissions.

2 Methodology

2.1 Flight information

- 100 From an internal CoMet inventory based on E-PRTR 2018 emission data, there are 59 ventilation shafts related to hard coal mining operations located within the USCB. Fig. 1 indicates the size of this region. We sampled air from 5 of these ventilation shafts based on their accessibility, and performed a total of 59 flights during the period from May 18 to June 1, 2018. 34 of the 59 flights fulfilled the sampling criteria presented in Andersen et al. (2021), i.e., the mean wind speed during the flight is larger than 2 m/s and that the flights are performed perpendicular to the wind direction (within 15°)." The
- 105 flights were performed downwind of a specific ventilation shaft while flying perpendicular tracks transecting the plume at incremental heights. This technique effectively creates a vertical curtain transecting the ventilation shaft plume. The curtain is spaced out into gridded boxes in horizontal(y)- and vertical (z)-direction of size equal to the largest distance between two data point coordinates in the flight, and the largest altitude difference between two point coordinates throughout the flight. The criteria states that the mean wind speed during the flight is larger than 2 m/s and that the flights are performed
- 110 perpendicular to the wind direction (within 15 degrees). Table (1) shows the number of flights per shaft that fulfilled these criteria, along with the number of measurement days present for each shaft. The flight pattern for the flights was a 'curtain' shape downwind the plume, attempting to intersect the plume at different altitude levels. Fig. 2a shows an example of this pattern. The flight duration varied between 8 and 12 minutes, altitudes up to 100 m above ground, and distances downwind the plume ranged between 100 to 350 m downwind the ventilation shafts.

Table 1.	The location of the sampled ventilation shafts, along with the number of days of sampling occurred for each shaft and the number
of succes	ful flights each shaft has for emission quantification.

Coal mining ventilation shaft	Latitude	Longitude	Flights per shaft	Days with sampling
Borynia VI	49.996697°N	18.648178°E	4	2
Brzeszcze IX	50.009589°N	19.156781°E	5	1
Pniowek IV	49.980367°N	18.676131°E	7	1
Pniowek V	49.975407°N	18.735400°E	15	5
Zofiowka IV	49.968117°N	18.627664°E	5	1



120

Figure 1. The location of the 5 measured facilities (round markers) and the meteorological station where wind data for flights #5 to #33 was obtained. The red border indicates the total size of the Silesia Coal Basin where the majority of coal mining shafts were located. We have primarily performed measurements in the south-western part of the region.

2.2 UAV-based Active AirCore system

- 125 The active AirCore system was introduced in Andersen et al. (2018), and further refined in Andersen et al. (2021). The active AirCore system is an air sampling tool which collects air along the trajectory of a UAV flight by pulling air through a long coiled-up stainless-steel tube. The pump is a small KNF020L micropump, which provides a vacuum downstream of a 45 μm pinhole orifice in order to create conditions for critical flow. Thus, the sampling flow rate of the AirCore only depends on the upstream pressure (ambient pressure), which is measured through the datalogger, along with ambient temperature, ambient
- 130 relative humidity, temperature within the carbon fiber box housing, and GPS coordinates. The inlet of the AirCore system was positioned to the side of the carbon fiber box that is beneath the propellers. Therefore, the air sampled into the AirCore is effectively from above the propellers, within less than 0.5 m above the propellers (Lampert et al., 2020). As the UAV is most of time moving forward at a steady speed of 1-2 m/s, the collected air samples will not be disturbed. This study used three different active AirCore systems, all having 1/8 in. tubing. The lengths of the AirCore were 48.2 m, 46.9 m, and 48.5 m, with
- 135 estimated volumes of 323 cc, 315 cc, and 325 cc, respectively. The UAV that the active AirCore system is attached to is a DJI Inspire Pro 1. Once an air sample has been obtained, the air is analyzed by a cavity ringdown spectrometer (CRDS, model no. G2401-m, Picarro Inc.) for CO₂, CH₄, and CO mole fractions. The CRDS used a high-CH₄ analysis mode due to the large

range of observed CH₄ mole fractions (up to 200 ppm). A two-point calibration was used using a known WMO-scale gas mixture around ambient CH₄ mole fractions (WMO X2007, X2004A, and X2014A scales for CO₂, CH₄, and CO, respectively),

140 and a certified mole-fraction gas mixture from the Dutch National Metrology Institute (VSL) containing a high mole-fraction of CH₄ (301.1 ppm).

The AirCore samples were collected at the outlet of the Picarro, downstream of the pump, and were stored in Tedlar bags for further analysis of isotopic signatures of δ^{13} C-CH₄ and δ^{2} H-CH₄ at a later time in the laboratory using a continuous flow isotope

145 ratio mass spectrometer system. More details about the analytical system and the calibration are provided in Brass and Röckmann, 2011; Röckmann et al, 2016; Menoud et al., 2021. Out of the 59 flights performed during this study, the air samples from 34 flights were stored in Tedlar bags for further analysis of isotopic composition. Shafts Borynia VI, Pniowek IV, and Pniowek V had two separate days where isotopic compositions were measured, while Brzeszcze IX and Zofiowka IV had 1 day. Each day collected between 4 and 5 samples which were used to determine the isotopic signature using a keeling plot.

150

AirCore concentration peaks are dampened due to molecular and Taylor diffusions in the sampling tube, but mostly due to mixing of air samples in the cavity of the analyzer (Andersen et al., 2018). Deconvolving the measured signal to obtain the unaffected concentration peaks is possible, as is done in Andersen et al. (2021). However, we have found that the moving averages of the original data using an averaging kernel of 33–34 s can well match the convoluted signal. Therefore, the

155 simulated data from the Gaussian model is smoothed with such an averaging kernel before comparing with the AirCore observations. This was thus performed for all flights during the processing of the data.

2.3 Meteorological data

During the first four flights of the campaign, meteorological parameters (ambient temperature, pressure, relative humidity, wind speed, and wind direction) were measured using a radiosonde (Sparv Embedded AB, Sweden, model S1H2-R)
identical to the one used in Andersen et al. (2021). The radiosonde was tethered through a fishing pole for easier retrieval and reuse, but was lost during the fourth flight due to getting too close to power lines. Four flights had radiosonde profiles to estimate the wind speeds and directions. The data for flights #5 to #33 were obtained from a nearby meteorological station operated by the Polish meteorological office (IMGW). This was the Katowice Synoptic meteorological station, located at coordinates 50.240556N, 19.032778E. The use of this meteorological data, located a few
tens of kilometers away from the measurement sites, may add significant uncertainty to the wind speed and direction for those flights, which was not quantified. For the second half of the campaign, from flight #34 to #59, a mobile onsite meteorological station was used. The surface wind speed and wind direction were measured using a Campbell CSAT3 3-D Sonic Anemometer at about 1.5 m above ground. The mean differences wind speed and wind direction between the Katowice Synoptic meteorological station and the mobile meteorological stations for flights #34 and onward were 1.7 ± 0.7 m/s and

 $38.8 \pm 29.6^{\circ}$, respectively. 170

2.4 Emission determination

The emitted CH_4 emanating from the ventilation shafts is quantified using the methodology derived in Andersen et al. (2021). At each ventilation shaft, CH₄ is vented to the atmosphere through one or more diffusers. Given the distance of 100 -300 m between the UAV measurements and the ventilation shaft, the emission source can be regarded as a point source. The

175 gridded plane is then used to quantify the emitted emission by applying an IG approach and a MB approach. The Gaussian model is given as:

 $C'(x, y, z) = \frac{Q}{2\pi \sigma_v \sigma_z u} exp\left(-\frac{1}{2}\left(\frac{y}{\sigma_v}\right)^2\right).$ (1) $\left[exp\left(-\frac{1}{2}\left(\frac{h-z}{\sigma_z}\right)^2\right) + exp\left(-\frac{1}{2}\left(\frac{h+z}{\sigma_z}\right)^2\right)\right] \cdot \frac{V}{M_{CH_z}}$

where C' is the dry mole fraction at a given position x, y, and z, which are the projected positional coordinates 180 downwind the plume, across the plume horizontally, and across the plume vertically. The units of C'(x, y, z) in mol/mol, and the units of x, y, and z are given in m. The emission rate Q is given in kg/s, the wind speed u in m/s, and the stack height h is given in m. The parameters σ_v and σ_z describe the dispersion of the pollutants in the horizontal- and vertical direction, respectively, and have units of m. V is the dry molar volume in m^3/mol , and M_{CH_4} is the molar mass of CH₄, 0.016 kg/mol.

185

For the MB approach, the gridded flight pattern is extrapolated into a full 2D plane using a kriging method, to which the MB equation is applied. Fig. 2 shows a measured UAV-based active AirCore profile of CH₄ mole fractions along with the 2D extrapolated kriged CH₄ plane, and the IG's estimate plane of CH₄ mole fractions. The MB equation is given as:

$$Q = \frac{\nu \cdot \Delta X \cdot M_{CH_4}}{R \cdot T} \sum_{i}^{k_i} \sum_{j}^{k_j} C_{i,j} \cdot P_{i,j}$$
(2)

190

where the output of the emission rate Q is in kg/s, v is the wind speed in m/s and assumed to be constant throughout the duration of the flights, k_i is the number of horizontal grid boxes in the kriged plane, k_i is the number of vertical grid boxes in the kriged plane, M_{CH4} is the molecular mass of CH4 in kg/mol, $C_{i,j}$ is the CH4 mole fraction in grid box i, j in mol/mol, ΔX is the area of each grid box in m², R is the universal gas constant, 8.3145 kg m²/s² K mol, T is the temperature in K, and $P_{i, j}$ is the pressure at each grid box in Pa.

195 The minimum concentration of the entire flights was used as background, which was subtracted from the measured concentrations before calculation of the emissions for both the MB and the IG approach. The minimum concentration is not the same as a typical choice of e.g., 10 percentile (Vinković et al., 2022); however, the difference of the two values is relatively small compared to the large CH₄ enhancements, and thus causes negligible difference in the calculated CH₄ emissions.



200 Figure 2. (a) a sampled downwind CH₄ mole fraction profile, (b) a kriged extrapolated 2D plane of CH₄ mole fractions for the MB approach and (c) an estimated 2D CH₄ mole fraction plane using the parameters retrieved from the IG approach.

The AirCore flight data (*Y*) presented in fig 2(a) is compared with the plume simulations of the Gaussian dispersion model. A best fit for eq. 1 to the data can be found for these five parameters by minimizing the cost function $J(Q, \sigma_y, \sigma_z, H, D) = (C(Q, \sigma_y, \sigma_z, H, D) - Y)^2$ using a standard square error (SSE) approach. The five parameters include the dispersion

- 205 parameters in the horizontal and the vertical direction (σ_y and σ_z), the emission rate (Q) and the coordinates of the center of the plume in the curtain (height H and distance D). A group of random starting points for the five parameters between their lower and upper boundaries are set for the optimizer each time, and the optimization is run 1000 times to ensure that not only a local minimum is found (Andersen et al., 2021). In this way, we obtain a series of optimized values for each of the four parameters as the final results, and the five unknown parameters are optimized simultaneously.
- 210 A detailed description of the uncertainty analysis for both the IG and the MB methods has been presented in Andersen et al. (2021). Here, we only give a brief description. The uncertainty of the IG method is calculated as the standard deviation of a series of optimized emission rates generated by a large number of optimization runs (N = 1000). The uncertainty of the MB method is mainly determined by the uncertainty and the variability of wind speed and wind direction measurements.

2.5 Inventory emissions

215 The E-PRTR inventory gives the annual emission estimate for each coal mine in the Silesia region. An internal CoMet inventory, which is based on reported 2018 E-PRTR inventories (Gałkowski et al., 2021), lists 59 facilities related to coal mining operations in the USCB, and divides the annual coal mine inventory by geo-localized (via Google Earth) active ventilation shafts for each coal mine. For the comparison used in this study, the active ventilation shafts are assumed to be

the same as the ones stated in the internal CoMet inventory, but the E-PRTR values that are being divided equally among

- 220 active shafts, have been updated to the reported E-PRTR 2018 inventories. Pniowek, with a reported emission rate of 54.7 kt CH₄/year and three active shafts thus yields an average emission rate of 18.2 kt CH₄/year for ventilation shafts Pniowek III, IV, and V. The inventory value for Borynia VI is 6.4 kt CH₄/year, for Zofiowka IV 13.9 kt CH₄/year, and for Brzeszcze IX 13 kt CH₄/year.
- A second set of inventory data for May to June 2018 is also used for comparison during this study. This is hourly data calculated from raw CH₄ concentration measurements and air flow rate measurements obtained within each specific ventilation shaft. Fig. 3 shows a schematic design of a ventilation shaft. The concentration of CH₄ is measured with an EMAG-Serwis type DCH methane sensor placed 10 to 15 m down into the exhaust shaft. This sensor has a measurement range of 0 -100 % with measurement errors of 5 % of the reading value. The air flow rate is measured using a Prandtl's tube located
- 230 between the main valve and the fan. According to Swolkień (2020), the relative uncertainty for the air flow rate is 10 %. According to the statements of ventilation engineers, the measured air flow includes about 5% ambient air from the ventilation shaft closure, and we have taken that into account during the calculation of the hourly emission rates, i.e., CH₄ concentrations multiplied by 95% of the measured air flow rates.
- 235 The conversion into CH₄ emissions rate is done as follows:

$$Q_{Inventory} = \frac{P \cdot V_{flow}}{R \cdot T} \rho \tag{3}$$

Where *P* is the atmospheric pressure in Pa, *R* is the universal gas constant in J mol⁻¹ K⁻¹, *T* is the ambient temperature in K, V_{flow} is the volumetric flow rate of CH₄ in m³ s⁻¹, given by the air flow rate multiplied by the CH₄ concentration. Lastly, ρ is the molar density of CH₄ in g mol⁻¹ (16.043 g mol⁻¹). A temperature of 20 °C and a pressure of 101325 Pa was used for the calculation.



Figure 3. Figure from (Swolkień (2020), Fig. 5) showing a coal mine ventilation shaft scheme. This Figure has been re-illustrated with updated graphics and readability for this paper. The original Figure was published under a Creative Commons Attribution 4.0 International License, http://creativecommons.org/licenses/by/4.0/.

2.6 Up-scaling

- As mentioned in Sect. 2.3, more than 70 facilities related to coal mining operations are located in the USCB. According to the internal CoMet inventory, 59 are active ventilation shafts. After obtaining CO₂ and CH₄ emissions from 5 of the 59 shafts in the USCB, three distinct approaches are used to obtain an estimate of the regional emission rate. The first method uses the linear correlation of shaft-averaged emissions between our UAV quantified and high frequency (hourly) reported emissions to scale the annual E-PRTR emissions. To avoid the large influence of the intercept, the linear curve has been forced through
- 250 zero, making the slope the only factor to scale the emissions. The second approach uses the mean quantified shaft emissions, multiplied with the number of ventilation shafts in the region. The third approach scales the mean hourly inventory emission rate to derive the mean quantified emission rate based on the linear correlation of shaft-averaged emissions between our UAV quantified and high frequency (hourly) reported emissions, which is then multiplied by the number of active ventilation shafts in the region. The equations are shown below:

255
$$Q_{M1} = Q_{E-PRTR-regional} \times k_1,$$

$$Q_{M2} = Q_{UAV-shaft} \times n,$$

$$Q_{M3} = \left(\bar{Q}_{hourly-shaft} \times k_2 + b\right) \times n,$$

where Q_{E-PRTR-regional} is the annual E-PRTR emission rate, Q_{UAV-shaft} is the mean quantified shaft emission rate, Q_{hourly-shaft} is the mean hourly inventory emission rate, k₂ and b are the slope and the intercept of the linear fit of shaftaveraged emissions between our UAV quantified and high frequency (hourly) reported emissions, while k₁ is the slope of the linear fit that is forced through zero, and n is the number of active ventilation shafts in the region.

3 Results and discussion

3.1 Isotopic signature

Fig. 4 shows the sampled isotopic signatures of δ¹³C-CH₄ and δ²H-CH₄ from the flights during the study, separated into
different shafts and different days. For the five sampled ventilation shafts, the δ¹³C-CH₄ values ranged between -53.4 and -41.3 ‰ and the δ²H-CH₄ values ranged between -175.0 and -151.2 ‰. According to Sherwood et al., 2021, isotopic signature values from coal mining vary from country to country and the source signature in Poland was found to be -48 ± 15 (± 1σ) ‰ for δ¹³C-CH₄ and -194 ± 37 for δ²H-CH₄, respectively. Source signatures found during the same measurement campaign, CoMet 1.0, by other groups indicate that the source signatures for δ¹³C-CH₄ and δ²H-CH₄ in the Upper Silesia Coal Basin range between -59.4 to -41.0 ‰ and -218 to -142 ‰, respectively (Stanisavljevic, 2021). Overall, the addition of δ¹³C-CH₄

and δ^2 H-CH₄ measurements, and the good agreement between the found source signatures with those of other groups during the same campaign, indicate that we have clearly sampled the coal mine ventilation shafts using the UAV-based active AirCore system. Based on what is shown in Fig. 4 it is unlikely that other regional CH₄ sources (such as biomass burning, landfills, and ruminants) have influenced the active AirCore measurements.



Figure 4. Scatter plot indicating the isotopic signature for each measured ventilation shaft. The shaded areas indicate typical δ^{13} C-CH₄ and δ^{2} H-CH₄ values for different CH₄ sources, and are given with a 1 σ uncertainty. The values and uncertainties for coal mining are determined from measurements in Poland, and for other sources from the whole world (Sherwood et al., 2021; Lan et al., 2021). The gray-shaded area indicates the isotopic signatures found from other groups during the CoMet 1.0 campaign, and represents the calculated weighted average for the coal in the USCB (Stanisavljevic, 2021; Menoud et al., 2020)

280

275

3.2 Quantified CH₄ emissions

Fig. 5&6 show the estimated CH₄ emission rates from individual ventilation shafts, for each day, along with the hourly inventory presented the next section. Averages range between 2.7 ± 2.0 and 15.0 ± 2.3 kt/year for the IG approach, and between 0.8 ± 1.0 and 14.4 ± 3.7 kt/year for the MB approach. Large variations are seen from day-to-day for the same coal mine ventilation shafts. The IG approach and MB approach have a mean difference of 2.5 kt/year, with a maximum difference of 8.9 kt/year on May 31. This is likely due to the majority of the plume being located outside of the gridded curtain, which causes the IG to move the center line of the plume off the grid to obtain the best fit between model and data, while the MB is constrained to only include what is included in the kriged plane. The same is seen in the first flight on May 25 for Pniowek IV (see Fig. 6), where the majority of the IG plume is located outside the measured grid. Note that both the IG and MB approaches have been applied to all flights that fulfilled the criteria. The missing quantifications from the IG

method for some flights are entirely due to failures of the optimization. The uncertainty in the emissions quantified by UAVbased AirCore measurements is linked to the stability of the wind, as discussed in Andersen et al. (2021). The 10-12 minute snapshots are not instantaneously sampled, and an unstable wind may cause the emission plume to meander across the plane.

295



Figure 5. CH_4 emission estimates for each ventilation shaft per measurement day. light red: IG approach; light blue: MB approach. The bar height is the average of all flights during a specific day. Error bar indicates the standard deviation of the individual flights for that specific day, where the number of flights used for each bar is indicated with N. The two values for N refer to the MB approach and IG approach, respectively. The error is indicated as NaN when only one estimate is available.



Figure 6. The quantified CH₄ emission for each flight divided into different ventilation shaft and separated by individual flight days, with
the hourly inventory. The emissions are also color differentiated by IG approach (red) or MB approach (blue). The number of quantifications on each day from the two methods is indicated in the parenthesis.

3.3 Comparison with inventory

Fig. 7 shows the hourly inventory emissions for each ventilation shaft. The inventory reported to the E-PRTR is based on this data. Note that inventory measurement for Borynia VI is missing for the period between May 19 and May 30 (Fig. 310 7a). We assume this was due to a malfunctioning CH₄ sensor inside the ventilation shaft. The listed inventory data for Borynia VI in Table (2) was therefore calculated with data from May 30 to June 02. The Borynia VI inventory may therefore not represent the actual inventory of the days of measurements. The same can be concluded for Brzeszcze IX (Fig. 7b), which only has one given measurement point. The variability in the emitted CH₄ is clearly seen in the data from Pniowek IV, Pniowek V, and Zofiowka IV (Fig. 7c,d,e).



Figure 7. Time series of hourly inventory emissions from CH₄ concentration and air flow measurements in the shaft for each investigated coal mine ventilation shaft. Prior to May 30 data in (a) are missing. In (b) only a constant value is available from May 19 to June 1.

320

In comparing the quantified CH₄ emission rate on an individual flight basis with the annual emission rate reported to the E-PRTR, we found that the correlation is very low ($R^2 < 0.05$). Fig. 8a shows the correlation between the E-PRTR annual emissions that has been divided by the number of active ventilation shafts for a particular coal mine, and the UAV-based active AirCore IG quantified CH₄ emissions averaged by shaft emissions. Also, here the correlation is low ($R^2 < 0.08$, N =

325 5). When the total reported mine emissions for a specific mine from the E-PRTR inventory are divided equally by the number of active shafts, shaft-specific emission info is lost. The non-existing correlation indicates that the agreement between the snapshot flight quantified emissions with the E-PRTR inventory is poor.

The hourly inventory data shown in Fig. 8b is therefore required for a direct comparison with the quantified emissions.

- Comparing this data on a daily-averaged basis with daily-averaged flight data sees a slight improvement in the obtained correlation (R² = 0.11, N = 9), although the correlation is still weak. Due to the lack of hourly data for Brzeszcze IX, it has been omitted for the comparison. There can still be large variations on an hourly basis, and thus a direct comparison between the hourly inventory over a day with snapshot flight profiles during the same day may not always align. Therefore, we have averaged the days together and compare shaft-specific averaged hourly data with shaft-specific averaged UAV quantified emissions from the same days. This is shown in Fig. 8c, which obtains a stronger correlation than the two
- previous comparisons, with an $R^2 = 0.86$ (N = 4). The quantified emissions are roughly 50 % lower than those of the hourly inventory; however, this is not significant when considering the large standard deviation of the measurements.
- The much-improved correlation from comparing hourly inventory data from individual shafts as opposed to a total mine emission divided equally over active shafts (i.e., based on the E-PRTR 2018 inventory), indicates that translating shaftquantified snapshot emissions to annual inventories is difficult. The hourly inventory data is not always available, but our evaluations indicate that they are required to make meaningful comparisons between quantified emissions and inventories. Due to the good correlation between the hourly inventory and the quantified emissions per shaft, we can use the hourly inventory data to scale up the quantified emissions. We use the slopes and the intercepts found in Figure 8c to scale up our quantified emissions. This will be discussed in Sect. 4. For the MB approach (data not shown), the correlations are also much improved when hourly inventory data is used for comparison, although the R² values are slightly lower than those for the IG approach.



350 Figure 8. Scatter plot of UAV quantified shaft-averaged emissions over multiple days or individual days against annual or hourly inventory data (a) shaft-averaged emissions over multiple days vs. annual coal mine emissions from the E-PRTR 2018 (Gałkowski, 2021) inventory; (b) daily shaft-averaged emissions vs. daily high frequency(hourly) shaft-averaged emissions; (c) shaft-averaged emissions over multiple days vs. shaft-averaged high frequency (hourly) emissions over the same days; (d) same as (c) except that the fit has been forced through origin. All panels display only the data from the IG approach; however, the title lists the curve fit from the MB approach as well. The E-355 PRTR inventory has been divided by the number of active ventilation shafts, and the number of active shafts is taken from the internal

CoMet inventory, which had emission profiles based on 2018.

Fig. 9 shows the boxplot comparison between estimated emissions from both the IG approach and the MB approach, against the hourly inventory for each ventilation shaft. The inventory data includes data for the same days as the flights, except for Borynia VI and Brzeszcze XI. As previously mentioned, Brzeszcze XI contains only an annual estimate, while for Borynia VI inventory data are missing for the specific days when this shaft was sampled. Pniowek V, the shaft with the most overflights (N = 13 for the IG and N = 14 for the MB approach over 5 different days), has largely overlapping distributions with the hourly inventory data, although leaning towards the lower end of the hourly inventory distribution. Pniowek IV and Zofiowka IV have N = 5/N = 4 for the IG, and N = 7/N = 5 for the MB, respectively. Zofiowka IV has overlapping

365 distributions with the hourly inventory, but the quantified emissions largely span the lower hourly inventory distribution. This

is seen with all other shafts as well. Pniowek IV has only a small overlap with the hourly inventory distribution for both the IG approach. Brzeszcze IX is difficult to compare, due to the lack of hourly inventory data, and the only hour inventory data matches the upper end of the IG estimates. Finally, Borynia VI has the fewest flights with N = 2 for the IG and N = 3 for the MB approach over two different days. There is no overlap between the distributions. Borynia VI, as well as Brzeszcze

370 IX, are difficult to compare, due the lack of direct hourly inventory data around the days of flying.

Thus, the measured distributions for Pniowek V, Pniowek IV, and Zofiowka IV overlap with the hourly inventory distributions, with a minimum of $N \ge 5$ flights. The largest overlap is as mentioned found in Pniowek V, containing several days of sampling and $N \ge 13$. These distribution comparisons suggest that although single flight estimates may not be correlated well with the

375 hourly inventory, the averaged estimates of multiple flights show a strong correlation with those of the inventory, which suggests that multiple flights are required to obtain a good estimate. Note that for all shafts, the UAV estimated emission distribution is located on the lower end of the inventory distribution. This could be due to a lack of statistics in the number of quantifications or the possible biases of the measured hourly inventory.



380 **Figure 9.** Boxplot comparison of estimated emission vs. hourly inventory data. The hourly inventory data has been calculated from shaft emission data from the mining companies, using CH₄ concentration and flow rate measurements.

3.4 Carbon dioxide emission

Similar to the coal mining shaft sampled in Andersen et al. (2021), a strong correlation is found between the emitted CO_2 and CH_4 . The way of obtaining the emitted CO_2 using the correlation between CO_2 and CH_4 mole fractions, the CH_4

385 emissions, and the molar mass constants of CO₂ and CH₄ is given as:

$$Q_{CO_2} = \frac{Q_{CH_4} \cdot M_{CO_2}}{slope \cdot M_{CH_4}} \tag{4}$$

where Q_{CH4} is the quantified CH₄ emission, the *slope* is the slope of the linear fit between CO₂ and CH₄ (CH₄/CO₂), and M_{CO2} and M_{CH4} are the molar masses of CO₂ and CH₄, respectively. There were some flights that had no, or low correlation, and were thus omitted from the CO₂ emission calculation (see Figs. B5-8). These were flights with R² < 0.5. Of the 34 flights that fulfilled the criteria list, the number of flights above an R² value of 0.5 was 25, with an average R²

390 of 0.8. The average CH₄/CO₂ slope was 4.6 ± 2.9 ppmCH₄ /ppmCO₂. We've used the linear correlation between enhanced CH₄ and CO₂ to calculate the CO₂ emissions instead of directly using the CO₂ data for two reasons: 1) the CO₂ signal is relatively small compared to its variabilities, which makes it difficult to find a robust background signal; 2) we aim to quantify the CO₂ emissions from the shaft only."

395

Fig. 10 shows the calculated CO₂ emission on a daily-averaged basis for each coal mine ventilation shaft. Expectedly, the CO₂ follows the same trend as the CH₄, seeing strong variations on a day-to-day basis. The mean difference between the IG and the MB approach is 1.5 kt/year. The average CO₂ emission rate over all shafts calculated using the IG approach is 4.4 \pm 2.2 kt/year, with a minimum of 0.8 \pm NaN kt/year and a maximum of 7.2 \pm 4.1 kt/year. For the MB approach, the average CO₂ emission rate is 3.8 \pm 2.3 kt/year, with a minimum of 0.5 \pm NaN kt/year and a maximum of 7.5 \pm 1.8 kt/year.



Figure 10. shows CO_2 emission bar plots for each ventilation shaft divided into separate days. Emission quantifications for both the IG approach (light red) and MB approach (light blue) are shown. The bar height is the mean of all flights during a specific day. The error bar is indicated as NaN when only one estimate is available.

405 **3.5 Upscaling to regional estimates**

410

As shown in Table (2), the mean quantified CH₄ emission of the five sampled coal mine ventilation shafts is 5.5 ± 2.6 kt CH₄/year for the IG approach and 5.4 ± 3.2 kt CH₄/year for the MB approach, respectively. For CO₂, the mean emission is 4.2 ± 2.2 kt CO₂/year for the IG approach and 3.8 ± 2.3 kt CO₂/year for the mass balance, respectively. As many as 59 active ventilation shafts are located across the entire USCB. According to the 2018 E-PRTR inventory, the regional CH₄ emissions adds up to 447.9 kt CH₄/year, while the regional CO₂ emissions are stated to be 35.3 [Mt CO₂/year].

Three distinct approaches have been used to obtain an estimate of the regional emission rate. The first method uses the linear correlation of shaft-averaged emissions between our UAV quantified and high frequency (hourly) reported emissions shown

in Fig. 8d to scale the annual E-PRTR emissions. Here we assume that the correlation between the shaft-averaged hourly

- 415 inventory and UAV-quantified emissions are representative for the whole basin and that the very low correlation between the shaft-averaged E-PRTR inventory and UAV-quantified emissions is mainly due to large errors introduced to the E-PRTR inventory for individual shafts by dividing the inventory for individual coal mines by the number of active shafts. To avoid the large influence of the intercept, the linear curve has been forced through zero, making the slope the only factor to scale the emissions. For the IG approach, the slope is 0.571, which multiplied with the 447.9 kt CH₄/year inventory results in 255.8 kt
- 420 CH₄/year. For the mass balance, with a slope of 0.508, the resulting emissions are 227.5 kt CH₄/year. These results are shown in Fig. 11a as yellow bars.

The second approach uses the mean quantified shaft emissions of 5.5 ± 2.6 kt CH₄/year for the IG approach and 5.4 ± 3.2 kt CH₄/year for the MB approach, multiplied with the number of ventilation shafts in the region. This amounts to a regional

425 emission of 324.5 ± 153.4 kt CH₄/year for the IG approach and 318.6 ± 188.8 kt CH₄/year for the MB approach, respectively. These emission estimates compare well with the ones from the previous approach, but are lower than the emissions estimated by Fiehn et al. (2020) and Kostinek et al. (2021). These are shown in Fig. 11a as blue bars. We acknowledge that potentially large biases may have been introduced to the upscaling as the number of quantified shafts (5) is small compared to the total number of shafts (59).

430

The third approach uses the line from Fig. 8c to scale the mean hourly emission rate, calculated from hourly inventory data, to derive the mean quantified emission rate, which is then multiplied by the number of active ventilation shafts in the region. Here, both the slope and intercept are used for the scaling. The mean hourly inventory emission rate is 11.2 ± 3.5 kt CH₄/year. The line using the IG approach has a slope of 0.81 and an intercept of -2.6, resulting in a derived mean quantified emission

rate of 6.5 ± 2.8 kt CH₄/year. For the mass balance, a slope of 0.895 and an intercept of -4.3 results in a derived mean quantified emission rate of 5.7 ± 3.1 kt CH₄/year. Multiplying these numbers with the number of active ventilation shafts results in regional emission rates of 383.1 ± 165.8 kt CH₄/year for the IG and 339.0 ± 183.4 kt CH₄/year for the MB approach, respectively. The regional estimates for the IG approach and MB approach resulting from the third upscaling approach are shown in Fig. 11a as purple bars.



Figure 11. A comparison of regional inventory emissions for CH₄. The first bar (red) represents the E-PRTR inventory. The second bar (yellow) represents the E-PRTR inventory scaled by the linear fit. Bars three and four (teal) represent the estimated regional emissions from Fiehn et al. (2020) from their two flights. Bars five and six (green) represent the estimated regional emissions from the two flights of Kostinek et al. (2021). Bars number seven (blue) and eight (light blue) represent the regional emission using the quantified IG and MB estimates, respectively. The last two bars, ten (purple) and eleven (light purple), represent the scaled regional emission using the IG approach and the MB approach, respectively.

Comparing the IG-derived regional emission with both the annual E-PRTR inventory and the regional estimates from Fiehn

- 450 et al. (2020), the results are close to one another, and are not statistically different when their uncertainties are considered, although the uncertainties are as large as 20-43%. Fiehn et al. (2020) estimated the regional emissions over two separate flights during the same CoMet campaign to be 437.6 ± 114.2 kt CH₄/year and 478.8 ± 95.1 kt CH₄/year, similar to the 447.9 kt CH₄/year E-PRTR inventory. Kostinek et al. (2021) also estimated the regional emissions over two separate flights, and found emissions rates of 451 ± 77 kt CH₄/year and 423 ± 79 kt CH₄/year. Our estimated emissions appear to be lower.
- 455 Since we have only quantified 5 individual shafts out of 59 active shafts in the region, the small number of quantified shafts could be one of the main causes of the difference.

The upscaling process for CO_2 cannot be explored by the same approaches as for CH_4 , since the linear fits from Fig. 8 are only valid for CH_4 . Therefore, only the second approach can be used, where the mean quantified CO_2 emission will be multiplied with the number of active ventilation shafts in the region. According to Swolkien, 2020, there are collocated CO_2 emissions

along with CH₄ emissions during the extraction of coal. However, CO₂ emissions from coal mining activities are not included in the E-PRTR inventory. The mean CO₂ emission is 4.2 ± 2.2 kt CO₂/year for the IG approach and 3.8 ± 2.3 kt CO₂/year for the mass balance, which yields a regional emission estimate of 0.3 ± 0.1 Mt CO₂/year for the IG approach and 0.2 ± 0.1 Mt CO₂/year for the MB approach, respectively. This is significantly less than the E-PRTR inventory of 35.3 Mt CO₂/year and

465 the estimated regional emissions rates from Fiehn et al. (2020) of 38.2 ± 22.7 Mt CO₂/year and 35.3 ± 11.7 Mt CO₂/year. Comparatively, these estimates are ~ 1 % or less of the listed E-PRTR inventory. According to the E-PRTR (2018) inventory, 98.2 % of emitted CH₄ in the USCB originates from underground and related operations, 1.5 % coming from opencast mining and quarrying, and 0.3% from waste and waste water management. For CO₂, the major contributors are thermal power stations and other combustion installations and production and processing of metals. These account for 78.9 % and 16.3 %, respectively.

470 Residential heating accounts for 2.6 %, while other industrial manufacturing accounts for 2.2 %.

The upscaling method uses daily snapshots to estimate an annual emission by multiplying the annual average of the five sampled shafts by the number of ventilation shafts in the region. As shown in Sect. 3.3, each ventilation shaft can have significant variations in its daily emissions, thus this adds uncertainty to the daily snapshots extrapolated to an annual emission.

- 475 Ventilation shafts can have significantly different emission rates, thus grouping the 5 shafts together to obtain the average does not accurately represent the emission distribution in the whole region. This adds additional uncertainty to the upscaled regional emission. Despite this, we see a good agreement with the two flights from Fiehn et al. (2020), Kostinek et al. (2021) and the E-PRTR inventory for CH₄ within the error bars (see Fig. 11a), especially using the third approach of deriving the quantified emissions from hourly inventory data and scaling this to a regional emission rate. This indicates that the upscaling
- 480 of the ventilation shafts emission estimated from the UAV-based active AirCore can be a useful tool for relatively cheap and easy-to-obtain regional emission estimates. Estimated regional CO₂ emissions are vastly smaller than the suggested regional inventory and also the regional emissions found by Fiehn et al. (2020). The estimated regional CO₂ emissions are ~1 % of the regional inventory estimate, confirming that the coal mine ventilation shafts are not a major source of CO₂ in the USCB. This is also reflected in the E-PRTR inventory, which does not list coal mining as a CO₂ source at all.

485 4 Conclusions and outlook

USCB regional CH₄ and CO₂ estimate.

It is important to obtain independent estimates of the emission magnitudes from coal mining shafts and verify reported emission inventories to be able to reduce the overall emissions. Using the UAV-based active AirCore system, we have made atmospheric measurements of CH₄ and CO₂ mole fractions downwind of five different coal mine ventilation shafts in the USCB. We apply an IG approach as well as a MB approach to quantify the CH₄ and CO₂ point-source emissions for the five sampled ventilation shafts, and compare these estimates with reported inventory data. The estimated point sources are used to extrapolate a total

The CH₄ emission estimates indicate that the coal mine ventilation shafts have highly variable emission rates. Over the five quantified shafts, the quantified emissions using the IG approach range between 1.2 and 15.0 kt CH₄/year, with a mean of

- 495 5.5 ± 2.6 kt CH₄/year. For the MB approach, the quantified emissions range between 0.3 and 19.3 kt CH₄/year with a mean value of 5.4 ± 3.2 kt CH₄/year. This large variability is reflected in the hourly inventory data for the same coal mine ventilation shafts, and it is therefore clear that comparisons of the UAV-based active AirCore quantified emissions and annually averaged inventories show very low correlation (R² = 0.08). Day-by-day comparisons of the quantified emissions with hourly inventory during the same days yields a better correlation (R² = 0.11), but the best correlation is found on
- 500 shaft-by-shaft comparisons, obtaining an R² of 0.86 for the IG approach and 0.72 for the MB approach. Distribution comparisons between the hourly inventory and the quantified emissions show that more flights are beneficial to accurately estimate the shaft emissions. Due to the large variability of the shaft emissions, single flights may sample at times of small or large emission. Correlation between CH₄ and CO₂ mole fractions is large for 25 out of 34 flights (average R² = 0.8) and has an average slope value of 4.6 ppm_{CH4}/ppm_{CO2}. Quantified CO₂ emissions for the combined five ventilation shafts yield an average of 4.4 ± 2.2 kt CO₂/year for the IG and 3.8 ± 2.3 kt CO₂/year for the MB approach.

To obtain regional estimates, we use three upscaling approaches by scaling the E-PRTR annual inventory, the quantified shaftaveraged emission rate, and the shaft-averaged emission rate that are derived from the hourly emission inventory. The first approach obtains emission rates of 256 kt CH₄/year from the inverted Gaussian approach and 228 kt CH₄/year from the MB

- 510 approach, respectively, which compares well with the second approach of 325 ± 148 kt CH₄/year (Gaussian) and 318.6 ± 189 kt CH₄/year (mass balance). These estimates are lower than the previous results from Fiehn et al. (2020), Kostinek et al. (2021) and the E-PRTR inventory of 448 kt CH₄/year. The third approach results in regional emission estimates of 383 ± 165.8 kt CH₄/year (Gaussian) and 339 ± 183 kt CH₄/year (mass balance), providing a good comparison with both the E-PRTR inventory and previous results from Fiehn et al. (2020) and Kostinek et al. (2021). The differences are not significant
- 515 when the relatively large uncertainties are considered. Upscaled regional emissions for CO₂ amount to 0.2 0.3 Mt CO₂/year for both quantification approaches, which is ~ 1 % of the reported inventory and regional CO₂ estimates from Fiehn et al. (2020), confirming that the coal mine ventilation shafts are not a minor contributor to the regional CO₂ emissions.
- The uncertainty in the emissions quantified by UAV-based AirCore measurements is linked to the stability of the wind, as 520 discussed in Andersen et al. (2021). The 10-12 minute snapshots are not instantaneously sampled, and an unstable wind may cause the emission plume to meander across the plane. Although a single flight may not accurately represent the ventilation shaft emissions, this study shows that with multiple flight quantifications for a single shaft a good estimate of the shaft's emission rate can be made. Short-term flights over the span of two weeks are used to estimate an annual average, where emission rates may vary week-to-week. The E-PRTR shaft-scale estimates assume that all shafts of a single coal mine emit an
- 525 equal amount, which clearly is not true. A more accurate up-scaling model taking into account the individual emission size

of different shafts would help improve this estimate.

The use of UAV-based active AirCore measurements in combination with the IG approach and the MB approach has been demonstrated to be able to quantify the emissions from individual ventilation shafts, which can then be used to estimate

- 530 regional emissions of both CH₄ and CO₂. However, the uncertainty of individual flight quantification may be large, due to variable wind conditions under complexed turbulent schemes. Also, the in situ plume sampled by the AirCore does not necessarily follow the assumed Gaussian dispersion, as the averaging time is not sufficiently long, i.e., less than 30 minutes, which inevitably increases the uncertainty of the estimates by the IG method. To this end, optimization schemes that do not rely on the simple assumption of a Gaussian dispersion may be valuable (Shi et al., 2022). On the other hand, the complexed
- 535 dispersion of the plume can be simulated by 3D large eddy simulation (LES), which can provide guidance to the design of the sampling strategy and help develop a suitable method to estimate the emission rates based on the in situ plume sampling (Ražnjević et al., 2022).

The uncertainty of the estimate of individual shaft can be reduced by increasing the number of the quantification flights, although it is challenging to determine the exact number of needed flights to achieve a target uncertainty. Analysis of a large number of controlled tracer release experiments may provide an opportunity to directly address this issue, as has been performed for UAV measurements as well as many other different measurement platforms (Feitz et al., 2018; Bell et al., 2020; Morales et al., 2022).

545 Also, the uncertainty of the regional estimates can be reduced by increasing the number of quantified shafts. The limited number of quantified shafts makes our upscaling to the regional emission vulnerable. Nevertheless, the UAV system is flexible and versatile, and opens up opportunities to quickly obtain regional estimates in regions that are otherwise hard to access. The UAV-based active AirCore system, thus, has shown to be a valuable tool to estimate CH₄ emissions on local to regional scales.



Figure B1. The measured flight profiles for flights #1 to #15.



Figure B2. The measured flight profiles for flights #16 to #30.



Figure B3. measured flight profiles for flights #31 to #45.



Figure B4. measured flight profiles for flights #46 to #59.



Figure B5. Scatter plots for flights #1 to #15.



Figure B6. Scatter plots for flights #16 to #30.



Figure B7. Scatter plots for flights #32 to #45.



Figure B8. Scatter plots for flights #46 to #59.

	Annual E-PRTR		Hourly inventory			IG			Mass balance					
	inventory													
	[kt/year]		[kt/year]			[kt/year]			[kt/year]					
Shaft			Ν	Min	Mean	Max	Ν	Min	Mean	Max	Ν	Min	Mean	Max
Pniowek IV		18.2	24	5.3	6.1	6.1	5	1.2	2.7	6.1	7	1.6	1.8	2.1
					$\pm \ 0.2$				± 2.0				± 0.2	
Pniowek V		18.2	120	5.7	13.3	22.6	13	4.2	9.5	15	14	0.8	9.8	19.3
					± 4.1				± 3.5				± 5.0	
Borynia VI		6.4	66	7.1	9.3	11.1	2	3.2	4.4	5.6	3	0.3	3.2	4.9
					± 1.1				± 1.7				± 2.5	
Zofiowka IV		13.9	24	11	12.5	13.3	4	2.7	6.3	11.3	5	1.1	4.9	9.6
					± 0.5				± 4.0				± 3.5	
Brzeszcze IX		13.0	1	14.8	14.8	14.8	3	3.3	4.5	5.3	5	2.2	7.2	10.6
					± -				± 1.1				± 3.5	
Average		13.9		8.8	11.2	13.6		2.9	5.5	8.7		1.2	5.4	9.3
		± 4.8			± 3.5				± 2.6				± 3.2	

Table C1. The statistics for the annual CH_4 inventory (E-PRTR (2018)), the hourly inventory during the days of flying, and the UAV-575based active AirCore IG quantified CH_4 emissions for each coal mine ventilation shaft.

580 *Data availability.* The raw data sets and flight logs, as well as wind data from the period May 18 – June 1 (2018), can be accessed at <u>https://doi.org/10.5281/zenodo.5786532</u> (Andersen et al., 2021).

Author contributions. HC, TA, AR planned the campaign; TA, MdV, HC, MM performed the measurements; TA and HC analyzed the data; TA and HC wrote the manuscript draft; WP, JN, JS, MM, TR, AR, AF, ZZ reviewed and edited the manuscript.

Competing interests. The authors declare that they have no conflict of interest.

585

Acknowledgements. This study is partially funded by the MEthane goes Mobile: MEasurement and MOdeling (MEMO²)
 project from the European Union's Horizon 2020 research and innovation programme under the Marie Sklodowska-Curie grant agreement No 722479. We would like to thank the CoMet project for the opportunity to participate in an exciting and stimulating campaign and collaborate with the participants of the campaign with tons of great discussions and good times.

References

Allen, G., Hollingsworth, P., Kabbabe, K., Pitt, J. R., Mead, M. I., Illingworth, S., Roberts, G., Bourn, M., Shallcross,

595 D. E., Percival, C. J.: The development and trial of an unmanned aerial system for the measurement of methane emission from landfill and greenhouse gas emission hotspots, Waste Management, 87, 883 – 892, https://doi.org/10.1016/j.wasman.2017.12.024, 2019.

Andersen, T., B. Scheeren, W. Peters, and H. Chen: A UAV-based active AirCore system for measurements of greenhouse gases, Atmos. Meas. Tech., 11 (5), 2683–2699, https://doi.org/10.5194/amt-11-2683-2018, 2018.

600 Andersen, T., Vinkovic, K., de Vries, M., Kers, B., Necki, J., Swolkien, J., Roiger, A., Peters, W., Chen, H.: Quantifying methane emissions from coal mining ventilation shafts using a small Unmanned Aerial Vehicle (UAV)-based active AirCore system, Atmos. Environ.: X, Volume 12, 100135, ISSN 2590-1621, https://doi.org/10.1016/j.aeaoa.2021.10013, 2021.

Andrews, A. E., Kofler, J. D., Trudeau, M. E., Williams, J. C., Neff, D. H., Masarie, K. A., Chao, D. Y., Kitzis, D. R.,
Novelli, P. C., Zhao, C. L., Dlugokencky, E. J., Lang, P. M., Crotwell, M. J., Fischer, M. L., Parker, M. J., Lee, J. T.,
Baumann, D. D., Desai, A. R., Stanier, C. O., De Wekker, S. F. J., Wolfe, D. E., Munger, J. W., and Tans, P. P.: CO₂,
CO, and CH₄ measurements from tall towers in the NOAA Earth System Research Laboratory's Global Greenhouse Gas
Reference Network: instrumentation, uncertainty analysis, and recommendations for future high-accuracy greenhouse
gas monitoring efforts, Atmos. Meas. Tech., 7 (2), 647–687, doi:10.5194/amt-7-647-2014, 2014.

610 Bell, C. S., Vaughn, T., and Zimmerle, D.: Evaluation of next generation emission measurement technologies under repeatable test protocols, Elementa: Science of the Anthropocene, 8, https://doi.org/10.1525/elementa.426, 2020.

Brosy, C., K. Krampf, M. Zeeman, B. Wolf, W. Junkermann, K. Schäfer, S. Emeis, and H. Kunstmann: Simultaneous multicopter-based air sampling and sensing of meteorological variables, Atmos. Meas. Tech., 10 (8), 2773–2784, https://doi.org/10.5194/amt-10-2773-2017, 2017.

615 Brownlow, R., Lowry, D., Thomas, R. M., Fisher, R. E., France, J. L., Cain, M., Richardson, T. S., C., Greatwood, Freer, Pyle, J., J. A., MacKenzie, A. R., Nisbet, E. G.: Methane mole fraction and δ13C above and below the trade wind inversion at Ascension Island in air sampled by aerial robotics, Geophys. Res. Lett., 43 (22), 11 893–11 902, doi:10.1002/2016GL071155, 2016.

 Chang, C.-C., J.-L. Wang, C.-Y. Chang, M.-C. Liang, and M.-R. Lin: Development of a multicopter-carried whole air
 sampling apparatus and its applications in environmental studies, Chemosphere, 144, 484 –492, https://doi.org/10.1016/j.chemosphere.2015.08.028, 2016.

Dlugokencky, E.: Trends in Atmospheric Methane. National Oceanic and Atmospheric Administration (NOAA)/Global Monitoring Laboratory (GML), www.esrl.noaa.gov/gmd/ccgg/trends_CH₄/, Accessed: 2020-06-22, 2020.

Ehret, G., Bousquet, P., Pierangelo, C., Alpers, M., Millet, B., Abshire, J. B., Bovensmann, H., Burrows, J. P., Chevallier,

625 F., Ciais, P., Crevoisier, C., Fix, A., Flamant, P., Frankenberg, C., Gibert, F., Heim, B., Heimann, M., Houweling, S., Hubberten, H. W., Jöckel, P., Law, K., Löw, A., Marshall, J., Agusti-Panareda, A., Payan, S., Prigent, C., Rairoux, P., Sachs, T., Scholze, M., Wirth, M.:: MERLIN: A French-German Space Lidar Mission Dedicated to Atmospheric Methane, Remote Sens.; 9(10):1052. https://doi.org/10.3390/rs9101052, 2017.

Etminan, M., G. Myhre, E. J. Highwood, and K. P. Shine: Radiative forcing of carbon dioxide, methane, and nitrous

630 oxide: A significant revision of the methane radiative forcing, Geophys. Res. Lett., 43 (24), 12,614–12,623, doi:10.1002/2016GL071930, 2016.

Feitz, A., Schroder, I., Phillips, F., Coates, T., Negandhi, K., Day, S., Luhar, A., Bhatia, S., Edwards, G., Hrabar, S., Hernandez, E., Wood, B., Naylor, T., Kennedy, M., Hamilton, M., Hatch, M., Malos, J., Kochanek, M., Reid, P., Wilson, J., Deutscher, N., Zegelin, S., Vincent, R., White, S., Ong, C., George, S., Maas, P., Towner, S., Wokker, N., and Griffith,

635 D.: The Ginninderra CH4 and CO2 release experiment: An evaluation of gas detection and quantification techniques, International Journal of Greenhouse Gas Control, Int. J. Greenhouse Gas Control, 70, 202-224, https://doi.org/10.1016/j.ijggc.2017.11.018, 2018.

Fiehn, A., Kostinek, J., Eckl, M., Klausner, T., Gałkowski, M., Chen, J., Gerbig, C., Röckmann, T., Maazallahi, H., Schmidt, M., Korbeń, P., Necki, J., Jagoda, P., Wildmann, N., Mallaun, C., Bun, R., Nickl, A.-L., Jöckel, P., Fix, A.,

640 and Roiger, A.: Estimating CH₄, CO₂ and CO emissions from coal mining and industrial activities in the Upper Silesian Coal Basin using an aircraft-based MB approach, Atmos. Chem. Phys., 20, 12675–12695, https://doi.org/10.5194/acp-20-12675-2020, 2020.

645

Fix, A., Amediek, A., Bovensmann, H., Ehret, G., Gerbig, C., Gerilowski, K., Pfeilsticker, K., Roiger, A., and Zöger, M.: CoMet: an airborne mission to simultaneously measure CO₂ and CH₄ using lidar, passive remote sensing, and insitu techniques, EPJ Web Conf., 176, 1–4, https://doi.org/10.1051/epjconf/201817602003, 2018.

Gałkowski, M., Fiehn, A., Swolkien, J., Stanisavljevic, M., Korben, P., Menoud, M., Necki, J., Roiger, A., Röckmann, T., Gerbig, C., & Fix, A. Emissions of CH₄ and CO₂ over the Upper Silesian Coal Basin (Poland) and its vicinity (4.01) [Data set], ICOS ERIC - Carbon Portal. https://doi.org/10.18160/3K6Z-4H73, 2021.

Grare, L., L. Lenain, and W. K. Melville: The Influence of Wind Direction on Campbell Scientific CSAT3 and Gill R3-

650 50 Sonic Anemometer Measurements, J. Atmos. Ocean Technol., 33 (11), 2477–2497, doi:10.1175/JTECH-D-16-0055.1, 2016.

Greatwood, C., Richardson, T. S., Freer, J., Thomas, R. M., MacKenzie, A. R., Brownlow, R., Lowry, D., Fisher, R. E., Nisbet, E. G.: Atmospheric Sampling on Ascension Island Using Multirotor UAVs, Sensors, 17 (6), 1189, doi:10.3390/s17061189, 2017.

655 Hannun, R. A., Wolfe, G. M., Kawa, S. R., Hanisco, T. F., Newman, P. A., Alfieri, J. G., Barrick, J., Clark, K. L.,

DiGangi, J. P., Diskin, G. S.: Spatial heterogeneity in CO₂, CH₄, and energy emissiones: in-sights from airborne eddy covariance measurements over the Mid-Atlantic region, Environ. Res. Lett., 15 (3), 035 008, doi:10.1088/1748-9326/ab7391, 2020.

Karion, A., Sweeney, C., Pétron, G., Frost, G., Hardesty, R. M., Kofler, J., Miller, B. R., Newberger, T., Wolter, S.,
Banta, R., Brewer, A., Dlugokencky, E., Lang, P., Montzka, S. A., Schnell, R., Tans, P., Trainer, M., Zamora, R. and
Conley, S.: Methane emissions estimate from airborne measurements over a western United States natural gas field,
Geophys. Res. Lett., 40 (16), 4393–4397, doi:10.1002/grl.50811., 2013.

Kirschke, S.; Bousquet, P.; Ciais, P.; Saunois, M.; Canadell, J. G.; Dlugokencky, E. J.; Bergamaschi, P.; Bergmann, D.; Blake, D. R.; Bruhwiler, L.; Cameron-smith, P.; Castaldi, S.; Chevallier, F.; Feng, L.; Fraser, A.; Heimann, M.; Hodson,

- E. L.; Houweling, S.; Josse, B.; Fraser, P. J.; Krummel, P. B.; Lamarque, J.; Langenfelds, R. L.; Le Quéré, C.; Naik, V.;
 O'doherty, S.; Palmer, P. I.; Pison, I.; Plummer, D.; Poulter, B.; Prinn, R. G.; Rigby, M.; Ringeval, B.; Santini, M.;
 Schmidt, M.; Shindell, D. T.; Simpson, I. J.; Spahni, R.; Steele, L. P.; Strode, S. A.; Sudo, K.; Szopa, S.; Van Der Werf,
 G. R.; Voulgarakis, A.; Van Weele, M.; Weiss, R. F.; Williams, J. E.; Zeng, G.: Three decades of global methane sources and sinks, Nature Geoscience, 6 (10), 813, doi:10.1038/ngeo1955, 2013.
- 670 Kostinek, J., Roiger, A., Eckl, M., Fiehn, A., Luther, A., Wildmann, N., Klausner, T., Fix, A., Knote, C., Stohl, A., and Butz, A.: Estimating Upper Silesian coal mine methane emissions from airborne in situ observations and dispersion modeling, Atmos. Chem. Phys., 21, 8791–8807, https://doi.org/10.5194/acp-21-8791-2021, 2021.

Krautwurst, S., Gerilowski, K., Jonsson, H. H., Thompson, D. R., Kolyer, R. W., Iraci, L. T., Thorpe, A. K., Horstjann, M., Eastwood, M., Leifer, I., Vigil, S. A., Krings, T., Borchardt, J., Buchwitz, M., Fladeland, M. M., Burrows, J. P., and

675 Bovensmann, H.: Methane emissions from a Californian landfill, determined from airborne remote sensing and in situ measurements, Atmos. Meas. Tech., **10** (9), 3429–3452, doi:10.5194/amt-10-3429-2017, 2017.

Kunz, M., Lavric, J. V., Gasche, R., Gerbig, C., Grant, R. H., Koch, F.-T., Schumacher, M., Wolf, B., and Zeeman, M.: Surface emission estimates derived from UAS-based mole fraction measurements by means of a nocturnal boundary layer budget approach, Atmos. Meas. Tech., 13 (4), 1671–1692, https://doi.org/10.5194/amt-13-1671-2020, 2020.

680 Lampert, A., Pätzold, F., Asmussen, M. O., Lobitz, L., Krüger, T., Rausch, T., Sachs, T., Wille, C., Sotomayor Zakharov, D., Gaus, D., Bansmer, S., and Damm, E.: Studying boundary layer methane isotopy and vertical mixing processes at a rewetted peatland site using an unmanned aircraft system, Atmos. Meas. Tech., 13, 1937-1952, https://doi.org/10.5194/amt-13-1937-2020, 2020.

Lan, X., Basu, S., Schwietzke, S., Bruhwiler, L. M. P., Dlugokencky, E. J., Michel, S. E., Sherwood, O. A., Tans, P.

685 P., Thoning, K., Etiope, G., Zhuang, Q., Liu, L., Oh, Y., Miller, J. B., Pétron, G., Vaughn, B. H., and Crippa, M.: Improved Constraints on Global Methane Emissions 460 and Sinks Using Δ¹³C-CH₄, Global Biogeochem. Cycles, 35, https://doi.org/10.1029/2021GB007000, 2021. Lowry, D., Brownlow, R., Fisher, R., Nisbet, E., Lanoisellé, M., France, J., Thomas, R., Mackenzie, R., Richardson, T., Greatwood, C., Freer, J., Cain, M., Warwick, N., and Pyle, J.: Methane at Ascension Island, southern tropical

690 Atlantic Ocean: continuous ground measurement and vertical profiling above the Trade Wind Inversion, EGU General Assembly Conference Abstracts, 17, p. 7100, 7100 pp, 2015.

Martinez, B., T. W. Miller, and A. P. Yalin: Cavity Ring-Down Methane Sensor for Small Unmanned Aerial Systems, Sensors, 20(2), 1–11, doi:10.3390/s20020454, 2020.

Menoud, M., Röckmann, T., Fernandez, J., Bakkaloglu, S., Lowry, D., Korben, P., Schmidt, M., Stanisavljevic, M.,
Necki, J., Defratyka, S., & Yver Kwok, C.: mamenoud/MEMO2_isotopes: v8.1 complete (Version v8.1.0) Data set,
Zenodo, https://doi.org/10.5281/zenodo.4062356, 2020.

Morales, R., Ravelid, J., Vinkovic, K., Korbe, P., Tuzson, B., Emmenegger, L., Chen, H., Schmidt, M., Humbel, S., and Brunner, D.: Controlled-release experiment to investigate uncertainties in UAV-based emission quantification for methane point sources, Atmos. Meas. Tech., 15, 2177-2198, https://doi.org/10.5194/amt-15-2177-2022, 2022.

700 Menoud, M., van der Veen, C., Necki, J., Bartyzel, J., Szénási, B., Stanisavljević, M., Pison, I., Bousquet, P., and Röckmann, T.: Methane (CH₄) sources in Krakow, Poland: insights from isotope analysis, Atmos. Chem. Phys., 21, 13167–13185, https://doi.org/10.5194/acp-21-13167-2021, 2021.

Nathan, B. J., Golston, L. M., O'Brien, A. S., Ross, K., Harrison, W. A., Tao, L., Lary, D. J., Johnson, D. R., Covington, A. N., Clark, N. N., and Zondlo, M. A.: Near-Field Characterization of Methane Emission Variability from a Compressor Station Using a Model Aircraft, Environ. Sci. Technol., 49 (13), 7896–7903, doi:10.1021/acs.est.5b00705,

Nickl, A.-L., Mertens, M., Roiger, A., Fix, A., Amediek, A., Fiehn, A., Gerbig, C., Galkowski, M., Kerkweg, A., Klausner, T., Eckl, M., and Jöckel, P.: Hindcasting and forecasting of regional methane from coal mine emissions in the Upper Silesian Coal Basin using the online nested global regional chemistry-climate model MECO(n) (MESSy

2015.

710

Ražnjević, A., Van Heerwaarden, C., Van Stratum, B., Hensen, A., Velzeboer, I., Van Den Bulk, P., and Krol, M.: Technical note: Interpretation of field observations of point-source methane plume using observation-driven large-eddy simulations, Atmos. Chem. Phys., 22, 6489-6505, https://doi.org/10.5194/acp-22-6489-2022, 2022.

v2.53), Geosci.Model Dev., 13 (4), 1925–1943, doi:10.5194/gmd-13-1925-2020, 2020.

Röckmann, T., Brass, M., Borchers, R., and Engel, A.: The isotopic composition of methane in the stratosphere: highaltitude balloon sample measurements, Atmos. Chem. Phys., 11, 13287–13304, https://doi.org/10.5194/acp-11-132872011, 2011.

Röckmann, T., Eyer, S., van der Veen, C., Popa, M. E., Tuzson, B., Monteil, G., Houweling, S., Harris, E., Brunner, D., Fischer, H., Zazzeri, G., Lowry, D., Nisbet, E. G., Brand, W. A., Necki, J. M., Emmenegger, L., and Mohn, J.: In situ

observations of the isotopic composition of methane at the Cabauw tall tower site, Atmos. Chem. Phys., 16, 10469– 10487, https://doi.org/10.5194/acp-16-10469-2016, 2016.

Satar, E., T. A. Berhanu, D. Brunner, S. Henne, and M. Leuenberger: Continuous CO2/CH4/CO measurements (2012–2014) at Beromünster tall tower station in Switzerland, Biogeosciences, 13 (9), 2623–2635, doi:10.5194/bg-13-2623-2016, 2016.

Saunois, M., R. B. Jackson, P. Bousquet, B. Poulter, and J. G. Canadell: The growing role of methane in anthropogenic climate change, Environ. Res. Lett., 11(12), 120 207, doi:10.1088/1748-9326/11/12/120207, 2016a.

- Saunois, M., Bousquet, P., Poulter, B., Peregon, A., Ciais, P., Canadell, J. G., Dlugokencky, E. J., Etiope, G., Bastviken,
 D., Houweling, S., Janssens-Maenhout, G., Tubiello, F. N., Castaldi, S., Jackson, R. B., Alexe, M., Arora, V. K.,
 Beerling, D. J., Bergamaschi, P., Blake, D. R., Brailsford, G., Brovkin, V., Bruhwiler, L., Crevoisier, C., Crill, P., Covey,
 K., Curry, C., Frankenberg, C., Gedney, N., Höglund-Isaksson, L., Ishizawa, M., Ito, A., Joos, F., Kim, H.-S., Kleinen,
- 730 T., Krummel, P., Lamarque, J.-F., Langenfelds, R., Locatelli, R., Machida, T., Maksyutov, S., McDonald, K. C., Marshall, J., Melton, J. R., Morino, I., Naik, V., O'Doherty, S., Parmentier, F.-J. W., Patra, P. K., Peng, C., Peng, S., Peters, G. P., Pison, I., Prigent, C., Prinn, R., Ramonet, M., Riley, W. J., Saito, M., Santini, M., Schroeder, R., Simpson, I. J., Spahni, R., Steele, P., Takizawa, A., Thornton, B. F., Tian, H., Tohjima, Y., Viovy, N., Voulgarakis, A., van Weele, M., van der Werf, G. R., Weiss, R., Wiedinmyer, C., Wilton, D. J., Wiltshire, A., Worthy, D., Wunch, D., Xu, X.,
- Yoshida, Y., Zhang, B., Zhang, Z., and Zhu, Q.: The global methane budget 2000–2012, Earth Syst. Sci. Data, 8 (2), 697–751, doi:10.5194/essd-8-697-2016, 2016b.

Saunois, M., Bousquet, P., Poulter, B., Peregon, A., Ciais, P., Canadell, J. G., Dlugokencky, E. J., Etiope, G., Bastviken, D., Houweling, S., Janssens-Maenhout, G., Tubiello, F. N., Castaldi, S., Jackson, R. B., Alexe, M., Arora, V. K., Beerling, D. J., Bergamaschi, P., Blake, D. R., Brailsford, G., Bruhwiler, L., Crevoisier, C., Crill, P., Covey, K.,

- 740 Frankenberg, C., Gedney, N., Höglund-Isaksson, L., Ishizawa, M., Ito, A., Joos, F., Kim, H.-S., Kleinen, T., Krummel, P., Lamarque, J.-F., Langenfelds, R., Locatelli, R., Machida, T., Maksyutov, S., Melton, J. R., Morino, I., Naik, V., O'Doherty, S., Parmentier, F.-J. W., Patra, P. K., Peng, C., Peng, S., Peters, G. P., Pison, I., Prinn, R., Ramonet, M., Riley, W. J., Saito, M., Santini, M., Schroeder, R., Simpson, I. J., Spahni, R., Takizawa, A., Thornton, B. F., Tian, H., Tohjima, Y., Viovy, N., Voulgarakis, A., Weiss, R., Wilton, D. J., Wiltshire, A., Worthy, D., Wunch, D., Xu, X.,
- 745 Yoshida, Y., Zhang, B., Zhang, Z., and Zhu, Q.: Variability and quasi-decadal changes in the methane budget over the period 2000–2012, Atmos. Chem. Phys., 17 (18), 11 135–11 161, doi:10.5194/acp-17-11135-2017, 2017.

Saunois, M., Stavert, A. R., Poulter, B., Bousquet, P., Canadell, J. G., Jackson, R. B., Raymond, P. A., Dlugokencky, E.
J., Houweling, S., Patra, P. K., Ciais, P., Arora, V. K., Bastviken, D., Bergamaschi, P., Blake, D. R., Brailsford, G.,
Bruhwiler, L., Carlson, K. M., Carrol, M., Castaldi, S., Chandra, N., Crevoisier, C., Crill, P. M., Covey, K., Curry, C.

750 L., Etiope, G., Frankenberg, C., Gedney, N., Hegglin, M. I., Höglund-Isaksson, L., Hugelius, G., Ishizawa, M., Ito, A., Janssens-Maenhout, G., Jensen, K. M., Joos, F., Kleinen, T., Krummel, P. B., Langenfelds, R. L., Laruelle, G. G., Liu, L., Machida, T., Maksyutov, S., McDonald, K. C., McNorton, J., Miller, P. A., Melton, J. R., Morino, I., Müller, J.,
Murguia-Flores, F., Naik, V., Niwa, Y., Noce, S., O'Doherty, S., Parker, R. J., Peng, C., Peng, S., Peters, G. P., Prigent,
C., Prinn, R., Ramonet, M., Regnier, P., Riley, W. J., Rosentreter, J. A., Segers, A., Simpson, I. J., Shi, H., Smith, S. J.,

- Steele, L. P., Thornton, B. F., Tian, H., Tohjima, Y., Tubiello, F. N., Tsuruta, A., Viovy, N., Voulgarakis, A., Weber, T. S., van Weele, M., van der Werf, G. R., Weiss, R. F., Worthy, D., Wunch, D., Yin, Y., Yoshida, Y., Zhang, W., Zhang, Z., Zhao, Y., Zheng, B., Zhu, Q., Zhu, Q., and Zhuang, Q.: The Global Methane Budget 2000–2017, Earth Syst. Sci. Data, 12 (3), 1561–1623, doi:10.5194/essd-12-1561-2020, 2020.
- Shah, A., J. R. Pitt, H. Ricketts, J. B. Leen, P. I. Williams, K. Kabbabe, M. W. Gallagher, and G. Allen: Testing the
 near-field Gaussian plume inversion emission quantification technique using unmanned aerial vehicle sampling,
 Atmos. Meas. Tech., 13 (3), 1467–1484, doi:10.5194/amt-13-1467-2020, 2020.

Sherwood, O. A., Schwietzke, S., and Lan, X.: Global Δ^{13} C-CH₄ Source Signature Inventory 2020, 2021.

Shi, T., Han, Z., Han, G., Ma, X., Chen, H., Andersen, T., Mao, H., Chen, C., Zhang, H., and Gong, W.: Retrieving coal mine CH4 emissions using UAV-based AirCore observations and the GA-IPPF model, Atmos. Chem. Phys. Discuss., 2022, 1-17, https://doi.org/10.5194/acp-2022-180, 2022.

Stanisavljevic, M., 2021: Isotopic signatures from coal mining shafts in the Upper Silesia Coal Basin, in prep., 1 (1), 1–1

Swolkień, J.: Polish underground coal mines as point sources of methane emission to the atmosphere, Int. J. Greenh. Gas Control., 94, 102 921, https://doi.org/10.1016/j.ijggc.2019.102921, 2020.

770 Turnbull, J. C., E. D. Keller, T. Baisden, G. Brailsford, T. Bromley, M. Norris, and A. Z. van: Atmospheric measurement of point source fossil CO₂ emissions, Atmos. Chem. Phys., 14 (10), 5001–5014, doi:10.5194/acp-14-5001-2014, 2014.

Turner, A. J., C. Frankenberg, and E. A. Kort: Interpreting contemporary trends in atmospheric methane, Proc. Natl. Acad. Sci. U.S.A., 116 (8), 2805–2813, doi:10.1073/pnas.1814297116, 2019.

775 Tuzson, B., M. Graf, J. Ravelid, P. Scheidegger, A. Kupferschmid, H. Looser, R. P. Morales, and L. Emmenegger: A compact QCL spectrometer for mobile, high-precision methane sensing aboard drones, Atmos. Meas. Tech., 13 (9), 4715–4726, doi:10.5194/amt-13-4715-2020, 2020.

Van Dingenen, R., M. Crippa, G. Maenhout, D. Guizzardi, and F. Dentener: Global trends of methane emissions and their impacts on ozone concentrations. Tech. rep., EUR 29394 EN, Publications Office of the European Union,

780 Luxembourg, ISBN: 978-92-79-96550-0, doi: 10.2760/820175, 2018.

765

Villa, T. F., F. Gonzalez, B. Miljievic, Z. D. Ristovski, and L. Morawska: An Overview of Small Unmanned Aerial Vehicles for Air Quality Measurements: Present Applications and Future Prospectives, Sensors, 16 (7), 1–29,

doi:10.3390/s16071072, 2016.

Vinković, K., Andersen, T., De Vries, M., Kers, B., Van Heuven, S., Peters, W., Hensen, A., Den Bulk, P., Chen, H.: Evaluating

785 the use of an Unmanned Aerial Vehicle (UAV)-based active AirCore system to quantify methane emissions from dairy cows, Sci. Total Environ., 831, 154898, https://doi.org/10.1016/j.scitotenv.2022.154898, 2022

Werner, C., K. Davis, P. Bakwin, C. Yi, D. Hurst, and L. Lock: Regional-scale measurements of CH4 exchange from a tall tower over a mixed temperate/boreal lowland and wetland forest, Glob. Chang. Biol., 9 (9), 1251–1261, doi:10.1046/j.1365-2486.2003.00670.x, 2003.

790 Zazzeri, G., Lowry, D., Fisher, R. E., France, J. L., Lanoisellé, M., Kelly, B. F. J., Necki, J. M., Iverach, C. P., Ginty, E., Zimnoch, M., Jasek, A., and Nisbet, E. G.: Carbon isotopic signature of coal-derived methane emissions to the atmosphere: from coalification to alteration, Atmos. Chem. Phys., 16 (21), 13 669–13 680, doi:10.5194/acp-16-13669-2016, 2016.