

High sulphur dioxide deposition velocities measured with the flux/gradient technique in a boreal forest in the Alberta oil sands region

5 Mark Gordon¹, Dane Blanchard², Timothy Jiang^{1*}, Paul A. Makar³, Ralf M. Staebler³, Julian Aherne²,
Cris Mihele³, Xuanyi Zhang¹

¹Earth and Space Science, York University, Toronto, M3J 1P3, Canada

²Environmental and Life Science, Trent University, Peterborough, K9L 0G2, Canada

³Air Quality Research Department, Environment and Climate Change Canada, Toronto, M3H 5T4, Canada

*Now at School of Environmental Sciences, Guelph University, Guelph, N1G 2W1, Canada

10 *Correspondence to:* Mark Gordon (mgordon@yorku.ca)

Abstract. The emission of SO₂ from the Athabasca oil sands region (AOSR) has been shown to impact the surrounding forest area and human exposure. Recent studies using aircraft-based measurements have demonstrated that deposition of SO₂ to the forest is at a rate many times higher than model estimates. Here we use the flux/gradient method to estimate SO₂ deposition rates at two tower sites in the boreal forest downwind of AOSR SO₂ emissions. We use both continuous and
15 passive sampler measurements and compare both techniques. The measurements predict SO₂ deposition velocities ranging from 2.1–5.9 cm s⁻¹ (when corrections are applied). There are uncertainties associated with the passive sampler flux/gradient analysis, primarily due to an assumed Schmidt number, a required assumption of independent variables, and potential wind effects. We estimate the total uncertainty as ±2 cm s⁻¹. Accounting for these uncertainties, the measurements are near (or slightly higher than) the previous aircraft-based measurements (1.2–3.4 cm s⁻¹) and significantly higher than model estimates
20 for the same measurement periods (0.1–0.6 cm s⁻¹), suggesting that SO₂ has a much shorter lifetime in the atmosphere than is currently predicted by models.

1 Introduction

Emissions of sulphur dioxide (SO₂) from the Athabasca oil sands region (AOSR) in Alberta, Canada and its subsequent wet and dry deposition to the surrounding boreal forest ecosystems may lead to soil acidification (Aherne and Shaw, 2010).
25 Several studies in the AOSR have shown that total sulphur deposition has the potential to cause soil and surface water acidification (Whitfield et al., 2010; Cathcart et al., 2016) and exceedance of critical loads of acidity (Makar et al., 2018). However, ecosystem impacts within the AOSR are ultimately dependant upon dry SO₂ deposition velocities given the low rainfall volumes (Clair and Percy, 2015). In concert, the lifetime of SO₂ in the atmosphere may affect downwind ambient air concentration and human exposure (Wright et al., 2018).

30 Recent studies using aircraft-based measurements (downwind of oil sands production) have demonstrated that dry SO₂
deposition velocities in the AOSR could be between 1.7 and 5.9 times higher than previous model estimates (Hayden et al.,
2021). Hayden et al. determined total deposition fluxes between multiple 2-dimensional (vertical and crosswind) flux screens
created using interpolated aircraft-based wind and concentration measurements. The aircraft is flown in crosswind transects
at various heights to determine the total advective flux passing through a screen, and the deposition flux is determined as the
35 difference in advective flux between screens following a Lagrangian trajectory. For the three flights analyzed by Hayden et
al. (2021), the dry deposition velocities were 1.2, 2.4, and 3.4 cm s⁻¹. In contrast, model parameterizations suggested
deposition velocities of 0.72, 0.63, and 0.58 cm s⁻¹ for the same respective flight areas and periods.

Alternatively, dry deposition can be calculated directly at a measurement location using eddy covariance; however, this
requires a fast-response instrument that can make measurements at 1 Hz or faster. This is not possible with current SO₂
40 instrumentation that measure at frequencies < 0.2 Hz, which necessitates using a flux/gradient approach (e.g., Wu et al.,
2016). Using this method, a deposition velocity of 4.1 cm s⁻¹ was calculated over a 3-day period at a tower site in Fort
McKay in the AOSR (Hayden et al., 2021).

Similarly, passive samplers can also be used to measure vertical gradients over long periods (c.f. Quant et al., 2021 and
references therein). This is especially useful for remote locations, since the samplers are relatively inexpensive, easy to
45 deploy, have weekly to monthly exposure periods, and require no power. Quant et al. (2021) describe four vertical gradient
passive sampler installations to measure gaseous mercury. They consider these results semi-quantitative and estimated an
uncertainty factor of four. The bulk of this uncertainty (a factor of three) was due to the estimation of an appropriate average
turbulent diffusion coefficient (K).

Bolinus et al. (2016) assessed the uncertainty of turbulent fluxes with long-term gradient profile measurements using the
50 modified Bowen ratio to determine eddy diffusivity (K) from heat flux measurements. They tested this theory with highly
variable and bi-directional fluxes of CO₂ and water vapour and found that the gradient method resulted in fluxes that differed
by factors of three for CO₂ and 10 for H₂O.

This study used measurements of SO₂ gradients in a boreal forest to determine dry SO₂ deposition velocities downwind of oil
sands production facilities. Measurements were made with both long-term (2-3 week exposure period) passive samplers and
55 continuous in-situ gas analyzers at two tower locations in the same forest. Continuous SO₂ measurements demonstrated that
the site was subjected to relatively strong, intermittent plumes of SO₂, which we assumed were not re-emitted from the forest
(hence eliminating uncertainty due to bi-directional fluxes). Here we determine average values of turbulent diffusion
coefficients (K) based on momentum flux and stability measurements, and we assess the uncertainties due to the long-term
averaging of these variables using continuous SO₂ gradient measurements. Following this approach, we determine a range of
60 SO₂ dry deposition velocities. This paper is a companion paper to Jiang et al. (2022) and Zhang et al. (2023) which
respectively investigate aerosol and ozone deposition at this site.

2 Methods

2.1 Site Location and Instrumentation

This study incorporates measurements made at two towers in a mature jack pine (*Pinus banksiana*) forest. The location of the towers relative to surrounding mines and processing facilities is shown in Fig. 1a. The York Athabasca Jack-Pine (YAJP) tower was located at 57.1225 N 111.4264 W. The second meteorological tower was operated by the Wood Buffalo Environmental Association (WBEA), a non-profit environmental group, which monitors pollutants in the AOSR. WBEA identified this tower as “1004”. It is approximately 540 m directly south of the YAJP tower. The forest extends for at least 10 km in all directions. Images of the YAJP and WBEA (1004) towers and surrounding forest are shown in Figs. 1b and 1c, respectively. The ground beneath the forest is covered in reindeer moss (*Cladonia spp.*). Undergrowth vegetation in the area is limited to sparsely distributed blueberry bushes. The soil is sandy and well drained. The forest canopy height is approximated as 19 m tall (with the tallest trees in the area ranging from 16 m to 21 m in height).

The village of Fort McKay is approximately 15 km to the NW of the site and the town of Fort McMurray is 40 km south. The site is surrounded by oil sand production facilities. These include thermal in-situ extraction, such as Husky Sunrise and Suncor Firebag (approximately 23 km NW and 34 km WNW respectively); open pit mining, such as Shell Jackpine (10 km North), Syncrude Aurora (20 km NNW), and Shell Muskeg (15 km NW); as well as combined mining and upgrading facilities, such as Suncor (13.5 km South), Syncrude (18 km SW), and CNRL (30 km NW). The upgrading facilities produce significant SO₂ plumes (c.f., Gordon et al., 2015) which are intermittently brought to the tower sites when the winds are from the South and SW directions (see Section 3.2). Additionally, the Hammerstone limestone aggregate quarry is located 10 km NW of the tower.

The 1004 tower measured wind speed and direction at heights of 2, 16, 21, and 29 m and recorded the data as 1-hour averages. The YAJP tower measured high-frequency wind data with a 3D sonic anemometer (Type A, Applied Technology Inc.) mounted at a height of 29 m. Between September 2017 and August 2018, a second anemometer (Type V) was mounted within the canopy at height of 5.5 m. All flux, wind, and temperature measurements from the YAJP tower were calculated in 30-minute periods, unless stated otherwise.

Between 4-8 June 2018, SO₂ measurements were made at a height of 2 m at the YAJP tower with a 43i Thermo Scientific analyzer (herein referred to as “43i”). A Tethered Balloon system made measurements of SO₂ using modified ozonesondes up to a height of 300 m between 13-15 July 2018. Between 7-26 August 2021, SO₂ measurements were made at heights of 2 m and 29 m using two 43i instruments sampling through lengths of ¼” Teflon tubing. For the 29-m height, the residence time of the tubing was measured as 14 s (a flow rate of 1.0 LPM). Between 20 July and 31 August 2021 an Envea AF22e gas analyzer (herein “AF22e”) measured SO₂ at a height of 2 m. The AF22e was solar powered when generator power was not available. It was therefore operated for a longer timespan than the 19 days of 43i measurements in 2021. All 43i measurements were at a frequency of 0.2 Hz, while AF22e measurements were once per minute. Calibration of the 43i instruments determined a standard deviation of less than 0.07 ppb at 0 ppb and less than 0.43 ppb at 80 ppb. The AF22e was

95 not laboratory-calibrated but was corrected against the co-deployed 43i (sampling from the same inlet) for measurement values ranging from 0 to 60 ppb ($R^2 = 0.97$).

To investigate the vertical structure of SO₂ plumes, a Tethered-Balloon system was used to lift two ozonesondes. Following the technique outlined in Yoon et al. (2022), one ozonesonde sampled through a filter tube coated with KMnO₄ solution (which absorbs SO₂) so that the difference between the two ozonesonde measurements gives SO₂ mixing ratio. The
100 procedure for ozonesonde preparation and calibration are outlined in Yoon et al. (2022).

Passive samplers were deployed at the YAJP and 1004 towers over eight separate exposure periods between October 2020 and October 2021. The first two deployments were at YAJP, the third was a co-deployment at YAJP and 1004 for the same period, and the remaining five were at 1004. The deployments ranged in duration from 2 to 3 weeks. Samplers were mounted at heights of 2, 4, 8.5, 13.5, 18, and 23 m on the YAJP tower and heights of 4, 8, 13, 17.5, and 22 m on the 1004 tower. The
105 samplers mounted at a height of 2 m on the YAJP tower were only used for 2 of the 3 deployments.

The devices used in this work were badge-type passive samplers (Blanchard and Aherne, 2019; Islam et al., 2016; Zbieranowski and Aherne, 2012) that housed a Whatman 40 filter paper pretreated with a KOH solution (Hallberg et al., 1984; Salem et al., 2009). Following field exposure, filters were extracted in 10 ml of 0.3% hydrogen peroxide solution and the resulting sulphate (SO₄²⁻) concentrations were determined via ion chromatography. The mass of SO₂ collected (Q [μg])
110 on the filter paper was calculated following Zbieranowski and Aherne (2012) as

$$Q = V M_R (S_f - S_b), \quad (1)$$

where S_f [$\mu\text{g l}^{-1}$] is the measured SO₄²⁻ concentration in the extraction solution, S_b is the average field blank SO₄²⁻ concentration (three per deployment), V [l] is the extraction volume, and $M_R = 6.67 \times 10^{-4}$ is the molar conversion from SO₄²⁻ to SO₂. For this study, the average value of S_b was 0.01 mg l⁻¹ SO₄²⁻, compared to an average S_f of 1.38 mg l⁻¹ SO₄²⁻, hence
115 the uncertainty due to blank subtraction was assumed to be negligible. The atmospheric concentration of SO₂ was then calculated from Q as

$$C = \frac{Q R_t}{A t}, \quad (2)$$

where C is the concentration of SO₂ ($\mu\text{g m}^{-3}$), A is the sampler cross-sectional surface area (m^2), t is the exposure time (s), and R_t is the total badge-sampler resistance (s m^{-1}). A study specific R_t value was estimated through the co-deployment of
120 passive samplers at five WBEA monitoring stations equipped with continuous SO₂ monitors. Refer to Appendix A for further detail regarding R_t determination and WBEA sampling site information.

Samplers were deployed in duplicate or triplicate on the underside of rain shelters. Data variability was assessed by calculating the coefficient of variation (CV) among replicate samplers. To reduce vibration and sway with winds, a rigid mounting system was developed to attach the samplers to a pulley rope (YAJP) or metal cable (1004), as shown in Figure 2.
125 At the YAJP site, the samplers were attached to a 1.5 m plastic tube that was fixed to the pulley rope at the top and bottom of the tube. Three of the five tubes were guyed to the ground with strings for additional stability. The lowest (2-m height)

sampler at the YAJP site (used for 2 of the 3 deployments) was fixed to the tower base. At the 1004 site, the pulley system used a metal cable loop. Here the mounting system was fixed to one side of the loop, while the other side of the loop passed through forked stabilizers to eliminate vibration and sway.

130 The passive samplers co-deployed at the five WBEA continuous monitoring stations allowed the evaluation of sampler performance. Comparison with corresponding continuous measurement data enabled the calculation of passive sampler bias (%) while a Spearman Rank-Order Correlation test was applied to test the level of agreement ($\alpha < 0.05$) between samplers. At the YAJP tower, the AF22e was operational for the duration of the 4th sampler exposure period and the 43i was operational for the duration of the 3rd sampler co-deployment at both the YAJP and 1004 towers. These comparisons are
135 discussed in Section 3.3.

2.2 Flux/Gradient Methodology

Deposition fluxes were calculated from the passive-sampler mixing ratio gradients following the gradient flux method from a procedure outlined in You et al. (2021). The relationship between the SO₂ deposition flux (F , positive downward) and the gradient (dC/dz) is

$$140 \quad F = K_C \frac{dC}{dz}, \quad (3)$$

where the trace gas diffusion coefficient (K_C) and vertical concentration gradient (dC/dz) are modeled as constant throughout the height of the canopy. This also assumes that the flux divergence is insignificant in the canopy (equivalent to assuming all deposition is to the surface and not to the canopy elements). This assumption is discussed in Section 4.1. The gradient was determined using a least-squares fit to the measured 5 or 6-point profile. While K_C was not measured, the
145 momentum diffusion constant ($K_{M,G}$) can be determined through the momentum flux/gradient relationship as

$$u_*^2 = K_{M,G} \frac{du}{dz}, \quad (4)$$

where u_* is the friction velocity (measured at a 29 m height) and the wind speed gradient (du/dz') is approximated from the wind velocity difference between 29 m and 5.5 m, assuming a linear gradient. Since the wind speed gradient was only measured between September 2017 and August 2018, the 2020 – 2021 measurements require a parameterization of the
150 diffusion constant. Ignoring the effects of the canopy on diffusion, Prandtl's mixing length model is adjusted for stability to give (Garratt, 1994)

$$K_{M,P} = \frac{\kappa z_m u_*}{\phi}, \quad (5)$$

where $\kappa = 0.4$ is the von-Karman constant, z_m is the flux measurement height, and the stability parameter (ϕ) can be determined from the Obukhov length (L) following Garratt (1994) as

$$155 \quad \phi = \begin{cases} (1 - 16(z/L))^{-1/4} & -5 < z/L < 0 \\ 1 + 5(z/L) & 0 < z/L < 1 \end{cases}, \quad (6)$$

Between 23 September 2017 and 2 August 2018, two anemometers were functional on the YAJP tower and a gradient (du/dz) was measured. For this period, we calculated $K_{M,G}$ from the flux/gradient method (Eq. 4) and compared this to the parameterization of $K_{M,P}$ from Eq 5 and 6. A least-squares fit to all the 30-min values of $K_{M,P}$ as a function of $K_{M,G}$ over the ~10-month period gave a slope of 2.6 with $R^2 = 0.83$ (Fig. 3). Hence the diffusion can be more accurately parameterized as

160 $K_{M,P} = \kappa z_m u_* / 2.6 \phi$, which is simplified to $K_{M,P} = \kappa z'_m u_* / \phi$, where $z'_m = z_m / 2.6 = 11$ m. We note that the height of $z'_m = 11$ m lies between the two measurement heights (5.5 and 29 m), which supports the use of this technique. As demonstrated in Fig. 3, values of $K_{M,G} > 5 \text{ m}^2 \text{ s}^{-1}$ will be underestimated by this parameterization; however, less than 6% of the $K_{M,G}$ measurements in the 10-month period are greater than $5 \text{ m}^2 \text{ s}^{-1}$. Other parameterizations (not shown here) that account for the effects of the canopy on mixing and turbulence are described in Stroud et al. (2005), Wu et al. (2016), and

165 Makar et al. (2017). While these parameterizations provide greater accuracy for vertically resolved modeling within the canopy, they do not improve the correlation between $K_{M,P}$ and $K_{M,G}$ for these data. This is likely because we are here approximating diffusion with a single value throughout the canopy.

The trace gas diffusion constant can be related to the momentum diffusion constant by the turbulent Schmidt number as

$$Sc = \frac{K_M}{K_C}, \quad (7)$$

170 Schmidt numbers determined in previous studies demonstrate a range of values. Similarly, Flesch et al. (2002) measured values between 0.17 and 1.34, while Gualtieri et al. (2017) report values in experimental and numerical studies between 0.1 and 1.3. You et al. (2021) defined a modified Sc that incorporates the stability parameter (z/L) and found that the value varied between 0.04 and 2.90. The average values (or values determined by least-squares fitting) from Flesch et al. (2002), You et al. (2021), and Gualtieri et al. (2017) are $Sc = 0.6, 0.74,$ and 0.99 respectively. Here we use an average of 0.8 and

175 estimate the uncertainty in the calculated values based on the 0.6 to 0.99 range of values.

With these assumptions, Equations 3 to 7 are combined to give the deposition flux as

$$F = \frac{\kappa z'_m u_*}{Sc \phi} \frac{dC}{dz}. \quad (8)$$

2.3 Aerodynamic Resistance

The total resistance to pollutant deposition at height z ($r_{t,z}$) is modeled as the sum of the aerodynamic (r_a), quasi-laminar

180 sublayer (r_b), and bulk surface (r_c) resistances. The deposition velocity is the inverse of the total resistance as

$$v_{d,z} = \frac{1}{r_{t,z}} = \frac{1}{r_a + r_b + r_c} = \frac{F}{C_z - C_0}, \quad (9)$$

where C_z and C_0 are the concentrations at height z and at a compensation point, respectively. Typically, a zero concentration is assumed at the compensation point ($C_0 = 0$) either within the soil or the leaf, and the deposition velocity ($v_{d,z}$) can be related to the flux as $v_{d,z} = F/C_z$.

185 Our measurements in this study were limited to a height of 23 m and are therefore a calculation of $v_{d,23m}$. We compared these values to values determined by the GEM-MACH deposition parameterization (described in Section 2.5 below), which are also determined at a height of 23 m.

The deposition velocities in Hayden et al. (2021) were initially determined from aircraft measurements at heights > 150 m and then adjusted to a height of 40 m to give $v_{d,40m}$. This accounts for reduced aerodynamic resistance between 40 and 150
190 m. Hayden et al. (2021) state that this extrapolation is considered their largest source of uncertainty. For comparison of the deposition velocity calculated from YAJP and 1004 tower measurements, we added the aerodynamic resistance between heights of 23 m and 40 m, which can be calculated by integrating Eq. 3 between these two heights with $K_c = \kappa z u_* / Sc \phi$, and averaging to give

$$r_{a,23-40m} = \frac{Sc}{\kappa} \left\langle \frac{\phi}{u_*} \right\rangle \ln \left(\frac{40}{23} \right), \quad (10)$$

195 This is added to the total resistance to give $v_{d,40m} = (r_{t,23m} + r_{a,23-40m})^{-1}$. The uncertainty associated with the added resistance is discussed below.

2.4 Deposition Velocity Calculation

The total deposition can be calculated combining Equations 8, 9, and 10. The use of long-term passive samplers (2 to 3 weeks in duration) to determine the gradients necessitates time-averaging the equations. If it is assumed that K_M (a function
200 of u_*/ϕ), the concentration (C), and the gradient (dC/dz) are all independent variables, this gives

$$v_{d,40m} = \left(\left(\frac{\kappa z'_m}{Sc} \left\langle \frac{u_*}{\phi} \right\rangle \frac{1}{\langle C \rangle} \left\langle \frac{dC}{dz} \right\rangle \right)^{-1} + \frac{Sc}{\kappa} \left\langle \frac{\phi}{u_*} \right\rangle \ln \left(\frac{40}{23} \right) \right)^{-1}, \quad (11)$$

where the angle brackets $\langle \rangle$ indicate time-averaging over the sampling period. This assumes that there is no correlation between the stability-corrected friction velocity (u_*/ϕ), the concentration (C), and the concentration gradient (dC/dz), since they are averaged separately in the equation. If u_*/ϕ , C , and dC/dz are correlated, the assumption of independent variables
205 will introduce an error in this flux estimation (since $\langle u_*/\phi C dC/dz \rangle \neq \langle u_*/\phi \rangle 1/\langle C \rangle \langle dC/dz \rangle$). In order to estimate the error associated with the assumption of independent variables, we also calculate the deposition velocity (in Section 4.1) using a time series of 30-minute average, concurrent friction velocity, stability, and concentration measurements (using the high-frequency, SO₂ gradient measurements made with the two 43i instruments in August 2021), which does not require long-term averaging of these terms.

210 During some of the long-term averaging periods, due to a lack of sunlight to charge the batteries or instrumentation failure, a complete time-series of turbulence measurements (u_*/ϕ) was not available. In these cases, missing values of u_* were filled using the hourly-averaged wind speed (U) at the 1004 tower, which demonstrates a strong correlation ($R^2 > 0.8$) with u_* at the YAJP tower. Missing heat flux values (to determine Obukhov length, L) were filled based on a median diurnal pattern determined from the available measurements. The extent of each case of turbulence data replacement is presented in the
215 Results section below and the uncertainty based on the parameterization is discussed in Section 4.1.

2.5 GEM-MACH Deposition Parameterization

The GEM-MACH deposition parameterization used to compare to our measured values is described in Makar et al. (2018). The reader is referred to their Supplement S1 (their Equations S.1–S.20) for a detailed description. Very briefly, the parameterization accounts for aerodynamic (r_a), quasi-laminar (r_b), and bulk surface resistance (r_c), which includes
220 resistances associated with soil, canopy, mesophyll, cuticle, and stomatal surfaces as well as resistance to buoyant convection. Here we model the forest as an evergreen needleleaf. The parameterization is a function of temperature, relative humidity, atmospheric stability, solar radiation, and CO₂ mixing ratio. For these values, we used measurements from the YAJP and 1004 towers and we calculated deposition velocity (herein $v_{d,GEM}$) for the time periods coincident with the profile measurements.

225 As discussed above, the parameterized GEM-MACH deposition velocity values were significantly lower than the observations of Hayden et al (2021) for the same time periods and locations. Hayden et al. used a Monte Carlo analysis of the GEM-MACH deposition algorithm to demonstrate that the most likely cause of underestimation was in the standard model assumption that concentration of hydrogen ions on the mesophyll, cuticle and exposed surfaces corresponded to a neutral pH (6.68). The Oil Sands facilities are known sources of significant base cation emissions (the neutralizing impact of
230 the base cations on acidifying deposition was noted in Makar et al (2018)). Hayden et al (2021) showed that the increase in surface pH associated with deposited base cations could account for the discrepancy between modelled and measured SO₂ deposition velocities and fluxes. That is, SO₂ deposition close to the sources is likely being enhanced by the co-deposition of base cations.

3 Results

235 3.1 Passive Sampler Evaluation

An analyte detection limit was calculated as the product of standard deviation (five blanks per sampler batch) and the t-value for a 99.0% confidence critical value. The sampler batch detection limits (assigning shortest exposure length for conservative values) ranged between 0.016 to 0.022 ppb SO₂, with a study avg. of 0.019 ppb SO₂. A significant linear correlation ($R^2 = 0.95$; $\alpha < 0.05$) was observed between the 14 co-located passive samplers and WBEA continuous SO₂ measurements. The

240 estimated sampler bias was low (2.3%), while replicate sampler variability remained low throughout the study period with a CV = 4.5%.

3.2 Characterizing the SO₂ Plume

A time series of SO₂ measurements is shown in Figure 4. These measurements demonstrate the intermittency of the plumes and range of values. There are also 10 days of data from 2018 not shown here which demonstrate a similar intermittency. 245 Figure 5 plots all the measurements (including the 2018 measurements) with wind direction. This distribution demonstrates that most of the SO₂ is transported from the Suncor (13.5 km at 195°) and Syncrude (18 km at 225°) stacks. All the measurements between 1 and 10 ppb (green dots) outside the 160° to 250° range are from one day in July with low winds and variable wind direction measured with the AF22e. This is maybe a recirculation event drawing back a Syncrude or Suncor plume from different directions.

250 Figures 4 and 5 demonstrate how winds bring elevated SO₂ levels from the south to south-west. Plumes of SO₂ with 5 ppb or higher appear on the majority of days, typically occurring between 09:00 and 18:00, although the duration of the plume exposure through the day can last from 1 to 8 hours. The skewness of the data (i.e., a majority of near-zero values with some strong intermittent pulses of high SO₂ levels) have implications for how an average passive sampler value should be interpreted. For example, when comparing passive-sampler measurements at two locations, slight differences in wind 255 patterns between the two locations could lead to vastly different average SO₂ values.

SO₂ measurements were made from a modified ozonesonde on a tethered balloon. These measurements are compared here to ground SO₂ measurements (43i) in Figure 6. The figure demonstrates decoupling and coupling of the different vertical layers of air in the boundary-layer above the forest. During the first half of the ascent (elevation shown by black line), the balloon and ground SO₂ measurements are nearly equal (red and green lines respectively), demonstrating a well-mixed boundary- 260 layer. At the end of the ascent (~13:10), the sonde samples an SO₂ plume while the ground 43i samples clean air. The plume begins to mix to the ground level near 13:25 and things become well-mixed near 13:40 with nearly equal ground and elevated SO₂ values. This demonstrates that plumes are not only intermittent due to horizontal variation in wind direction but can also vary considerably in the vertical direction. Our analysis of deposition using a flux/gradient approach assumes that when these horizontal and vertical variations are averaged over a 2 to 3-week period, a smooth vertical gradient is observed.

265 3.3 Deposition Velocity

The 9 passive sampler profiles (from 8 time periods) are listed in Table 1. Durations of the sample periods range from just over 12 days to more than 3 weeks. The sampler vertical profiles of SO₂ mixing ratio with height are shown in Fig. 7. The gradients (dC/dz) are determined from a least-squares fit to each profile. The R^2 values for these fits are given in Table 1. Using these gradients and the mixing ratio value from the highest sampler location (C), the deposition velocities calculated 270 with Eq. 8 range from 2.9 to 9.4 cm s⁻¹. Adjusting these deposition velocities to a height of 40 m (from 23 m) reduces the range to 2.7 to 7.7 cm s⁻¹ with an average value of 5.9 cm s⁻¹. The difference between $v_{d,23m}$ and $v_{d,40m}$ for each profile

ranges from 7 to 18%. The values measured here are similar to or higher than those of Hayden et al. (2021) which range from 1.2 to 3.4 cm s⁻¹. As was seen in Hayden et al., the values are considerably higher than the GEM-MACH parameterization (Makar et al. 2018) and an inference model used Hsu et al. (2016) for the AOSR, which range from 0.2 to 0.3 cm s⁻¹.

The AF22e and 43i analyzer measurements are compared to the passive sampler measurements in Figure 7 for coincident periods during Profiles 3a and 3b (two sampler installations at the same time at the YAJP and 1004 towers) and Profile 4 (1004 only). In both cases, measurements near the surface show good agreement with passive samples measurements (accounting for the gradient of mixing ratio with height). During the Profile 4 period, the 43i measurements at a height of 29 m are much lower than the highest passive sampler measurement over the same period. Using the linear fit to the passive sampler gradient and assuming a linear interpolation of the 2-point gradient, the mixing ratio at canopy height (19 m) would be approximately 1.37 ppb from the passive sampler profile versus 0.93 ppb from the 43i profile (a 32% difference). One potential reason for this discrepancy could be a dependence of the passive sampler resistant (R_t) on wind speed, which could lead to overestimation of passive sampler measured concentration above the canopy (where the wind speed is greater). This potential effect is investigated in greater detail in Section 4.2. The deposition velocity calculated with the 43i profile measurements (adjusted for aerodynamic resistance between 29 m and 40 m) is 4.4 cm s⁻¹, which is 68% of the 6.5 cm s⁻¹ deposition velocity determined by the passive sampler gradient over the same period (Profile 4, Table 1). This value is in close agreement with the flux/gradient measurement (4.1 cm s⁻¹) of Hayden et al. (2021).

4 Discussion

4.1 Uncertainty Analysis

There is approximately a factor of 2 difference between the range of deposition velocities reported here ($v_{d,40m}$ between 2.7 and 7.7 cm s⁻¹) and the aircraft-based measurements in the region (1.2 – 3.4 cm s⁻¹, Hayden et al., 2021), but in both cases the measured values are considerably higher than the GEM-MACH parameterized values and the values determined by an inference model for the AOSR region of Hsu et al. (2016). For comparison, the range of deposition velocities for different methods and studies are listed in Table 2. We note that the aircraft measurements of the Hayden et al. study covers a range of different forests and land types, including lakes, wetlands, and surfaces modified by oil sands extraction, waste, and tailings. The estimate made using a flux/gradient approach in Hayden et al. is from a 3-day period (4.1 cm s⁻¹) at a tower in the town of Fort McKay. This value is closer to our measured values, but still 30% less than our average value. Below we investigate whether measurement uncertainty based on assumptions in the methodology might be responsible for the observed differences.

The deposition velocities ($v_{d,40m}$) from the 9 profiles can be compared to a normal distribution, with 78% (7 values) within one standard deviation (σ) of the mean, 1 value (Profile 8) 1.3 σ higher than the mean and 1 value (Profile 5) 2.4 σ lower than

the mean. The anomalous deposition velocity of 2.9 cm s^{-1} for Profile 5 is due to a combination of a weak gradient and high mixing ratio relative to the other profiles (Fig. 7). The fit to the profile is moderate ($R^2 = 0.72$), but not the weakest fit. Meteorological conditions shown in Appendix A (Fig. A1) demonstrate some rainfall ($> 25 \text{ mm}$) and some cloudy, humid conditions, but similar conditions are seen in other profile periods (e.g. rain in profile periods 1 and 3, and clouds and high humidity in profile periods 6 and 8). Hence the reason for this anomalous value is unknown.

The two highest deposition velocities ($v_{d,40\text{m}} = 6.9$ and 7.7 cm s^{-1} for Profiles 1 and 8) are from periods when most of the turbulence data were unavailable (61.5% and 96% missing respectively). As discussed in Section 2.2, u_* and the heat flux were parameterized based on measured wind speed and an assumed diurnal profile. Hence there will be greater uncertainty in these measurements. As an example, recalculating all the deposition velocities with completely parameterized u_* and heat flux results in a range of $v_{d,40\text{m}}$ from 3.2 to 7.8 cm s^{-1} with an average of 6.3 cm s^{-1} . This suggests that the parameterization of missing turbulence data may lead to an approximate 10% overestimation of v_d .

Eq. 5 was used to parameterize K_M due to a lack of wind gradient measurements during the passive sampler measurement period. As demonstrated by Fig. 3, this introduces some uncertainty to the measurements. Previous measurements at the site demonstrate deviation from a linear fit for values of $K_{M,G} > 5 \text{ m}^2 \text{ s}^{-1}$, which corresponds to values of $K_{M,P} > 12.5 \text{ m}^2 \text{ s}^{-1}$ or $u_*/\phi_M > 2.8 \text{ m s}^{-1}$. By comparison, the maximum value reached during Profile 3b (for example), is $u_*/\phi_M = 1.4 \text{ m s}^{-1}$ (or $K_{M,P} = 6.2 \text{ m}^2 \text{ s}^{-1}$), so the effect of this deviation from the linear fit should not be significant. The uncertainty can be approximated from the standard error of the slope, which is 0.017. From Eq. 8, this standard error gives an uncertainty of less than 2% in the final v_d estimate using a 95% confidence interval.

The flux/gradient analysis outlined in Section 2.2 assumes that the vertical concentration profile is not significantly modified by deposition flux to canopy elements (such as pine needles). While the uncertainty due to this assumption is difficult to quantify, any strong flux divergence through the canopy should result in a consistent curvature of the concentration profile through the canopy. The profiles shown in Fig. 7 do not appear to demonstrate any consistent curvature away from a linear profile, suggesting that flux divergence may be minimal, and that deposition can be approximated following a “big-leaf” assumption.

Since v_d is inversely proportional to the Schmidt number, our assumption of a constant value of $Sc = 0.8$ can be assessed against other published average values of $Sc = 0.6$ and 0.99 . Using a value of $Sc = 0.6$ would result in an increase of 33% in v_d , while a value of $Sc = 0.99$ would result in a 20% decrease. You et al. (2021) suggest a Schmidt number which is a function of stability (based on the ratio of measured momentum diffusivity coefficient to measured concentration diffusivity coefficient). We use the turbulence data from Profile 3b to investigate the use of this variable Schmidt number. Profile 3b is chosen because of the strong fit of the slope ($R^2 = 0.91$) and the completeness of the turbulence data over that period (Table 1). For this reanalysis, $Sc = 0.08 + 3.13 \times 10^{-9} \exp((z/L + 19.5)/1.008)$ for $z/L < -0.18$ and $Sc = 0.74$ for $z/L \geq -0.18$ (following You et al. 2021). It is noted we are using a parameterized momentum diffusivity coefficient ($K_{M,P}$) to estimate the gradient momentum diffusivity coefficient ($K_{M,G}$) and the parameterization (Eq. 5) includes a correction for stability. Hence,

this method includes two stability corrections: one for the assumption of $K_{M,P} = K_{M,G}$ and one for the variability observed in $Sc = K_{M,G}/K_C$. Regardless of this complication, the use of this variable Schmidt number results in a decrease in $v_{d,40m}$ of 50% (to 2.7 cm s⁻¹) for Profile 3b.

As discussed in Section 2.4, the assumption that u_*/ϕ , C , and dC/dz are independent variables will result in an error if they are correlated. We investigate this assumption by calculating the deposition velocity using a continuous time series of 30-min averages of the friction velocity, stability, and SO₂ observations (measured with the 43i instruments at 2 m and 29 m heights). The use of 30-min averages is long enough to give confidence in the calculated turbulent statistics but should allow for co-variation in u_*/ϕ , C , and dC/dz . This allows for a calculation of $v_{d,40m}$ for each 30-min period. The average of these 30-min $v_{d,40m}$ values can then be compared to an average over the entire period following Eq. 11 (i.e. $\langle \frac{\kappa z_m}{Sc} \frac{u_*}{\phi} \frac{1}{C} \frac{dC}{dz} \rangle$) compared to $\frac{\kappa z_m}{Sc} \langle \frac{u_*}{\phi} \rangle \frac{1}{\langle C \rangle} \langle \frac{dC}{dz} \rangle$.) In order to avoid large numbers caused when $C \approx 0$, the analysis is restricted to times when a plume is present using a criteria of $C > 1$ ppb SO₂ (cf. Fig 4). This gives 73 30-min averages for analysis when SO₂ mixing ratio and turbulence data are available (no filling of missing turbulence data is applied here). The average of all the 73 30-min deposition velocities is $v_{d,40m} = 3.3$ cm s⁻¹. The deposition velocity calculated using the averages of $\langle u_*/\phi \rangle$, $\langle C \rangle$, and $\langle dC/dz \rangle$ for the same 73 30-min values is $v_{d,40m} = 4.4$ cm s⁻¹. This indicates that the assumption of independent variables required by long-term averaging could lead to a 30% overestimation of the deposition velocity. Here we define a corrected deposition velocity (which assumes the 30% overestimation applies to all measurements) as $v_{d,40m}^* = v_{d,40m} / 1.3$. Applying this correction to the range of deposition velocities listed in a Table 1 gives a corrected range of 2.1 to 5.9 cm s⁻¹, with an average of 4.6 cm s⁻¹.

4.2 Wind Speed Effects

Some of the profiles shown in Fig. 7 have mixing ratios near or above the canopy which are much higher than the within-canopy values. Although the within-canopy values demonstrate an increase with height, for many profiles that increase is much more pronounced across the canopy top. For example, Profiles 1 and 4 show a sharp increase in mixing ratio above the canopy, while Profiles 3a and 8 show a sharp increase in the two highest measurement heights (relative to measurements in the sub-canopy). These 4 profiles (1, 3a, 4, and 8) demonstrate higher than average deposition velocities (≥ 6.3 cm s⁻¹). By comparison, Profiles 2 and 3b show the best agreement to the linear least-squares fit ($R^2 = 0.99$ and 0.91 respectively) and have the lowest deposition velocities (5.3 and 5.4 cm s⁻¹). These results suggest that the greater-than-average increase in mixing ratio at the top of the canopy is associated with higher estimates of v_d and a lower correlation of the profile with a linear fit.

Wind speed can affect the sampling rate of badge type samplers; however, the effect is reduced by the diffusion membrane (Plaisance, 2011) and use of a wind shield (Masey et al., 2017). Hofschreuder et al. (1999) noted that with proper sampler and draught shield design the influence of wind speed can be reduced to less than 10%. Although our sampler concentrations

were corrected using samplers mounted at WBEA stations coincident with continuous gas analyzers, the wind conditions at these stations might show significant differences compared to the canopy, and the increase in wind speed near the canopy top may have significant effect on the measured SO₂ gradient.

370 Using the wind speeds profiles measured at 1004, the correlation of the above-canopy concentration gradient (dC/dz) between 18 and 23 m can be compared to wind data for each profile period. The values of dC/dz for each period show no correlation ($0.001 < R^2 < 0.03$) with either: the average wind speed gradient (dU/dz between 16 and 29 m); the average wind speed at 29 m; or the variance in hourly wind speeds at 29 m (all measured over the same time periods as the profiles). If wind speed had a direct effect on the sampler uptake, leading to higher measured SO₂ mixing ratios for higher wind
375 speeds, then a stronger correlation would be expected between the upper concentration gradient across the canopy top, where the wind gradient is largest. However, the low correlation between dC/dz and various variables related to wind speed suggests that the vertical gradient of wind speed between the sub-canopy and above the canopy does not have a significant effect on the measured SO₂ mixing ratios.

In order to assess passive sampler performance, passive samplers were deployed at 5 WBEA continuous monitoring sites
380 over five 2-week periods, resulting in 14 comparisons between passive sampler and continuous measurements (the number of deployment sites for the five periods were 2, 3, 4, 4, and 1 respectively). During these periods, wind speeds at the site (measured at a 10-m height) ranged from an average of 1.3 m s⁻¹ to 4.0 m s⁻¹. The passive sampler measurement error (the difference between the passive sampler and continuous measurements) ranged from -0.36 to 0.29 ppb. If the passive sampler resistance (R_t) varies with wind speed it would be expected that this error would correlate with the average wind speed for
385 each sampler comparison. However, the correlation between sampler error and average wind speed is $R^2 = 0.003$. Similarly, the correlation between sampler error and either maximum wind speed or wind speed variance is $R^2 < 0.003$. Hence, these results do not suggest a strong influence of wind speed on the measured passive sampler concentration.

5 Conclusions

The 2-point SO₂ gradient measurements made by gas analyzers were averaged to a frequency of 30 min to assess the
390 assumption of independent variables that is required for the averaging of turbulence measurements to determine deposition rates from long-term passive sampler measurements. For the 19-day period analyzed, these results suggest an overestimation of v_d of 30% due to the assumption of independent variables. Assuming this overestimation is the same for all profile periods, the corrected range of deposition velocities would be 2.1 to 5.9 cm s⁻¹ with an average of 4.6 cm s⁻¹.

There is disagreement between the passive sampler gradient and the 2-point SO₂ 43i gradient measurements made by gas
395 analyzers over the same period. The predicted mixing ratio at canopy height from the passive sampler profile is 47% higher than the predicted mixing ratio at canopy height from the 2-point 43i gradient profile (assuming a linear profile in each case). This could be partially due to wind effects causing overestimation of the passive sampler concentrations. However, our investigation of wind speed effects on the measurements shows no correlations between measured wind speed and

concentration gradients or the error in R_t . The difference in slopes (dC/dz) between the 2-point measurements and the
400 passive sampler profiles results in a nearly 50% difference in predicted deposition velocity. Correcting the passive sampler
deposition estimation for the 30% overestimation due to the independent variable assumption gives $v_d = 5.0 \text{ cm s}^{-1}$. Hence,
given the uncertainties involved, these two measurement methods give comparable deposition velocity estimates for the
same time period within $\pm 1 \text{ cm s}^{-1}$.

The predicted range of deposition velocities (2.1 to 5.9 cm s^{-1} accounting for independent variables) is higher than the range
405 of values of 1.2 to 3.4 cm s^{-1} determined by Hayden et al. (2021) using aircraft measurements, although these values are
close to a deposition velocity of 4.1 cm s^{-1} reported in the Hayden et al. (2021) study determined using a flux/gradient
approach from a tower located in Fort McKay. However, these results support the conclusion of Hayden et al. (2021) that
deposition to forest surfaces is likely underestimated in regional and global chemical transport models as both sets of results
are considerably higher (by an order of magnitude in our case) than parameterized values.

410 The flux/gradient method does not account for flux divergence through the canopy and is equivalent to assuming that total
deposition occurs near the surface only. Although the uncertainty associated with that assumption is difficult to quantify, we
note that the vertical concentration profile shapes do not show any consistent curvature away from a linear gradient and that
the deposition estimates show good agreement with the Hayden et al. tower measurements located in a relatively clear and
residential area in Fort McKay. To quantify this uncertainty, the use of a high-resolution, one-dimensional canopy model
415 (such as the model used in the Zhang et al., 2023) with varied deposition profiles is recommended for future studies.

A near-unity value of $Sc = 0.99$ would result in a 20% reduction in the estimated values and the use of a variable Sc
parameterization based on stability results in an 50% decrease in the estimated deposition rate. Hence, there is substantial
uncertainty ($\pm 1.5 \text{ cm s}^{-1}$) based on the assumed Sc value.

The use of passive sampler gradients to determine fluxes is relatively new and previous studies (e.g., Quant et al., 2021) have
420 suggested large uncertainties. The uptake to the passive samplers may depend on properties such as wind speed and
temperature, which also have strong vertical gradients, especially within and above a canopy. More study of known fluxes is
required to fully quantify the uncertainties of this measurement technique.

Despite the uncertainties in the measurements, all of the measurements for the AOSR in this study and the Hayden et al.
(2021) study are significantly greater than model parameterizations. These results suggest much shorter lifetime of SO_2 in
425 the atmosphere and significantly more sulphur deposition to the environment than has previously been modeled, in
agreement with the conclusions of Hayden et al. (2021). These results support the hypothesis discussed in Hayden et al. that
 SO_2 co-deposition with base cations may influence local SO_2 deposition fluxes. This has consequences for both the
contribution of sulphur to atmospheric aerosols (which affect climate forcing) as well as ecosystem health of the boreal
forest environment. The discrepancy between these measured deposition velocities and parameterizations for this region
430 suggests that further study is required to investigate these differences.

Appendix A

Passive samplers were co-deployed at five WBEA active monitoring stations in order to estimate the R_t value for the filter solutions during each exposure (Zbieranowski and Aherne, 2012)

$$R_t = \frac{A_c A t}{Q}, \quad (\text{A1})$$

435 Where A_c is the active sampler measured SO_2 concentration ($\mu\text{g m}^{-3}$) during the exposure period, and the remaining variables are described in section 2.1. Passive sampler concentrations were calibrated using the average R_t observed over the entire study period.

WBEA sampling site information, listing station names, locations, and links to website description (last accessed Sept, 2022) are listed in Table A1.

440 Meteorological data is shown in Fig. A1 for the 8 sampling periods on the YAJP and 1004 towers (as listed in Table 1). These data demonstrate the variation in precipitation, wind speed, sunlight (as demonstrated by photosynthetically active radiation), relative humidity and temperature. 3 of the 8 sampling periods showed significant rainfall (1, 3, and 5). Sampling period 2 showed the coldest temperatures (reaching -20°C), while sampling period 3 was the warmest (reaching 30°C).

Acknowledgements

445 We acknowledge the shared data, technical support, and assistance of the Wood Buffalo Environment Association (WBEA) of Alberta. We thank James Flynn at the University of Houston (Texas) and Mark Spychala at St. Edward's University (Texas) for joining our field study in 2018 to test their novel SO_2 sonde (see Yoon et al., 2022) and for sharing the sonde data measured from our tethered balloon.

References

- 450 Aherne, J. and Shaw, P. D.: Impacts of sulphur and nitrogen deposition in western Canada. *J. Limnol.*, 69 (s1):1-3. doi:10.4081/jlimnol.2010.s1.1, 2010.
- Bolinus, D.J., Jahnke, A., and MacLeod, M.: Comparison of eddy covariance and modified Bowen ratio methods for measuring gas fluxes and implications for measuring fluxes of persistent organic pollutants, *Atmos. Chem. Phys.*, 16, 5315-5322, doi:10.5194/acp-16-5315-2016, 2016.
- 455 Cathcart, H., Aherne, J., Jeffries, D., and Scott, K.: Critical loads of acidity for 90 000 lakes in northern Saskatchewan: A novel approach for mapping regional sensitivity to acidic deposition, *Atmos. Environ.*, 146, 290–299, doi: 10.1016/j.atmosenv.2016.08.048, 2016.
- Clair, T.A. and K.E. Percy (Editors): Assessing forest health in the Athabasca Oil Sands Region. WBEA Technical Report. 2015-05-25, 180 pp +Appendices, 2015.

- 460 Blanchard, D. and Aherne, J.: Spatiotemporal variation in summer ground-level ozone in the Sandbanks Provincial Park, Ontario. *Atmos. Poll. Res.*, 10(3), 931-940, doi:10.1016/j.apr.2019.01.001, 2019.
- Flesch, T. K., Prueger, J. H., and Hatfield, J. L.: Turbulent Schmidt number from a tracer experiment, *Agric. For. Meteorol.*, 111, 299–307, doi:10.1016/S0168-1923(02)00025-4, 2002.
- Garratt, J.R., *The Atmospheric Boundary Layer*, Cambridge University Press, UK, 1994.
- 465 Gordon, M., Li, S.-M., Staebler, R., Darlington, A., Hayden, K., O'Brien, J., and Wolde, M.: Determining air pollutant emission rates based on mass balance using airborne measurement data over the Alberta oil sands operations, *Atmos. Meas. Tech.*, 8, 3745–3765, doi:10.5194/amt-8-3745-2015, 2015.
- Gualtieri, C., Angeloudis, A., Bombardelli, F., Jha, S., and Stoesser, T.: On the Values for the Turbulent Schmidt Number in Environmental Flows, *Fluids*, 2, 17, doi:10.3390/fluids2020017, 2017.
- 470 Hallberg, B., Rudling, J., Hultman, A., and Hultengren, M.: A filter method for the active and passive monitoring of sulfur dioxide in workplace air. *Scand. J. Work Environ. Health*, 10(5), 305-309, doi:10.5271/sjweh.2324, 1984.
- Hayden, K., Li, S.-M., Makar, P., Liggio, J., Moussa, S. G., Akingunola, A., McLaren, R., Staebler, R. M., Darlington, A., O'Brien, J., Zhang, J., Wolde, M., and Zhang, L.: New methodology shows short atmospheric lifetimes of oxidized sulfur and nitrogen due to dry deposition, *Atmos. Chem. Phys.*, 21, 8377–8392, doi:10.5194/acp-21-8377-2021, 2021.
- 475 Hofschreuder, P., van der Meulen, W., Heeres, P., Slanina, S.: The influence of geometry and draught shields on the performance of passive samplers, *J. Environ. Monit.*, 1, 143–147, doi:10.1039/A809269I, 1999.
- Hsu, Y.-M., Bytnerowicz, A., Fenn, M.E., and Percy, K.E.: Atmospheric dry deposition of sulfur and nitrogen in the Athabasca Oil Sands Region, Alberta, Canada, *Sci. Total Environ.*, 568, 285-295, doi:10.1016/j.scitotenv.2016.05.205, 2016.
- 480 Islam, S. M. N., Jackson, P. L. and Aherne, J.: Ambient nitrogen dioxide and sulfur dioxide concentrations over a region of natural gas production, Northeastern British Columbia, Canada. *Atmos. Environ.*, 143, 139-151, 2016.
- Jiang, T., Gordon, M., Makar, P.A., Staebler, R., and Wheeler, M.: Aerosol deposition to the boreal forest in the vicinity of oil sands, *Atmos. Chem. Phys. Discuss.* [preprint], <https://doi.org/10.5194/acp-2022-656>, in review, 2022.
- Makar, P., Staebler, R., Akingunola, A. Zhang, J., McLinden, C., Kharol, S.K., Pabla, B., Cheung, P., and Zheng, Q.: The effects of forest canopy shading and turbulence on boundary layer ozone. *Nat. Commun.*, 8, 15243. doi:10.1038/ncomms15243, 2017.
- 485 Makar, P. A., Akingunola, A., Aherne, J., Cole, A. S., Aklilu, Y.-A., Zhang, J., Wong, I., Hayden, K., Li, S.-M., Kirk, J., Scott, K., Moran, M. D., Robichaud, A., Cathcart, H., Baratzedah, P., Pabla, B., Cheung, P., Zheng, Q., and Jeffries, D. S.: Estimates of exceedances of critical loads for acidifying deposition in Alberta and Saskatchewan, *Atmos. Chem. Phys.*, 18, 9897–9927, doi:10.5194/acp-18-9897-2018, 2018.
- 490 Masey, N., Gillespie, J., Heal, M. R., Hamilton, S., and Beverland, I. J.: Influence of wind-speed on short-duration NO₂ measurements using Palmes and Ogawa passive diffusion samplers. *Atmos. Environ.*, 160, 70-76, doi:10.1016/j.atmosenv.2017.04.008, 2017.

- 495 Plaisance, H.: The effect of the wind velocity on the uptake rates of various diffusive samplers. *Intern. J. Environ. Anal. Chem.*, 91(14), 1341–1352, doi:10.1080/03067311003782625, 2011.
- Quant, M.I., Feigis, M., Mistry, S., Lei, Y.D., Mitchell, C.P.J., Staebler, R., Di Guardo, A., Terzaghi, E., and Wania, F.: Using passive air samplers to quantify vertical gaseous elemental mercury concentration gradients within a forest and above soil. *Journal of Geophysical Research: Atmospheres*, 126, e2021JD034981, doi:10.1029/2021JD034981, 2021.
- 500 Salem, A., Soliman, A., and El-Haty, I.: Determination of nitrogen dioxide, sulfur dioxide, ozone, and ammonia in ambient air using the passive sampling method associated with ion chromatographic and potentiometric analyses. *Air Qual. Atmos. Health*, 2(3), 133-145. doi:10.1007/s11869-009-0040-4, 2009.
- Whitfield, C. J., Aherne, J., Watmough, S.A., and McDonald, M.: Estimating the sensitivity of forest soils to acid deposition in the Athabasca Oil Sands Region, Alberta. *Journal of Limnology*, 69 (s1):201-8. doi:10.4081/jlimnol.2010.s1.201, 2010.
- 505 Wright, L. P., Zhang, L., Cheng, I., and Aherne, J.: Impacts and effects indicators of atmospheric deposition of major pollutants to various ecosystems – a review, *Aerosol Air Qual. Res.*, 18, 1953–1992, doi:10.4209/aaqr.2018.03.0107, 2018
- Yoon, S., Katsakis, A., Alvarez, S.L., Spychala, M.G., Klovenski, E., Walter, P., Morris, G., Corrales, E., Alan, Al., Diaz, J.A., and Flynn, J.H.: Development and testing of a novel sulfur dioxide sonde, *Atmos. Meas. Tech.*, 15, 4364-4384, doi:10.5194/amt-15-4373-2022, 2022.
- 510 You, Y., Staebler, R. M., Moussa, S. G., Beck, J., and Mittermeier, R. L.: Methane emissions from an oil sands tailings pond: a quantitative comparison of fluxes derived by different methods, *Atmos. Meas. Tech.*, 14, 1879–1892, doi:10.5194/amt-14-1879-2021, 2021.
- Wu, Z., Staebler, R., Vet, R., and Zhang, L.: Dry deposition of O₃ and SO₂ estimated from gradient measurements above a temperate mixed forest. *Environ. Poll.*, 210: 202-210, doi:10.1016/j.envpol.2015.11.052, 2016.
- 515 Zbieranowski A. and Aherne J.: Ambient concentrations of atmospheric ammonia, nitrogen dioxide and nitric acid across a rural-urban-agriculture transect in southern Ontario, Canada. *Atmos. Environ.*, 62: 481–491, doi:10.1016/j.atmosenv.2012.08.040, 2012.
- Zhang, X., Gordon, M., Makar, P.A., Jiang, T, Davies, J., Tarasick, D.: Ozone in the boreal forest in the Alberta oil sands region, *Atmos. Chem. Phys. Discuss.* [preprint], doi:10.5194/acp-2023-26, in review, 2023

520

525 **Table 1: Details of the passive sampler installations and the resulting deposition velocity estimates. The available turbulence data indicates the completeness of the u_* and heat flux data in that period. Deposition velocities calculated from the GEM-MACH parameterization ($v_{d,GEM}$) over the same periods are also shown (determined at a height of 23 m). The average value (and standard deviation) of v_d from all the profiles is shown in the bottom row. Deposition velocities adjusted to a height of 40 m are shown for comparison with Hayden et al. (2021).**

Profile ID	Instal. Date	Duration (days)	Location	Turb. data	Profile R^2	[SO ₂] (ppb)	$v_{d,23m}$ (cm s ⁻¹)	$v_{d,GEM}$ (cm s ⁻¹)	$v_{d,40m}$ (cm s ⁻¹)
1	2020-10-07	13.9	YAJP	28.5%	0.73	0.37	8.0	0.14	6.9
2	2021-03-09	14.9	YAJP	89.2%	0.99	2.24	6.0	0.21	5.3
3a	2021-07-20	14.0	YAJP	100%	0.85	1.55	7.5	0.50	6.3
3b	2021-07-20	14.0	1004	100%	0.91	1.68	6.1	0.50	5.4
4	2021-08-03	20.9	1004	91.4%	0.78	1.19	7.6	0.53	6.5
5	2021-08-24	21.1	1004	98.3%	0.72	1.89	2.9	0.55	2.7
6	2021-09-14	14.9	1004	93.8%	0.85	0.57	7.6	0.47	6.3
7	2021-10-01	13.0	1004	100%	0.62	1.88	7.4	0.48	6.2
8	2021-10-14	12.2	1004	4%	0.87	1.48	9.4	0.45	7.7
Avg							6.9	0.42	5.9
(Std)							(1.7)	(0.14)	(1.3)

530 **Table 2: A comparison of deposition velocities measured in the AOSR with different measurement methods or parameterizations. The height refers to either measurement height (23 or 32 m) or an adjusted height of 40 m (which modifies the aerodynamic resistance term, r_a). Passive Gradient and Continuous Gradient refer to the flux/gradient method using either long-term passive samplers or continuous measurements, respectively. The Passive Gradient (corrected) method includes a correction based on a demonstrated overestimation due to the assumption of independent variables. The Continuous Gradient does not require this correction. The Aircraft method used mass-balance of SO₂ plumes at multiple locations downwind of the emissions source.**

Method	Variable	Height	Range (cm s ⁻¹)	Source
Passive Gradient	$v_{d,23m}$	23 m	2.9 - 9.4	This study
Model Parameterization	$v_{d,23m}$	23 m	0.1 - 0.6	GEM-MACH, from Makar et al., 2018
Model Parameterization	v_d	†	0.2 - 0.3	NOAA-MLM, from Hsu et al., 2016
Passive Gradient	$v_{d,40m}$	40 m	2.7 - 7.7	This study
Passive Gradient (corrected)	$v_{d,40m}^*$	40 m	2.1 - 5.9	This study
Continuous Gradient	$v_{d,40m}$	40 m	3.3	This study
Continuous Gradient	$v_{d,32m}$	32 m	4.1	Hayden et al., 2021
Aircraft	$v_{d,40m}$	40 m	1.2 - 3.4	Hayden et al., 2021

535 † Given only as a “shallow sub-layer within the atmospheric constant flux layer”






Figure 1: (a) The study area and surrounding location showing the location of the towers (red dot) relative to oil sands mining and production facilities. (b) A photo of YAJP tower, and (c) a photo of WBEA 1004 tower. Map image is © Google Maps. Photos taken by authors.

540



545

Figure 2: Schematic of passive sampler mounts (not to scale). Grey lines indicate pulley rope (YAJP) or pulley cable loop (1004). Orange dashed lines show where the system is fixed against the rope or cable. The YAJP system used guy ropes and the 1004 system used a tong or forked support against the looped pulley cable to inhibit rotation. Multiple passive samplers were fixed to the underside of the rain shelter lids.



550 **Figure 3:** A comparison of momentum diffusion coefficients (K_M) determined through flux/gradient method ($K_{M,G}$), compared to the parameterization of Eq. 5 and 6 ($K_{M,P}$). The parameterized values are binned by flux/gradient values. Black circles show medians, grey shading shows 25th and 75th percentiles, red pluses show averages, and the red straight line shows a least-squares fit to all 30-min data.







Figure 4: SO₂ measurements from gas analyzers at YAJP tower. 43i measurements are every 5-sec, AF22e are every minute.



560 **Figure 5: SO₂ measurements as a function of wind direction. Green dots are AF22e measurements. All others are 43i measurements. All measurements here are 30-min averages.**



565 **Figure 6:** SO₂ measurements on a tethered balloon flight (SO₂ sonde, red line) and ground level measurements (43i, green line). Balloon altitude (black line) also shown. Ground level is ~340 m ASL.



570

Figure 7: Measurements of SO₂ mixing ratio with height. Profile numbers correspond to those listed in Table 1. Open symbols are profiles measured at YAJP. Closed symbols are profiles measured at site 1004. Circle (○) plot markers (blue with dashed line) show average measurements of two 43i instruments over a period coincident with Profile 4. Plus (+) plot markers show average measurement of AF22e instrument over two periods coincident with Profiles 3a and 3b (black) and Profile 4 (blue). The approximate canopy height is shown as a dashed horizontal line.

575

Table A1: WBEA sampling site information, listing station names, locations, and links to website description (last accessed Sept, 2022).

WBEA ID	Name	Lat. (N)	Lon. (W)	Website
AMS01	Fort McKay Bertha Ganter	57.1894	111.6406	https://wbea.org/stations/bertha-ganter-fort-mckay/
AMS06	Patricia McInnes	56.7514	111.4767	https://wbea.org/stations/patricia-mcinnnes/
AMS07	Athabasca Valley	56.7334	111.3905	https://wbea.org/stations/athabasca-valley/
AMS17	Wapasu	57.2592	111.0386	https://wbea.org/stations/wapasu/
AMS18	Stoney Mountain	55.6214	111.1727	https://wbea.org/stations/stony-mountain/

580




Figure A1: Meteorological data during the 8 sampling periods. Daily precipitation is from Mildred Lake (ECCC), which is 12 km SW of the towers. Wind speed at 29-m (U), photosynthetically active radiation (PAR), relative humidity (RH), and temperature are from the 1004 tower.

585