# 1 Measuring and modeling investigation of the Net

## 2 Photochemical Ozone Production Rate via an improved

## dual-channel reaction chamber technique

- 4 Yixin Hao<sup>1,2#</sup>, Jun Zhou<sup>1,2#\*</sup>, Jie-Ping Zhou<sup>1,2</sup>, Yan Wang<sup>1,2</sup>, Suxia Yang<sup>1,2</sup>, Yibo
- 5 Huangfu<sup>1,2</sup>, Xiao-Bing Li<sup>1,2</sup>, Chunsheng Zhang<sup>3</sup>, Aiming Liu<sup>3</sup>, Yanfeng Wu<sup>1,2</sup>, Yaqing
- 6 Zhou, Shuchun Yang<sup>1,2</sup>, Yuwen Peng<sup>1,2</sup>, Jipeng Qi<sup>1,2</sup>, Xianjun He<sup>1,2</sup>, Xin Song<sup>1,2</sup>, Yubin
- 7 Chen<sup>1,2</sup>, Bin Yuan<sup>1,2\*</sup>, Min Shao<sup>1,2</sup>
- 8 <sup>1</sup>Institute for Environmental and Climate Research, Jinan University, Guangzhou 511443, China
- <sup>9</sup> Guangdong-Hongkong-Macau Joint Laboratory of Collaborative Innovation for Environmental
- 10 Quality, Guangzhou 511443, China
- <sup>3</sup>Shenzhen National Climate Observatory, Shenzhen 518040, China
- 12

3

- 13 \*Jun Zhou and Yixin Hao contribute equally to this work.
- \*Correspondence to: Jun Zhou (Junzhou@jnu.edu.cn) and Bin Yuan (byuan@jnu.edu.cn)
- 15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

Abstract. Current process-based research mainly uses box models to evaluate the photochemical ozone production and destruction rates, and it is unclear to what extent the photochemical reaction mechanisms are elucidated. Here, we modified and improved a net photochemical ozone production rate (NPOPR, P(O<sub>3</sub>)<sub>net</sub>) detection system based on the current dual-channel reaction chamber technique, which makes the instrument applicable to different ambient environments, and its various operating indicators were characterized, i.e., airtightness, light transmittance, wall losses of the reaction and reference chambers, conversion rate of O<sub>3</sub> to NO<sub>2</sub>, air residence time, and performance of the reaction and reference chambers. The limits of detection of the NPOPR detection system were determined to be 0.07, 1.4, and 2.3 ppbv h <sup>1</sup> at sampling flow rates of 1.3, 3, and 5 L min<sup>-1</sup>, respectively. We further applied the NPOPR detection system to field observations at an urban site in the Pearl River Delta (China). During the observation period, the maximum value of  $P(O_3)_{net}$  was 34.1 ppbv h<sup>-1</sup>, which was  $\sim 0$  ppbv h<sup>-1</sup> at night within the system detection error and peaked at approximately noon local time. The daytime (from 6:00-18:00) average value of P(O<sub>3</sub>)<sub>net</sub> was 12.8 (±5.5) ppbv h<sup>-1</sup>. We investigated the detailed photochemical O<sub>3</sub> formation mechanism in the reaction and reference chambers of the NPOPR detection system using a zero-dimensional box model. We found that the photochemical reactions in the reaction chamber were very close to those in ambient air, but it was not zero chemistry in the reference chamber, the reaction related to the production and destruction of RO<sub>2</sub> (=HO<sub>2</sub>+RO<sub>2</sub>) continued in the reference chamber, which led to a small amount of  $P(O_3)_{net}$ . Therefore, the  $P(O_3)_{net}$  measured here can be regarded as the lower limit of the real  $P(O_3)_{net}$  in the atmosphere; however, the measured  $P(O_3)_{net}$  was still ~ 7.5 to 9.3 ppbv h<sup>-1</sup> higher than the modeled  $P(O_3)_{net}$  value depending on different modeling methods, which may be due to the inaccurate estimation of  $HO_2/RO_2$  radicals in the modeling study. Short-lived intermediate measurements coupled with direct  $P(O_3)_{net}$  measurements are needed in the future to better understand  $O_3$  photochemistry. Our results show that the NPOPR detection system can achieve high temporal resolution and continuous field observations, which helps us to better understand photochemical  $O_3$  formation and provides a key scientific basis for continuous improvement of air quality in China.

#### 1 Introduction

Surface O<sub>3</sub> pollution has become a major challenge in air quality management in China (Shen et al., 2021). Elevated surface O<sub>3</sub> mixing ratios exert severe adverse effects on public health, such as respiratory diseases, and the estimated annual mortality attributable to surface O<sub>3</sub> exposure exceeds 150,000 deaths in China (Malley et al., 2017). O<sub>3</sub> pollution is also detrimental to key staple crop yields, reducing the yields of wheat, soybean, and maize by up to 15 %, and is threatening global food security (Avnery et al., 2011; Mills et al., 2018; Karakatsani et al., 2010; Berman et al., 2012; O'Neill et al., 2003). As a greenhouse gas, O<sub>3</sub> also contributes significantly to climate change (Bell et al., 2004). With the rapid economic development and urbanization in the Pearl River Delta (PRD) region in China, O<sub>3</sub> pollution is pretty severe, especially in summer and autumn (Zou et al., 2015; Zhang et al., 2021).

The variation in  $O_3$  in the planetary boundary layer is predominantly influenced by deposition, advection transport, vertical mixing (i.e., entrainment from the stratosphere), meteorological factors, and chemical reactions. Therefore, the  $O_3$  budget in the boundary layer can be expressed as Eq. (1):

56 
$$\frac{\partial[O_3]}{\partial t} = P(O_3) - D(O_3) - \frac{v}{H}[O_3] + u_i \frac{\partial[O_3]}{\partial x_i} + STE$$
57 
$$P(O_3)_{\text{net}} \quad SD \quad A$$

where SD, A, and STE represent the surface deposition, advection, and stratosphere-troposphere exchange (STE), respectively;  $[O_3]$ ,  $P(O_3)$  and  $D(O_3)$  are the ambient  $O_3$  mixing ratios, photochemical  $O_3$  production and its loss rate, respectively; v, H, and  $u_i$  represent the  $O_3$  deposition velocity, mixing layer height, and velocity in three directions, respectively; and A consists of  $u_i$  times the  $O_3$  gradient in those three directions.

Tropospheric  $O_3$  is a key component of photochemical smog, mainly formed by photochemical reactions of nitrogen oxides (NO<sub>x</sub>=NO+NO<sub>2</sub>) and volatile organic compounds (VOCs) (Lee et al., 2010). The specific process of the photochemical reaction is the photolysis of NO<sub>2</sub> at < 420 nm to generate  $O(^3P)$  atoms, thereby promoting the formation of  $O_3$  (Sadanaga et al., 2017). Simultaneously, there is a  $RO_X$  (RO<sub>X</sub> =OH + HO<sub>2</sub> +RO<sub>2</sub>) radical cycle in the troposphere, which continuously provides HO<sub>2</sub> and RO<sub>2</sub> to oxidize NO to NO<sub>2</sub> resulting in the accumulation of O<sub>3</sub> (Shen et al., 2021; Sadanaga et al., 2017; Cazorla et al., 2010).

Typical meteorological scenarios for the occurrence of O<sub>3</sub> pollution episodes in polluted urban

centers are usually characterized by weak winds, strong solar radiation, and high temperature (T). Under such conditions, local formation of O<sub>3</sub> plays a crucial role in the rapid increase of surface O<sub>3</sub> in daytime. In addition, in Eq. (1), the surface deposition and advection of O<sub>3</sub> are proportional to ambient O<sub>3</sub> mixing ratios, [O<sub>3</sub>], which is mainly generated by local photochemistry (Carzorla et al., 2010). If  $P(O_3)_{net}$  can be reduced by regulatory measures, overall O<sub>3</sub> levels will decline proportionately over time (Cazorla et al., 2010), thus, the investigation of  $P(O_3)_{net}$  formation mechanism is urgently needed.

Current studies on  $P(O_3)_{net}$  estimation mainly rely on modeling methods, the gas-phase chemical mechanisms were frequently used to identify key drivers of  $O_3$  pollution events and provide guidance for making effective  $O_3$  reduction strategies, such as the Master Chemical Mechanism (MCM), the regional atmospheric chemistry mechanism (RACM), the Carbon Bond mechanisms (CBM) and the Mainz Organic Mechanism (MOM) (Shen et al., 2021; Kanaya et al., 2016; Wang et al., 2014; Tadic et al., 2020; Ren et al., 2013; Lu et al., 2010; Zhou et al., 2014; Mazzuca et al., 2016). However, uncertainties in emission inventories, chemical mechanisms, and meteorology make it difficult to perfectly reproduce real atmospheric processes, which can lead some bias in modeling the  $P(O_3)_{net}$ . According to the existing field observations, researchers found that the mixing ratios of  $HO_2$  or  $RO_2$  obtained from the model simulation was inconsistent with that obtained from the direct measurement, leading to the deviation of  $P(O_3)_{net}$  between observation and model simulation results (Wang et al., 2014; Tadic et al., 2020; Ren et al., 2013; Martinez et al., 2003). Therefore, we urgently need a method that can directly measure the  $P(O_3)_{net}$ .

Recently, researchers have developed sensors that can directly measure  $P(O_3)_{net}$  in the atmosphere using the dual-channel chamber technique (Sadanaga et al., 2017; Cazorla et al., 2010; Baier et al., 2015 and 2017; Sklaveniti et al., 2018), where ambient air is introduced into two chambers of identical size, one UV transparent chamber (reaction chamber) and one UV protection chamber (reference chamber). In the presence of solar UV light,  $O_3$  is produced by photochemical reactions in the reaction chamber, but not in the reference chamber. The system does not directly measure  $O_3$  mixing ratios, it measures the combined mixing ratios of  $O_3$  and nitrogen dioxide (NO<sub>2</sub>).  $P(O_3)_{net}$  is determined by the difference of  $O_X(O_X=O_3+NO_2)$  mixing ratios between the reaction and reference chambers. These studies have greatly helped us to understand the  $O_3$  photochemical formation mechanism, but defects still exists in current studies, for example, the sensors developed by Cazorla et al. (2010) and Baier et al. (2015) both have an

NO<sub>2</sub>-to-O<sub>3</sub> converter unit, and uses a modified O<sub>3</sub> monitor (Thermo Scientific, Model 49i, USA) to measure Ox, but the zero point of the O<sub>3</sub> monitor is easy to drift, together with the limitation of the conversion efficiency of NO<sub>2</sub> to O<sub>3</sub> ( $\sim$  99.9 %) and the effects of the *T* and relative humidity (RH) to O<sub>3</sub> monitor, this method can introduce large measurement uncertainties. Sklaveniti et al. (2018) have shorten the average residence time in the chambers to 4.5 min, which reduced the scattering and increased the time resolution of  $\Delta$ Ox measurement, but large wall loss still exists in their system, which are 5 % and 3 % for O<sub>3</sub> and NO<sub>2</sub>, respectively. Sadanaga et al. (2017) passed the NO standard gas into the PFA tube to convert O<sub>3</sub> into NO<sub>2</sub> to detect Ox, which is easy to operate, but the LIF-NO<sub>2</sub> detector is less portable and maintainable. Furthermore, all the current sensors have different degrees of wall loss of NO<sub>2</sub> and O<sub>3</sub> that can even reach 15 %, which largely affect the accuracy of the evaluation of P(O<sub>3</sub>)<sub>net</sub>.

In this study, we modified and improved a  $P(O_3)_{net}$  sensor based on the dual-channel technique as described above and named it the net photochemical ozone production rate (NPOPR) detection system. Section 2 provides the improvement and characterization of the NPOPR detection system. Furthermore, we applied the NPOPR detection system to an observation campaign conducted at Shenzhen Meteorological Gradient Tower (SZMGT) in the Pearl River Delta (PRD) region in China. A zero-dimensional box model based on the Framework for 0-D Atmospheric Modeling (F0AM) v3.2 coupled with MCM v3.3.1 was used to simulate the photochemical reactions inside both the reaction and reference chambers in the NPOPR system, which allowed us to assess the ability of the current modeling method to model  $P(O_3)_{net}$ , as described in Sect. 3. The current research could help us study the source and formation mechanism of  $O_3$  and provide effective theoretical support for the prevention and control of  $O_3$  pollution. Because the system can directly obtain real-time  $P(O_3)_{net}$  under different environmental conditions, it can meet richer and more specific research needs.

### 2 Method and materials

## 2.1 Development of the NPOPR detection system

A schematic and actual diagram of the NPOPR detection system are shown in Fig. 1. The integral construction is similar to the P-L(Ox) measurement system built by Sadanaga et al. (2017) and Sklaveniti et al. (2018), which mainly consists of reaction and reference chambers with the same geometry and made of quartz (190.5 mm inner diameter and 700 mm length; more details can be found in Fig. S1). To

prevent photochemical reactions inside the reference chamber, an ultraviolet (UV) protection Ultem film (SH2CLAR, 3 M, Japan) was used to cover the outer surface to block sunlight with wavelengths < 390 nm. During the experiment, both the reaction and reference chambers were located outdoors and exposed to sunlight directly to simulate genuine ambient photochemistry reactions. Ambient air was introduced into the reaction and reference chambers at the same flow rate, and a Teflon filter was mounted before the chamber inlet to remove fine particles. A stream of air from the two chambers was alternately introduced into an NO-reaction chamber every 2 min to convert O<sub>3</sub> in the air to NO<sub>2</sub> in the presence of high mixing ratios of NO (O<sub>3</sub>+NO=NO<sub>2</sub>), and the Ox mixing ratios from the outlet NO-reaction chamber, i.e., the total NO<sub>2</sub> mixing ratios including the inherent NO<sub>2</sub> in the ambient and that converted from O<sub>3</sub>. were measured by a Cavity Attenuated Phase Shift (CAPS) NO<sub>2</sub> Monitor (Aerodyne research, Inc., Billerica MA, USA) to avoid other nitrogen oxide interferences to the NO<sub>2</sub> measurement (such as alkyl nitrates, peroxyacyl nitrates, peroxynitric acid, nitrogen pentoxide, etc.). Compared to previous studies that used a dual-channel UV-absorption O<sub>3</sub> monitor (Cazorla et al., 2010) or a laser-induced fluorescence (LIF) LIF-NO<sub>2</sub> monitor (Sadanaga et al., 2017) for Ox measurements, our choice could make the NPOPR detection system have a more stable zero-baseline and be more portable by assembling each part together, i.e., put the CAPS NO<sub>2</sub> monitor, the automatic sampling system, and the automatic data sampling system onto the indoor cabinets with the push-pull base, and put the dual chambers onto the outdoor shelf with the push-pull base. Additionally, we modified the air sampling system to adjust the total air flow rates freely from 1.3 to 5 L min<sup>-1</sup> in the reaction and reference chambers, which enabled us to achieve different air residence times from 3.8 to 21 min. This time range covered all the residence times from previous studies using different Ox measurement techniques, which ranged from 4.5 to 20.5 min (Cazorla et al., 2010; Baier et al., 2015; Sadanaga et al., 2017; Sklaveniti et al., 2018). According to the simulation results described in Sect. 3, the reaction rates of O<sub>3</sub> formation and destruction pathways and the radicals that play critical roles in photochemical O<sub>3</sub> formation, such as HO<sub>2</sub>, RO<sub>2</sub> and OH, reached quasi-steady states in approximately 3 min, so it was reasonable for us to set the air flow rate highest at 5 L min<sup>-1</sup>, where the sampled air has already reacted for 3.8 min in the reaction and reference chambers. On the other hand, this also demonstrated that it was reasonable to set the alternate sampling time for the reaction and reference chambers at 2 min, where the sampled air actually has already reacted for at least 3.8 min in the reaction and reference chambers. The switch system was controlled by two Teflon three-way

128

129

130

131

132

133

134

135

136

137

138

139

140

141

142

143

144

145

146

147

148

149

150

151

152

153

154

155

solenoid valves (001-0028-900, Parker, GER) located before the NO-reaction chamber (see Fig. 1). We used homemade circuit control software (Four-Channel-Valves boxed) and a solenoid valve (001-0028-900, Parker, GER) to automatically switch the sampling lines every 2 min. To keep the flow rates in the reaction and reference chambers the same and avoid gas flow accumulation in the chamber, a pump (pump 3) was connected to the Teflon three-way solenoid valves in parallel to the NO-reaction chamber to evacuate the air that was not introduced into the NO-reaction chamber. To reduce NO interference, the system used  $O_X$  to infer the amount of  $O_3$  generated by photochemical reactions (Liu et al., 1977; Pan et al., 2015; Lu et al., 2010). The difference between the Ox mixing ratios in the reaction and reference chambers, denoted by  $\Delta O_X$ , represents the amount of  $O_3$  generated by the photochemical reaction.  $P(O_3)_{net}$  was obtained by dividing  $\Delta O_X$  by the average residence time of air in the reaction chamber  $\langle \tau \rangle$ :

$$P(O_3)_{\text{net}} = P(O_X) = \frac{\Delta O_X}{\tau} = \frac{[O_X]_{\text{reaction}} - [O_X]_{\text{reference}}}{\tau}$$
(2)

Igor Pro version 6 was used to calculate  $P(O_3)_{net}$  as follows: ① separate the data of the reaction and the reference chambers into two sets using the recorded valve number of 1 (reaction chamber) and 0 (reference chamber) during the sampling time; ② for each 2 min period of data, delete the first 20 s and the last 20 s when the signal was not stable, then average the rest data, and do the interpolate calculation of the reference chamber dataset; ③ calculate the difference between the Ox mixing ratios in the reaction and reference chambers (i.e.,  $\Delta O_X$ ) at the time when the reaction chamber measured Ox; ④ divide  $\Delta O_X$  by the average residence time of air in the reaction chamber  $\langle \tau \rangle$  and obtain  $P(O_3)_{net}$  at a time resolution of 4 min.






Figure 1: (a) Schematic and (b) actual diagram of the NPOPR detection system.

The major improvements of the NPOPR detection system described here compared to previous studies to optimize  $P(O_3)_{\text{net}}$  measurements are as follows: (1) we improved the design of the reaction and reference chambers to ensure that they have good airtightness, which will increase the measurement accuracy of different species inside the chambers. More details can be found in Sect. 2.2 and Appendix I; (2) two pumps (labeled pump 1 and pump 2 in Fig. 1) were added directly after the reaction and reference chambers to continuously draw ambient air through the two chambers (as the makeup flow) to adjust the total air flow rates freely from 1.3 to 5 L min<sup>-1</sup> in the chambers. By doing this, we were able to achieve different limits of detection (LODs) of the NPOPR system (see Sect. 2.4), making the instrument applicable to different ambient environments, i.e., in highly polluted areas, we could use higher air flow rates to reduce the wall loss effects of the chambers, and in less polluted areas, we could use lower flow rates to increase the instrument LOD. (3) We characterized the NPOPR detection system

at different air flow rates (including 1.3, 2, 3, 4, and 5 L min<sup>-1</sup>) and tested the conversion efficiency of  $O_3$  by NO to NO<sub>2</sub> in the NO-reaction chamber at different NO mixing ratios and NO-reaction chamber lengths. These efforts enabled us to better understand the running parameters of the NPOPR system and perform data corrections under different air flow rates (see Sect. 2.2); (4) we tested the performance of both the reaction and reference chambers by combining the field measurements and MCM modeling, which indicated that reaction pathways of  $P(O_3)$  and  $D(O_3)$  and the radicals that play critical roles in photochemical  $O_3$  formation, such as  $HO_2$ ,  $RO_2$  and OH, reached quasi-steady states in approximately 3 min, thus ensuring that the lowest air residence time of 3.8 min (at an air flow rate of 5 L min<sup>-1</sup>) in the reaction and reference chambers was long enough to obtain accurate  $P(O_3)_{net}$  values (see Sect. 3.2). These efforts made the NPOPR system less prone to biases than other systems and increased its applicability.

#### 2.2 Characterization of the NPOPR detection system

We characterized the NPOPR detection system following the same procedures as previous researchers, including the residence time of the air, the wall losses of NO<sub>2</sub> and O<sub>3</sub>, the transmittance of light and temperature differences in the reaction and reference chambers, and the quantitative conversion efficiency of O<sub>3</sub> to NO<sub>2</sub> (α) in the NO-reaction chamber. Additionally, we investigated the residence time of the air and the wall losses of NO<sub>2</sub> and O<sub>3</sub> in the reaction and reference chambers at different flow rates (including 1.3, 2, 3, 4, and 5 L min<sup>-1</sup>) and the conversion efficiency of O<sub>3</sub> by NO to NO<sub>2</sub> in the NO-reaction chamber at different NO mixing ratios and NO-reaction chamber lengths. The detailed experimental performances and data analysis are shown in Appendix I, and the corresponding results are described as follows.

The residence time. We tested the residence time of air in both chambers under different air flow rates, including 1.3, 2, 3, 4, and 5 L min<sup>-1</sup>, the obtained related residence time in the reaction chamber were 0.35, 0.16, 0.11, 0.07, and 0.06 h, respectively. By setting different air flow rates, we were able to obtain different residence time thus different limit of detection of NPOPR system, which make it applicable to different ambient environment. To make sure that the mean residence time of air is the same in the reaction and reference chambers, we also tested the residence time of air in the reference chamber in parallel, which were not much difference with that in the reaction chamber, as shown in Table S1. The experimental schematic diagram is shown in Fig. S2, the related results of different air flow rates are

shown in Fig. S3 and Table S1.

217

218

219

220

221

222

223

224

225

226

227

228

229

230

231

232

233

234

235

236

237

238

239

240

241

242

243

244

245

and J(HCHO R) are shown in Table S7.

Wall losses of NO2 and O3. At air flow rates of 1.3, 2, 3, 4, and 5 L min<sup>-1</sup>, the wall losses of O3 in the reaction chamber were found to be approximately 2 %, 0 %, 0 %, 0 %, and 0 %, respectively, and the wall losses of O<sub>3</sub> in the reference chamber were found to be approximately 2 %, 1 %, 1 %, 0 %, and 0.7 %, respectively. While the wall losses of NO<sub>2</sub> in the reaction chamber at air flow rates of 1.3, 2, 3, 4, and 5 L min<sup>-1</sup> were found to be approximately 4 %, 4 %, 2 %, 0 %, and 0.3 %, respectively, the wall losses of NO<sub>2</sub> in the reference chamber were found to be approximately 2 %, 1 %, 0 %, 0 %, and 0. 6 %, respectively. The experimental schematic diagram is shown in Fig. S4, and the related results of different air flow rates are shown in Figs. S5-S6 and Tables S2-S5. We further compared the wall losses of O3 and NO<sub>2</sub> in the reaction and reference chambers at 5 L min<sup>-1</sup> with previous studies (as shown in Table S6) and found that they were significantly smaller, but even with a flow rate of 1.3 L min<sup>-1</sup>, the wall losses were still smaller than 4 % and 2 % in the reaction chamber and the reference chambers, respectively. We also tested the wall losses of  $NO_2$  and  $O_3$  in the chamber at a 5 L min<sup>-1</sup> flow rate at different humidities of 35-75 %, the detailed results are shown in Fig. S7 and S8, which shows that the variation in humidity effected the wall loss of NO<sub>2</sub> and O<sub>3</sub> by 0.03-0.12 % and 1.06-1.19 %, respectively, which is much smaller than the instrument detection error (which is 2 % at ambient NO<sub>2</sub> mixing ratios of 0-100 ppb), which indicates the small effects of Ox loss on  $P(O_3)_{net}$  measurements in our NPOPR detection system. The light transmittance and temperature differences in the reaction and reference chambers. It is worth noting that there was still low transmittance of light ranging from 390 nm to 790 nm through the UV protection film, and the reference chamber could not be regarded as completely dark; thus, we tested the solar UV transmittance through the reaction and reference chambers of the NPOPR detection system in the laboratory using a sunlight simulation lamp (SERIC XG-500B, Japan) to provide different intensities of illumination. The photolysis frequencies of NO<sub>2</sub>, O<sub>3</sub>, HONO, H<sub>2</sub>O<sub>2</sub>, NO<sub>3</sub> M (photolysis of NO<sub>3</sub> generates NO+O<sub>2</sub>), NO<sub>3</sub> R (photolysis of NO<sub>3</sub> generates NO<sub>2</sub>+O), HCHO M (photolysis of HCHO generates H2+CO), and HCHO\_R (photolysis of HCHO generates H+HCO) inside and outside the reaction and reference chambers were measured using an actinic flux spectrometer (PFS-100; Focused Photonics Inc., China). Table 1 presents the J(NO<sub>2</sub>), J(O<sup>1</sup>D), and J(HONO) results for the outside and inside chambers from this study and from the literature.  $J(H_2O_2)$ ,  $J(NO_3\_M)$ ,  $J(NO_3\_R)$ ,  $J(HCHO\_M)$ ,

The photolysis frequencies of all species inside the reaction chamber were in agreement with those measured outside the reaction chamber within 4 %. Table S7 shows that the transmittivities of J(H<sub>2</sub>O<sub>2</sub>), J(NO<sub>3</sub> M), J(NO<sub>3</sub> R), J(HCHO M), and J(HCHO R) in the reaction chamber were more than 90 %. However, we have observed that the transmittivities of  $J(O^1D)$  were even higher than those of J(HONO)(as shown in Table 1) in the reference chamber (which blocks sunlight at wavelengths < 390 nm), theoretically, this is not possible according to JPL Publication 19-5 (Burkholder et al., 2020), where the absorption cross section of HONO at wavelengths of 390-395 ranged from approximately 4.0-17.1×10<sup>-</sup> <sup>21</sup> cm<sup>2</sup>, which is about two or three orders of magnitude higher than that of ozone (which ranged from approximately 0.8-2.6 ×10<sup>-23</sup> cm<sup>2</sup> at wavelengths of 390-410 nm), and the photolysis quantum yield of HONO at wavelengths of 390-395 is unity, which is about ten times higher than that of ozone ( $\sim 0.08$ ). This will surely make the J values of HONO inside the reference chamber (which only has sunlight with wavelengths > 390 nm) higher than that of ozone, according to the Eq. (S9). We also found that the transmittivity of HONO and O<sub>3</sub> in the reference chamber obtained from the TUV simulation (as described in Sect. 3.2) were 0.01 and 0, respectively, as shown in Table S13. Therefore, we believe the non-zero measurement results of the transmittivity of O<sub>3</sub> shown in Table 1 and Table S7 are mostly probably due to the instrument measurement error, this error is relatively large due to a limit number of measurement points (3 points for each species). We further evaluated the measurement error of J values based on the instrument measurement error of the actinic flux spectrometer, which can reach  $\pm 5$  % according to Bohn et al. (2017), and re-evaluated the transmittivity error listed in Table 1 and Table S7 following the procedures described in supplementary materials (Sect. 1.5). The calculation result from Eq. (S5) show that the transmittivities errors are 0.07 for all species, within this error range, J(O1D), J(HONO), J(H<sub>2</sub>O<sub>2</sub>), J(HCHO M), and J(HCHO R) can be considered statistically indistinguishable from 0 in reference chamber. However, J(NO<sub>2</sub>), J(NO<sub>3</sub>\_M), and J(NO<sub>3</sub>\_R) still distinctly positive values. Specifically, the transmittivities of J(NO<sub>3</sub> M) and J(NO<sub>3</sub> R) of the reference chamber were more than 90 % (Table S7). The influence of the measurement error of J values of all species on  $P(O_3)_{net}$  will be discussed in Sect. 3.

270271

246

247

248

249

250

251

252

253

254

255

256

257

258

259

260

261

262

263

264

265

266

267

268

269

272

273

274

275276

Table 1. Transmittivities of photolysis frequency  $J(s^{-1})$  values of different species in the reaction and reference chambers. The shaded and clear regions correspond to the transmittivities of J values in the reference (Ultem coated) and reaction (clear) chambers, respectively. The "transmittivities" column shows the transmittivities of the tested species from the measurements conducted with the set photolysis frequencies using SERIC XG-500B sunlight (this study) and ambient (literature). It should be noted that the errors listed here are relatively large and may not reliable due to a limit number of measurement points (3 points for each species). The calculated transmittivity errors are 0.07 for all species based on the  $\pm 5$  % measurement error of the instrument.

		Transmi		
_	Averaged (this study)	Cazorla et al., 2010	et al.,	,
$J(NO_2)$	$0.985 \\ \pm 0.037$	0.974	0.990	0.986
	$0.094 \\ \pm 0.014$	0.021	0.01	0.121
$J(O^1D)$	$1.020 \pm 0.04$	0.991	0.978	1.030
	$0.019 \pm 0.011$	0.0058	0.001	~0
J(HONO)	$0.983 \\ \pm 0.037$	0.976	0.982	0.988
	$0.002 \\ \pm 0.0002$	0.0067	~0	0.017

We further detected the temperature in both the reaction and reference chambers when running the NPOPR system in an ambient observation campaign during November 2022 on the Panyu campus of Jinan University in Guangzhou, China (113° 36′ E, 23° 02′ N). We found that the UV protection Ultem film on the reference chamber did not block the heat outside the chamber, and the temperature remained the same in the reaction and reference chambers during the measurement test, as shown in Fig. S10.

The quantitative conversion efficiency of  $O_3$  to  $NO_2$  (a) in the NO-reaction chamber is crucial for accurate measurement of  $P(O_3)_{net}$ . Here, we used a perfluoroalkoxy (PFA) tube (outer diameter of 12.7 mm; inner diameter of 9.5 mm) as the NO-reaction chamber. The experimental schematic diagram is shown in Fig. S12. Known mixing ratios of  $O_3$  and NO standard gas were introduced into the NO-reaction chamber, and NO reacted with  $O_3$  to produce  $NO_2$ . To avoid the influence of small amounts of  $NO_2$  impurity in the NO standard gas used for conversion, we added a cylinder filled with partialized crystals of  $FeSO_4 \cdot 7H_2O$  to reduce  $NO_2$  in the  $NO/N_2$  gas cylinder to NO. We injected ~1800 ppbv NO into the NO-reaction chamber and tested the  $NO_2$  mixing ratios from its outlet using a CAPS  $NO_2$  monitor, as shown in Fig. S13. We found that the standard deviation of the  $NO_2$  mixing ratios was lower than 0.027

ppbv, which is smaller than the baseline drifts of the CAPS (which were 0.043 and 0.030 ppbv (1  $\sigma$ ) at integration times of 35 and 100 s, respectively, as mentioned in Sect. 2.3), so we believe the particulate crystals of FeSO<sub>4</sub>·7H<sub>2</sub>O performed well and the potential bias introduced by the impurity in NO mixing ratio for  $P(O_3)_{net}$  was negligible. Finally, the total NO<sub>2</sub> mixing ratios, including that from the ambient air, were measured using a CAPS NO<sub>2</sub> monitor ([NO<sub>2</sub>]<sub>CAPS</sub>). The O<sub>3</sub> mixing ratios were controlled at approximately 310 ppbv according to the maximum mixing ratio range in the normal ambient atmosphere (to ensure that all ambient and newly generated O<sub>3</sub> can react with NO and produce equivalent amounts of NO<sub>2</sub>). An O<sub>3</sub> generator equipped with a low-pressure mercury lamp was employed to generate O<sub>3</sub>, and the generated O<sub>3</sub> mixing ratios ([O<sub>3</sub>]<sub>g</sub>) were measured by a 2B O<sub>3</sub> monitor as mentioned above. Here, we note that the O<sub>3</sub> mixing ratios were diluted by the added NO/N<sub>2</sub> gas (with a flow rate of 20 mL min<sup>-1</sup>) in the NO-reaction chamber (with a total flow rate of 1.11 L min<sup>-1</sup>), taking 1800 ppbv NO/N<sub>2</sub> gas as an example, the relationship between [NO<sub>2</sub>]<sub>CAPS</sub> and [O<sub>3</sub>]<sub>g</sub> can be described by Eq. (3):

314 
$$[NO_2]_{CAPS} = \frac{1.09}{1.11} [O_3]_g \alpha$$
 (3)

To determine the optimal length of the NO-reaction chamber and NO mixing ratios, we performed a cross test of  $\alpha$  under the following scenarios: the NO-reaction chamber lengths were increased from 30 to 650 cm in 50 cm steps, and the NO standard gas (102.1 ppmv) was diluted to 600, 900, 1200, 1500, 1800, 2100, and 2400 ppbv in the NO reaction chamber. The results are shown in Fig. 2. We found that at  $[O_3]_g$  of approximately 310 ppbv, with NO mixing ratios  $\geq$ 1800 ppbv in the NO reaction chamber,  $\alpha$  reached 99 %, 99.6 %, and 99.9 % with NO-reaction chamber lengths of 50, 70, and 100 cm, respectively, where the corresponding  $O_3$  residence times in the NO reaction chamber were 1.95, 2.74, and 3.91 s, respectively. Considering both the optimal reaction time in the NO reaction chamber and  $\alpha$ , we selected the NO reaction chamber length as 100 cm with an NO mixing ratio of 1800 ppbv for the NPOPR detection system.




Figure 2: The conversion efficiency of O<sub>3</sub> by NO to NO<sub>2</sub> in the NO reaction chamber as a function of the NO chamber length, color coded by the NO mixing ratios.

The airtightness of the reaction and reference chambers We also checked the airtightness of the reaction and reference chambers by passing through gases with different flow rates based on the schematic diagram shown in Fig. S14 and compared the values of [air flow rate × pressure] between the inlet and outlet of the chambers (as indicated in Fig. 3). We found that the deviations in [air flow rate × pressure] at the inlet and outlet of the reaction and reference chambers at different flow rates were <3 % (as shown in Table S8), indicating the good airtightness of the reaction and reference chambers. This ensured that the photochemical reactions in the reaction and reference chambers would not be affected by the ambient air outside the chambers.




Figure 3: The relationship of the values of [air flow rate  $\times$  pressure] between the inlet and outlet of the chambers (psia: Pounds Per Square Inch Absolute).

The flow states in the reaction and reference chambers We calculated the Reynolds number to check the gas flow state in the reaction and reference chambers. The Reynolds number (expressed as Eq. (4)) is a dimensionless number that can be used as the basis for judging the flow characteristics of a fluid:  $Re=\rho vd/\mu$  (4) where v,  $\rho$  and  $\mu$  are the flow velocity, density and viscosity coefficient of the fluid, respectively. In this study, the fluid is air, and d is the equivalent diameter of the reaction and reference chambers. The calculated Reynolds numbers in the two chambers under flow rates of 1.3, 2, 3, 4, and 5 L min<sup>-1</sup> were 9.39, 14.58, 21.75, 29.05, and 36.34, respectively, indicating laminar flows in both chambers at different flow rates.

The HONO production in the reaction and reference chambers We tested the HONO production in the reaction and reference chambers under weather conditions similar to those during the SZMGT observations (humidity of 60-90% at a temperature of  $\sim 20$  °C and  $J(NO_2)$  of  $\sim 0.8 \times 10^{-3}$  s<sup>-1</sup>) at a 5 L min<sup>-1</sup> sampling flow rate. We found that the HONO mixing ratios in the reaction and reference chambers were almost the same and not statistically different from that in the ambient air within the standard deviation, as shown in Fig. S9; therefore, we assumed that the HONO production in the reaction and reference chambers would not cause a significant difference in  $P(O_3)_{net}$  in the two chambers. Unfortunately, we did not test HONO during the field observation period, but we have added the modeled HONO produced from the precursors before the ambient air was injected into the NPOPR system, as described in Sect. 3.2.

### 2.3 Calibration and measurement error of the CAPS NO<sub>2</sub> monitor

The Ox in the NPOPR detection system was measured by the CAPS NO<sub>2</sub> monitor. Detailed descriptions of this technique can be found elsewhere (Kebabian et al., 2008, 2005). We calibrated the CAPS NO<sub>2</sub> monitor using a NO<sub>2</sub> standard gas (with an original mixing ratio of 2.08 ppmv), which was first calibrated using the gas-phase titration method using NO standard gas and excessive O<sub>3</sub>. The related experimental results are shown in Fig. S15. The detailed calibration procedure is as follows: a. injected  $\sim 10$ –100 ppbv of NO<sub>2</sub> standard gas for 30 min to passivate the surfaces of the monitor and then injected dry pure air for  $\sim 10$  min to minimize the zero point drift, which were 0.043 and 0.047 ppbv at integration times of 35 and 100 s, respectively, and resulted in LODs of CAPS of 0.13 and 0.14 ppbv (3  $\sigma$ ), respectively; b.

injected a wide range of NO<sub>2</sub> mixing ratios (from 0–160 ppbv) prepared by mixing the NO<sub>2</sub> standard gas with ultrapure air into the CAPS NO<sub>2</sub> monitor and repeated the experiments three times at each NO<sub>2</sub> mixing ratio. The final results are shown in Fig. 4. To check the baseline drift of the CAPS at different humidities, we added another two sets of tests (as shown in Fig. S11) using ambient air and wet pure air and found that (a) when injecting ambient air into the CAPS (RH ranged from ~30-35%), the baseline drifts were 0.035 and 0.032 ppbv (1  $\sigma$ ) at integration times of 35 and 100 s, respectively; and (b) when injecting wet pure air into the CAPS (RH ranged from 35-70%), the baseline drifts were 0.043 and 0.030 ppbv (1  $\sigma$ ) at integration times of 35 and 100 s, respectively. These baseline drifts were smaller than those when injecting dry pure air to estimate the LOD of the CAPS. We chose the largest baseline drift when injecting dry pure air to estimate the  $P(O_3)_{net}$  error in the following analysis; by doing this, we were able to include all the short-duration baseline drifting in the CAPS NO<sub>2</sub> monitor under different humidities.

To obtain an accurate measurement error of the CAPS NO<sub>2</sub> monitor ( $(O_{X_{CAPS}})_{error}$ ), we fitted the calibration results with a 68.3 % confidence level, and the blue line in Fig. 4 represents the maximum fluctuation range under this confidence level.  $(O_{X_{CAPS}})_{error}$  was then calculated from the fluctuation range of the 68.3 % confidence interval of the calibration curve. The relationship between  $(O_{X_{CAPS}})_{error}$  and the measured Ox value ( $[Ox]_{measured}$ ) can be expressed as a power function curve, as shown in Eq. (5):

386 
$$(O_{X_{CAPS}})_{error} = 9.72 \times [O_X]_{measured}^{-1.0024}$$
 (5)

Subsequent  $P(O_3)_{net}$  error estimation according to the instrument measurement error of the CAPS  $NO_2$  monitor and the  $O_3$  light-enhanced loss in the reaction and reference chambers are described in Appendix II.




Figure 4: Calibration results of the CAPS NO<sub>2</sub> monitor with different NO<sub>2</sub> mixing ratios. The y-axis represents the NO<sub>2</sub> mixing ratios measured by the CAPS NO<sub>2</sub> monitor, and the x-axis represents the prepared NO<sub>2</sub> mixing ratios from the diluted NO<sub>2</sub> standard gas.

## 2.4 The measurement error of P(O<sub>3</sub>)<sub>net</sub> and the LOD of the NPOPR detection system

To assess the measurement error of  $P(O_3)_{net}$  and the LOD of the NPOPR detection system, dry pure air was introduced into the NPOPR detection system in sequence to adjust the system for  $\sim 2$  h, followed by dry pure air or ambient air when the time resolution of the CAPS NO<sub>2</sub> monitor was 1 s and the integration time period was 100 s (the measurement durations for the reaction and reference chambers were both 2 min). The LOD of the NPOPR detection system was obtained as three times the measurement error of  $P(O_3)_{net}$ , which was determined at a time resolution of 4 min by propagating the errors of the Ox measured by the CAPS NO<sub>2</sub> monitor when ultrapure air or ambient air was introduced into the NPOPR detection system, combined with the related  $\langle \tau \rangle$  under different flow rates, i.e.,  $\langle \tau \rangle$  was 0.063 h at a flow rate of 5 L min<sup>-1</sup>. The detailed calculation method is shown in Eq. (6):

$$LOD = \frac{3 \times \sqrt{([O_X]_{rea\_std})^2 + ([O_X]_{ref\_std})^2}}{\tau}$$
 (6)

where  $[O_X]_{rea\_std}$  and  $[O_X]_{ref\_std}$  represent the standard deviation of  $O_X$  in the reaction and reference chambers measured by the CAPS  $NO_2$  monitor with an integration time period of 100 s, respectively.

However, considering that the background Ox mixing ratios (measured by the CAPS  $NO_2$  monitor of the air in the reference chamber) changed when measuring the ambient air, the measured  $O_X$  errors in the reaction and reference chambers changed with the Ox mixing ratios (as shown in Sect. 2.3), and the LOD must also be a function of the intrinsic ambient and photochemically formed  $O_3$  and  $NO_2$  mixing

ratios (i.e., the Ox mixing ratios measured by the CAPS  $NO_2$  monitor). It is worth noting that the measured  $O_X$  errors may also be influenced by the light-enhanced loss of  $O_3$  in the reaction and reference chambers under ambient conditions when the light intensity (especially  $J(O^1D)$ ) and  $O_3$  mixing ratios are high, as tested and shown in Appendix II, but this effect is included in the measured  $O_X$  errors. Therefore, when injecting ambient air into the NPOPR system, the error and LOD of  $P(O_3)_{net}$  with a residence time of  $\tau$  can be calculated using Eq. (7) and Eq. (8), respectively:

$$P(O_3)_{\text{net\_error}} = \frac{\sqrt{(O_{X\gamma})_{\text{rea\_error}}^2 + ((9.72 \times [(O_X]_{\text{rea\_measured}}^{-1.0024}))_{\text{rea\_std}}^2 + ((9.72 \times [(O_X]_{\text{ref\_error}}^{-1.0024}))_{\text{ref\_error}}^2 + ((9.72 \times [(O_X]_{\text{ref\_measured}}^{-1.0024}))_{\text{ref\_std}}^2}{\tau}}{\tau}$$
(7)

418 LOD= 
$$3 \times P(O_3)_{\text{net error}}$$
 (8)

where  $(O_{X_{\gamma}})_{rea\_error}$  and  $(O_{X_{\gamma}})_{ref\_error}$  represent the measurement error caused by the light-enhanced loss

of  $O_3$  in the reaction and reference chambers, respectively, and  $(9.72 \times [O_X]_{measured}^{-1.0024})_{rea\ std}$  and

 $(9.72 \times [O_X]_{measured}^{-1.0024})_{ref \ std}$  represent the standard deviation of  $O_X$  in the reaction and reference

chambers caused by the CAPS NO<sub>2</sub> monitor with an integration time period of 100 s, respectively. More

details about the  $(O_{X_{\gamma}})_{rea\ error}$  and  $(O_{X_{\gamma}})_{ref\ error}$  estimation method can be found in Appendix II.

In conclusion, the LOD of the NPOPR detection system is determined to be three times  $P(O_3)_{\text{net\_error}}$ , where  $P(O_3)_{\text{net\_error}}$  is mainly determined by the measurement error of Ox (including the Ox measurement error of the CAPS NO<sub>2</sub> monitor, the light-enhanced loss of O<sub>3</sub>, and the chamber Ox losses). Because the measurement error of the CAPS NO<sub>2</sub> monitor decreases with increasing Ox mixing ratios (as shown in Sect. 2.3), higher LODs could be obtained when injecting dry pure air into the NPOPR detection system, which were approximately 0.07, 1.4, and 2.3 ppbv h<sup>-1</sup> at air flow rates of 1.3, 3, and 5 L min<sup>-1</sup>, respectively. The results are summarized in Table S9.

During the field observations, the LOD values were highly dependent on the ambient conditions, especially the light intensity and the Ox mixing ratios, and higher O<sub>3</sub> mixing ratios and lower light intensity will likely result in lower LOD values.

## 2.5 Laboratory tests of the NPOPR detection system

We conducted an experiment in the laboratory to test the performance of the NPOPR detection system at Jinan University Panyu Campus (23.0° N, 113.4° E) on 26 March 2021. Ambient air (5 L min<sup>-1</sup>) was

simultaneously injected into the reaction and reference chambers of the NPOPR detection system in parallel, and the sunlight simulation lamp mentioned above was used to simulate sunlight radiation. The light intensities of the sunlight simulation lamp were decreased from 26000 cd to 0 cd in steps of 3700 cd, where cd indicates the light intensity SI unit candela.  $P(O_3)_{net}$  was 28.6 ppbv h<sup>-1</sup> at a light intensity of 26000 cd and gradually approached 0 ppbv h<sup>-1</sup> at 0 cd (as shown in Fig. 5), indicating that the  $P(O_3)_{net}$  change due to the different sunlight radiation could be well captured by the NPOPR detection system.




Figure 5: (a) Measured Ox mixing ratios in the reaction and reference chambers and (b) the related  $P(O_3)_{net}$  as a function of the light intensity during the experiment.

#### 3 Atmospheric study and discussion

#### 3.1 Field observations

The self-built NPOPR detection system was employed in the field campaign conducted at SZMGT, which is located in Shenzhen, China (as shown in Fig. S17), from 7 to 9 December 2021. During the campaign, to achieve the lowest  $O_3$  and  $NO_2$  wall loss, we used a 5 L min<sup>-1</sup> air flow rate in the reaction and reference chambers (with a residence time of  $\sim$  4 min). The photolysis frequencies of different species were measured using the actinic flux spectrometer as mentioned above.  $O_3$  and  $NO_X$  (NO+NO<sub>2</sub>) mixing ratios were measured using a 2B  $O_3$  monitor and a chemiluminescence NOx monitor (Model 42i, Thermo

Fisher Scientific, USA), respectively. T and RH were measured by a portable weather station (Met Pak, Gill Instruments Ltd, UK). Volatile organic compounds (VOCs) were measured by high-resolution proton transfer reaction time-of-flight mass spectrometry (PTR-ToF-MS, Ionicon Analytik, Austria) (Wang et al., 2020a; Wu et al., 2020) and an off-line gas chromatography mass spectrometry flame ionization detector (GC-MS-FID) technique (Wuhan Tianhong, Co. Ltd, China) (Yuan et al., 2012) (Table S11). Additionally, a self-built formaldehyde analyzer was used to detect formaldehyde (HCHO) (Zhu et al., 2020). Figure 6 presents the temporal and diurnal variations in the  $P(O_3)_{net}$ ,  $O_X$ ,  $O_3$ ,  $O_3$ ,  $O_4$ ,  $O_4$ ,  $O_5$ ,  $O_5$ ,  $O_7$ ,  $O_8$ ,




Figure 6: (a) Time series and (b) average diurnal variations of  $P(O_3)_{net}$ ,  $J(NO_2)$ ,  $J(O^1D)$ , T, RH, Ox, NO<sub>2</sub> and NO measured at SZMGT from 7 to 9 December 2021. The shaded areas represent the error of each measured species, where the error of  $P(O_3)_{net}$  was calculated according to the method described in Appendix II (the estimation of the  $P(O_3)_{net}$  error).

During the measurement period,  $P(O_3)_{net}$  ranged from  $\sim 0$  to  $34.1\pm7.8$  ppbv h<sup>-1</sup>, with an average daytime (from 6:00-18:00) value of  $12.8 (\pm 5.5)$  ppbv h<sup>-1</sup>. The maximum  $P(O_3)_{net}$  at SZMGT was lower than that measured in the urban area of Houston in the US (40-50 ppbv h<sup>-1</sup> and 100 ppbv h<sup>-1</sup> in autumn and spring, respectively) (Baier et al., 2015; Ren et al., 2013), close to that measured in Indiana in the US ( $\sim 30$  ppbv h<sup>-1</sup> in spring) (Sklaveniti et al., 2018), and much higher than that measured at the

Wakayama Forest Research Station, a remote area of Japan (10.5 ppbv h<sup>-1</sup> in summer) (Sadanaga et al., 2017) and an urban area of Pennsylvania in the US ( $\sim$  8 ppbv h<sup>-1</sup> in summer) (Cazorla et al., 2010). The result indicates the rationality of the measured  $P(O_3)_{net}$  in this study. From previous studies, the  $O_3$  pollution in the PRD area is more severe in summer and autumn than in winter and spring (Zhang et al., 2021). In this study,  $P(O_3)_{net}$  was measured in wintertime, which was already high, so we believe that the  $O_3$  pollution of the PRD is severe and urgently needs to be controlled. More measurements of  $P(O_3)_{net}$  worldwide are listed in Table S10, and we found that  $P(O_3)_{net}$  was much higher in urban areas than in remote areas using both modeling and direct measurement methods.

According to the diurnal variation in all the measured pollutant indicators,  $P(O_3)_{net}$  started to increase at approximately 7:00 local time, which may be due to two reasons: (1) the rise in  $O_3$  precursors (i.e., VOCs) due to the high-altitude atmospheric residual layer transported downward near the surface at this time and (2) the increase in solar radiation intensity after 7:00, which increased the oxidation capacity of the pollutants. These two factors jointly enhanced the photochemical oxidation reaction of VOCs and gradually increased  $P(O_3)_{net}$ .  $P(O_3)_{net}$  then peaked at approximately 12:00, which was consistent with  $J(NO_2)$ , but this peak time occured earlier than that of  $O_3$ , which peaked at approximately 14:00, which may be due to the photochemical reactions dominating  $O_3$  mixing ratio changes between 12:00 and 14:00. After 14:00, the  $O_3$  mixing ratios started to decrease, which may be due to other processes dominating the  $O_3$  mixing ratio changes at this time, such as  $O_3$  reacting with other pollutants or surface deposition and the outflow of  $O_3$  by physical transport. In conclusion, the changes in  $O_3$  mixing ratios were influenced by both photochemical production and physical transport. Because  $HO_2$  and  $RO_2$  were not well captured in the model, the simulations could lead to an underestimation of  $P(O_3)_{net}$ .

#### 3.2 Model simulation of $P(O_3)_{net}$ in the reaction and reference chambers

## 3.2.1 Modeling method

To obtain a comprehensive understanding of the ozone production rate  $P(O_3)$  and ozone destruction rate  $D(O_3)$  during a 4-min photochemical reaction in the reaction and reference chambers, we modeled  $P(O_3)$  and  $D(O_3)$  at 12:00 on 7 December 2021 based on field observation data using a zero-dimensional box model based on the F0AM v3.2 coupled with MCM v3.3.1, which contains a total of 143 VOCs, more than 6700 species, involving more than 17000 reactions (Jenkin et al., 2015).  $P(O_3)_{\text{net}}$  can be expressed by the difference between  $P(O_3)$  and  $P(O_3)$ , and  $P(O_3)$  and  $P(O_3)$  can be expressed as Eqs. (9) and (10),

502 respectively.

503 
$$P(O_3)=k_{HO_2+NO}[HO_2][NO]+\sum_i k_{RO_{2,i}+NO}[RO_{2i}][NO]\phi_i$$
 (9)  
504  $D(O_3)=k_{O(^1D)+H_2O}[O(^1D)][H_2O]+k_{OH+O_3}[OH][O_3]+k_{HO_2+O_3}[HO_2][O_3]$ 

$$+\sum_{i} (k_{\text{O}_3+\text{Alkene}_i}[\text{O}_3][\text{Alkene}_i) + k_{\text{OH+NO}_2}[\text{OH}][\text{NO}_2] + k_{\text{RO}_{2,i}+\text{NO}_2}[\text{RO}_{2i}][\text{NO}_2]$$
(10)

where  $k_{M+N}$  represents the bimolecular reaction rate constant of M and N, and  $\varphi_i$  is the yield of NO<sub>2</sub> from the RO<sub>2i</sub> +NO reaction. The relevant reaction rates of  $P(O_3)$  and  $D(O_3)$  and the VOCs mixing ratios from 7–9 December 2021 at the SZMGT used in the model are listed in Tables 2 and S11.

Table 2. O3 production and destruction reactions and the relevant reaction rates used in the model.

Reactions	Rate coefficient/unit	Number
O <sub>3</sub> production pathways - P(O <sub>3</sub> )		
$RO_2+NO \rightarrow RO+NO_2$	2.7×10 <sup>-12</sup> ×exp(360/T)/molecules <sup>-1</sup> cm <sup>3</sup> s <sup>-1</sup>	(R1)
$HO_2+NO \rightarrow OH+NO_2$	$3.45{\times}10^{\text{-}12}{\times}\text{exp}(270/\text{T})/\text{molecules}^{\text{-}1}\text{ cm}^3\text{ s}^{\text{-}1}$	(R2)
O <sub>3</sub> loss pathways - D(O <sub>3</sub> )		
$O_3 + hv \rightarrow O^1D + O_2$	Measured JO <sup>1</sup> D/s <sup>-1</sup>	(R3)
$O_3 + C_2H_4 \rightarrow HCHO + CH_2OOA$	$9.1\times10^{-15}\times exp(-2580/T)/molecules^{-1} cm^3 s^{-1}$	(R4)
$O_3 + C_3H_6 \rightarrow CH_2OOB + CH_3CHO$	2.75×10 <sup>-15</sup> ×exp(-1880/T)/molecules <sup>-1</sup> cm <sup>3</sup> s <sup>-1</sup>	(R5)
$O_3 + C_3H_6 \rightarrow CH_3CHOOA + HCHO$	2.75×10 <sup>-15</sup> ×exp(-1880/T)/molecules <sup>-1</sup> cm <sup>3</sup> s <sup>-1</sup>	(R6)
$O_3 + C_5H_8 \rightarrow CH_2OOE + MACR$	3.09×10 <sup>-15</sup> ×exp(-1995/T)/molecules <sup>-1</sup> cm <sup>3</sup> s <sup>-1</sup>	(R7)
$O_3 + C_5H_8 \rightarrow CH_2OOE + MVK$	2.06×10 <sup>-15</sup> ×exp(-1995/T)/molecules <sup>-1</sup> cm <sup>3</sup> s <sup>-1</sup>	(R8)
$O_3 + C_5H_8 \rightarrow HCHO + MACROOA$	3.09×10 <sup>-15</sup> ×exp(-1995/T)/molecules <sup>-1</sup> cm <sup>3</sup> s <sup>-1</sup>	(R9)
$O_3 + C5H_8 \rightarrow HCHO + MVKOOA$	2.06×10 <sup>-15</sup> ×exp(-1995/T)/molecules <sup>-1</sup> cm <sup>3</sup> s <sup>-1</sup>	(R10)
$O_3+HO_2 \rightarrow OH$	$2.03\times10^{-16}\times (T/300)^{4.57}\times exp(693/T)/molecules ^{-1} cm^3 s^{-1}$	(R11)
$RO_2 + NO_2 \rightarrow peroxy nitrates$	$(3.28\times10^{-28}\times7.24\times10^{18}\times P/T\times(T/300)^{-6.87}\times1.125$	(R12)
	$\times 10^{\text{-}11} \times (\text{T}/300)^{\text{-}1.105}) \times 10^{(\log 10(0.30)} / (1 + (\log 10(2.93) + (\log 10(2.93)))) \times 10^{-11} \times (10^{-11}) $	
	$\times 10^{-17} \times 7.24 \times 10^{18} \times P/T \times (T/300)^{-5.765})/0.75-1.27$	
	$\times log10(0.30))^{2}))/(2.926\times 10^{-17}\times 7.24\times 10^{18}\times P/T)$	
	$\times$ (T/300) <sup>-5.765</sup> )/molecules <sup>-1</sup> cm <sup>3</sup> s <sup>-1</sup>	
$NO_2+OH \rightarrow HNO_3$	$3.2 \times 10^{-30} \times 7.24 \times 10^{18} \times P/T \times (T/300)^{-4.5} \times 3 \times 10^{-11}$	(R13)
	$\times 10^{\log 10(0.41)} / (1 + (\log 10(3.2 \times 10^{-30} \times 7.24 \times 10^{18} \times P/T$	
	×(T/300) <sup>-4.5</sup> /3×10 <sup>-11</sup> )/(0.75-1.27	
	$\times (\log 10(0.41))^2)/(3.2 \times 10^{-30} \times 7.24 \times 10^{18} \times P/T)$	
	$\times (T/300)^{-4.5} + 3 \times 10^{-11})$ /molecules <sup>-1</sup> cm <sup>3</sup> s <sup>-1</sup>	
$O_3+OH \rightarrow HO_2$	$1.70 \times 10^{-12} \times \exp(-940/T)/\text{molecules}^{-1} \text{ cm}^3 \text{ s}^{-1}$	(R14)

<sup>\*</sup>The rate coefficient obtained from the MCM v3.3.1 model.

In total, three-stage simulations were carried out to obtain the 4-min photochemical reactions in the reaction and reference chambers, and all three-stage models were operated in a time-dependent mode with a 1 s resolution. In the 1 st-stage, to establish a real atmospheric environment system, all observations on 7 December 2021, from 6:00-11:30, were used to constrain the model to obtain the mixing ratios of the unmeasured species in the ambient atmosphere, including oxygenated VOCs (OVOCs, in total 16 species), and nonmethane hydrocarbons (in total 47 species), O<sub>3</sub>, NO, NO<sub>2</sub>, J values, T, RH, and pressure (P). Because O<sub>3</sub>-NO-NO<sub>2</sub> was not in a steady state when all species were constrained, we conducted a 2<sup>nd</sup>-stage simulation from 11:30–12:00. In this stage, we used the output mixing ratios of the unmeasured species from the simulation in the last 1 s of the 1st-stage simulation as the input, which were not constrained after providing initial values. For the measured species, O<sub>3</sub>, NO, and NO<sub>2</sub> were no longer constrained after providing initial values, while all other variables (including NO<sub>X</sub>, VOCs, J values, RH, T, P, etc.) were still constrained in a time-dependent mode with a 1 s resolution after providing initial values. In the 3<sup>rd</sup>-stage, we modeled the 4-min photochemical reactions in the reaction and reference chambers. We used the output mixing ratios of the unmeasured species (i.e., OH, HO<sub>2</sub>, RO<sub>2</sub>, SO<sub>2</sub>, HONO, etc.) from the simulation in the last 1 s of the 2<sup>nd</sup>-stage simulation and all measured values (i.e., O<sub>3</sub>, NO, NO<sub>2</sub>, VOCs, J values, RH, T, P, etc.) as the model input, which were not constrained after providing initial values. In addition, while maintaining the setup conditions for the 2<sup>nd</sup>-stage of the simulation, we extended the simulation of the environment to 12:04 to obtain the modeled  $P(O_3)_{net}$  in the environment in the 3<sup>rd</sup>-stage simulation. The result is shown in orange marker in Fig. 10d. Figure 7 shows an explicit explanation of the 3<sup>rd</sup>-stage simulation in the reaction and reference chambers.

512

513

514

515

516

517

518

519

520

521

522

523

524

525

526

527

528

529

530

531

532 533

534

535




Figure 7: Explicit explanation of the 3<sup>rd</sup>-stage model simulation (input meteorological conditions: *P*: 1015.3 hPa, *T*: 295.6 K, RH: 39.7 %).

Specifically, because the photolysis frequencies play critical roles in the simulation of P(O<sub>3</sub>)<sub>net</sub>, the

J values obtained from two methods (labeled methods I and II) were used in the 3<sup>rd</sup>-stage 4-min simulation. The J values used in method I were obtained from the measured values (including J(NO<sub>2</sub>), J(O¹D), J(HONO), J(H<sub>2</sub>O<sub>2</sub>), J(NO<sub>3</sub>\_M), J(NO<sub>3</sub>\_R), J(HCHO\_M), and J(HCHO\_R)) and the simulated values using the Tropospheric Ultraviolet and Visible (TUV) radiation model (version 5.3) (including J(HNO<sub>3</sub>), J(CH<sub>3</sub>CHO), J(MACR), J(MEK), J(HOCH<sub>2</sub>CHO), J(C<sub>2</sub>H<sub>5</sub>CHO), J(C<sub>3</sub>H<sub>7</sub>CHO), and J(C<sub>4</sub>H<sub>9</sub>CHO). ), while the J values in method II were all obtained from the simulated values using the TUV model, detailed information on these two methods is introduced in Appendix IV (Tables S12 and S13, respectively).

#### 3.2.2 Radical chemistry in the reaction and reference chambers

The variations in the radical mixing ratios (i.e., HO<sub>2</sub>, OH, RO<sub>2</sub>) and NO<sub>3</sub>, NO, NO<sub>2</sub>, and O<sub>3</sub> mixing ratios obtained from method I and method II during the 3<sup>rd</sup>-stage 4-min model simulation are shown in Fig. 8 and Fig. S18, respectively. The production and destruction reactions of HO<sub>2</sub>, OH, RO<sub>2</sub>, and NO<sub>3</sub> in the reaction and reference chambers obtained from methods I and II are shown in Fig. 9 and Fig. S19, respectively, the production and destruction reactions of RO<sub>X</sub> in the reaction and reference chambers obtained from methods I and II are shown in Fig. S20, the detailed RO<sub>X</sub> production pathways of NO<sub>3</sub>+VOCs are shown in Fig. S21, and the final modeling results are shown in Fig. 10 and Fig. S22.

From Fig. 8, in the reaction chamber, the HO<sub>2</sub>, OH, RO<sub>2</sub>, and NO<sub>3</sub> concentrations first slightly increased and then became stable, and their final concentrations were 2.00×10<sup>8</sup>, 7.64×10<sup>6</sup>, 1.08×10<sup>8</sup>, and 8.47×10<sup>6</sup> molecules cm<sup>-3</sup>, respectively. In the reference chamber, the HO<sub>2</sub> and RO<sub>2</sub> concentrations dropped during the 1<sup>st</sup> half minute and rose afterward. The final HO<sub>2</sub> concentration (1.35×10<sup>8</sup> molecules cm<sup>-3</sup>) was lower than that in the reaction chamber, while the RO<sub>2</sub> concentration exceeded that in the reaction chamber at the end of the 2<sup>nd</sup> minute and gradually became stable at 1.27×10<sup>8</sup> molecules cm<sup>-3</sup>. The OH concentration dropped significantly at the 1<sup>st</sup> minute and then became stable at approximately 6.16×10<sup>5</sup> molecules cm<sup>-3</sup>. The NO<sub>3</sub> concentration rose significantly during the 4-min simulation and reached 3.55×10<sup>7</sup> molecules cm<sup>-3</sup> at the end, which was much higher than that in the reaction chamber.




Figure 8: The variations of (a)HO<sub>2</sub>, (b) RO<sub>2</sub>, (c) OH, (d)NO<sub>3</sub>, (e) NO, NO<sub>2</sub>, and (f) O<sub>3</sub> mixing ratios during the 3<sup>rd</sup>-stage 4-min model simulation using method I. The mixing ratios changes of these items for method II is shown in Fig. S18.

562

563

564

565

566

567

568

569

570

571

572

573

574

575

576

577

578

579

580

The OH, HO<sub>2</sub>, RO<sub>2</sub>, and NO<sub>3</sub> concentrations greatly impact the O<sub>3</sub> production and destruction rate. To better understand the factors that drive the OH, HO2, RO2, and NO3 concentration changes, we have added their production and destruction pathways in Fig. 9. We found that the decrease in HO<sub>2</sub> and RO<sub>2</sub> concentrations in the reference chamber in the 1st half minute was mainly due to NO titration effects, as high NO mixing ratios existed during the 1st half minute. The increase in HO2 concentrations afterward was largely attributable to RO+O2 reaction/RO decomposition, OH+CO/VOCs reaction, OVOCs photolysis (i.e., C<sub>3</sub>H<sub>4</sub>O<sub>2</sub>, C<sub>2</sub>H<sub>2</sub>O<sub>2</sub>, C<sub>4</sub>H<sub>6</sub>O<sub>2</sub>), and NO<sub>3</sub>+VOCs reaction, and the increase in RO<sub>2</sub> concentrations afterward were largely attributable to OH+VOCs oxidation, OVOCs photolysis and O<sub>3</sub>+VOCs reaction. The main OH sources in the reference chamber were both HO<sub>2</sub>+NO in method I and method II. Due to sufficiently high J(NO<sub>3</sub>) (~ 90% of that in the reaction chamber) and NO<sub>2</sub> concentrations in the reference chamber, the NO<sub>3</sub> photolysis and NO<sub>2</sub>+NO<sub>3</sub> reaction consumed NO<sub>3</sub> in the reference chamber, but the NO<sub>3</sub> concentrations were still sufficiently high due to high production rates of NO<sub>3</sub> at the same time. The main NO<sub>3</sub> source in the reference chamber was the NO<sub>2</sub>+O<sub>3</sub> reaction, followed by N2O5 decomposition. The NO concentrations were relatively high in the 1st minute and consumed NO<sub>3</sub> very quickly, but due to continuous NO<sub>3</sub> sources, the net NO<sub>3</sub> production rates ( $P(NO_3)_{net}$ ) were positive (as shown in Fig. 9), which caused the NO<sub>3</sub> concentration to continue to increase (as shown in Fig. 8d). The main difference in NO<sub>3</sub> production in the reference chamber compared to that in the

reaction chamber was the much higher  $N_2O_5$  decomposition, which was mainly due to the high  $NO_2$  concentrations in the reference chamber. On the other hand, although the  $NO+NO_3$  reaction was also one of the dominant  $NO_3$  destruction pathways,  $NO_3$  consumed by the  $NO+NO_3$  reaction was significantly smaller than  $NO_3$  produced by the  $NO_2+O_3$  reaction. Furthermore, in order to check if the  $NO_3+VOC_3$  reactions exists, we extracted all the P(ROx) pathways related to  $NO_3+VOC_3$  reactions during the  $3^{rd}$ -stage 4-min model simulation in the reaction and reference chambers in method I, as shown in Fig. S20. We found that the  $NO_3+VOC_3$  reactions are mostly related to the OVOCs (i.e. 6-Ethyl-m-cresol and 3-Ethyl-6-methylbenzene-1,2-diol) in Fig. S21. The production and destruction rates of ROx are shown in Fig. S20.




Figure 9: Production and destruction pathways of OH (a<sub>1</sub>-b<sub>1</sub>), HO<sub>2</sub> (a<sub>2</sub>-b<sub>2</sub>), RO<sub>2</sub> (a<sub>3</sub>-b<sub>3</sub>), and NO<sub>3</sub> (a<sub>4</sub>-b<sub>4</sub>) during

the 3<sup>rd</sup>-stage 4-min model simulation in the reaction and reference chambers in method I. The related contents for method II (c)-(d) are shown in Fig. S19 in the supplementary materials.

## 3.2.3 P(O<sub>3</sub>)<sub>net</sub> formation and destruction pathways in the reaction and reference chambers

Figures 10a–d show the modeled  $P(O_3)_{net}$  and the sources and sinks of various species during the  $3^{rd}$ -stage 4-min simulation. Figure 10a shows the steady state of  $P(O_3)_{net}$  and the various species in the ambient atmosphere achieved in the last 1 s of the  $2^{nd}$ -stage simulation; Figures 10b and c show the modeled  $P(O_3)_{net}$  and the  $O_3$  chemical budgets in the reaction and reference chambers during the model simulation period; Figure 10d summarizes the modeled  $P(O_3)_{net}$  in the ambient air (represented as blue and orange markers at the time when the ambient air was going in and out of the NPOPR system, respectively) and the modeled  $P(O_3)_{net}$  in the reaction and reference chambers. To compare the modeled results with our measured results, we calculated the integral mean of the modeled  $P(O_3)_{net}$  in the reaction and reference chambers and appended the related measured  $P(O_3)_{net}$  value during the 4-min simulation time onto Fig. 10d (green maker). Furthermore, the reaction weights of different production and destruction reaction processes of  $O_3$  are shown in Figs. 10e–h.




Figure 10: (a)—(c) Modeled  $P(O_3)_{net}$  values and  $O_3$  chemical budgets in (a) ambient air when injected into the reaction and reference chambers and (b—c) the reaction and reference chambers during the 4-min model simulation; (d)  $P(O_3)_{net}$ , where  $P(O_3)_{net}$ \_modeled\_ambient represent the modeled  $P(O_3)_{net}$  in the ambient air at the time before (blue marker) and after (orange marker) the sampled ambient air was injected into the dual-channel reaction chamber.  $P(O_3)_{net}$ \_modeled\_reaction chamber and  $P(O_3)_{net}$ \_modeled\_reference chamber represent the  $P(O_3)_{net}$  change trends during the 4-min photochemical reactions in the reaction and reference chambers, respectively.  $P(O_3)_{net}$  modeled\_chamber =  $P(O_3)_{net}$  modeled\_reaction chamber—

 $P(O_3)_{\text{net}}$ \_modeled\_reference chamber, and  $P(O_3)_{\text{net}}$ \_modeled\_integral mean represents the integral mean of the  $P(O_3)_{\text{net}}$ \_modeled\_chamber. Moreover,  $P(O_3)_{\text{net}}$ \_measured\_NPOPR is the  $P(O_3)_{\text{net}}$  measured by NPOPR detection system. (e)–(h) Reaction weights of each production and destruction reaction process of  $O_3$  in the reaction and reference chambers in method I.

615

616

617

618

619

620

621

622

623

624

625

626

627

628

629

630

631

632

633

634

635

636

637

638

639

640

641

642

643

644

645

Figure 10a-h show the contributions of different reaction pathways to  $P(O_3)$  and  $D(O_3)$ .  $P(O_3)$  and D(O<sub>3</sub>) were almost the same within the 4-min reaction in the reaction chamber (all species reached a steady-state condition), while  $P(O_3)$  and  $D(O_3)$  in the reference chamber significantly decreased within the 1st min and remained stable in the following minutes. In the reaction chamber, the HO<sub>2</sub>+NO reaction contributed the most to  $P(O_3)$ , accounting for 62.6 % of the total  $P(O_3)$ , with an integral mean value of 17.5 ppbv  $h^{-1}$  in the reaction chamber. The second important pathway of  $P(O_3)$  was  $RO_2+NO$  (accounting for 37.4 % of the total P(O<sub>3</sub>)). The RO<sub>2</sub>+NO core reaction accounts for more than approximately 1200 types of RO<sub>2</sub> radicals, and the pathway of CH<sub>3</sub>O<sub>2</sub>+NO contributed 7.5 % to the total P(O<sub>3</sub>). The most important contributor of  $D(O_3)$  was OH+NO<sub>2</sub> (48.8 %), followed by RO<sub>2</sub>+NO<sub>2</sub> (33.3 %), O<sub>3</sub> photolysis (13.0%),  $O_3+OH$  (2.3%),  $O_3+HO_2$  (1.7%),  $C_5H_8+O_3$  (0.4%),  $C_3H_6+O_3$  (0.3%), and  $C_2H_4+O_3$  (0.2%). In the reference chamber, the integral mean value of the HO<sub>2</sub>+NO reaction was 2.3 ppbv h<sup>-1</sup>, which had the largest contribution to  $P(O_3)$  (accounting for 55.0 %). The second largest contributor to  $P(O_3)$  was RO<sub>2</sub>+NO (accounting for 45.0 % of the total  $P(O_3)$ ), in which the pathway of CH<sub>3</sub>O<sub>2</sub>+NO contributed 6.6 % to the total P(O<sub>3</sub>). The most important contributor of D(O<sub>3</sub>) was RO<sub>2</sub>+NO<sub>2</sub> (50.8 %), followed by OH+NO<sub>2</sub> (37.0 %), O<sub>3</sub>+HO<sub>2</sub> (4.9 %), C<sub>5</sub>H<sub>8</sub>+O<sub>3</sub> (2.3 %), C<sub>3</sub>H<sub>6</sub>+O<sub>3</sub> (1.5 %), O<sub>3</sub>+OH (1.4 %), O<sub>3</sub> photolysis (1.2 %), and C<sub>2</sub>H<sub>4</sub>+O<sub>3</sub> (0.9 %). For all P(O<sub>3</sub>) reactions, the weight of the RO<sub>2</sub>+NO reaction in the reference chamber was 7.5 % higher than that in the reaction chamber; however, for all  $D(O_3)$  reactions, the weight of the RO<sub>2</sub>+NO<sub>2</sub> reaction in the reference chamber was 17.5 % higher than that in the reaction chamber, which mitigated the high P(O<sub>3</sub>) value caused by RO<sub>2</sub>+NO in the reference chamber. Furthermore, the weight of the OH+NO<sub>2</sub> reaction in the reference chamber was 11.9 % lower than that in the reaction chamber, which may be the main reason that led to NO2 mixing ratios in the reference chamber being much higher than those in the reaction chamber. It is worth noting that the different reaction pathways of  $P(O_3)$  and  $D(O_3)$  stabilized at approximately 1.5 min for both methods I and II (as shown in Figs. 10 and S22, respectively), and the radicals that play critical roles in photochemical O<sub>3</sub> formation, such as HO2, RO2 and OH, reached quasi-steady states in approximately 3 min (as shown in Figs. 8 and S18). As the lowest experimental residence time in the reaction and reference chambers was 3.8 min at an air flow rate of 5 L min<sup>-1</sup>, the photochemical reaction time at different air flow rates in the

NPOPR system was sufficient for  $P(O_3)_{net}$  investigation, and it is reasonable for us to set the alternate ambient air sampling time for the reaction and reference chambers to 2 min, where the ambient air actually had already reacted for at least 3.8 min in the chambers.

The  $P(O_3)_{\text{net}}$  value measured by the NPOPR detection system at 12:04 was 26.0 ppbv h<sup>-1</sup>, which is 1.4 ppbv h<sup>-1</sup> higher than the modeled  $P(O_3)_{\text{net}}$  value in the ambient air (orange marker in Fig. 10d; 24.6 ppbv h<sup>-1</sup>) and 7.5 ppbv h<sup>-1</sup> higher than the modeled  $P(O_3)_{\text{net}}$  value of the NPOPR system (brown marker in Fig. 10d; 18.5 ppbv h<sup>-1</sup>, as calculated from the integral mean of  $P(O_3)_{\text{net}}$  in the 3<sup>rd</sup>-stage 4-min simulation in the reaction and reference chambers). Here, we note that for a better comparison between the measured and modeled  $P(O_3)_{\text{net}}$  values, the measured  $P(O_3)_{\text{net}}$  used here was obtained from a 4-min time resolution, which is 1.4 ppbv h<sup>-1</sup> higher than the measured  $P(O_3)_{\text{net}}$  value used in Fig. 6 (1-h time resolution). The ratio of the measured and modeled  $P(O_3)_{\text{net}}$  values was 1.4, which is consistent with the measured-to-modeled ratio of the cumulative  $P(O_3)_{\text{net}}$  values was 1.4, which is consistent with the atmosphere and were independent of the OH and HO<sub>2</sub> measurements. The reason for the difference between the measured and modeled  $P(O_3)_{\text{net}}$  here may be due to the inaccurate estimation of HO<sub>2</sub>/RO<sub>2</sub> radicals; for example, Ren et al. (2013) found that  $P(O_3)$  calculated from the modeled HO<sub>2</sub> was lower than that calculated from the measured HO<sub>2</sub>. The unknown HO<sub>2</sub> source should be identified for a more accurate estimation of  $P(O_3)_{\text{net}}$  in future studies.

Additionally, the modeled  $P(O_3)_{net}$  using the J values obtained from method II was 9.3 ppbv h<sup>-1</sup> lower than the measured  $P(O_3)_{net}$ , and this discrepancy was slightly larger than that using method I, as shown in Appendix IV (Fig. S22). The differences in the measured and modeled  $P(O_3)_{net}$  by methods I and II were 28.8 % and 35.8 %, respectively. This difference was mainly due to the transmittance of  $J(NO_2)$  in method II (30 %) being much higher than that in method I (9 %), and  $NO_2$  photolysis products were involved in the main reaction of  $O_3$  production through  $HO_2$ +NO and  $RO_2$ +NO, so the modeled  $P(O_3)_{net}$  in the reference chamber was slightly overestimated in method II, thus leading to an underestimation of the final  $P(O_3)_{net}$ .

Furthermore, because the NO<sub>2</sub> data used here were measured by a commercially available chemiluminescence NOx monitor, the NO<sub>2</sub> and NOx mixing ratios could be overestimated due to NOz interference (i.e., HNO<sub>3</sub>, peroxyacetyl nitrate (PANs), HONO, etc.) (Dunlea et al., 2007). According to

our results, the chemiluminescence technique could bias  $NO_2$  by 5 % compared to the CAPS technique, which is regarded as a trustworthy  $NO_2$  measurement technique without chemical interference. Therefore, we simulated the interference of  $NO_2$  measured by a chemiluminescence  $NO_2$  monitor in method I as follows: reducing and increasing the ambient  $NO_2$  mixing ratios in the reaction and reference chambers by 5 % in the  $3^{rd}$ -stage 4-min simulation. The results showed that increasing and decreasing  $NO_2$  by 5 % resulted in a decrease in  $P(O_3)_{net}$  by 1.64 % and 3.68 %, respectively (as shown in Fig. S23), which is much smaller than the bias caused by  $P(O_3)_{net}$  in the reference chamber (which were 13.9 % and 22.3 % for methods I and II, respectively). To evaluate  $P(O_3)_{net}$  error caused by the measurement error of J values, we introduced a  $\pm 5$  % error to the measured J values during the  $3^{rd}$  stage of the 4-min simulation in method I. The modeled  $P(O_3)_{net}$  results are presented in Fig. S24 in the supplementary materials. We observed that the inclusion of a -5 % measurement error in J values led to a decrease in  $P(O_3)_{net}$  by 7.27 %, while adding a +5 % measurement error in J values caused an increase in  $P(O_3)_{net}$  by 3.08 %. This implies that the maximum bias of  $P(O_3)_{net}$  caused by the measurement error of J values falls within the error range of the currently assessed  $P(O_3)_{net}$  error, which was 13.9 % for method I. Therefore, we conclude that this type of error will not influence our final modeling results and conclusions.

In conclusion, modeling tests demonstrated that the radicals and gas species in the reaction chamber of the NPOPR detection system were similar to those in genuine ambient air, while these radicals also unexpectedly existed in the reference chamber. This was mainly because the UV protection film used by the reference chamber did not completely filter out sunlight, which led to the low transmittance of light ranging from 390 nm to 790 nm. The  $P(O_3)_{\text{net}}$  biases caused by this interference modeled in methods I and II were 13.9 % and 22.3 %, respectively, which ensured that the measured  $P(O_3)_{\text{net}}$  by the NPOPR detection system should be regarded as the lower limit values of real  $P(O_3)_{\text{net}}$  in the atmosphere. We recommend that the J values obtained from method I should be used in the model simulation, which can better explain the photochemical formation of  $O_3$  in the actual atmosphere, but if direct J value measurements cannot be achieved during field observations, the J values obtained from method II would also be acceptable in modeling studies.

#### 4 Conclusions

We modified and improved a net photochemical ozone production rate (NPOPR) detection system based

on a dual-channel reaction chamber technique, which provides more accurate results and has broader application potential compared to previous studies. The main improvements of NPOPR detection system compared to previous studies were as follows: (1) improved the design of the reaction and reference chambers to make sure they have good airtightness; (2) changed the air sampling structure to enable the total air flow rates change freely from 1.3 to 5 L min<sup>-1</sup> in the reaction and reference chambers, which can make the NPOPR system achieve different limits of detection (LODs) and appliable to different ambient environment; (3) characterized the NPOPR detection system at different air flow rates to optimize the  $P(O_3)_{net}$  measurements, the LODs of the NPOPR detection system are 0.07, 1.4, and 2.3 ppbv h<sup>-1</sup> at air flow rates of 1.3, 3, and 5 L min<sup>-1</sup>, respectively; (4) tested the performance of both reaction and reference chambers by combining the field measurement and the MCM modeling method.

The NPOPR detection system was employed in the field observation at the Shenzhen Meteorological Gradient Tower (SZMGT), which is located in PRD, China. During the measurement period, the  $P(O_3)_{net}$  was around zero during nighttime and ranged from  $\sim 0$  to  $34.1\pm7.8$  ppbv h<sup>-1</sup> during daytime (from 6:00-18:00), with the average value of 12.8 ( $\pm5.5$ ) ppbv h<sup>-1</sup>. Besides,  $P(O_3)_{net}$  start to increase at around 7:00 at local time, this may be due to the rise of the  $O_3$  precursors (i.e., VOCs) transported down from the high-altitude atmospheric residual layer to the near-surface and the increase of solar radiation intensity increased the atmospheric oxidation capacity.  $P(O_3)_{net}$  was then reaches a peak at around 12:00 at noon time, by coupling with diurnal  $O_3$  mixing ratios trends, we confirmed that the ground-level  $O_3$  mixing ratios were influenced by both photochemical production and physical transport.

In order to clarify the detailed photochemical reaction processes in the reaction and reference chambers of NPOPR system, we modeled the  $P(O_3)_{net}$  on 7 December 2021, 12:00-12:04 in the reaction and reference chambers using MCM v3.3.1. As the photolysis frequencies of different species (J values) play critical roles in the formation of  $P(O_3)_{net}$ , the J values obtained from two methods were used in the 4-min chamber photochemical reaction (labeled as method I and method II), in method I, eight main J values (e.g.,  $J(NO_2)$ ,  $J(O^1D)$ , J(HONO), etc.) were measured directly, and other J values were obtained from the simulated values using the Tropospheric Ultraviolet and Visible (TUV) radiation model, while in method II, J values were all obtained from the simulated values using TUV model (as described in Sect. 3.2). Modeling tests demonstrated that the mixing ratios of different radicals and gas species (i.e., OH, HO<sub>2</sub>, RO<sub>2</sub>, NO<sub>3</sub>, NO, NO<sub>2</sub>, and O<sub>3</sub>) in the reaction chamber were similar with those in the real

ambient environment, while due to the UV protection film used by the reference chamber does not completely filter out the sunlight, there was low transmittance of the light ranged from 390 nm to 790 nm. In the reaction chamber, the contribution of different reactions to  $P(O_3)$  and  $D(O_3)$  modeled by method I and II were quite similar, where the HO<sub>2</sub>+NO reaction contributed most to  $P(O_3)$  (~ 62.6 %), followed by the RO<sub>2</sub>+NO reaction (~ 37.4 %). The OH+NO<sub>2</sub> reaction contributed most to D(O<sub>3</sub>), which accounted for ~48.9 %, followed by the RO<sub>2</sub>+NO<sub>2</sub> reaction O<sub>3</sub> photolysis, which accounted for ~33.3 % and 13.0 %, respectively. In the reference chamber, the contribution of different reactions to  $P(O_3)$  and  $D(O_3)$  modeled by method I and II were different, where the HO<sub>2</sub>+NO reaction contributed ~ 55.0 % and  $\sim$  58.2 % to the total  $P(O_3)$ , respectively, and  $RO_2$ +NO contributed  $\sim$  44.9 % and 41.8 % to the total  $P(O_3)$ , respectively. The most important contributor of  $D(O_3)$  modeled by method I was  $RO_2+NO_2$ (50.8 %), followed by OH+NO<sub>2</sub> (37.0 %), while the most important contributor of  $D(O_3)$  modeled by method II was OH+NO<sub>2</sub> (46.8 %), followed by RO<sub>2</sub>+NO<sub>2</sub> (44.1 %). For all P(O<sub>3</sub>) reactions, the weight of RO<sub>2</sub>+NO reaction in the reference chamber was 7.5 % and 4.3 % higher than that in the reaction chamber in method I and II, respectively, however, for all D(O<sub>3</sub>) reactions, the weight of RO<sub>2</sub>+NO<sub>2</sub> reaction in the reference chamber was 17.5 % and 10.9 % higher than that in the reaction chamber in method I and II, respectively, which will somehow mitigate the high P(O<sub>3</sub>) caused by RO<sub>2</sub>+NO in the reference chamber. The different reaction pathways of  $P(O_3)$  and  $D(O_3)$  had stabilized at around 1.5 min, and the radicals that play critical roles in photochemical O<sub>3</sub> formation, such as HO<sub>2</sub>, RO<sub>2</sub> and OH, reached quasi-steady states in about 3 min, the long enough ambient air residence time in the reaction and reference chambers (≥ 3.8 min) make the photochemical reaction time at different air flow rates in the NPOPR system sufficient enough for investigating the  $P(O_3)_{net}$ , and it is reasonable for us to set the alternate ambient air sampling time for the reaction and reference chambers at 2 min, where the ambient air actually has already reacted for at least 3.8 min in the chambers. The biases of the modeled  $P(O_3)_{net}$  caused by the interference of the reactions in the reference

732

733

734

735

736

737

738

739

740

741

742

743

744

745

746

747

748

749

750

751

752

753

754

755

756

757

758

759

760

The biases of the modeled  $P(O_3)_{\text{net}}$  caused by the interference of the reactions in the reference chamber in methods I and II were 13.9 % and 22.3 %, respectively; thus, the measured  $P(O_3)_{\text{net}}$  by the NPOPR detection system should be regarded as the lower limit values of the real  $P(O_3)_{\text{net}}$  in the atmosphere. Nevertheless, the measured  $P(O_3)_{\text{net}}$  values were 7.5 and 9.3 ppbv h<sup>-1</sup> higher than the modeled  $P(O_3)_{\text{net}}$  values obtained from methods I and II, respectively, which may be due to the inaccurate modeling of  $HO_2/RO_2$  radicals. Short-lived intermediate measurements coupled with direct  $P(O_3)_{\text{net}}$ 

- measurements are needed in future study in order to studies to better understand the photochemical production and destruction mechanisms of  $O_3$ . We recommend that the J values obtained from method I should be used in the model simulation, which can better explain the photochemical formation of  $O_3$  in the actual atmosphere, but if direct J value measurements cannot be achieved during field observations, the J values obtained from method II would also be acceptable in modeling studies.
- The self-built NPOPR detection system in this study filled the gap in the observation method in China. The research results not only help us to better understand the tropospheric O<sub>3</sub> budget but also provide an important data basis for formulating correct O<sub>3</sub> pollution prevention measures and control strategies.

761

762

763

764

765

- 771 Data availability. The observational data used in this study are available from corresponding authors
- upon request (junzhou@jnu.edu.cn).
- 773 Author contributions. JZ, BY, and MS designed the experiment, JZ and YXH developed and assembled
- the NPOPR detection system, YXH, JZ, JPZ, BY, YW, YFW, SCY, YWP, JPQ, XJH, XS and YBC
- 775 collected and analyzed the data, YXH and JZ wrote the manuscript, all authors revised the manuscript.
- 776 Competing interests. The authors declare that they have no known competing interests.
- 777 Acknowledgements. This study was funded by the Natural Science Foundation of Guangdong Province
- 778 (grant no. 2020A1515110526), and the Key-Area Research and Development Program of Guangdong
- Province (grant no. 2020B1111360003). We thank Nan Ma and Xiaofeng Su in Jinan University for the
- 780 HONO production experiment.

### References

- 782 Avnery, S., Mauzerall, D. L., Liu, J., and Horowitz, L. W.: Global crop yield reductions due to surface
- 783 ozone exposure: 1. Year 2000 crop production losses and economic damage, Atmos. Environ., 45,
- 784 2284-2296, https://doi.org/10.1016/j.atmosenv.2010.11.045, 2011.
- Baier, B. C., Brune, W. H., Lefer, B. L., Miller, D. O., and Martins, D. K.: Direct ozone production rate
- measurements and their use in assessing ozone source and receptor regions for Houston in 2013, Atmos.
- 787 Environ., 114, 83-91, http://dx.doi.org/10.1016/j.atmosenv.2015.05.033, 2015.
- Baier B C, Brune W H, Miller D O, et al., Higher measured than modeled ozone production at increased

- NOx levels in the Colorado Front Range, Atmos. Chem. Phys., 17: 11273-11292,
- 790 https://doi.org/10.5194/acp-17-11273-2017, 2017.
- 791 Bell, M. L., McDermott, A., Zeger, S. L., Samet, J. M., and Dominici, F.: Ozone and short-term mortality
- 792 in 95 US urban communities, J. Am. Med. Assoc. 1987-2000., 292, 2372-
- 793 2378, https://doi.org/10.1001/jama.292.19.2372, 2004.
- 794 Berman, J. D., Fann, N., Hollingsworth, J. W., Pinkerton, K. E., Rom, W. N., Szema, A. M., Breysse, P.
- N., White, R. H., and Curriero, F. C.: Health benefits from large-scale ozone reduction in the United
- 796 States, Environ. Health. Persp., 120, 1404-10, https://doi.org/10.1289/ehp.1104851, 2012.
- 797 Bohn B, Lohse I. Calibration and evaluation of CCD spectroradiometers for ground-based and airborne
- 798 measurements of spectral actinic flux densities. Atmos. Meas. Tech., 10, 3151-3174,
- 799 https://doi.org/10.5194/amt-10-3151-2017, 2017.
- 800 Burkholder, J., Sander, S., Abbatt, J., Barker, J., Cappa, C., Crounse, J., Dibble, T., Huie, R., Kolb, C.,
- and Kurylo, M.: Chemical kinetics and photochemical data for use in atmospheric studies, evaluation
- 802 number 19, Pasadena, CA: Jet Propulsion Laboratory, National Aeronautics and
- Space Administration, 2020, http://jpldataeval.jpl.nasa.gov. 2020.
- 804 Cazorla, M., Brune, and W. H.: Measurement of ozone production sensor, Atmos. Meas. Tech., 3, 545-
- 805 555, https://doi.org/10.5194/amt-3-545-2010, 2010.
- 806 Cazorla, M., Brune, W. H., Ren, X., and Lefer, B.: Direct measurement of ozone production rates in
- Houston in 2009 and comparison with two estimation methods, Atmos. Chem. Phys., 12, 1203-1212,
- 808 https://doi.org/10.5194/acp-12-1203-2012, 2012.
- 809 Dunlea, E. J., Herndon, S. C., Nelson, D. D., Volkamer, R. M., Martini, F. S., Sheehy, P. M., Zahniser,
- 810 M. S., Shorter, H., Wormhoudt, J. C., Lamb, B. K., Allwine, E. J., Gaffney, J. S., Marley, N. A., Grutter,
- M., Marquez, C., Blanco, S., Cardenas, B., Retama, A., Villegas, C. R. R., Kolb, C. E., Molina, L. T.,
- and Molina, M. J.: Evaluation of nitrogen dioxide chemiluminescence monitors in a polluted urban
- environment, Atmos. Chem. Phys., 7, 2691–2704, https://doi.org/10.5194/acp-7-2691-2007, 2007.
- Jenkin, M. E., Young, J. C., and Rickard, A. R.: The MCM v3.3.1 degradation scheme for isoprene,
- 815 Atmos. Chem. Phys., 15, 11433-11459, https://doi.org/10.5194/acp-15-11433-2015, 2015.
- 816 Kanaya, Y., Tanimoto, H., Yokouchi, Y., Fumikazu Taketani, F. T., Komazaki, Y., Irie, H., Takashima, H.,
- Pan, X., Nozoe, S., and Inomata, S.: Diagnosis of photochemical ozone production rates and limiting

- factors in continental outflow air masses reaching Fukue Island, Japan: ozone-control implications,
- 819 Aerosol. Air. Qual. Res., 16, 430-441, https://doi.org/10.4209/aaqr.2015.04.0220, 2016.
- 820 Karakatsani, A., Kapitsimadis, F., Pipikou, M., Chalbot, M. C., Kavouras, I. G., Orphanidou, D., Papiris,
- 821 S., and Katsouyanni, K.: Ambient air pollution and respiratory health effects in mail carriers, Environ.
- Res., 110, 278-85, https://doi.org/10.1016/j.envres.2009.11.002, 2010.
- 823 Lee, S.-B., Bae, G.-N., Lee, Y.-M., Moon, K.-C., and Choi, M.: Correlation between light intensity and
- 824 ozone formation for photochemical smog in urban air of seoul, Aerosol. Air. Qual. Res., 10, 540-549,
- 825 https://doi.org/10.4209/aaqr.2010.05.0036, 2010.
- 826 Liu, S. C.: Possible effects on fropospheric O3 and OH due to NO emissions, Geophys. Res. Lett., 4,
- 325-328, https://doi.org/10.1029/GL004i008p00325, 1977.
- Liu, X., Wang, N., Lyu, X., Zeren, Y., Jiang, F., Wang, X., Zou, S., Ling, Z., and Guo, H.: Photochemistry
- 829 of ozone pollution in autumn in Pearl River Estuary, South China, Sci. Total Environ., 754, 141812,
- https://doi.org/10.1016/j.scitotenv.2020.141812, 2020.
- Luecken, D. J., Phillips, S., Sarwar, and G., Jang, C.: Effects of using the CB05 vs. SAPRC99 vs. CB4
- 832 chemical mechanism on model predictions: Ozone and gas-phase photochemical precursor
- 833 concentrations, Atmos. Environ., 42, 5805-5820, https://doi.org/10.1016/j.atmosenv.2007.08.056,
- 834 2008.
- Lu, K., Zhang, Y., Su, H., Brauers, T., Chou, C. C., Hofzumahaus, A., Liu, S. C., Kita, K., Kondo, Y.
- Shao, M., Wahner, A., Wang, J., Wang, X., and Zhu, T.: Oxidant (O3+ NO2) production processes and
- 837 formation regimes in Beijing, J. Geophys. Res. Atmos., 115, D07303,
- 838 https://doi.org/10.1029/2009JD012714, 2010.
- Malley, C. S., Henze, D. K., Kuylenstierna, J. C. I., Vallack, H. W., Davila, Y., Anenberg, S. C., Turner,
- 840 M. C., and Ashmore, M. R.: Updated global estimates of respiratory mortality in adults ≥30 years of
- age attributable to long-term ozone exposure, Environ. Health. Persp., 125, 087021,
- https://doi.org/10.1289/EHP1390, 2017.
- 843 Martinez, M.: OH and HO2 concentrations, sources, and loss rates during the Southern Oxidants Study
- in Nashville, Tennessee, summer 1999, J. Geophys. Res.-Atmos., 108, 4617,
- https://doi.org/10.1029/2003JD003551, 2003.
- Mazzuca, G. M., Ren, X., Loughner, C. P., Estes, M., Crawford, J. H., Pickering, K. E., Weinheimer, A.

- 847 J., and Dickerson, R. R.: Ozone production and its sensitivity to NOx and VOCs: results from the
- DISCOVER-AQ field experiment, Houston 2013, Atmos. Chem. Phys., 16, 14463-14474,
- 849 https://doi.org/10.5194/acp-16-14463-2016, 2016.
- 850 Mills, G., Sharps, K., Simpson, D., Pleijel, H., Broberg, M., Uddling, J., Jaramillo, F., Davies, W. J.,
- Dentener, F., Van den Berg, M., Agrawal, M., Agrawal, S. B., Ainsworth, E. A., Buker, P., Emberson,
- 852 L., Feng, Z., Harmens, H., Hayes, F., Kobayashi, K., Paoletti, E., and Van Dingenen, R.: Ozone
- 853 pollution will compromise efforts to increase global wheat production, Glob. Chang. Biol., 24, 3560-
- 854 3574, https://doi.org/10.1111/gcb.14157, 2018.
- 855 O'Neill, M. S., Jerrett, M., Kawachi, I., Levy, J. I., Cohen, A. J., Gouveia, N., Wilkinson, P., Fletcher, T.,
- 856 Cifuentes, L., Schwartz, J.: Health, wealth, and air pollution: advancing theory and methods, Environ.
- Health. Persp., 111, 1861-70, https://doi.org/10.1289/ehp.6334, 2003.
- 858 Pan, X.; Kanaya, Y., Tanimoto, H., Inomata, S., Wang, Z., Kudo, S., and Uno, I.: Examining the major
- 859 contributors of ozone pollution in a rural area of the Yangtze River Delta region during harvest season,
- 860 Atmos. Chem. Phys., 15, 6101-6111, https://doi.org/10.5194/acp-15-6101-2015, 2015.
- Ren, X., van Duin, D., Cazorla, M., Chen, S., Mao, J., Zhang, L., Brune, W. H., Flynn, J. H., Grossberg,
- N., Lefer, B. L., Rappenglück, B., Wong, K. W., Tsai, C., Stutz, J., Dibb, J. E., Thomas Jobson, B.,
- Luke, W. T., and Kelley, P.: Atmospheric oxidation chemistry and ozone production: results from
- 864 SHARP 2009 in Houston, Texas, J. Geophys. Res.-Atmos., 118, 5770-5780,
- https://doi.org/10.1002/jgrd.50342, 2013.
- 866 Sadanaga, Y., Kawasaki, S., Tanaka, Y., Kajii, Y., and Bandow, H.: New system for measuring the
- photochemical ozone production rate in the atmosphere, Environ. Sci. Technol., 51, 2871-2878,
- 868 https://doi.org/10.1021/acs.est.6b04639, 2017.
- 869 Shen, H., Liu, Y., Zhao, M., Li, J., Zhang, Y., Yang, J., Jiang, Y., Chen, T., Chen, M., Huang, X., Li, C.,
- 870 Guo, D., Sun, X., Xue, L., and Wang, W.: Significance of carbonyl compounds to photochemical ozone
- formation in a coastal city (Shantou) in eastern China, Sci. Total. Environ., 764, 144031,
- https://doi.org/10.1016/j.scitotenv.2020.144031, 2021.
- 873 Sklaveniti, S., Locoge, N., Stevens, P. S., Wood, E., Kundu, S., and Dusanter, S.: Development of an
- 874 instrument for direct ozone production rate measurements: measurement reliability and current
- limitations, Atmos. Meas. Tech., 11, 741-761, https://doi.org/10.5194/amt-11-741-2018, 2018.

- Tadic, I., Crowley, J. N., Dienhart, D., Eger, P., Harder, H., Hottmann, B., Martinez, M., Parchatka, U.,
- Paris, J.-D., Pozzer, A., Rohloff, R., Schuladen, J., Shenolikar, J., Tauer, S., Lelieveld, J., and Fischer,
- 878 H.: Net ozone production and its relationship to nitrogen oxides and volatile organic compounds in the
- marine boundary layer around the Arabian Peninsula, Atmos. Chem. Phys., 20, 6769-6787,
- 880 https://doi.org/10.5194/acp-20-6769-2020, 2020.
- 881 Wang, C., Yuan, B., Wu, C., Wang, S., Qi, J., Wang, B., Wang, Z., Hu, W., Chen, W., Ye, C., Wang, W.,
- 882 Sun, Y., Wang, C., Huang, S., Song, W., Wang, X., Yang, S., Zhang, S., Xu, W., Ma, N., Zhang, Z.,
- Jiang, B., Su, H., Cheng, Y., Wang, X., and Shao, M.: Measurements of higher alkanes using NO+
- chemical ionization in PTR-ToF-MS: important contributions of higher alkanes to secondary organic
- aerosols in China, Atmos. Chem. Phys., 20, 14123–14138, https://doi.org/10.5194/acp-20-14123-
- 886 2020, 2020a.
- Wang, F., An, J., Li, Y., Tang, Y., Lin, J., Qu, Y., Chen, Y., Zhang, B., and Zhai, J.: Impacts of uncertainty
- 888 in AVOC emissions on the summer ROx budget and ozone production rate in the three most rapidly-
- developing economic growth regions of China, Adv. Atmos. Sci., 31, 1331-1342,
- 890 https://doi.org/10.1007/s00376-014-3251-z, 2014.
- 891 Wolfe, G. M., Marvin, M. R., Roberts, S. J., Travis, K. R., and Liao, J.: The Framework for 0-D
- 892 Atmospheric Modeling (F0AM) v3.1, Geosci. Model. Dev., 9, 3309-3319,
- 893 https://doi.org/10.5194/gmd-9-3309-2016, 2016.
- 894 Wu, C., Wang, C., Wang, S., Wang, W., Yuan, B., Qi, J., Wang, B., Wang, H., Wang, C., Song, W., Wang,
- 895 X., Hu, W., Lou, S., Ye, C., Peng, Y., Wang, Z., Huangfu, Y., Xie, Y., Zhu, M., Zheng, J., Wang, X.,
- 896 Jiang, B., Zhang, Z., and Shao, M.: Measurement report: Important contributions of oxygenated
- 897 compounds to emissions and chemistry of volatile organic compounds in urban air, Atmos. Chem.
- 898 Phys., 20, 14769–14785, https://doi.org/10.5194/acp-20-14769-2020, 2020.
- 899 Yuan, B., Chen, W., Shao, M., Wang, M., Lu, S., Wang, B., Liu, Y., Chang, C.-C., and Wang, B.:
- 900 Measurements of ambient hydrocarbons and carbonyls in the Pearl River Delta (PRD), China, Atmos.
- 901 Res., 116, 93-104, https://doi.org/10.1016/j.atmosres.2012.03.006, 2012.
- 202 Zhang, A., Lin, J., Chen, W., Lin, M., and Lei, C.: Spatial-temporal distribution variation of ground-level
- 903 ozone in China's Pearl River Delta metropolitan region, Int. J. Environ. Res. Public Health., 18, 872,
- 904 https://doi.org/10.3390/ijerph 18030872, 2021.

905 Zhou, W., Cohan, D. S., and Henderson, B. H.: Slower ozone production in Houston, Texas following 906 emission reductions: evidence from Texas Air Quality Studies in 2000 and 2006, Atmos. Chem. Phys., 907 14, 2777-2788, https://doi.org/10.5194/acp-14-2777-2014, 2014. 908 Zhu, M., Dong, H., Yu, F., Liao, S., Xie, Y., Liu, J., Sha, Q., Zhong, Z., Zeng, L., Zheng, J.: A new 909 portable instrument for online measurements of formaldehyde: from ambient to mobile emission sources. Environ. Sci. Technol. Lett, 7, 292-297, https://dx.doi.org/10.1021/acs.estlett.0c00169, 2020. 910 911 Zou, Y., Deng, X. J., Zhu, D., Gong, D. C., Wang, H., Li, F., Tan, H. B., Deng, T., Mai, B. R., Liu, X. T., 912 and Wang, B. G.: Characteristics of 1 year of observational data of VOCs, NOX and O3 at a suburban site in Guangzhou, China. Atmos. Chem. Phys., 15, 6625-6636, https://doi.org/10.5194/acp-15-6625-913 2015, 2015. 914